MILITARY SPECIFICATION

CARTRIDGE, IGNITION, M702 PARTS FOR

This Amendment forms a part of Military Specification MIL-C-48161B (AR), dated 12 August 1987, and is approved for use within the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 9

4.4.2.3, Major category:

Major 112: Change "0.065%" AQL to read "(a)" and add note (a) which reads "See 4.4.3.1."

Major 113: Delete in its entirety and substitute:

"113. Depth of pellet cavity...0.40%...3.2...Gage"

Major 114: Delete in its entirety.

PAGE 11

4.4.2.4 Minor 206: Change "Depth of spanner holes" to read "Depth of spanner holes, min."

PAGE 14

4.4.2.6 Body:

Major category:

Major 121: Change "0.065%" AQL to read "(a)" and add note (a) which reads "See 4.4.3.1."

Major 122: Delete in its entirety.

Major 123: Delete in its entirety.

Minor category: Minor 201: Change "Gage" to read "Visual".

AMSC N/A
FSC 1310

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.

PAGE 15

4.4.3.1: Add new paragraph which reads:

"4.4.3.1 Salt spray test. Samples shall be selected from each inspection lot and tested per 4.5.3. An inspection lot shall consist of parts anodized in the same equipment with the same process parameters during an eight hour shift. Samples shall be selected per MIL-STD-105D, Table II A, Level S-3 at 0.65 percent AQL."

PAGE 19

4.5.3, Line 6: Change "336" to read "96"

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1310-A449)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:15Z
Check the source to verify that this is the current version before use.