MILITARY SPECIFICATION

CONTAINER, METAL, SHIPPING

1. SCOPE

1.1 This specification covers requirements, quality assurance provisions, and the preparation for delivery criteria for one type of container, metal, shipping used on the atomic demolition charge.

2. APPLICABLE DOCUMENTS

2.1 The following documents, of the issue in effect on date of invitation for bids or request for proposals, form a part of this specification to the extent specified herein:

SPECIFICATIONS

MILITARY

MIL-C-6054	- Drum, Metal - Shipping and Storage
MIL-I-48191	- Indicator, Humidity, Plug
MIL-V-48190	- Vent Assembly

STANDARDS

MILITARY

AN335-5	- Nut, Plain, Hexagon
MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168	- Lot Numbering of Ammunition

DRAWINGS

ORDNANCE CORPS

8791645 - Bolt, Machine
8795621 - Vent
8804101 - Nut, Plain, Hexagon

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

8807378 - Container, Metal, Shipping
8812245 - Plug, Vent
8812244 - Flange, Vent
8846465 - Covers, Gaskets and Locking Rings for Container, Metal, Shipping
8853791 - Vent Assembly
ET8807378 - Equipment Tabulation

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The container shall comply with all requirements specified on the drawing (dwg) 8807378, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Threads. Threads shall be full and undamaged for the entire minimum length or depth as required on the applicable drawing.

3.3.3 Burrs. Parts shall be free from burrs.

3.3.4 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.5 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.2 First article inspection. Not applicable.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacutrer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance with the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.

Table I
Major Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-16	all	28-29	23	52-56	31	132-156	39
17	16	30-31	24	57-62	32	157-191	40
18	17	32-34	25	63-69	33	192-244	41
19-20	18	35-36	26	70-76	34	245-334	42
21	19	37-40	27	77-86	35	335-519	43
22-23	20	41-43	28	87-97	36	520-1120	44
24-25	21	44-47	29	98-112	37	over 1120	45
26-27	22	48-51	30	113-131	38		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

Table II
Minor Characteristics

Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size	Lot Size	Sample Size
1-9	all	14-16	12	28-33	16	77-121	20
10	9	17-18	13	34-41	17	122-273	21
11	10	19-22	14	42-54	18	over 273	22
12-13	11	23-27	15	55-76	19		

4.3.2.1 Classification of characteristics (see 3.2). Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Bolt, Machine (see dwg 8791645) covering a detail of dwg 8807378.

Categories	Characteristics	Method of Inspection

Critical: None defined

Major:

101.	Diameter of hole (.078) min.	Gage
102.	Pitch diameter of thread	Gage
103.	Major diameter of thread	Gage
104.	Length of thread (2.00)	Gage
105.	Length from head to end (3.31)	Gage
106.	Material (see 3.1)	Visual
107.	Objective evidence (see 6.2) for protective finish in accordance with dwg 8791645	Visual

Minor:

201.	Surface finish	Visual
202.	Workmanship (see 3.3)	Visual

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

4.3.2.1.2 Container, Metal, Shipping (see dwg 8807378) covering part Number 8808402.

Categories	Characteristics	Method of Inspection
Critical: None defined.		
Major:		
101.	Objective evidence (see 6.2) for Indicator humidity, plug (see dwg 8971666) in accordance with MIL-I-48191 (MU)	Visual
102.	Objective evidence (see 6.2) for nut, plain, hex (see dwg 8804101) in accordance with AN 335-5	Visual
103.	Objective evidence (see 6.2) for vent assembly (see dwg 88795621 and 8853791) in accordance with MIL-V-48190 (MU)	Visual
104.	Objective evidence (see 6.2) for plug, vent in accordance with dwg 8812245	Visual
105.	Objective evidence (see 6.2) for flange, vent in accordance with dwg 8812244	Visual
106.	Torque on indicator	Gage
107.	Torque on indicator ring securing glass	Gage
108.	Nicks and scratches touched up	Visual
109.	Vent located on top of container as per drawing	Visual
110.	Humidity indicator correctly located	Visual
111.	Humidity indicator and vent properly assembled	Visual
112.	Objective evidence (see 6.2) for container in accordance with MIL-C-6054	Visual
113.	Objective evidence (see 6.2) for protective finish in accordance with dwg 8807378	Visual
114.	Correct nut and bolt furnished	Visual
Minor:		
201.	Workmanship (see 3.3)	Visual-Manual

4.3.2.1.3 Preparation for delivery (see section 5).

Categories	Characteristics	Method of Inspection
Critical: None defined		

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

Categories	Characteristics	Method of Inspection
Major:		
	101. Containers prepared for delivery in accordance with section 5, MIL-C-6054	Visual-Manual
Minor: None defined		

4.3.3 Testing. Testing shall be in accordance with MIL-C-6054.

4.3.4 Acceptance inspection equipment.

4.3.4.1 Critical and major characteristics and tests. Inspection and testing shall be performed with the acceptance inspection equipment, operating instructions, and calibration instructions specified on the Equipment Lists (EL). ELs for assemblies are listed on the Equipment Tabulation, ET. When either of the conditions listed below exist, the contractor shall design required equipment or specify suitable commercial equipment and obtain approval prior to use on the contract.

a. Any deviation from equipment or procedures specified on the EL is desired (see 6.3).
b. The code "CD" is listed in the "Part or Identifying Number" column on the EL (see 6.1.2).

4.3.4.2 Minor characteristics and tests. Acceptance inspection equipment for minor characteristics is not specified on the ELs. The acceptance inspection equipment, operating instructions and calibration instructions used by the contractor for minor classification inspection shall be approved by the Government representative authorized by the procuring agency.

4.4 Test methods. Test methods shall be in accordance with MIL-C-6054.

5. PREPARATION FOR DELIVERY

5.1 The container shall be prepared for delivery in accordance with MIL-C-6054.

6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

6.1.1 Procurement requirements.

a. Title, number, and date of this specification.
b. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.

6.1.2 Contract data requirements (see 4.3.4.1). Data specified in 4.3.4.1 will be delivered as identified on DI-E-1118 DD Form 1423 incorporated in the contract.

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

6.3 Acceptance inspection equipment (see 4.3.4.1). The contractor shall obtain approval from the Commanding Officer, Picatinny Arsenal, Dover, New Jersey 07801, ATTN: SMUPA-QA-N-I

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 8140-A084

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:17Z
Check the source to verify that this is the current version before use.