MILITARY SPECIFICATION

FUZE, PD, M935
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-F-48172(AR), dated 17 January 1977, and is approved for use within the US Army Armament Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

4.3.1: Delete "188" and substitute "203".

PAGE 5

TABLE I: Delete "124" (2 places) and substitute "154".

PAGE 14

4.4.2.8:

Critical 3: Change "124" to "108".

Delete majors 101 and 102 in their entirety and substitute the following:

"101	Ballistic test SQ	88	(a)	3.5.2	4.5.5
102	Ballistic test delay	10	(b)	3.5.2	4.5.5
103	Transportation vibration firing phase non-function	10	(c)	3.5.2	4.5.2

(a) Three (3) or more duds shall cause the lot to be rejected. After three(3) consecutive lots have been accepted according to this criteria, a special double sampling plan shall be used - see paragraph 4.5.5.1.3.

AMSC N/A FSC 1390

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check this source to verify that this is the current version before use.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

(b) Five (5) fuzes from the charge zero quantity shall be TV conditioned prior to ballistic test. Results for information only except for premature functioning.

(c) Two (2) or more duds shall cause the lot to be rejected.".

* Add pages "14A and 14B" (included).

PAGE 16

4.5.2, line 10: Delete the sentence "If the x-rays indicate ..." in its entirety and substitute: "If the x-rays indicate the fuzes safe and operable, then they shall be assembled to 60MM, M720 rounds and fired at Charge 0 set SQ, as detailed in paragraph 4.5.5".

4.5.5, Delete in its entirety and substitute"

"4.5.5 Performance test (proving ground ballistic).

4.5.5.1 Functioning test. The sample fuzes shall be assembled to 60MM, HE, M720 cartridges and fired from an appropriate mortar between 45° and 75° elevation. If any fuze fails to cause the shell to function high order, that fuze shall be classified as defective. If any fuze in either SQ or Delay setting mode causes the round to function prematurely, that fuze shall be classified as having critical defect. The proving ground shall utilize a geophonic sensing device to differentiate superquick and delay functionings at maximum charge.

4.5.5.1.1 SQ phase. The sample fuzes shall be divided into two (2) equal groups. The groups shall be fired at Charge 0 set SQ and maximum charge set SQ.

4.5.5.1.2 Delay phase. The sample fuzes shall be divided into two (2) equal groups. The groups shall be fired at Charge 0 set Delay and maximum charge set Delay, respectively. Sample fuzes required to be TV tested shall be conditioned in accordance with para. 4.5.2 except that the fuzes shall be set Delay after conditioning. This test is for informational purposes only and shall not be considered for lot acceptance purposes except for premature functions.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Packing and Marking of Container, M548 for Fuze, PD, M935 (Unsealed)	1 OF 1	9381686
			NEXT HIGHER ASSEMBLY: 9395584

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any material containing condensate or surface moisture		0.40%	5.1	Visual
102	Bottom support or separators missing		0.40%	5.1	Visual
103	Partition missing or incomplete		0.40%	5.1	Visual
104	Top filler missing or insufficient (contents loose)		0.40%	5.1	Visual/Manual
105	Incorrect number of assemblies		0.40%	5.1	Visual
106	Fuze supports missing		0.40%	5.1	Visual
Minor	None defined				

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-F-48172 (AR)
AMEMDMENT 2

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Packing and Marking of Container, M548 for Fuze, PD, M935 (Sealed)	1 OF 1	9381686
			NEXT HIGHER ASSEMBLY: 9395584

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major 101	Air leakage test		100%	5.1	4.5.7
Minor 201	Marking missing or unidentifiable		0.65%	5.1	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

4.5.5.1.3 Double sample SQ. After three (3) consecutive lots have met the ballistic requirements of para. 4.4.2.8, a special double sample for the ballistic, SQ phase shall be employed. Forty-four (44) sample fuzes shall be fired in accordance with para. 4.5.5.1.1. If no (0) duds result, the lot shall be accepted. If two (2) or more duds are found, the lot shall be rejected. If one (1) dud results, another sample of forty-four (44) fuzes shall be fired. If more than one (1) additional dud results, the lot shall be rejected. If only the first sample is required, the Premature Burst sample size shall be reduced to sixty-four (64).".

PAGE 17

* Add new paragraph 4.5.7 as follows:

"4.5.7 Air leakage test (see drawing 9381686). The sealed metal ammunition container shall be tested in accordance with the procedures of 9246386."

* Add to paragraph 5.1 the following:

"For other than intraplant shipment, packaging, packing and marking shall be in accordance with the requirements of drawing 9381686."

6.4 Delete in its entirety and substitute:

"6.4 Performance test summary.

6.4.1 Quality conformance test.

FUNCTIONING

Weapon	Cartridge	Charge	Fuze Setting	Quantity
60MM Mortar	60MM, HE, M720	0	SQ	44(a)
		0	Delay	5(b)
		4	SQ	44(a)
		4	Delay	5(b)

(a) Quantity reduced to twenty-two (22) per test phase as required when employing special double sample.

(b) Results for information purposes only except for premature functionings. Charge zero quantity shall be TV conditioned prior to functioning test.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

ARMING DELAY

Weapon	Cartridge	Charge	Fuze Setting	Quantity
60MM Mortar	M720 Inert	0	SQ	12

TRANSPORTATION VIBRATION

Weapon	Cartridge	Charge	Fuze Setting	Quantity
60MM Mortar	M720 HE	0	SQ	10

6.4.2 First article inspection test.

FUNCTIONING

Weapon	Cartridge	Charge	Fuze Setting	Quantity
60MM Mortar	M720 HE	0	SQ	62
		0	Delay	15(a)
		4	SQ	62
		4	Delay	15(a)

(a) Results for information only except for premature functioning. Five (5) fuzes of the charge zero quantity shall be TV conditioned prior to functioning test.

ARMING DELAY

Weapon	Cartridge	Charge	Fuze Setting	Quantity
60MM Mortar	M720 Inert	0	SQ	12

TRANSPORTATION VIBRATION

Weapon	Cartridge	Charge	Fuze Setting	Quantity
60MM Mortar	M720 HE	0	SQ	10

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

NOTE: The margins of this amendment are marked with an asterisk or vertical line to indicate where changes (additions, modifications, corrections, deletions) from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1390-A511)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.