INCH-POUND
MIL-P-48189D (AR)
AMENDMENT 1
27 March 1998

MILITARY SPECIFICATION

PROJECTILE, 155MM, HE, M692 AND M731
HOUSING, TIMING AND FUZING FOR

MIL-P-48189D was inactivated after 14 February 1997 for New Design.

This amendment forms a part of MIL-P-48189D (AR), dated 25 August 1992, and is approved for use by the U.S. Army Armament Research, Development and Engineering Center, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 10

Add new paragraph 3.20.2.1 through 3.20.2.8 as follows:

"3.20.2.1 Workmanship - Printed wiring board, Electronics. The Printed wiring board, Electronics shall be free of solder bridges and foreign material on the board which could cause solderability problems.

3.20.2.2 Workmanship - S&A assembly. The S&A assembly shall be free from cracks or porosity which expose the internal moving parts including the slider, springs, or set-back pin. The lead cup area, including the dovetail section shall be properly formed to prevent intrusion of the molding compound into the lead cup pocket. The external parts shall be free of oil or grease which would prevent proper adhesion of the molding compound.

3.20.2.3 Workmanship - S&A assembly and Laminate assembly. The S&A assembly and Laminate assembly shall be free from cracks or porosity which expose the internal moving parts including the slider, springs, or set-back pin. The lead cup area, including the dovetail section shall be properly formed to prevent intrusion of the molding compound into the lead cup

AMSC N/A FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

pocket. The external parts shall be free of oil or grease which would prevent proper adhesion of the molding compound.

3.20.2.4 Workmanship - Diaphragm. The Diaphragm shall have no tears, rips, incomplete fill or die trim into the part. The parts shall not be warped, lack a center hole or have foreign material molded into the part.

3.20.2.5 Workmanship - Sensor assembly. The Sensor assembly shall be free from cracks, porosity, incomplete crimp, or missing parts which expose the internal moving parts. The external parts shall be free of oil or grease which would prevent proper adhesion of the molding compound.

3.20.2.6 Workmanship - Can, switch. The Can, switch shall not have residue or discoloration that could cause an increase in contact resistance or degradation over time. The can edges shall not have any burrs.

3.20.2.7 Workmanship - Electronics component. Electronic components shall not have foreign material or discoloration that could cause solderability problems. The components shall not have any nicked wires which would expose base metal.

3.20.2.8 Workmanship - Wiring assembly, printed flexible. The Wiring assembly, printed flexible shall not have ragged or nicked edges that would cause the tape to tear easily. The annular ring must be centered on the holes.

PAGE 17

4.4.2.1, Minor 201: Delete “3.20” and substitute “3.20.2.1” under REQUIREMENT PARAGRAPH.

PAGE 19

4.4.2.3, Minor 201: Delete “3.20” and substitute “3.20.2.2” under REQUIREMENT PARAGRAPH.

PAGE 20

4.4.2.4, Minor 202: Delete “3.20” and substitute “3.20.2.2” under REQUIREMENT PARAGRAPH.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

PAGE 21

4.4.2.5, Minor 201: Delete “3.20” and substitute “3.20.2.2” under REQUIREMENT PARAGRAPH.

PAGE 22

4.4.2.6, Minor 201: Delete “3.20” and substitute “3.20.2.3” under REQUIREMENT PARAGRAPH.

PAGE 25

4.4.2.9, Minor 201: Delete “3.20” and substitute “3.20.2.4” under REQUIREMENT PARAGRAPH.

PAGE 26

4.4.2.10, Minor 201: Delete “3.20” and substitute “3.20.2.5” under REQUIREMENT PARAGRAPH.

PAGE 27

4.4.2.11, Minor 201: Delete “3.20” and substitute “3.20.2.6” under REQUIREMENT PARAGRAPH.

PAGE 30

4.4.2.14, Minor 201: Delete “3.20” and substitute “3.20.2.7” under REQUIREMENT PARAGRAPH.

PAGE 31

4.4.2.15, Minor 201: Delete “3.20” and substitute “3.20.2.7” under REQUIREMENT PARAGRAPH.

PAGE 32

4.4.2.16, Minor 201: Delete “3.20” and substitute “3.20.2.7” under REQUIREMENT PARAGRAPH.

PAGE 33

4.4.2.17, Minor 201: Delete “3.20” and substitute “3.20.2.7” under REQUIREMENT PARAGRAPH.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.

PAGE 50

4.4.2.32, Minor 202: Delete “3.20” and substitute “3.20.2.8” under REQUIREMENT PARAGRAPH.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-0035)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:16Z
Check the source to verify that this is the current version before use.