MIL-T-48140 (PA)
AMENDMENT 1
14 May 1974

MILITARY SPECIFICATION

TUNGSTEN POWDER
(FOR PYROTECHNICS)

This Amendment forms a part of Military Specification MIL-T-48140(MU), dated 24 April 1973 and is approved for use by all Departments and Agencies of the Department of Defense.

Delete "MU" and substitute "PA" where applicable.

Paragraph 1.2: After Type I, delete "as supplied", and substitute "Agglomerated".

Paragraph 3.1: Delete ("see 6.5)"

Paragraph 3.2:

Table I; Molybdenum, delete "0.040" and substitute "0.060"
Nickel, delete "0.001" and substitute "0.005"

Below Table I: add "The sum of the values of metallic impurities analyzed shall not exceed 0.1% on a gas free basis."

Paragraph 3.4:

a. Type I, Delete "4.2 ± 0.5 microns" and substitute "4.5 ± 0.5 microns."

b. Type II, as supplied: Delete "4.2 ± 0.6 microns" and substitute "4.5 ± 0.5 microns"

c. Type II , lab milled: Delete "3.9 ± 0.5 microns" and substitute "4.2 ± 0.6 microns".

FSC: 1376

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:14Z
Check the source to verify that this is the current version before use.

Paragraph 3.5, Table II: Delete in its entirety and substitute:

TABLE II

Particle Size distribution, microns	Weight Percent					
	Type I Agglomerated As supplied		Type II De-Agglomerated			
			As supplied		Lab milled	
	Min	Max	Min	Max	Min	Max
0-5	6	18				
5-10	22	38				
10-15	20	35				
15-20	12	25				
20-25	0	25				
0-1			0	2	0	5
1-2			1	5	1	11
2-3			5	14	10	20
3-4			10	20	15	27
4-5			11	23	15	27
5-6			11	21	10	20
6-7			8	17	4	12
7-25			Balance		Balance	

Paragraph 4.3: Add new paragraph:

"4.3.3 Inspection Equipment. The government reserves the right to inspect the contractor's equipment and determine that he has available and utilizes correctly, measuring and test equipment of the required accuracy and precision and that the instruments are of the proper type and range to make measurements of the required accuracy. Commercial inspection equipment, shall be employed where applicable for all tests and examinations specified in 4.4. The contractor is responsible for assuring proper calibration procedures are followed. Government approval of all inspection equipment is required prior to its use for acceptance purpose."

Paragraph 4.4.1, after last sentence: Add "(see 6.5)"

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:14Z
Check the source to verify that this is the current version before use.

Paragraph 4.4.2, after last sentence: Add "(see 6.5)"

Paragraph 4.4.5, second sentence: Delete "and oxygen content".

Paragraph 6.5: Delete in its entirety,and substitute:

"6.5 Prior approval of the Contracting Officer is required for use of equivalent test methods. A description of the proposed method should be submitted through the Contracting Officer to: Commander, ATTN: SARPA-QA-A-P, Picatinny Arsenal, Dover, New Jersey 07801. This description should include but not be limited to the procedures used, the accuracy and precision of the method, test data to demonstrate the accuracy and precision and drawings of any special equipment required."

Custodian:
Army-PA

Preparing Activity:
Army-PA

Project Number: 1376-A026

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:14Z
Check the source to verify that this is the current version before use.