MILITARY SPECIFICATION SHEET

CONNECTORS, PLUG AND RECEPTACLE , ELECTRIC,
RECTANGULAR, HIGH DENSITY, POLARIZED CENTER JACKSCREW,
GENERAL SPECIFICATION FOR

This amendment forms a part of MIL-C-28804C, dated 12 April 1991, and is approved for use by all Departments and Agencies of the Department of Defense.

PAGE 3

After ELECTRONIC INDUSTRIES ASSOCIATION (EIA), delete:

"EIA-364-11-1987 - Test Procedure No. 11, Resistance to Solvents, Test Procedure for electrical Connectors

PAGE 11

3.5.24, delete in its entirety.

DISTRIBUTION STATEMENT A Approved for public release, distribution is unlimited

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:00Z
Check the source to verify that this is the current version before use.

TABLE IX, delete and substitute:

TABLE IX. Qualification and periodic inspection (connectors).

Inspection	Requirement paragraph	Method paragraph	Test samples								
			1	2	3	4	5	6 2/	7	8	9
Inspection of product	3.1, 3.3, 3.4, 3.5.26, and 3 5.27	4.7.1	X	X	X	X	X	X	X	X	X
Magnetic permeability 1/	3.5.1	4.7.2			X	X					
Maintenance aging (crimp contact only)	3.5.2	4.7.3	X		X						
Contact insertion and removal force	3.5 3	4.7.4	X		X						
Mating and unmating force	3.5 4	4.7.5	X		X						
Contact retention	3.5.5	4.7.6	X	X	X	X					
Dielectric withstanding voltage 1/											
At sea level	3.5 6	4.7.7.1	X	X	X	X	X				
At altitude	3.5.6	4.7.7.2	X	X	X	X	X				
Insulation resistance 1/	3.5.7	4.7.8	X	X	X	X	X				
Contact resistance 2/	3.5.8	4.7.9	X	X	X	X					
Contact engagement and separation force 2/	3 5.9	4.7.10	X	X	X	X	X				
Mating and unmating force	3 5 4	4.7.5	X	X	X	X	X				
Thermal shock	3.5.10	4 7.11	X	X	X	X	X				
Humidity	3.5 11	4.7.12	X	X	X	X	X				
Dielectric withstanding voltage	3.5.6	4.7.7	X	X	X	X	X				
Insulation resistance	3 5 7	4.7.8	X	X	X	X	X				
Vibration	3 5 12	4 7.13	X	X	X	X	X				
Shock (specified pulse)	3.5.13	4.7.14	X	X	X	X	X				
Durability	3.5 14	4.7.15	X	X	X	X	X				
Mating and unmating force	3 5 4	4 7.5	X	X	X	X	X				
Contact engagement and separation force	3 5 9	4.7.10	X	X	X	X	X				
Altitude immersion	3 5.22	4.7.23	X	X	X	X	X				
Salt spray (corrosion)	3.5.15	4.7.16	X	X	X	X	X				
Mating and unmating force	3.5.4	4.7.5	X	X	X	X	X				
Contact resistance	3.5.8	4.7.9	X	X	X	X	X				
Contact retention	3.5.5	4.7.6	X	X	X	X					
Oversize pin exclusion 2/	3.5.16	4.7.17	X	X	X	X					
Contact resistance 2/	3.5.8	4.7.9	X	X	X	X					
Probe damage 2/	3.5.17	4.7.18	X	X	X	X					
Contact engagement and separation force 2/	3.5.9	4.7.10	X	X	X	X					
Fluid immersion 1/	3.5.18	4.7.19	X	X	X	X	X				
Mating and unmating force 1/	3.5.4	4.7.5	X	X	X	X	X				
Crimp contact deformation 1/ 2/	3.5.19	4.7.20						X			
Contact pin strength 1/ 2/	3.5.20	4.7.21						X			
Crimp tensile strength 1/ 2/	3.5.21	4.7.22						X			
Inspection of product 1/ 2/	3.1, 3.3, 3.4, 3 5.26, and 3.5.27	4.7.1	X	X	X	X	X	X			
Resistance to solder heat 1/ 3/	3.5.23	4.7.24							X	X	X
Contact retention 1/ 3/	3.5.5	4.7.6							X	X	X
Solderability (printed wiring tails only)	3 5 25	4.7.26							X	X	X
Inspection of product 1/ 3/	3 1, 3.3, 3.4, 3.5 26, and 3.5.27	4.7.1							X	X	X

1/ Not applicable for retention of qualification.
2/ When using previously qualified crimp contacts these tests are not required.
3/ Connectors with printed wiring tails only

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:00Z
Check the source to verify that this is the current version before use.

4.7.25, delete in its entirety

CONCLUDING MATERIAL

Custodians.
Army - CR
Navy - EC
Air Force - 85

Review activities:
Army - AT, MI
Navy - AS
Air Force - 99
DLA - ES

User activities:
Army - AM, AR, ME
Navy - MC

Preparing activity
Navy - EC

Agent:
DLA - ES

(Project 5935-3950)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:00Z
Check the source to verify that this is the current version before use.