INCH-POUND
MIL-DTL-28804/2E
w/Amendment 1
23 August 2021
SUPERSEDING
MIL-DTL-28804/2E
24 February 2020

DETAIL SPECIFICATION SHEET

CONNECTORS, PLUG, ELECTRIC, RECTANGULAR, HIGH DENSITY, POLARIZED CENTER, JACKSCREW, CRIMP REMOVABLE PIN CONTACTS, CLASS G

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-28804.





FIGURE 1. Connector, crimp removable pin contacts, class G.

AMSC N/A
FSC 5935
DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:02Z
Check the source to verify that this is the current version before use.



Inches	mm
.001	0.03
.005	0.13
.008	0.20
.010	0.25
.015	0.38
.021	0.53
.043	1.09
.050	1.27
.123	3.12
.125	3.18
.138	3.51
.156	3.96
.194	4.93
.195	4.95
.232	5.89
.260	6.60
.283	7.19
.312	7.92
.375	9.53
.598	15.19

FIGURE 1. Connector, crimp removable pin contacts, class G – Continued.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:02Z
Check the source to verify that this is the current version before use.

Dash no. (see notes 4 and 5)	Shell size	No. of contacts	Insert arrangement no section (see note 6)	A ± .015 (0.38)	B ± .015 (0.38)	C ± .005 (0.13)	D ± .005 (0.13)	E ± .005 (0.13)	F ± .015 (0.38)	G BSC	H ± .008 (0.20)	J ± .008 (0.20)	K ± .015 (0.38)	L ± .025 (0.64)	Weight (max) (with contacts) grams
1	8	14	10 No. 1	1.520 (38.61)	.725 (18.42)	.800 (20.32)	.548 (13.92)	.688 (17.48)	.436 (11.07)	1.200 (30.48)	.625 (15.88)	.888 (22.56)	.050 (1.27)	1.360 (34.54)	16.5
2	10	38	20 No. 1	1.945 (49.40)	. .725 (18.42)	1.220 (30.99)	.548 (13.92)	1.108 (28.14)	.436 (11.07)	1.625 (41.27)	.625 (15.88)	1.308 (33.22)	.050 (1.27)	1.360 (34.54)	23.0
3	12	88	30 No. 1	2.780 (70.61)	.725 (18.42)	2.060 (52.32)	.548 (13.92)	1.948 (49.48)	.436 (11.07)	2.460 (62.48)	.625 (15.88)	2.148 (54.56)	.050 (1.27)	1.360 (34.54)	28.5
4	14	108	40 No. 1	1.990 (50.55)	1.077 (27.36)	1.444 (36.68)	.897 (22.78)	1.332 (33.83)	.785 (19.94)	1.718 (43.64)	.977 (24.82)	1.532 (38.91)	.058 (1.47)	1.360 (34.54)	34.5
5	16	132	50 No. 1	2.790 (70.87)	.902 (22.91)	2.068 (52.57)	.732 (18.59)	1.956 (49.68)	.620 (15.75)	2.470 (62.73)	.802 (20.37)	2.156 (54.76)	.100 (2.54)	1.360 (34.54)	40.5
6	18	244	60 No. 1	4.128 (104.85)	.902 (22.91)	3.410 (86.61)	.732 (18.59)	3.304 (83.92)	.630 (16.00)	3.808 (96.72)	.802 (20.37)	3.494 (88.75)	.100 (2.54)	1.360 (34.54)	67.0
7	8	14	10 No. 1	1.520 (38.61)	.725 (18.41)	.800 (20.32)	.548 (13.92)	688 (17.48)	.436 (11.07)	1.200 (30.48)	.625 (15.88)	.888 (22.56)	.050 (1.27)	.898 (22.81)	16.5
8	10	38	20 No. 1	1.945 (49.40)	.725 (18.41)	1.220 (30.99)	.548 (13.92)	1.108 (28.14)	.436 (11.07)	1.625 (41.27)	.625 (15.88)	1.308 (33.22)	.050 (1.27)	. 898 (22.81)	23.0
9	12	88	30 No. 1	2.780 (70.61)	.725 (18.41)	2.060 (52.32)	.548 (13.92)	1.948 (49.48)	.436 (11.07)	2.460 (62.48)	.625 (15.88)	2.148 (54.56)	.050 (1.27)	898 (22.81)	28.5
10	14	108	40 No. 1	1.990 (50.55)	1.077 (27.36)	1.444 (36.68)	.897 (22.78)	1.332 (33.83)	.785 (19.94)	1.718 (43.64)	.977 (24.82)	1.532 (38.91)	.058 (1.47)	898 (22.81)	34.5
11	16	132	50 No. 1	2.790 (70.87)	.902 (22.91)	2.068 (52.57)	.732 (18.59)	1.956 (49.68)	.620 (15.75)	2.470 (62.73)	.802 (20.37)	2.156 (54.76)	.100 (2.54)	898 (22.81)	40.5
12	18	244	60 No. 1	4.128 (104.85)	.902 (22.91)	3.410 (86.61)	.732 (18.59)	3.304 (83.92)	.630 (16.00)	3.808 (96.72)	.802 (20.37)	3.494 (88.75)	.100 (2.54)	898 (22.81)	69.0

NOTES:
1. Dimensions are in inches.
2. Metric equivalents are given for general information only.
3. Millimeters are in parentheses.
4. Dash number shall include N, V, W, X, Y, or Z to indicate polarization.
5. Dash numbers 1 through 6 are supplied with male turning jackscrews, dash numbers 7 through 12 are supplied with male fixed jackscrews.
6. For insert arrangements, see MIL-STD-1632.

FIGURE 1. Connector, crimp removable pin contacts, class G – Continued.

REQUIREMENTS:

Dimensions and configuration: See figure 1.

Contacts: Shall be in accordance with MIL-DTL-28804/9.

Mating connectors: M28804/2-1 through -6 mates with M28804/1-1 through -6, M28804/3-1 through -6, M28804/5-1 through -6, M28804/7-1 through -6. M28804/2-7 through -12 mates with M28804/1-7 through -12, M28804/3-7 through -12, M28804/5-7 through -12, and M28804/7-7 through -12.

Part or Identifying Number (PIN): M28804/2- (dash number from figure 1 and a suffix letter code to define polarization. See figure 1, note 4 herein, and MIL-DTL-28804.)

Part or Identifying Number (PIN): M28804/1-(dash number from figure 1 and a suffix letter code to define polarization. See figure 1, note 4 herein, and MIL-DTL-28804.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:02Z
Check the source to verify that this is the current version before use.

Amendment notations. The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations.

Referenced documents. In addition to MIL-DTL-28804, this document references the following:

MIL-DTL-28804/9
MIL-STD-1632

CONCLUDING MATERIAL

Custodians:
Army - CR
Navy - EC
Air Force - 85
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Army – AR, AT, CR4, MI
Navy – AS, MC

(Project 5935-2021-086)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T19:02Z
Check the source to verify that this is the current version before use.