[INCH-POUND]
A-A-1752B
July 30, 1996
SUPERSEDING
A-A-1752A
November 21, 1991

COMMERCIAL ITEM DESCRIPTION

DIPPER, KITCHEN

The General Services Administration has authorized the use of this commercial item description for all Federal agencies.

1. SCOPE

1.1 Scope. This commercial item description (cid) covers aluminum and corrosion resisting steel kitchen dippers.

2. CLASSIFICATION

2.1 Classification. The dippers shall be of the following types and sizes, as specified.

Type I - Aluminum Alloy
  Size 1 - 32 ounce capacity (0.95 L)
  Size 2 - 64 ounce capacity (1.9 L)

Type II - Corrosion-resisting Steel
  Size 0 - 16 ounce capacity (0.47 L)
  Size 1 - 32 ounce capacity (0.95 L)

3. SALIENT CHARACTERISTICS

3.1 Design and construction. The dimensions of the dippers shall be as listed in table I. The body of the dippers shall be formed without seams from a single piece of the specified material. The top edge of the body shall be finished with a half-round open bead, a closed bead, or finished smooth without a bead at the manufacturer's option.

3.1.1 Type I - Aluminum alloy. Type I dippers shall be constructed from 3000 series aluminum alloy. The type I dippers shall have a one piece tubular handle with a minimum wall thickness of 0.060 inch (1.5 mm). The handle shall have a minimum diameter of 1-1/8 inches (2.9 cm). The handle shall be mounted to the body by welding at an angle of 30 to 40 degrees. There shall be no openings in the handle and both ends shall be closed and sealed.

3.1.2 Type II - Corrosion-resisting steel. Type II dippers shall be constructed from 300 series (301 excluded) corrosion-resisting steel. The type II dippers shall have a handle constructed from flat stock with minimum widths of 1/2 inch (1.3 cm) for the size 0 dipper and 3/4 inch (1.9 cm) for the size 1 dipper. The handles shall be formed with an open end hook and shall be mounted to the body of the dipper at an angle of 30 to 40 degrees. The handles shall be attached to the body by spot welds (minimum of six for size 1 and three for size 0), projection welding, or fillet welding all around the edge in contact with the body.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: General Services Administration, Engineering Group (7FXEE), 819 Taylor St., Fort Worth, TX 76102.

FSC 7330

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

When spot welding or projection welding is used the crevice between the handle and body shall be sealed by welding, brazing, or silver solder. The welding shall be smooth, sound, and free from pits and flashes. All flux shall be removed. The handles shall have a minimum thickness of 0.071 inch (1.8 mm). The size 1 dipper shall have graduation markings at 8 ounce (0.24 L) intervals.

TABLE I - Dimensions

Type	Size	Capacity (oz.)	Handle length (inches, min.)	Body Thickness (inch, min.)
I	1	32 ± 3 (0.95 ± 0.09 L)	6-1/8 (15.6 cm)	0.051 (1.3 mm)
I	2	64 ± 4 (1.9 ± 0.12 L)	6-1/8 (15.6 cm)	0.057 (1.4 mm)
II	0	16 ± 2 (0.47 ± 0.06 L)	8 (20.3 cm)	0.025 (0.6 mm)
II	1	32 ± 3 (0.95 ± 0.09 L)	12 (30.5 cm)	0.025 (0.6 mm)

3.2 Finish. The dippers shall be smooth on all surfaces and edges. The measures shall be free from corrosion, discoloration, or stain.

3.3 Workmanship. The dippers shall be clean and free from dirt, grease, rough or sharp edges, slivers, burrs, deep scratches, tool marks, or other defects which may affect appearance or serviceability. The dippers shall not be fractured, dented, punctured or otherwise malformed or damaged.

3.4 Standard compliance. The dipper shall comply with the requirements of NSF International Criteria C-2 or Standard No. 2.

3.5 Metric products. Products manufactured to metric dimensions will be considered on an equal basis with those manufactured using inch-pound units, providing they fall within tolerances specified and all other requirements of this document are met. If a product is manufactured to metric dimensions and those dimensions exceed the tolerances specified in the inch-pound units, a request should be made to the contracting officer to determine if the product is acceptable.

3.6 Standard commercial product. The dippers shall, as a minimum, be in accordance with the requirements of this CID and shall be the manufacturer's standard commercial product. A standard commercial product is a product which has been sold or is currently offered for sale on the commercial market through advertisements, manufacturer's catalogs, or brochures, and represents the latest production model.

4. REGULATORY REQUIREMENTS

4.1 Recovered materials. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Product conformance. The products provided shall meet the salient characteristics of this commercial item description, conform to the producer's own drawings, specifications, standards, and quality assurance practices and be the same product offered for sale in the commercial market. The Government reserves the right to require proof of such conformance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.

5.2 NSF International compliance. The contractor shall submit to the contracting officer or authorized representative, prior to awarding of contract, satisfactory evidence that the items offered meet the requirements of NSF International Criteria C-2 or Standard No. 2. Satisfactory evidence of this compliance may be any of the following:

(1) Listing in the current edition of the "NSF International Listing Food Service Equipment and Related Products, Components and Materials", and display of the NSF International mark on the finished item; or

(2) Certification issued by NSF International under their special contract evaluation/certification program for government contracts; or

(3) Certified test report from a recognized independent testing laboratory acceptable to the medical authority of the service for which the item(s) are being procured stating that the item has been tested and conforms to NSF International Criteria C-2 or Standard No. 2.

6. PACKAGING

6.1 Preservation, packing, and marking. Preservation, packing, and marking shall be as specified in the contract or order.

7. NOTES

7.1 Sources of non-Government association documents.

NSF International standards are available from NSF International, P.O. Box 130140, Ann Arbor, MI 48113-0140.

7.2 Ordering data. Purchasers should select the preferred options permitted herein and include the following information in procurement documents (if applicable).

a. Title, number and date of this commercial item description.
b. Type and size required.
c. Preservation, packing, and marking desired.

7.3 Part Numbering. The following part identification numbering procedure is for government purposes and does not constitute a requirement for the contractor.

```
AA1752-11     Example - Type I, Size 1 dipper
   |   ||
   |   ||---- Size (0, 1, or 2)
   |   |---- Type (1 - I or 2 - II)
   |---- Commercial Item Description Number
```

7.4 National Stock Numbers (NSN's): The following is a list of NSN's assigned which correspond to this CID. The list may not be indicative of all possible NSN's associated with the CID.

NSN	Type	Size No.	Capacity (ounces)
7330-00-680-2757	I	1	32
7330-00-680-2756	I	2	64
7330-00-272-2488	II	0	16
7330-00-272-2489	II	1	32

Source: https://assist.dla.mil -- Downloaded: 2026l0-26T08:16Z
Check the source to verify that this is the currentversion before use.

MILITARY INTERESTS:

Military Coordinating Activity:

Army - GL

Custodians:
Army - GL
Navy - SA
Air Force - 99

Review Activities:
Army - MD1, QM1
Navy - MC
Air Force - 35, 84

Civil Agencies Coordinating Activities:
HHS - NIH

Preparing Activity:
GSA - FSS

(DoD Project 7330-0728)

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:16Z
Check the source to verify that this is the current version before use.