INCH-POUND

A-A-50362A
October 10, 1995
SUPERSEDING
A-A-50362
July 25, 1983

COMMERCIAL ITEM DESCRIPTION

OVERSHOES, MEN'S, RUBBER, 5 BUCKLE TYPE

The General Services Administration has authorized the use of this commercial item description as a replacement for MIL-O-836 for all Federal agencies.

1. SCOPE. This commercial item description covers one type of black, medium weight, rubber, 5 buckle overshoes, for land and shipboard use.

2. CLASSIFICATION. The overshoes are available in sizes 5 through 15 (inclusive).

3. SALIENT CHARACTERISTICS

3.1 Description. The overshoes shall be of medium weight construction, with semi-blucher throat opening, closed with 5 buckles.

3.2 Materials

3.2.1 Rubber compound. The rubber compound shall be natural and/or synthetic, colored black, meeting applicable requirements of 3.2.1.1 and 3.2.1.2.

Beneficial comments, recommendations, additions, deletions, clarifications, etc. and any data which may improve this document should be sent to: Defense Personnel Support Center, Clothing and Textiles Directorate, Attn: DPSC-FQSE, 2800 South 20th Street, Philadelphia, PA 19145-5099.

AMSC N/A

FSC 8430

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

3.2.1.1 Upper compound. The upper compound shall meet the following requirements:

Tensile strength		
Initial	1450 lb/in^2 (minimum)	ASTM D-412
After aging	75% of original (minimum)	ASTM D-412 1/
Ultimate enlongation	350% (minimum)	ASTM D-412

3.2.1.2 Outsole and heel. The outsole and heels shall be non-marking, and shall meet the following requirements:

Abrasive index		
Initial	45 (minimum)	ASTM D-1630
After aging	75% of original (minimum)	ASTM D-1630 1/
Hardness		
Initial	55 $\pm$ 5	ASTM D-2240
After aging	65 (maximum)	ASTM D-2240 1/

1/ The aging test shall consist of 16 hours at 212° ($\pm$ 2°F), using TM 7221 of FED-STD-601.

3.2.2 Lining fabrics. Lining fabric shall be of a commercial/industry construction and type.

3.2.3 Buckles. The buckles shall be a ladder and clasp type, commercial size, with either a black enamel finish or a black chemical finish.

3.3 Construction. The overshoes shall be constructed in accordance with approved patterns and molds utilizing commercial methods. All overlapped parts shall be substantially rolled or pressed before vulcanization.

3.3.1 Patterns and molds. The contractor's patterns and molds shall be approved by the contracting officer prior to production (see 7.3.c).

3.3.1.1 Height. The overshoes shall be 13 1/2 ($\pm$ 1/2) inches high for size 10. The contractor's grading is allowed for the remaining sizes.

3.3.1.2 Vulcanization. The overshoes shall be vulcanized under pressure. Blisters or air pockets are not allowed in the seams. All parts shall be cured into a single unit.

3.4 Labeling. In addition to any commercial markings, each overshoe shall have the size and contract number indicated. The overshoe shall have the size incised or branded on the outsole in the shank area near the heel. Alternatively, on the overshoe, the size may be pin stamped at the top edge of the back strip.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

The contract number shall be stamped or printed on the leg or pocket lining of the overshoe, approximately 1 inch below the top of the overshoe.

3.4.1 Label/tag. Each pair of overshoes shall be individually bar-coded with a paper tag. The tags shall have a hole and shall be attached to each item by a fastener, clearly legible and readable by a scanner.

3.5 Leakage requirement. After vulcanization, the overshoes shall show no leakage when tested as specified in 5.3.

3.6 Finish. The overshoes shall have a natural heater finish.

4. REGULATORY REQUIREMENTS. The offeror/contractor is encouraged to use recovered materials to the maximum extent practicable, in accordance with paragraph 23.403 of the Federal Acquisition Regulation (FAR).

5. QUALITY ASSURANCE PROVISIONS

5.1 Certification. The contractor shall certify and maintain substantiating evidence that the product offered meets the salient characteristics of this commercial item description and conforms to the producer's own drawings, specifications, standards, and quality assurance practices. The Government reserves the right to require proof of such conformance prior to the first delivery and thereafter as may be otherwise provided for under the provisions of the contract.

5.2 Visual examination. The overshoes shall be visually examined for the following defects:

Defect	Classification Major	Minor
MATERIAL DEFECTS AND DAMAGES		
a. Any ladder or clasp (buckle) omitted, misplaced, damaged or malformed interfering with proper functioning	X	
WORKMANSHIP		
b. Air pocket or channel in any seam	X	
c. Poor or uneven lasting affecting serviceability	X	
d. Poor or uneven lasting affecting appearance		X
DESIGN AND ASSEMBLY		
e. Not fabricated in accordance with the product demonstration model	X	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

(Contd.)

Defect	Classification Major	Minor
LABEL		
f. Contractual data markings omitted, incorrect, illegible or misplaced		X
g. Size marking omitted, incorrect, illegible or misplaced	X	
MATERIAL DEFECTS AND DAMAGES		
HEIGHT		
h. Height of overshoe less than specified		X
GENERAL		
i. Any defect not otherwise classified herein but at variance with the product demonstration model	X	

5.3 End item performance testing. The overshoes shall be tested as specified below for leakage in accordance with 3.4. The sample unit shall be one overshoe for each test method and the lot size shall be expressed in units of one overshoe. Requirements are applicable to the individual unit.

5.3.1 Leakage test

5.3.2 Overshoes filled with water. A dry specimen shall be filled with water to within 3 inches of the top of the overshoes and allowed to stand for 5 minutes. Evidence of leakage shall be indicated by the appearance of water on the exterior surface of the overshoe.

5.3.3 Acceptance criteria. Acceptance criteria shall be as specified in the contract or purchase order.

5.4 Market acceptance criteria. The item offered, or a generic equivalent, must have been sold to the commercial market or to the Government for at least two years.

5.4.1 Warranty. The item offered shall include the standard warranty given to the commercial market beginning with the date of delivery of the individual items.

6. PACKAGING

6.1 Preservation, packing, and marking. The preservation, packing, and marking shall be as specified in the contract or order.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.

7. NOTES

7.1 Source of Government documents. Copies of military and Federal documents are available from:

Standardization Documents Order Desk
Bldg. 4D
700 Robbins Avenue
Philadelphia, PA 19111-5094

7.2 Source of non-Government documents

ASTM Test Methods

(Applications for copies should be addressed to American Society For Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

7.3 Ordering data

a. Title and date of this document
b. Sizes required (see 2.)
c. Approval of patterns and molds (see 3.3.1)
e. When palletization is required (see 6.1)

MILITARY INTERESTS:

Custodians

Navy - NU
Army - GL
Air Force - 99

CIVIL AGENCY COORDINATING ACTIVITY:
GSA - FSS

Review Activity

Army - MD

PREPARING ACTIVITY:
DLA - CT

Project 8430-0429

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T08:41Z
Check the source to verify that this is the current version before use.