INCH-POUND
MIL-DTL-32671
10 November 2020

DETAIL SPECIFICATION

STOWAGE SYSTEMS, SMALL ARMS, SHIPBOARD

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers shipboard lockers, racks, and bins intended for use as stowage systems for small arms on U.S. Navy surface ships.

1.2 Classification. Stowage systems are of the following types, as specified (see 6.2):

a. Type IA – Locker, non-topside use (see 6.5.5.1)

b. Type IB – Locker, topside use (see 6.5.5.1)

c. Type II – Rack (see 6.5.5.2)

d. Type III – Bin (see 6.5.5.3)

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3 and 4 of this specification, whether or not they are listed.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

COMMERCIAL ITEM DESCRIPTIONS

A-A-59486 - Padlock Set (Individually Keyed or Keyed Alike)

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-DTL-901 - Shock Tests, H.I. (High-Impact) Shipboard Machinery, Equipment, and Systems, Requirements for

MIL-DTL-24653 - Hasp, High Security, Shrouded, for Shipboard Doors and Hatches Using High Security Padlock, General Specification for

MIL-R-45012 - Rifle, 7.62mm, M14
NOTE: MIL-R-45012 is inactive for new design and is only cited for informational purposes regarding the dimensions of the M14 Rifle . It will eventually be replaced.

Comments, suggestions, or questions on this document should be addressed to Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard, DC 20376-5160 or emailed to CommandStandards@navy.mil, with the subject line “Document Comment”. Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.dla.mil.

AMSC N/A FSC 2090

DISTRIBUTION STATEMENT A. Approved for public release. Distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-108 - Definitions of and Basic Requirements for Enclosures for Electric and Electronic Equipment

MIL-STD-167-1 - Mechanical Vibrations of Shipboard Equipment (Type I - Environmental and Type II - Internally Excited)

(Copies of these documents are available online at https://quicksearch.dla.mil.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

MARINE CORPS SYSTEMS COMMAND PUBLICATIONS

TM 8000-10/1 - Principal Technical Characteristics of U.S. Marine Corps Ordnance Equipment

(Copies of this document are available online via https://mceits.usmc.mil/sites/pubs/.)

NAVAL AIR SYSTEMS COMMAND (NAVAIR) PUBLICATIONS

11-95-GAU17-1 - Organizational Maintenance with Illustrated Parts Breakdown, GAU17/A 7.62mm Aircraft Machine Gun

11-95-13 - Organizational Maintenance with Illustrated Parts Breakdown, XM-218/GAU-16/A .50 Caliber Aircraft Machine Gun

11-95GAU21-1 - Organizational Maintenance with Illustrated Parts Breakdown, GAU-21 .50 Caliber Machine Gun System

(Copies of these documents are available online via https://mynatec.navair.navy.mil/.)

NAVAL SEA SYSTEMS COMMAND (NAVSEA) DRAWINGS

803-8436640 - Hasp, High-Security, Shipboard, Pictorial and Parts List

(Copies of this document are available from the applicable repositories listed in S0005-AE-PRO-010/EDM, which can be obtained online via Technical Data Management Information System (TDMIS) at https://mercury.tdmis.navy.mil/. Copies of this/these document/s may also be obtained from the Naval Ships Engineering Drawing Repository (NSEDR) online at https://199.208.213.105/webjedmics/index.jsp. To request an NSEDR account for drawing access, send an email to NNSY_JEDMICS_NSEDR_HELP_DESK@navy.mil.)

NAVAL SEA SYSTEMS COMMAND (NAVSEA) PUBLICATIONS

S9074-AQ-GIB-010/248 - Requirements for Welding and Brazing Procedure and Performance Qualification

T9070-AJ-DPC-120/3010 - Shock Design Criteria for Surface Ships

(Copies of these documents are available online via Technical Data Management Information System (TDMIS) at https://mercury.tdmis.navy.mil/ by searching for the document number without the suffix. Refer questions, inquiries, or problems to: DSN 296-0669, Commercial (805) 228-0669. These documents are available for ordering (hard copy) via the Naval Logistics Library (NLL) at https://nll.navsup.navy.mil. For questions regarding the NLL, contact the NLL Customer Service at nllhelpdesk@navy.mil, (866) 817-3130, or (215) 697-2626/DSN 442-2626.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Qualification. Shipboard small arms stowage systems (see 6.1) furnished under this specification shall be products that are authorized by the qualifying activity for listing on the applicable qualified products list before contract award (see 4.2 and 6.3).

3.2 General.

3.2.1 Stowage. Using appropriate inserts, compartments, or hardware, each stowage system shall be capable of stowing all small arms listed in table I (see 6.5.4).

TABLE I. Navy and Marine Corps small arms requirements.

Weapon	Weapon Type	Technical Documentation
Pistol, semi-automatic, 9mm, M9	Pistol	TM 8000-10/1
Pistol, close quarters battle pistol (CQBP), M45A1	Pistol	TM 8000-10/1
Rifle, 5.56mm, M16	Rifle	TM 8000-10/1
Carbine, 5.56mm, M4	Rifle	TM 8000-10/1
Rifle, 7.62mm, M14	Rifle	MIL-R-45012[1/]
Launcher, grenade, 40mm, M203[2/]	Grenade launcher	TM 8000-10/1
Launcher, grenade, multi-shot, 40mm, M32	Grenade launcher	TM 8000-10/1
Light machine gun, 5.56mm, M249	Machine gun	TM 8000-10/1
Machine gun, 7.62mm, M240	Machine gun	TM 8000-10/1
Infantry automatic rifle (IAR), M27	Machine gun	TM 8000-10/1
Shotgun, 12-gauge, Mossberg M500	Shotgun	TM 8000-10/1
Shotgun, 12-gauge, joint service combat shotgun (JSCS), M1014	Shotgun	TM 8000-10/1
Heavy machine gun, 40mm, Mk19	Machine gun	TM 8000-10/1
Heavy machine gun, caliber .50, Browning, M2A1	Machine gun	TM 8000-10/1
GAU-16 .50-caliber aircraft machine gun	Machine gun	11-95-13
GAU-17 7.62 aircraft machine gun	Machine gun	11-95GAU17-1
GAU-21 .50-caliber aircraft machine gun	Machine gun	11-95GAU21-1
Launcher, assault, rocket, 83mm (SMAW), Mk153	Rocket launcher	TM 8000-10/1

NOTES:

1/ Not for new design. Reference is for informational purposes only regarding the dimensions of the M14 Rifle

2/ Stowed attached to the M16 or M4.

3.2.2 Materials. All stowage systems shall be made of 14-gauge steel minimum. Stowage systems intended for topside use (see 6.5.5.1) shall be made of minimum 14-gauge 316 stainless steel. Small arms to stowage interface points (inserts, bin shelves, etc.) shall be coated in plastisol, rubber, or similar material to prevent metal to small arms contact.

3.2.3 Weight (lockers and bins only). Stowage systems shall not exceed 20 pounds per M4 rifle when configured for the maximum number of M4 rifles. Weight of the stowage system includes any inserts or components required to stow M4 rifles.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

3.2.4 Density (lockers and bins only). Stowage systems shall not exceed 1.5 ft^3 of volume per M4 rifle when configured for the maximum number of M4 rifles.

3.2.5 Hatchability. Each stowage system shall be hatchable (see 6.5.2) using either of the following two methods:

a. As a fully assembled functional stowage system.

b. As parts that can be assembled into a functional stowage system without the use of hot work (see 6.5.3).

3.2.6 Doors (lockers and bins only). Stowage enclosures shall use doors as the only means of opening and closing the stowage. Doors shall be equipped with hold-open devices to prevent unintended door movement while opened. Hinge pins shall be peened over. Hinges shall be located within the secured area of the stowage system, or the door shall be fitted with hinge security brackets behind each external door hinge (total two brackets or continuous strip with a continuous weld spanning all hinges) to prevent the door from opening if the hinge pins are removed. Door designs which do not utilize hinges shall be approved by NAVSEA (see 6.2).

3.2.7 Forced entry deterrence. For small arms stowage located in armories or troop berthing, doors shall be secured with a shipboard high-security hasp in accordance with 803-8436640 and S&G 951 Padlock (or equal) or TUFLOC 60 Series lock (or equal). Small arms stowage located outside of armories or troop berthing shall be secured with a shipboard high-security hasp in accordance with 803-8436640 and S&G 951 Padlock (or equal). When subjected to forced entry testing as specified in 4.5.1, stowage systems shall prevent complete removal of any small arm for at least 5 minutes.

3.2.8 Shock.

3.2.8.1 Grade A shock. Stowage systems for the M2A1 .50-caliber machine gun and M240 machine gun shall meet the requirements for grade A shock in accordance with MIL-DTL-901 in the loaded condition, assuming the heaviest small arms weight load out. This applies to the stowage system as a whole (i.e., heaviest configuration of weapons in the stowage system) and the individual weapons inserts or compartments (i.e., the heaviest weapon that can go into each insert or compartment). Grade A shock acceptance criteria are listed below:

a. The system shall remain attached to its mounts or foundations.

b. The system’s doors shall open and close.

c. The system’s locking mechanism shall lock and unlock.

d. The weapons shall be retained in their inserts.

e. The weapons shall be removable from their inserts as designed (i.e., tools shall not be required to remove the weapon after shock testing).

3.2.8.2 Grade B shock. Stowage systems for all other small arms listed in table I shall meet the requirements for grade B shock in accordance with MIL-DTL-901 in the loaded condition, assuming the heaviest small arms weight load out. Grade B shock acceptance criteria are listed below:

a. The stowage shall remain attached to its mounts or foundations.

b. The small arms shall be retained within the stowage system but are not required to stay within their insert or compartment. For rack stowage, this requirement is the same as grade A, since racks are not located in an enclosure.

c. The small arms shall not strike any grade A equipment.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

3.2.9 Vibration. Stowage systems shall meet the requirements of type I vibration in accordance with MIL-STD-167-1 in the loaded condition, assuming the heaviest small arms weight load out. This applies to the stowage system as a whole (i.e., heaviest configuration of weapons in the stowage system) and the individual weapons inserts or compartments (i.e., the heaviest weapon that can go into each insert or compartment). Type I vibration acceptance criteria are listed below:

a. The system shall remain attached to its mounts or foundations.

b. The system's doors shall open and close.

c. The system's locking mechanism shall lock and unlock.

d. The weapons shall be retained in their inserts.

e. The weapons shall be removable from their inserts as designed (i.e., tools shall not be required to remove the weapon after vibration testing).

f. There shall be no cracking or deformation of any structure, welds, or fasteners.

g. There shall be no loosening of any fasteners.

3.2.10 Mounting. Stowage systems shall be designed to be welded to ship structure, secured with rivets (a minimum of ¼ inch in diameter) or studs or bolts installed such that the threads and nuts are within the locked enclosure. Stowage systems intended for topside use shall be mounted with bolts and nuts welded to the bolt body.

3.2.11 Water intrusion. Stowage systems intended for topside use shall be spray-tight when tested in accordance with MIL-STD-108.

3.2.12 Human interface. Stowage systems shall not require an operator to reach any higher than 76 inches (when measured from the deck) for the purposes of immediate stowing/unstowing of any weapon including opening/closing, locking/unlocking, or latching/unlatching of any item. This requirement does not apply to the installation or setup of the stowage system, including reconfiguration of the stowage system to accommodate different weapon load outs.

3.2.13 Size. If applicable, the overall height, width, and depth of the stowage shall be as specified (see 6.2).

3.3 Lockers. Lockers shall stow the types and quantities of small arms as specified (see 6.2). Lockers shall meet the requirements of 3.2.1, except that pistol lockers may be designed for stowage of pistols only.

3.3.1 Stowage flexibility. Lockers shall stow all models of small arms with any accessories requiring calibration (e.g., optics and laser sights) attached/installed by using removable inserts or adjusted hardware as defined below:

a. Removable inserts shall be capable of removal and installation by hand or with non-powered tools.

b. Individual removable inserts may be designed to secure multiple types of small arms.

3.4 Bins. Bins shall stow the types and quantities of small arms as specified (see 6.2). Bins shall meet the requirements of 3.2.1, except that bins are not required to accommodate pistols or small arms exceeding 50 pounds, unless otherwise specified (see 6.2). Bins may be designed for stowage of pistols only.

3.4.1 Stowage flexibility. Bin stowage shall utilize reconfigurable shelving and partitions to produce compartments of varying sizes. Shelving and partitions shall be reconfigurable by hand or with non-powered tools.

3.5 Racks. Racks shall stow the types and quantities of small arms as specified (see 6.2).

3.5.1 Forced entry deterrence. The forced entry deterrence requirements of 3.2.7 are not applicable for racks within a high-security space located in another high security space (see 6.1).

3.5.2 Stowage flexibility. If required, rack stowage shall be capable of reconfiguration by hand or with non-powered tools (see 6.2).

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Conformance inspection (see 4.3).

4.2 Qualification inspection. Qualification inspection shall include the examination of 4.4 and the tests of 4.5.1 through 4.5.4, as shown in table II.

TABLE II. Requirements to testing traceability matrix.

Requirement Title	Requirement	Qualification	Conformance
Stowage	3.2.1	4.4.1	4.4.1
Materials	3.2.2	4.4.2.1, 4.4.2.2, 4.4.2.3	4.4.2.1, 4.4.2.2, 4.4.2.3
Weight	3.2.3	4.4.3	4.4.3
Density	3.2.4	4.4.4	-
Hatchability	3.2.5	4.4.5	4.4.5
Doors	3.2.6	4.4.6	4.4.6, 4.4.8
Forced entry deterrence	3.2.7	4.5.1	-
Shock	3.2.8	4.5.2	-
Vibration	3.2.9	4.5.3	-
Mounting	3.2.10	4.4.7	4.4.7
Water intrusion	3.2.11	4.5.4	4.5.4
Human Interface	3.2.12	4.4.13	4.4.13
Size	3.2.13	4.4.14	-
Lockers	3.3	-	4.4.8
Stowage flexibility (lockers)	3.3.1	4.4.9	4.4.9
Bins	3.4	-	4.4.10
Stowage flexibility (bins)	3.4.1	4.4.11	4.4.11
Stowage flexibility (racks)	3.5.2	4.4.12	4.4.12

4.3 Conformance inspection. Unless otherwise specified (see 6.2), conformance testing shall be completed on 1 of every 40 stowage systems procured. If the procurement is for fewer than 40 stowage systems, then conformance testing shall be completed on 1 stowage system. The inspection shall be performed on one sample and shall include the examinations of 4.4.1 through 4.4.3, 4.4.5 through 4.4.12, and the test of 4.5.4, as shown in table II.

4.4 Examination. Examinations shall be performed to verify the following:

4.4.1 Stowage. The stowage system shall demonstrate the capability to stow all models of approved small arms to validate adherence to requirement 3.2.1. Demonstration shall be conducted with small arms, demilitarized small arms, or mock-up small arms. When actual, demilitarized, or mock-up small arms are not available, computer models shall be utilized to demonstrate that all models of approved small arms can be stowed within the stowage system.

4.4.2 Materials.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

4.4.2.1 Steel. The stowage system shall be inspected to verify the locker, bin, or rack is made of solid 14-gauge steel. Mechanical calipers shall be used to verify the material gauge.

4.4.2.2 Steel verification. Stowage systems intended for topside use shall have their stainless steel material verified by testing the magnetic response with a magnet. 316 stainless steel shall not be magnetic.

4.4.2.3 Metal interface points. All interface points within the stowage system shall be visually inspected to verify there are no metal-on-metal interface points.

4.4.3 Weight. When applicable, the stowage system shall be weighed while empty to verify adherence to the weight requirement of 3.2.3.

4.4.4 Density. When applicable, the stowage system shall demonstrate maximum rifle stowage capacity to validate the density requirement of 3.2.4.

4.4.5 Hatchability. Measurements shall be taken to validate adherence to the hatchability requirement of 3.2.5. Stowage systems furnished as parts in accordance with 3.2.5.b shall be broken down into hatchable parts for the measurement during the inspection.

4.4.6 Doors. When applicable, the stowage system shall be visually inspected to validate adherence to the door requirement of 3.2.6. The stowage door hold-open devices shall be checked for functionality. When actuated, the hold-open devices shall hold the door in an open position. When de-actuated, the doors shall close as designed.

4.4.7 Mounting. When applicable, the stowage system shall be visually inspected to validate adherence to the mounting requirement of 3.2.10.

4.4.8 Lockers. Lockers shall be visually inspected to validate adherence to the requirements of 3.3.

4.4.9 Lockers stowage flexibility. Lockers shall demonstrate the ability to reconfigure the internal small arms inserts to validate adherence to the stowage flexibility requirement of 3.3.1. Different locker inserts shall be positioned in multiple positions within the locker to ensure the inserts are reconfigurable within the system.

4.4.10 Bins. Bins shall be visually inspected to validate adherence to the requirements of 3.4.

4.4.11 Bins stowage flexibility. Bins shall demonstrate the ability to reconfigure the shelving and partitions to varying sizes to validate adherence to the stowage flexibility requirement of 3.4.1.

4.4.12 Racks stowage flexibility. When applicable, racks shall demonstrate the ability to stow multiple types of weapons to validate adherence to stowage flexibility requirement of 3.5.2

4.4.13 Human interface. Stowage shall be measured to validate adherence to human interface requirement of 3.2.12.

4.4.14 Size. Stowage shall be measured to verify the dimensions are as specified (see 3.2.13).

4.5 Tests.

4.5.1 Forced entry deterrence. When applicable, a forced entry test shall be conducted to validate compliance with 3.2.7. Forced entry testing shall be conducted in accordance with an approved test procedure based on appendix A.

4.5.2 Shock. The stowage system shall be tested in accordance with the requirements of MIL-DTL-901 (or Dynamic Design Analysis Method [DDAM] in accordance with T9070-AJ-DPC-120/3010) to validate adherence to the shock requirement of 3.2.8. The use of DDAM instead of MIL-DTL-901 testing shall first be approved by NAVSEA.

4.5.3 Vibration. The stowage system shall be tested for type I vibration in accordance with MIL-STD-167-1 to validate adherence to the vibration requirement of 3.2.9.

4.5.4 Water intrusion. When applicable, the stowage system shall be tested in accordance with MIL-STD-108 to validate the requirement of 3.2.11.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the military service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. A small arms stowage system is a locker, bin, or rack for stowing small arms onboard a Navy ship. It provides protection from shipboard vibration, ship motion, and underwater high-impact shock imposed on the ship. When equipped with locks, the stowage system provides deterrence from forced entry.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. The type of stowage system to be procured (see 1.2).

c. Whether the stowage requests to use hinge-free doors, requiring NAVSEA approval (see 3.2.6).

d. Whether the stowage system is to fit within specific dimensions (see 3.2.13 and 6.5.1).

e. The types and quantities of small arms to be stowed in each type of stowage system (see 3.3, 3.4, and 3.5).

f. Whether bins are to accommodate pistols, mortars, or small arms exceeding 50 pounds (see 3.4).

g. Whether racks are to be reconfigurable (see 3.5.2).

h. Conformance inspection (see 4.3).

i. Packaging requirements (see 5.1).

6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Products List QPL No. 32671 whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Commander, Naval Sea Systems Command, ATTN: SEA 05S, 1333 Isaac Hull Avenue, SE, Stop 5160, Washington Navy Yard, DC 20376-5160 or emailed to CommandStandards@navy.mil. An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.dla.mil.

6.4 Weight and density requirements. Weight and density requirements are based off the number of standard rifles the locker or bin is capable of stowing. Since multiple rifle models are in service, this document uses the M4 rifle as the baseline for weight and density metrics.

6.5 Definitions.

6.5.1 Dimensions. All dimensions are from the point of view of a person facing the front of the stowage system with any doors in the closed position.

a. Height is measured from the lowest horizontal plane to the highest horizontal plane that the stowage system fits within.

b. Depth is measured from the frontmost vertical plane to the rearmost vertical plane that the stowage system fits within.

c. Width is measured from the leftmost vertical plane to the rightmost vertical plane that the stowage system fits within.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

6.5.2 Hatchable. Able to fit through a standard opening of 26 inches by 66 inches, reduced by 8-inch radius corners.

6.5.3 Hot work. Flame heating, welding, torch cutting, brazing, or carbon arc gouging, or any operation which produces temperatures of 400 °F (204 °C) or higher.

6.5.4 Small arms. Small arms are broadly categorized as those weapons intended for use by individual members of armed or security forces. They include handguns, rifles and carbines, sub-machine guns, and light machine guns. Light weapons are broadly categorized as those weapons designed for use by two or three members of armed or security forces serving as a crew, although some may be used by a single person. They include heavy machine guns, handheld under-barrel and mounted grenade launchers, portable anti-aircraft guns, portable anti-tank guns, recoilless rifles, man-portable launchers of missile and rocket systems, and mortars. A list of small arms requiring stowage afloat is listed in table I.

6.5.5 Stowage system types.

6.5.5.1 Type I - locker. A totally enclosed structure with a hinged door (or doors) on the front surface for accessing the small arms contained within. The locking system is applied to the structure and doors of the locker, but not directly to the small arms within. The small arms are individually contained within inserts inside the locker. The arrangement of inserts is to be reconfigurable within the locker and with other lockers in order to: allow customizing the arrangement of small arms within a locker, accommodate variations in the types and quantities of small arms assigned to the ship, accommodate new weapon designs or changes in existing weapon designs, and/or allow a standardized design of a family of lockers.

a. Type IA lockers are made of steel intended for use within the ship’s interior.

b. Type IB lockers are made of 316 stainless steel and are spray tight, intended for use topside.

6.5.5.2 Type II - bin. A totally enclosed structure with a hinged door (or doors) on the top surface for accessing the small arms contained within. The locking system is applied to the structure and doors of the bin, but not directly to the small arms within. The small arms are individually contained within compartments formed by shelves and partitions inside the bin. The shelves and partitions are reconfigurable within the bin and with other bins in order to: allow customizing the arrangement of small arms within a bin, accommodate variations in the types and quantities of small arms assigned to the ship, accommodate new weapon designs or changes in existing weapon designs, and/or allow a standardized design of a family of bins.

6.5.5.3 Type III - rack. A structure with an open face on the front surface for accessing the small arms contained within. The small arms are mounted in the racks using various types of hardware. The hardware may be reconfigurable within the rack and with other racks in order to: allow customizing the arrangement of small arms within a rack, accommodate variations in the types and quantities of small arms assigned to the ship, accommodate new weapon designs or changes in existing weapon designs, and/or allow a standardized design of a family of racks. Rack stowage should only be used within unmanned high security spaces meeting the requirements of OPNAVINST 5530.13 whose entrance(s) is located within a separate high security space also under control of the armorer.

6.6 Subject term (key word) listing.

Bin

Locker

Rack

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

SMALL ARMS STOWAGE FORCED ENTRY TEST CRITERIA

A.1 SCOPE

A.1.1 Scope. Forced entry testing for small arms stowage shall be developed in accordance with the requirements of this appendix. The purpose of forced entry testing is to ensure unauthorized access to stowed small arms is deterred for a period of 5 minutes with equipment commonly found on ships. Unique forced entry tests shall be developed for each stowage system to ensure any weak points of stowage are sufficiently tested. This appendix is a mandatory part of the standard. The information contained herein is intended for compliance.

A.2 FORCED ENTRY TEST PERSONNEL/RESPONSIBILITIES

A.2.1 Government test director. This person directs the test mechanic in performing the test with the goal of defeating and gaining access into the stowage for the purpose of removal of a small arms.

A.2.2 Test mechanic. This person shall conduct the forced entry test and shall be familiar with and capable of using all of the tools listed in A.3.2.

A.2.3 Timer. This person shall signal the start of the test and the time of actual forced entry, as directed by the test director.

A.2.4 Photographer/recorder. This person shall photograph the before and after results of the specific feature of the stowage undergoing the test and shall operate the video recording equipment.

A.2.5 Government witness/observer. This person shall witness the test in accordance with the guidelines set forth by the test procedure. NAVSEA shall be contacted to arrange witnessing of the testing.

A.2.6 Safety witness/observer. This person shall ensure that all personnel involved with conducting the test have all proper personal protective equipment (PPE) and that the test is conducted in accordance with all applicable Navy and local safety standards.

A.3 FORCED ENTRY TEST-EQUIPMENT

A.3.1 Tools. The test mechanic shall have all tools listed in A.3.2 available for use during the testing. Tools which are battery operated shall have sufficient charge or spare batteries to last the duration of the testing. Loss of power from insufficient battery charge shall render the individual test void. Tools which use consumable components (e.g., grinding discs) shall be provided with sufficient consumables to last the duration of the test. Expenditure of all consumables during the test shall render the individual test void.

A.3.2 List of tools (for test mechanic).

a. Angle grinder, cordless battery powered, 20 volt minimum
b. Reciprocating saw, cordless battery powered, 20 volt minimum
c. Cut-off wheels
d. Grinding discs
e. Reciprocating saw blades, heavy duty metal cutting
f. Hammer, 3-pound
g. Pry bar, 18-inch construction
h. Pry bar, 18-inch wrecking bar
i. Pliers, adjustable 10-inch standard flat-jaw
j. Chisel set
k. Punch set

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

l. 1½-inch extra small pipe, steel, 18-inch length

m. Knife, pocket

n. Torch, propane or methylacetylene-propadiene propane, single tank

A.3.3 List of equipment (for test personnel).

a. Timer/stopwatch

b. Marker

c. Digital camera

d. Digital video recorder

e. PPE, including hard-hat, safety shoes, eye protection, hearing protection, safety gloves, and proper clothing

A.3.4 Test small arms.

a. Mock rifle

b. Mock pistol (as applicable)

A.4 ACCEPTANCE CRITERIA

A.4.1 Mock small arms. No mock small arms are removed during each individual test within 5 minutes.

A.4.2 Powered tools. Battery charge or power source to powered tools are maintained throughout each individual test. Batteries may be recharged in between individual test events.

A.4.3 Consumables. Source of consumables (e.g., grinding wheels or discs) are not completely expended during an individual test event. Additional consumables may be procured between individual test events.

A.4.4 Damaged tools. Any damaged tools are replaced prior to the next test event. If a tool is damaged during the individual event (e.g., crowbar breaks while trying to pry open door), this does not void the test.

A.4.5 Tools. All tools listed in A.3.2 are available to the test mechanic.

A.4.6 Personnel. All personnel listed in section A.2 are present.

A.5 TEST PROCEDURE AND TEST EVENT REQUIREMENTS

A.5.1 Identifying weak points. Prior to the test, weak points shall be identified in the stowage. Once identified, individual tests shall be developed for each weak point with general guidance regarding the attack method (e.g., grind off hinge or attempt to pry open door). This procedure shall be approved by NAVSEA prior to the start of testing.

A.5.2 Visually marking weak points. Prior to the test, the identified weak points of the stowage shall be visually marked with a marker. A work zone shall be inscribed around the weak point with marker to define the boundaries of the individual forced entry attempt.

A.5.3 Sequencing. The test procedure shall sequence the test events such that damage from a previous test event does not impact a subsequent test event. In the case where impact to a later test event is unavoidable, one of the following solutions shall be implemented:

a. Combine test events into a single event

b. Require multiple test stowage samples

A.5.4 Defects. Prior to the test, the stowage system shall be inspected for any defects or change in design. It shall be confirmed that the locking mechanism and doors function as designed. Mock test small arms shall be placed within the stowage at the most vulnerable points (e.g., nearest to the forced entry attempt).

A.5.5 Securing stowage. The stowage shall be secured to the ground or floor, similar to the shipboard installation configuration such that the stowage does not move freely, to ensure the safety of test personnel and that test results are valid.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

A.5.6 Test mechanic. Prior to each test event, the test personnel shall review the test procedures.

A.5.7 Test mechanic test procedures. During the test event, the test mechanic shall attempt to follow the test procedure as written. The test mechanic may improvise and utilize any of the tools listed in A.3.2 during the test, providing the mechanic stays within the work zone as outlined in A.5.2, and the improvisation follows all safety rules. The test mechanic may request to move outside the work zone if the mechanic believes there is an easier way to gain entry to the small arms inside the stowage. Upon request, the timer shall be stopped and the personnel shall discuss the change in forced entry testing. If approved, the time shall resume from the previous stoppage point, and the test mechanic may resume the forced entry attempt.

A.5.8 Individual forced entry attempts. All individual forced entry attempts shall cease at the 5-minute mark or when a small arm is retrieved from the stowage. Forced entry attempts may be allowed to proceed past the 5-minute mark until a small arm is retrieved if requested by the government test representative.

A.5.9 Results. Results of the test shall be documented. The entry points shall be photographed and the test shall be video recorded.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.

CONCLUDING MATERIAL

Custodians:
Army – AV
Navy – SH
Air Force – 03
DLA – IS

Review activities:
Army – GL, MI
Navy – CG, OS
Air Force – 11, 69
DLA – DH
NGA – MP

Civil Agency:
USDA – FGI

Preparing activity:
Navy – SH
(Project 2090-2020-001)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-21T07:32Z
Check the source to verify that this is the current version before use.