O-B-420B
Int. Amendment-3
October 10, 1975
SUPERSEDING
Int. Amendment-2 (GSA-FSS)
July 16, 1975

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

BLEACH, LAUNDRY, ORGANIC CHLORIDE

This interim amendment was developed by the General Services Administration, Federal Supply Service, Washington, DC 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this interim amendment as a valid exception to Federal Specification O-B-420B, dated July 22, 1970, as amended. This interim amendment supersedes Interim Amendment-2 (ARMY-GL), dated May 2, 1975, and Interim Amendment-2 (GSA-FSS), dated July 16, 1975.

PAGE 1

Paragraph 2.1, under "Federal Specifications:",

P-D-245 - Delete title and substitute "Detergent (Powder, Flake, Bead, or Granular) for Laundry and Dishwashing."
PPP-B-636 - Delete title and substitute "Boxes, Shipping, Fiberboard."
PPP-T-60 - Delete title and substitute "Tape, Packaging, Waterproof."

Paragraph 2.1, under "Federal Standards:",

Fed. Std. No. 123 - Delete title and substitute "Marking for Shipment (Civil Agencies)."

PAGE 2

Paragraph 2.1, after the list of Military Standards: Delete "U.S. Department of Health, Education, and Welfare Publication:" and substitute "Laws and Regulations:"

Paragraph 2.1, under "Laws and Regulations:" Delete "21CFR 191" and substitute "16 CFR 1500".

PAGE 3

Paragraph 2.2, lines 1 to 11: Delete and substitute:

National Motor Freight Traffic Association, Inc., Agent:

National Motor Freight Classification.

(Application for copies should be addressed to the American Trucking Associations, Inc., Tariff Order Section, 1616 P Street, N.W., Washington, DC 20036.)

Uniform Classification Committee, Agent:

Uniform Freight Classification.

(Application for copies should be addressed to the Uniform Classification Committee, Room 1106, 222 South Riverside Plaza, Chicago, IL 60606.)

Source: https://assist.dla.mil -- Downloaded: 2026-02-26 10:16
Check the source to verify that this is the current version before use.

Table I, line 2: After "Phosphates, as P_2O_5, percent 1/" and in the column for "Maximum" requirements, add "20.0".

Table I, line 7: After "Moisture content, percent", add the notation "3/" to reference the footnote.

PAGE 4

Table I, after footnote 1/: Add the following: "20.0 percent P_2O_5 is equivalent to 8.7 percent phosphorus."

Table I, below footnote 2/: Add the following footnote: "3/ When the source of available chlorine is a hydrated salt of dichloroisocyanuric acid, the maximum moisture content shall be 6.2 percent."

PAGE 5

Paragraph 4.3.1.1, line 7: Delete the defect applicable to "Closure" and substitute "Incomplete, imperfect, leakage or damage to the polyethylene or polyvinylidene liner as applicable.

Paragraph 4.3.1.1, line 9: Delete the third defect applicable to "Liner" and substitute "Not completely heat sealed at seams, mouth not double folded and taped, not tightly knotted, or not twisted, folded and closed with plastic coated wire as applicable."

PAGE 6

Paragraphs 4.3.2 and 4.3.2.1. Delete entirely and substitute:

"4.3.2 Examination of preparation for delivery requirements. An examination shall be made to determine that the packaging, packing, and marking complies with the section 5 requirements. Defects shall be scored in accordance with the list below. The sample unit shall be one shipping container fully prepared for delivery with the exception that it need not be closed. Defects of closure listed below shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot.

Examine	Defect
Marking (exterior)	Omitted, incorrect; illegible; of improper size, location, sequence or method of application.
Materials	Any component missing, damaged or not as specified.
Workmanship	Inadequate application of components, such as: Drum or plastic film not as specified. Bulged or distorted container.
Content	Quantity not as specified."

Paragraph 4.3.3, under "Examination paragraph", delete "4.3.2.1" and substitute "4.3.2".

PAGE 8

Table II, lines 11 to 14: After "Insoluble matter content, percent", in the column for "Requirements applicable to Individual unit", delete "X"; in the column for "Requirements applicable to Composite sample", add "X".

PAGE 13

Paragraph 4.4.10.2.b, line 4 under "Reagents": Delete "type I" and substitute "type III".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:13Z
Check the source to verify that this is the current version before use.

PAGES 14 thru 17

Section 5. Delete and substitute:

"5. PREPARATION FOR DELIVERY

5.1 Packing. Packing shall be level A, B or C as specified (see 6.2).

5.1.1 Level A. Twenty-five, fifty and 125-pound quantities of bleach shall be packed in a snug-fitting fiber drum conforming to type III, grade A, class 2 of PPP-D-723. Each fiber drum shall be fitted with a 0.004-inch minimum thickness polyethylene bag conforming to type I or II, grade A of PPP-B-26 or 0.002-inch minimum thickness polyvinylidene chloride bag. The plastic film bag may be closed by heat sealing; double-folding the plastic material at the mouth and taping it to the bag body with 1-inch minimum width pressure-sensitive tape conforming to PPP-T-60 or PPP-T-76; by tightly knotting the plastic material at the mouth; or tightly twisting the mouth opening, then folding over half of the twisted portion and applying a plastic coated wire tie around the center of the fold. Prior to or during the final closure operation, excess air within the plastic bag shall be expelled. Regardless of the closure method used, the plastic bag shall be of sufficient length to allow for a knotting closure. Each fiber drum shall be closed in accordance with the applicable requirements of PPP-D-723.

5.1.2 Level B. Twenty-five, fifty and 125-pound quantities of bleach shall be packed in a snug-fitting fiber drum conforming to type I, grade A, class 2 of PPP-D-723. Each fiber drum shall be fitted with a plastic bag and the bag closed as specified in 5.1.1. Each fiber drum shall be closed in accordance with the applicable requirements of PPP-D-723.

5.1.3 Level C (Commercial Packing). Bleach shall be packed in a manner to insure carrier acceptance and safe delivery at destination at the lowest transportation rate for such supplies. The quantity per shipping container shall be the same as that normally used by the supplier for retail distribution. Containers shall comply with Uniform Freight Classification Rules or National Motor Freight Classification Rules, as applicable.

5.2 Marking.

5.2.1 Civil agencies. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with Fed. Std. No. 123.

5.2.2 Military requirements. In addition to any special marking required by the contract or order, shipping containers shall be marked in accordance with MIL-STD-129.

5.2.3 Labeling. Unless otherwise specified in the contract or order, each shipping container shall be labeled in accordance with the Federal Hazardous Substances Act.

5.2.4 Special marking. Each shipping container shall be legibly printed, stencilled or stamped in black ink with capital letters with the following special marking:

"STORE IN A COOL, DRY PLACE".

Paragraph 6.2, subparagraphs (b) through (f). Delete and substitute:

"(b) Selection of the applicable level of packing (see 5.1)".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:13Z
Check the source to verify that this is the current version before use.