P-W-155a
INTERIM AMENDMENT-4
August 17, 1967

INTERIM AMENDMENT

TO

FEDERAL SPECIFICATION

WAX, FLOOR, WATER-EMULSION, SLIP-RESISTANT

This interim amendment was developed by the General Services Administration, Federal Supply Service, Washington, D. C. 20406, based upon currently available technical information. It is recommended that Federal agencies use it in procurement and forward recommendations for changes to the preparing activity at the address shown above.

The General Services Administration has authorized the use of this amendment as a valid exception to Federal Specification P-W-155a, August 11, 1960.

PAGE 1

Paragraph 2.1, under Federal Specifications: Delete "PPP-D-760 - Drums and Pails, Metal (5 and 16.64 Gallon)".

Paragraph 2.1, under Federal Specifications: Add: PPP-B-636 - Box, Fiberboard, PPP-P-704 - Pails: Shipping, Steel (1 Through 12 Gallon).

PAGE 2

Paragraph 2.2. Delete "Uniform Freight Classification Rules" and "(Copies may be obtained from the Uniform Freight Classification Committee, 1 Park Avenue, New York 16, N.Y.)".

PAGE 3

Following paragraph 4.2, add paragraph 4.2.1.

4.2.1 Inspection of preparation for delivery requirements. An inspection shall be made to determine that packaging, packing, and marking requirements of section 5 of this specification are complied with. Defects shall be scored in accordance with the table below. For examination of interior packaging, the sample unit shall be one shipping container fully prepared for delivery selected at random just prior to the closing operations. Sampling shall be in accordance with MIL-STD-105. Defects of closure listed shall be examined on shipping containers fully prepared for delivery. The lot size shall be the number of shipping containers in the end item inspection lot. The inspection level shall be II and the AQL shall be 6.0 defects per hundred units.

FSC 7930

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

Classification of preparation for delivery defects

Examine	Defect
Markings (exterior and interior)	Omitted; incorrect; illegible; or improper size, location, sequence, or method of application.
Materials	Any component missing or damaged.
Workmanship	Inadequate application of components such as incomplete closure of container flaps, loose strapping, inadequate sealing. Bulging or distortion of container.

PAGE 7

Section 5. Delete this section in its entirety and subsistute the following:

5. PREPARATION FOR DELIVERY

5.1 Packaging. Packaging shall be level A, B, or C, as specified (see 6.5)

5.1.1 Level A. The wax shall be furnished in 1-gallon, or 5-gallon, or 55-gallon quantities as specified (see 6.5). The 1-gallon quantity shall be packaged in an oblong metal container conforming to PPP-C-96, type V, class 4 with exterior coating plan B; or in a round, high density polyethylene bottle (.95 density minimum) with handle and screw type closure. The 5-gallon quantity shall be packaged in a pail conforming to PPP-P-704, type I, class 3,4, or 5 or type II, class 3 or 4 with pouring device. The 55-gallon quantity shall be packaged in a drum conforming to PPP-D-729, type II or IV. Fog spraying of interior surfaces shall not be required. Alternately a 55-gallon drum conforming to PPP-D-732, class 1 or 2 or PPP-D-001152 may be used.

5.1.2 Level B. The wax shall be furnished in 1-gallon, 5-gallon, or 55-gallon quantities as specified (see 6.5). The 1-gallon quantity shall be packaged in an oblong metal container conforming to PPP-C-96, Type V, class 4 with exterior coating plan A or in a round, high density polyethylene bottle (.95 density minimum) with handle and screw type closure. The 5-gallon quantity shall be packaged in a pail conforming to PPP-P-704, type I, class 3, 4, or 5 or type II, class 3 or 4 with pouring device, except that a commercial exterior enamel coating will be acceptable, with color optional. The 55-gallon quantity shall be packaged in a drum conforming to PPP-D-729, type II or IV, except that a commercial exterior enamel coating will be acceptable with color optional, and fog spraying of interior surfaces shall not be required.

5.1.3 Level C. The wax shall be packaged in accordance with the suppliers commercial practice.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.5).

5.2.1 Level A.

5.2.1.1 One-gallon metal containers. Six 1-gallon metal containers shall be packed together in a close-fitting box conforming to PPP-B-636, V3c. The box shall be closed and strapped in accordance with the appendix to the box specification.

5.2.1.2 One-gallon plastic bottles. Four 1-gallon plastic bottles shall be packed together in a box conforming to PPP-B-636, W5c. The bottles shall be nested in four separate non-slotted individual fiberboard separators. The fiberboard forming the separators shall be made of the same material used in the construction of the container. Each separator shall be one continuous piece, center folded, forming two faces of the separator. Separators shall be the full height of the containers. The box shall be close-fitting, except that there shall be not less than 3/8-inch clearance between the top of the plastic bottle and the inside surfaces of the inner-flaps. The box shall be closed and strapped in accordance with the appendix to the box specification.

5.2.1.3 Five-gallon pail or 55-gallon drums. Five-gallon pails or 55-gallon drums shall not require any packing for shipment or storage.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.

5.2.2 Level B.

5.2.2.1 One-gallon metal containers. Six 1-gallon metal containers shall be packed together in a close-fitting box conforming to PPP-B-636, class-domestic. The box shall be closed in accordance with the appendix to the box specification.

5.2.2.2 One-gallon plastic bottles. Six one-gallon plastic bottles shall be packed in a box conforming to grade W5c of PPP-B-636. The bottles shall be separated by an "angle H divider" made of the same material used in constructing the container. The divider shall be the full height of the inside of the container. The box shall be close fitting, except that there shall not be less than 3/8 inch clearance between the top of the plastic bottle and the inside surface of the inner flaps. The box shall be closed and strapped in accordance with the appendix to the box specification.

5.2.2.3 Five-gallon pail or 55-gallon drums. Five-gallon pails or 55-gallon drums shall not require any packing for shipment or storage.

5.2.3 Level C. The wax shall be packed to insure carrier acceptance and safe delivery to destination in containers complying with the rules and regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Freezing precaution. The label of the issue packages and shipping containers shall bear a plain and conspicuous legend:

KEEP FROM FREEZING

so as to insure the shipment and handling of the product in an unfrozen state.

5.3.2 Civil agencies. In addition to markings required by the contract or order, the packages and shipping containers shall be marked in accordance with Fed. Std. No. 123. Each unit package shall be marked with the Federal stock number, nomenclature and quantity.

5.3.3 Military activities. In addition to markings required by the contract or order, the packages and shipping comtainers shall be marked in accordance with MIL-STD-129.

PAGE 9

Paragraph 6.5. Add the following sub-paragraph:

(d) Quantity of wax required (see 5.1).

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:16Z
Check the source to verify that this is the current version before use.