S-F-695G
AMENDMENT-1
December 15, 1983

FEDERAL SPECIFICATION

FRYERS, DEEP-FAT (ELECTRIC)

This amendment, which forms a part of Federal Specification S-F-695G, dated June 25, 1981 is approved by the Assistant Administrator, Office of Federal Supply and Services, General Services Administration, for the use of all Federal agencies.

PAGE 3

2.1, under "Federal Specifications": Delete "QQ-S-698 - Steel Sheet and Strip, Low Carbon".

PAGE 4

2.2, under "American Society for Testing and Materials (ASTM)": Add "A 366 Steel, Carbon, Cold Rolled Sheet, Commercial Quality".

PAGE 5

3.4.1, line 2: Delete "QQ-S-698" and substitute "ASTM - A 366".

PAGE 10

3.6.8: Delete, and substitute:

"3.6.8 Thermostat. An adjustable thermostat shall be provided with a range from 200° to 275°F and a maximum range from 375° to 400°F. The thermostat shall have a positive "OFF" position and be marked at 50 degree intervals. A separate "ON-OFF" switch may be provided in addition to, or in lieu of, the positive "OFF" position to control power to the thermostat. Thermostat and switch shall be located so as to be readily accessible to the operator. The thermostat shall maintain an average temperature of 375 ± 5°F when tested as specified in 4.4.2.1. The temperature amplitude of the thermostat shall not exceed 25°F when tested as specified in 4.4.2.2. Instructions for calibrating the thermostat shall be provided with each fryer (see 3.8.2). The thermostat shall be equipped with an overload switch that will limit the maximum temperature to 425°F. The overload switch shall cut off the entire electrical system. The restart button shall be in an accessible location."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

PAGE 10 (cont'd)

3.6.8.1, line 6, following "4.4.3": Insert "A means shall be provided to facilitate checking the operation of the overtemperature thermostat by rendering the first thermostat inoperative. A signal light shall indicate when the overtemperature thermostat is operated when tested as specified in 4.4.3."

Line 7: Delete "thereof" and substitute "of the manual reset type overtemperature circuit."

PAGE 11

3.6.8.1.1: Delete.

PAGE 12

3.6.9.3 first sentence, following "above,": Delete "and shall be capable of recovery to 375°F prior to completion of frying cycle".

PAGE 17

Table IV, under "Examine" and following "Signal light or lights": Delete listed defect and substitute "Not provided (power "ON" and "overtemperature thermostat" lights)".

PAGE 18

4.2.2.3, line 2, after "and": Add "when required for shipboard use."

PAGE 19

4.4.3, 2nd and 3rd sentences: Delete and substitute "The first thermostat shall be rendered inoperative in accordance with the manufacturer's operating instructions. The hydrogenated vegetable oil temperature shall be increased until the overtemperature thermostat specified in 3.6.8.1 opens the heating element circuit."

PAGE 20

4.4.3 (cont'd), line 4, after "times": Add a period and delete the remainder of the sentence.

Line 5: Delete "sall" and substitute "shall".

4.4.4.2 (a) last sentence: Delete.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.

MILITARY INTERESTS:

Custodians:

Army - GL
Navy - YD
Air Force - 99

Review Activities

Army - MD, TX
Navy - SA, MC
Air Force - 84
DLA - GS

User Activity

Army - CE

CIVIL AGENCY COORDINATING ACTIVITIES:

GSA - FSS
VA - DMS

PREPARING ACTIVITY:

Army - GL

Project No. 7310-0674

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:19Z
Check the source to verify that this is the current version before use.