WW-P-471a
AMENDMENT—2
March 26, 1964

SUPERSEDING
Amendment—1
June 28, 1963

FEDERAL SPECIFICATION

PIPE-FITTINGS: BUSHINGS, LOCKNUTS, AND PLUGS; BRASS OR BRONZE, IRON OR STEEL, AND ALUMINUM; (SCREWED); 125-150 POUNDS

This amendment, which forms a part of Federal Specification WW-P-471a, dated September 27, 1960, was approved by the Commissioner, Federal Supply Service, General Services Administration for the use of all Federal agencies

Page 1, paragraph 1.2.1: Under type II delete and substitute the following:

Style A—Uncoated.
Style C—Zinc Coated.
Style D—Cadmium Plated.

Page 1, paragraph 1.2.1: Delete Class 1 and Class 2 entirely.

Page 1, paragraph 2.1: Delete "QQ-A-268" and substitute "QQ-A-225/6 Aluminum Alloy Bar, Rod, and Wire, Rolled, Drawn or Cold Finished, 2024".

Page 2, paragraph 2.1: Delete Military Specification MIL-P-3 in its entirety and substitute "MIL-V-3—Valves, Fittings, and Flanges (Except for Systems Indicated Herein); Packaging of".

Page 2, paragraph 2.1: Delete Military Specification MIL-C-13924 in its entirety.

Page 2, paragraph 2.1: Change title of MIL-STD-129 to read: "Marking for Shipment and Storage".

Page 2, paragraph 2.2, American Standards Association Inc.:

Delete sentence starting with the words "Copies may be obtained from the American Standards. . . . .", and substitute "Application for copies should be addressed to the American Standards Association, Inc., 10 East 40th Street, New York 16, N. Y.".

Page 2, paragraph 2.2:

Delete sentence starting with the words "Copies may be obtained from the American Trucking Association Inc. . . . . .", and substitute "Application for copies should be addressed to the American Trucking Associations, Inc., 1616 P Street, N.W., Washington, D. C. 20005".

Page 2, paragraph 2.2:

Add the following:

"Society of Automotive Engineers Standard—1962"

(Application for copies should be addressed to the Society of Automotive Engineers, Inc., 485 Lexington Avenue, New York 17, N. Y.)

Page 3, after paragraph 3.3, add the following new paragraph:

3.3.1 *Plug dimensions.* Dimensions for 1 inch and smaller sized plugs shall be in accordance with table 4a of SAEJ531 of the Society of Automotive Engineers Standard. Plugs sized 1-1/4 inch and larger shall have the dimensions specified in ASA Standard B16.14.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:23Z
Check the source to verify that this is the current version before use.

Page 3, paragraph 3.4.2, delete in its entirety.

Page 4, paragraph 4.1, delete and substitute the following:

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified (see 6.2), the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure that supplies and services conform to prescribed requirements.

Page 6, paragraph 5.2.1, line 3: Delete MIL-P-3 and substitute "MIL-V-3".

Page 6, paragraph 5.3.1, line 3: Delete MIL-P-3 and substitute "MIL-V-3".

Page 6, paragraph 5.3.2, line 3: Delete MIL-P-3 and substitute "MIL-V-3".

Page 7, paragraph 6.2(b) delete "class".

Page 7, section 6, add the following new paragraph:

6.6 Transportation description: Transportation descriptions and minimum weights applicable to this commodity are:

Rail: Type II—Bushings

Bushings, not otherwise indexed by name, iron or steel.
Carload minimum weight 36,000 pounds.

Motor:

Bushings, not otherwise indexed, iron or steel.
Truckload minimum weight 36,000 pounds, subject to Rule 115, National Motor Freight Classification.

Rail: *Type I and III*

Bushings, not otherwise indexed by name, metal, other than iron or steel.
Carload minimum weight 36,000 pounds.

Motor:

Bushings, not otherwise indexed, metal.
Truckload minimum weight 30,000 pounds, subject to Rule 115, National Motor Freight Classification.

Rail: *Type I—Locknuts*

Bolts and nuts, not otherwise indexed by name, brass or bronze.
Carload minimum weight 30,000 pounds.

Motor:

Bolts and nuts, not otherwise indexed, brass or bronze.
Truckload minimum weight 30,000 pounds, subject to Rule 115, National Motor Freight Classification.

Rail: *Type II*

Bolts or nuts, not otherwise indexed by name, iron or steel.
Carload minimum weight 40,000 pounds.

Motor:

Bolts or nuts, not otherwise indexed, iron or steel
Truckload minimum weight 40,000 pounds, subject to Rule 115, National Motor Freight Classification.

Rail: *Type III*

Nuts, aluminum.
Carload minimum weight 30,000 pounds.

Motor:

Nuts, aluminum.
Truckload minimum weight 30,000 pounds, subject to Rule 115, National Motor Freight Classification.

Rail: *Type I—Plugs*

Pipe fittings, brass or bronze, not oth-

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:23Z
Check the source to verify that this is the current version before use.

erwise indexed by name.
Carload minimum weight 30,000 pounds.

Motor:

Pipe fittings, not otherwise indexed, brass or bronze.
Truckload minimum weight 30,000 pounds, subject to Rule 115, National Motor Freight Classification.

Rail: *Type II*

Plugs, not otherwise indexed by name, iron or steel.
Carload minimum weight 36,000 pounds.

Motor:

Plugs, not otherwise indexed, iron steel.
Truckload minimum weight 36,000 pounds, subject to Rule 115, National Motor Freight Classification.

Rail: *Type III*

Aluminum articles, not otherwise indexed by name.
Carload minimum weights 14,000 and 24,000 pounds, subject to Rule 34, Uniform Freight Classification.

Motor:

Aluminum articles, not otherwise indexed.
Truckload minimum weight 14,000 pounds, subject to Rule 115, National Motor Freight Classification."

MILITARY CUSTODIANS:

Army—MO

Navy—Docks

Air Force—MOA

Preparing activity:

Navy—Docks

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T12:23Z
Check the source to verify that this is the current version before use.