INCH-POUND

MIL-DTL-3943/403
17 July 2017

DETAIL SPECIFICATION SHEET

DECORATION, DISTINGUISHED CIVILIAN SERVICE, NATIONAL SECURITY AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE



MINI REVERSE

Dash Number
-1: Regular Size
-2: Miniature Size

MATERIAL: (-1 and -2) Red Brass 85/15 (UNS Alloy No.C-230)

AMSC N/A

FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:26Z
Check the source to verify that this is the current version before use.

FINISH: (-1 and -2): 24K, Gold Plated, Matte Finish, Polished Highlights and shall match the Institute of Heraldry Metal Finish Chip Number 8.

DIMENSIONS:
HEIGHT:
-1: 1-7/8 inches (REF)
-2: 15/16 inch (REF)
WIDTH:
-1: 1-1/2 inches (REF)
-2: 3/4 inch (REF)
THICKNESS:
-1: 0.193 inch $\pm$ 0.010 inch
-2: 0.133 inch $\pm$ 0.010 inch

DECORATION SET: The decoration set packaged in a presentation case and shall consist of a regular size medal, a miniature size medal, a lapel button, and a service ribbon, and shall be arranged in accordance with MIL-C-14633 in a Type XV, Style 1 case with a Class 2 pad. The following text shall be inscribed on the top of the presentation case using 3 lines: (Line 1) NATIONAL SECURITY (Line 2) AGENCY (Line 3) DISTINGUISHED CIVILIAN (4) SERVICE MEDAL. Lettering shall be accomplished using Bodoni MT Bold type face, 24 point caps for the first letter in each word and 20 point caps for all other letters.

EPOXY: Epoxy resin shall be applied to the lapel button as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below. If hard cloisonné enamel is used, the base material must be Gilding Metal 95/5 (UNS Alloy No. C-210).

TIOH HARD ENAMEL COLOR CHIP NUMBER	LOCATION
Blue #33	Top (Chief) of the Shield
White #28	The First Stripe and Every Other Alternating Stripe
Red #1	The Second Stripe and Every Other Alternating Stripe

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon is MIL-DTL-11589/697

3. The specification slash sheet for the lapel button is MIL-DTL-11484/405.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2017-254)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:26Z
Check the source to verify that this is the current version before use.