NOT MEASUREMENT SENSITIVE

MIL-DTL-3943/407B(IH)
01 May 2024
SUPERSEDING
MIL-DTl-3943/407A(IH)
1 July 2019

DETAIL SPECIFICATION SHEET

MEDAL, CIVILIAN VALOR, NATIONAL SECURITY AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIAL: (-1 and -2) Red Brass 85/15 (UNS Alloy No.C-230)

FINISH (-1 and -2):
OBVERSE: 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.
REVERSE: 24K Gold Plated, Matte Finish and shall match TIOH Metal Finish Chip Number 7.

DIMENSIONS:
HEIGHT (Including suspension lug):
-1: 1-5/8 inches (REF)
-2: 7/8 inch (REF)

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:27Z
Check the source to verify that this is the current version before use.

WIDTH:
-1: 1-5/8 inches (REF)
-2: 13/16 inch (REF)
THICKNESS (At thickest Point):
-1: 0.217 inch ± 0.010 inch
-2: 0.138 inch ± 0.010 inch

DECORATION SET: The decoration set packaged in a presentation case and shall consist of a regular size medal, a miniature size medal, a lapel button, and a service ribbon, and shall be arranged in accordance with MIL-DTL-14633 in a Type IV, with 1A pad The following text shall be inscribed on the top of the presentation case using 2 lines: (Line 1) NATIONAL SECURITY AGENCY (Line 2) CIVILIAN VALOR MEDAL. Lettering shall be accomplished using Bodoni MT Bold type face, 24 point caps for the first letter in each word and 20 point caps for all other letters.

EPOXY: Epoxy resin shall be applied to the lapel button as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below

TIOH HARD EPOXY COLOR CHIP NUMBER	LOCATION
Blue #30	Top of the Shield
White #28	*First stripes and every other alternating stripes*
Red #1	*Second stripes and every alternating stripes*
Red #3	*The background of the diamond behind the eagle and The reverse side of the inside of the diamond shape*

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon is MIL-DTL-11589/701

3. The specification slash sheet for the lapel button is MIL-DTL-11484/410.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:27Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2024-130)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:27Z
Check the source to verify that this is the current version before use.