NOT MEASUREMENT SENSITIVE


MIL-DTL-3943/425
7 March 2025

DETAIL SPECIFICATION SHEET

MEDAL, NAVY ARCTIC SERVICE

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.



OBVERSE



REVERSE

DASH NO.
-1: Regular
-2: Miniature Size

MATERIAL: (-1 and -2) Red Brass 85/15 (UNS Alloy NO. C-230)

FINISH: (-1 and -2) Silver Plated, Oxidized, Buffed Relieved, Matte Finish, Polished Highlights and shall match The Institute of Heraldry Metal Finish Chip Number 15.

DIMENSION (Excluding lug):
DIAMETER:
-1: 1-1/4 inches (REF)
-2: 5/8 inch (REF)

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:31Z
Check the source to verify that this is the current version before use.

THICKNESS (At thickest point):
-1: 0.240 inch ± 0.010 inch
-2: 0.165 inch ± 0.010 inch

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape and service ribbon is MIL-DTL-11589/318

3. The specification slash sheet for the lapel button is MIL-DTL-11484/451.

4. For commercial sale only may be manufactured using Nickel Plate Mirror-like Polished and shall match TIOH Metal Finish Chip Number 16.

Custodians:
Army - IH
Navy - NU

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2025-064)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:31Z
Check the source to verify that this is the current version before use.