NOT MEASUREMENT SENSITIVE


MIL-DTL-3943/426(IH)
3 July 2024

DETAIL SPECIFICATION SHEET

DECORATION, AIR AND MARINE OPERATIONS PURPLE CROSS MEDAL, U.S. CUSTOM AND BORDER PROTECTION

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.




OBVERSE



REVERSE



DEVICE



ASSEMBLED

DASH NO.
-1: Regular Size
-2: Miniature Size

MATERIALS: (-1 and -2): Red Brass 85/15 (UNS Alloy No. C-230)

FINISH: (-1 and -2) OBVERSE, REVERSE AND DEVICE: 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.

DIMENSIONS:
BASE:
HEIGHT (Overall):
- 1 : 1-5/8 inches (REF)
-2: 13/16 inch (REF)
WIDTH (Overall):
-1: 1-5/8 inches (REF)
-2: 13/16 inch (REF)

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:32Z
Check the source to verify that this is the current version before use.

THICKNESS (At thickest point):
- 1 : 0.180 ± 0.010 inch
-2: 0.135 ± 0.010 inch

DEVICE:
HEIGHT:
- 1 : 27/32 inch (REF)
-2: 5/8 inch (REF)

WIDTH:
-1: 43/64 inch (REF)
-2: 21/64 inch (REF)

THICKNESS (At thickest point):
- 1 : 0.060 ± 0.010 inch
-2: 0.060 ± 0.010 inch

ASSEMBLED THICKNESS(At thickest point):
- 1 : 0.235 ± 0.010 inch
-2: 0.190 ± 0.010 inch

DECORATION SET: Decoration set shall consist of a regular size medal, a miniature size medal, a lapel button, and a service ribbon, all packaged in a presentation case conforming to MIL-DTL-14633, Type I, with a Class 7 pad.

ATTACHING DEVICE:

1. The device shall be soft soldered or riveted to the base by a solid brass rivet. The rivet may be extruded as an integral part of the device.

2. If the a rivet is to be used to attach the device to the base, the length of the rivet shall be controlled to ensure no deformation occurs on the reverse of the pendant.

EPOXY: Epoxy resin shall be applied to the Badge as indicated above and shall match TIOH Hard Enamel Color Chip Numbers listed below. If hard enamel is used, then the material will be Gilding Metal 95/5 (UNS Alloy C-210).

Enamel Chip Number	Location
White #26	Left to right 1st, 3rd, 5th, and 7th stripes on device shield
Red #3	Left to right 2nd, 4th, and 6th stripes on device shield
Blue #18	Shield Chief (Area Around stars)
Purple #41	Reverse side of pendant

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the lapel button is MIL-DTL-11484/452.

3. The specification slash sheet for the ribbon for the pendant drape and for the service ribbon is MIL-DTL-11589/726.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:32Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH
.
Review activity:
DLA - CT

Preparing activity:
Army - IH

(Project No. 8455-2024-192)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:32Z
Check the source to verify that this is the current version before use.