NOT MEASUREMENT SENSITIVE


MIL-DTL-3943/427(IH)
22 July 2024

DETAIL SPECIFICATION SHEET

DECORATION, AIR AND MARINE OPERATIONS FOR VALOR MEDAL.
U.S. CUSTOM AND BORDER PROTECTION

This specification is approved for use by all
Departments and Agencies of the Department of Defense


The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-3943.




OBVERSE



REVERSE



DEVICE



ASSEMBLED

MATERIAL: (-1 AND -2) Red Brass 85/15 (UNS Alloy No. C-230)

FINISH:
OBVERSE BASE: (-1 and -2): Floating epoxy, 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.
REVERSE: (-1 and -2): Stoned epoxy, 24K Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.
DEVICE: (-1 and -2): Floating Epoxy, 24K Gold Plated, Matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 8.

DIMENSIONS:
HEIGHT (Including lug):
-1: 1-41/64 inches (REF)
-2: 53/64 inch (REF)
WIDTH (Overall):
-1: 1-5/8 inches (REF)
-2: 13/16 inch (REF)
THICKNESS (At thickest point):
-1: 0.125 $\pm$ 0.010-inch
-2: 0.95 $\pm$ 0.010-inch

DEVICE:

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:32Z
Check the source to verify that this is the current version before use.

HEIGHT:
-1: 15/16 inch (REF)
-2: 15/32 inch (REF)
WIDTH (Overall):
-1: 15/16 inch (REF)
-2: 15/32 inch (REF)
THICKNESS (At thickest point):
-1: 0.105 ± 0.010-inch
-2: 0.070 ± 0.010
ASSEMBLED THICKNESS: To be determined during development.
-1: 0.225 ± 0.010-inch
-2: 0.165 ± 0.010-inch

DECORATION SET: Decoration set shall consist of a regular size medal, a service ribbon, and a lapel button all packaged in a presentation case conforming to MIL-DTL-14633, Type I, with a Class 1 or 2 pad

EPOXY: Epoxy resin shall be applied to the Badge as indicated above and shall match TIOH Hard Enamel Color Chip Numbers listed below. If hard enamel is used, then the material will be Gilding Metal 95/5 (UNS Alloy C-210).

TIOH HARD ENAMEL COLOR CHIPS

Enamel Chip Number	Location
White #28	Left to right 1st, 3rd, 5th, and 7th Stripes on Device Shield
Red #1	Left to right 2nd, 4th, and 6th Stripes on Device Shield, and Reverse Side Inside Cuter Rim Around Lettering
Blue #33	8-Pointed Star of Base
Blue #20	Area around Stars of Device Shield

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The specification slash sheet for the ribbon for the pendant drape and for the service ribbon is MIL-DTL-11589/727.

3. The specification slash sheet for the lapel button shall conform to MIL-DTL-11484/453.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2024-212)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T02:32Z
Check the source to verify that this is the current version before use.