INCH-POUND

MIL-C-28754/83(NW)
AMENDMENT 1
23 March 1994

MILITARY SPECIFICATION SHEET

CONNECTORS, ELECTRICAL, MODULAR, TYPE IV, CONNECTOR, 0.6 PITCH, 250 CONTACT, CENTER

This amendment forms a part of Military Specification MIL-C-28754/83(NAVY), dated 21 April 1989, and is approved for use by the Crane Division, Naval Surface Warfare Center, Department of the Navy, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 13

Insertion force: Delete and substitute the following:

"Insertion force: Force required to fully mate this connector with a corresponding backplane manufactured in accordance with MIL-C-28754/79, /80 or /81 shall be less than 18 pounds. Both backplane and connector shall be cleaned with mineral spirits, TT-T-291, followed by an isopropyl alcohol, TT-I-735, rinse and allowed to air dry in a lab environment for a minimum of 30 minutes and a maximum of 4 hours prior to testing. Testing shall be performed in accordance with the assembly engagement and separation force procedure of MIL-C-28754. Backplanes used for this test shall be correlated with a reference standard maintained by NAVSURFWARCENDIV, Crane, Code 6042."

Custodian:
Navy - NW

Preparing activity:
Navy - NW

(Project 5935-N504-1)

User activity:
Navy - AS

AMSC N/A
FSC 5935

DISTRIBUTION STATEMENT A Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-20T14:53Z
Check the source to verify that this is the current version before use.