# MILITARY SPECIFICATION

## Ring, Retaining

### 1. SCOPE

1.1 This specification covers requirements, quality assurance provisons, and the preparation for delivery criteria for one type of ring, retaining used on the Atomic Demolition Charge.

SPECIFICATIONS

MILITARY

MIL-P-116 - Preservation, Methods of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1168 - Lot Numbering of Ammunition
MIL-STD-1169 - Packaging, Packing and Marking for Shipments of Inert Ammunition Components

DRAWINGS

ORDNANCE CORPS

8808362 - Packing and Marking for Storage and Shipments
8825419 - Retaining Ring
8883534 - Bag Packing for Repair Parts



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, drawings, and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

## 3. REQUIREMENTS

3.1 Materials. The contractor shall furnish objective evidence (see 6.2) that the material complies with the specifications listed on the applicable drawing.

3.2 Assembly. The retaining ring shall comply with all requirements specified on the drawing(dwg) 8825419, with all requirements specified herein, and with the requirements of all applicable specifications to the extent specified on the drawing and herein.

3.3 Workmanship.

3.3.1 Plastic and metal characteristics. All components shall be free from cracks, splits, cold flow, shrinkage, cold shuts, inclusions, porosity, or any similar characteristic.

3.3.2 Burrs. Parts shall be free from burrs.

3.3.3 Foreign matter. Parts shall be free from chips, dirt, grease, rust, corrosion, or any embedded foreign material.

3.3.4 Cleaning. The cleaning method shall not be injurious to any of the parts, nor shall the parts be contaminated by the cleaning agent.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.2 First article inspection. - Not applicable.

4.3 Quality conformance inspection.

4.3.1 Lot formation.

4.3.1.1 Production lot. A lot shall consist of parts and assemblies produced by one manufacturer in one unchanged process, in accordance with the same drawing, same drawing revision, same specification and same specification revision. Drawing, specification and process changes not affecting



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

safety, performance, storage, or interchangeability, as determined by the Government, shall not necessitate changing the lot interfix number. The criteria and procedures for the assignment of lot numbers shall be in accordance with MIL-STD-1168.

4.3.1.2 Inspection lot. A lot or batch and its formation, size, and presentation is described in MIL-STD-105, Section 5. Accordingly, a lot shall mean an inspection lot and a batch shall mean an inspection batch for the purpose of this specification. The manner in which each inspection lot or batch is to be presented and identified by the contractor, shall be designated or approved by the Government representative.

4.3.2 Product inspection examination. Critical characteristics shall require 100 percent inspection of all items in the inspection lot. A sample shall be selected at random from each inspection lot in accordance ith the applicable major or minor characteristic table (see Table I and Table II), and inspected for all characteristics in the applicable classification. Any characteristics in the sample found to be defective shall reject the inspection lot. Sequence for the inspection of characteristics in each classification need not be followed as long as all characteristic inspections are performed.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

Table I
Major Characteristics

| Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size |
|---|---|---|---|---|---|---|---|
| 1-72 | all | 140-141 | 124 | 256-259 | 177 | 541-549 | 230 |
| 73 | 72 | 142 | 125 | 260-262 | 178 | 550-559 | 231 |
| 74 | 73 | 143-144 | 126 | 263-265 | 179 | 560-569 | 232 |
| 75 | 74 | 145 | 127 | 266-268 | 180 | 570-579 | 233 |
| 76 | 75 | 146-147 | 128 | 269-271 | 181 | 580-590 | 234 |
| 77 | 76 | 148-149 | 129 | 272-275 | 182 | 591-601 | 235 |
| 78 | 77 | 150 | 130 | 276-278 | 183 | 602-613 | 236 |
| 79 | 78 | 151-152 | 131 | 279-282 | 184 | 614-625 | 237 |
| 80 | 79 | 153-154 | 132 | 283-285 | 185 | 626-637 | 238 |
| 81-82 | 80 | 155-156 | 133 | 286-289 | 186 | 638-649 | 239 |
| 83 | 81 | 157 | 134 | 290-293 | 187 | 650-662 | 240 |
| 84 | 82 | 158-159 | 135 | 294-296 | 188 | 663-676 | 241 |
| 85 | 83 | 160-161 | 136 | 297-300 | 189 | 677-690 | 242 |
| 86 | 84 | 162-163 | 137 | 301-304 | 190 | 691-704 | 243 |
| 87 | 85 | 164-165 | 138 | 305-308 | 191 | 705-719 | 244 |
| 88-89 | 86 | 166-167 | 139 | 309-312 | 192 | 720-735 | 245 |
| 90 | 87 | 168 | 140 | 313-316 | 193 | 736-751 | 246 |
| 91 | 88 | 169-170 | 141 | 317-320 | 194 | 752-768 | 247 |
| 92 | 89 | 171-172 | 142 | 321-324 | 195 | 769-785 | 248 |
| 93 | 90 | 173-174 | 143 | 325-329 | 196 | 786-804 | 249 |
| 94-95 | 91 | 175-176 | 144 | 330-333 | 197 | 805-823 | 250 |
| 96 | 92 | 177-178 | 145 | 334-338 | 198 | 824-842 | 251 |
| 97 | 93 | 179-180 | 146 | 339-342 | 199 | 843-863 | 252 |
| 98 | 94 | 181-182 | 147 | 343-347 | 200 | 864-884 | 253 |
| 99-100 | 95 | 183-184 | 148 | 348-352 | 201 | 885-907 | 254 |
| 101 | 96 | 185-187 | 149 | 353-356 | 202 | 908-930 | 255 |
| 102 | 97 | 188-189 | 150 | 357-361 | 203 | 931-955 | 256 |
| 103 | 98 | 190-191 | 151 | 362-366 | 204 | 956-981 | 257 |
| 104-105 | 99 | 192-193 | 152 | 367-372 | 205 | 982-1008 | 258 |
| 106 | 100 | 194-195 | 153 | 373-377 | 206 | 1009-1036 | 259 |
| 107 | 101 | 196-197 | 154 | 378-382 | 207 | 1037-1066 | 260 |
| 108-109 | 102 | 198-200 | 155 | 383-388 | 208 | 1067-1098 | 261 |
| 110 | 103 | 201-202 | 156 | 389-393 | 209 | 1099-1131 | 262 |
| 111 | 104 | 203-204 | 157 | 394-399 | 210 | 1132-1166 | 263 |
| 112-113 | 105 | 205-207 | 158 | 400-405 | 211 | 1167-1204 | 264 |
| 114 | 106 | 208-209 | 159 | 406-411 | 212 | 1205-1243 | 265 |
| 115 | 107 | 210-212 | 160 | 412-417 | 213 | 1244-1285 | 266 |
| 116-117 | 108 | 213-214 | 161 | 418-424 | 214 | 1286-1330 | 267 |
| 118 | 109 | 215-217 | 162 | 425-430 | 215 | 1331-1378 | 268 |
| 119 | 110 | 218-219 | 163 | 431-437 | 216 | 1379-1429 | 269 |
| 120-121 | 111 | 220-222 | 164 | 438-443 | 217 | 1430-1483 | 270 |
| 122 | 112 | 223-224 | 165 | 444-450 | 218 | 1484-1542 | 271 |
| 123-124 | 113 | 225-227 | 166 | 451-457 | 219 | 1543-1605 | 272 |
| 125 | 114 | 228-230 | 167 | 458-465 | 220 | 1606-1673 | 273 |
| 126-127 | 115 | 231-232 | 168 | 466-472 | 221 | 1674-1747 | 274 |
| 128 | 116 | 233-235 | 169 | 473-480 | 222 | 1748-1827 | 275 |
| 129-130 | 117 | 236-238 | 170 | 481-488 | 223 | 1828-1914 | 276 |
| 131 | 118 | 239-241 | 171 | 489-496 | 224 | 1915-2010 | 277 |
| 132-133 | 119 | 242-243 | 172 | 497-504 | 225 | 2011-2115 | 278 |
| 134 | 120 | 244-246 | 173 | 505-513 | 226 | 2116-2232 | 279 |
| 135-136 | 121 | 247-249 | 174 | 514-521 | 227 | 2233-2361 | 280 |
| 137 | 122 | 250-252 | 175 | 522-530 | 228 | over 2361 | 293 |
| 138-139 | 123 | 253-255 | 176 | 531-540 | 229 | | |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

Table II
Minor Characteristics

| Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size | Lot Size | Sample Size |
|---|---|---|---|---|---|---|---|
| 1-16 | all | 28-29 | 23 | 52-56 | 31 | 132-156 | 39 |
| 17 | 16 | 30-31 | 24 | 57-62 | 32 | 157-191 | 40 |
| 18 | 17 | 32-34 | 25 | 63-69 | 33 | 192-244 | 41 |
| 19-20 | 18 | 35-36 | 26 | 70-76 | 34 | 245-334 | 42 |
| 21 | 19 | 37-40 | 27 | 77-86 | 35 | 335-519 | 43 |
| 22-23 | 20 | 41-43 | 28 | 87-97 | 36 | 520-1120 | 44 |
| 24-25 | 21 | 44-47 | 29 | 98-112 | 37 | over 1120 | 45 |
| 26-27 | 22 | 48-51 | 30 | 113-131 | 38 | | |

4.3.2.1 Classification of characteristics (see 3.2). - Critical, major and minor characteristics are defined in MIL-STD-105. Inspection shall be conducted as follows:

4.3.2.1.1 Retaining Ring (see dwg 8825419).

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: | None defined. | |
| Major: | | |
| | 101. Inside diameter | *Measure |
| | 102. Diameter of wire | Micrometer |
| | 103. Inside diameter of projection, min | *Measure |
| | 104. Material (see 3.1) | Visual |
| | 105. Objective evidence (see 6.2) for finish in accordance with dwg. 8825419 | Visual |

*Measure with suitable scale

| | | |
|---|---|---|
| Minor: | | |
| | 201. Workmanship (see 3.3) | Visual-Manual |

4.3.2.1.2 Preparation for delivery (see 5.1)

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: | None defined. | |
| Major: | | |
| | 101. Preservation, packaging, packing and marking in accordance with MIL-P-1169 | Visual |



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

4.3.2.1.3 Bag, packing for reapir parts (see dwg 8883534 covering dwg part number 883534-4 and 5.2)

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: | None defined. | |
| Major: | | |
| | 101. Material (see 3.1) | Visual |
| | 102. Length before packing, min | *Measure |
| | 103. Width before packing, min | *Measure |
| | 104. Properly packed | Visual-Manual |
| | 105. Proper heat seal | Visual-Manual |
| | 106. No tear, crack or hole in bag | Visual |
| | 107. Objective evidence (see 6.2) for Heat Seal Test in accordance with MIL-P-116 | Visual-Manual |

*Measure with suitable scale

| | | |
|---|---|---|
| Minor: | | |
| | 201. Marking | Visual |
| | 202. Workmanship (see 3.3) | Visual-Manual |

4.3.2.1.4 Packing and marking for storage and shipments (see dwg 8808362 and 5.2).

| Categories | Characteristics | Method of Inspection |
|---|---|---|
| Critical: | None defined. | |
| Major: | | |
| | 101. Gross load weight, max | *Measure |
| | 102. Contents tight in package | Visual-Manual |
| | 103. Correctly packed | Visual-Manual |
| | 104. Material (see 3.1) | Visual |

*Determine weight with suitable scale

| | | |
|---|---|---|
| Minor: | | |
| | 201. Marking | Visual |
| | 202. Workmanship (see 3.3) | Visual-Manual |

4.3.3 Testing. - Not applicable.
4.3.4 Acceptance inspection equipment. Not applicable.
4.4 Test Methods. - Not applicable.



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.

## 5. PREPARATION FOR DELIVERY

5.1 Production items.

5.1.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.1.1.1 Level A. The retaining ring shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.1.2 Level C. The retaining ring shall be preserved and packaged in accordance with instructions contained in MIL-STD-1169(MU).

5.1.2 Packing.

5.1.2.1 Levels A and C. The retaining ring shall be packed in accordance with the applicable instructions contained in MIL-STD-1169(MU).

5.1.3 Marking. Marking shall be in accordance with MIL-STD-1169(MU).

5.2 Repair parts.

5.2.1 Preservation and packaging. Preservation and packaging shall be level A or C as specified (see 6.1).

5.2.1.1 Level A. The retaining ring shall be packaged in accordance with dwg 8883534 and 8808362 using the specified moisture barrier.

5.2.1.2 Level C. The retaining ring shall be packaged in accordance with dwg 8808362 except that the moisture barrier may be omitted.

5.2.2 Packing.

5.2.2.1 Level A and C. The retaining ring shall be packed in accordance with dwg 8883534 and 8808362

5.2.3 Marking. Marking shall be as specified in accordance with dwg 8883534 and 8808362 as applicable.

## 6. NOTES

6.1 Ordering data. Procurement documents should specify the following:

a. Title, number, and date of this specification.
b. Production or Repair Part.
c. Selection of applicable level of packaging and packing required (see 5.1 and 5.2).

6.2 Objective evidence. Records of contractor quality control and inspections which can be verified.

Custodian:
Army - MU

Preparing activity:
Army - MU

Project No. 5365-A002



Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:09Z
Check the source to verify that this is the current version before use.