The documentation and process conversion measures necessary to comply with this revision shall be completed by 15 August 2010.

INCH POUND

MIL-PRF-19500/124K
17 May 2010
SUPERSEDING
MIL-PRF-19500/124J
20 May 2009

PERFORMANCE SPECIFICATION SHEET

SEMICONDUCTOR DEVICE, DIODE, SILICON, VOLTAGE REGULATOR TYPES 1N2970B THROUGH 1N2977B, 1N2979B, 1N2980B, 1N2982B, 1N2984B THROUGH 1N2986B, 1N2988B THROUGH 1N2993B, 1N2995B, 1N2997B, 1N2999B THROUGH 1N3005B, 1N3007B, 1N3008B, 1N3009B, 1N3011B, 1N3012B, 1N3014B, 1N3015B, PLUS RB TYPES, 1N3993A THROUGH 1N3998A, AND RA TYPES, JAN, JANTX, JANTXV, AND JANS

This specification is approved for use by all Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-PRF-19500.

1. SCOPE

1.1 Scope. This specification covers the performance requirements for 10 watt, silicon voltage regulator diodes: A and B type (standard polarity); RA and RB type (reverse polarity). Four levels of product assurance are provided for each device type as specified in MIL-PRF-19500.

1.2 Physical dimensions. See figure 1 (DO-4).

* 1.3 Maximum ratings. Maximum ratings are as shown in columns 4, 8, and 10 of the test ratings table herein and as follows:

$-65°C \leq T_J \leq +175°C$; P_T = 10 W at T_C = +55°C; derate at .083 W/°C above +55°C.
$-65°C \leq T_{STG} \leq +200°C$.

1.4 Primary electrical characteristics. Primary electrical characteristics are as shown in columns 2, 9, 12, and 14 of the test ratings table herein, and as follows:

Thermal resistance ($R_{\Theta JC}$) = 12°C/W maximum.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3, 4, or 5 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to ensure the completeness of this list, document users are cautioned that they must meet all specified requirements of documents cited in sections 3, 4, or 5 of this specification, whether or not they are listed.

* Comments, suggestions, or questions on this document should be addressed to Defense Supply Center, Columbus, ATTN: DSCC-VAC, P.O. Box 3990, Columbus, OH 43218-3990, or emailed to semiconductor@dscc.dla.mil . Since contact information can change, you may want to verify the currency of this address information using the ASSIST Online database at https://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those cited in the solicitation or contract.

DEPARTMENT OF DEFENSE SPECIFICATIONS

MIL-PRF-19500 - Semiconductor Devices, General Specification for.

DEPARTMENT OF DEFENSE STANDARDS

MIL-STD-750 - Test Methods for Semiconductor Devices.

* (Copies of these documents are available online at https://assist.daps.dla.mil/quicksearch or https://assist.daps.dla.mil or from the Standardization Document Order Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111-5094.)

2.3 Order of precedence. Unless otherwise noted herein or in the contract, in the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 General. The individual item requirements shall be as specified in MIL-PRF-19500 and as modified herein.

3.2 Qualification. Devices furnished under this specification shall be products that are manufactured by a manufacturer authorized by the qualifying activity for listing on the applicable qualified manufacturers list (QML) before contract award (see 4.2 and 6.3).

3.3 Abbreviations, symbols, and definitions. The abbreviations, symbols, and definitions used herein shall be as specified in MIL-PRF-19500.

3.4 Interface and physical dimensions. Interface and physical dimensions shall be as specified in MIL-PRF-19500, and on figure 1 (DO-4).

a. Device types 1N2970B through 1N3015B and 1N3993RA through 1N3998RA shall have the anode connected to the stud.

b. Device types 1N2970RB through 1N3015RB and 1N3993A through 1N3998A shall have the cathode connected to the stud.

3.4.1 Lead finish. Unless otherwise specified, lead finish shall be solderable in accordance with MIL-PRF-19500, MIL-STD-750, and herein. Where a choice of lead finish is desired, it shall be specified in the contract (see 6.2).


3.4.2 Diode construction. These devices shall be constructed in a manner and using materials which enable the diodes to meet the applicable requirements of MIL-PRF-19500 and this document.

3.5 Marking. Devices shall be marked as specified in MIL-PRF-19500.

3.6 Reverse polarity. Reverse polarity units (see 3.4.a and b) shall be marked with an "R" preceding the "A" or "B" in the type designation, as applicable.

3.7 Workmanship. Semiconductor devices shall be processed in such a manner as to be uniform in quality and shall be free from other defects that will affect life, serviceability, or appearance.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.



Symbol	Dimensions				Notes
	Inches		Millimeters		
	Min	Max	Min	Max	
C		.250		6.35	
C_1	.012	.065	0.30	1.65	5
CD	.255	.424	6.48	10.77	
CH	.300	.405	7.62	10.29	
HF	.424	.437	10.77	11.1	
HT_1	.075	.175	1.91	4.45	
HT_2	.060	.175	1.52	4.45	
OAH	.600	.800	15.24	20.32	
SD					2
SL	.422	.453	10.72	11.51	
SU		.078		1.98	4
UD	.163	.189	4.14	4.80	1
ΦT	.060	.095	1.52	2.41	

NOTES:
1. Dimensions are in inches. Millimeters are given for general information only.
2. Maximum pitch diameter (SD) of plated threads shall be basic pitch diameter .1697 inch (4.31 mm), 10-32 UNF-2B reference (FED-STD-H28, “Screw-Thread Standards for Federal Services”).
3. A chamfer or undercut on one or both ends of the hex portion is optional; minimum base diameter at seating plane .403 inch (10.24 mm).
4. Length of incomplete or undercut threads - SU.
5. The angular orientation and peripheral configuration of terminal 1 is undefined, however, the major surfaces over dimension C shall be flat.
6. Dimension CD can not exceed dimension HF.
7. In accordance with ASME Y14.5M, diameters are equivalent to Φx symbology.
* 8. Polarity - see 3.4.

* FIGURE 1. Physical dimensions (DO-4).

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. Qualification inspection (see 4.2).

b. Screening (see 4.3).

c. Conformance inspection (see 4.4 and tables I and II).

4.2 Qualification inspection. Qualification inspection shall be in accordance with MIL-PRF-19500.

4.3 Screening (JANS, JANTXV, AND JANTX levels only). Screening shall be in accordance with table E-IV of MIL-PRF-19500, and as specified herein. The following measurements shall be made in accordance with table I herein. Devices that exceed the limits of table I herein shall not be acceptable.

Screening (see table E-IV of MIL-PRF-19500)	Measurement	
	JANS level	JANTXV and JANTX level
9	I_{R1} and V_Z (for devices with $V_{Z(nom)} \geq 10$ V dc; see column 2 of table III)	Not applicable
11	I_{R1} and V_Z; ΔI_{R1} = 100 percent of initial value or 1 percent of column 12 of table III, whichever is greater, $\Delta V_Z = \pm 2.5$ percent of initial value (for devices with $V_{Z(nom)} \geq 10$ V dc, see column 2 of table III)	I_{R1} and V_Z
12	See 4.3.1	See 4.3.1
13	Subgroups 2, 3, and 4 of table I herein; ΔI_{R1} = 100 percent of initial value or 1 percent of column 12 of table III, whichever is greater; $\Delta V_Z = \pm 2.5$ percent of initial value	Subgroup 2 of table I herein; ΔI_{R1} = 100 percent of initial value or 1 percent of column 12 of table III, whichever is greater; $\Delta V_Z = \pm 2.5$ percent of initial value

* 4.3.1 Power burn-in conditions. Power burn-in conditions are as follows: T_J = 165°C minimum with I_Z not to exceed I_Z in column 15 of table III; V_Z = column 2 of table III.

4.4 Conformance inspection. Conformance inspection shall be in accordance with MIL-PRF-19500.

4.4.1 Group A inspection. Group A inspection shall be conducted in accordance with table E-IV of MIL-PRF-19500 and table I herein. End-point electrical measurements shall be in accordance with the applicable steps of table II herein.

4.4.2 Group B inspection. Group B inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VIa (JANS) and table E-VIb (JAN, JANTX, and JANTXV), of MIL-PRF-19500, and as follows. Electrical measurements (end-points) and delta requirements shall be in accordance with the applicable steps of table II herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

* 4.4.2.1 Group B inspection, table E-VIa (JANS) of MIL-PRF-19500.

Subgroup	Method	Conditions
B2	2026	Dwell time = 10 ±1 s; immersion to cover flat portion of terminal only.
B4	1037	2,000 cycles. See 4.5.6 herein.
B5	1027	I_Z = column 15 of table III for 96 hours, T_A = +125°C or adjusted, as required, to give an average lot T_J = +225°C. Option 1 – T_J = +200°C, 336 hours. Option 2 – T_J = +175°C, 1,000 hours.
B6	4081	$R_{\Theta JC}$ = 12°C/W maximum, T_A = +25°C. For purposes of this test “junction to case" shall be used in lieu of "junction to lead" and "$R_{\Theta JC}$" shall be used in lieu of "$R_{\Theta JL}$". The case shall be the reference point for calculation of junction to case thermal resistance ($R_{\Theta JC}$). The mounting arrangement shall be with heat sink to case.

* 4.4.2.2 Group B inspection, table E-VIb (JAN, JANTX and JANTXV) of MIL-PRF-19500.

Subgroup	Method	Conditions
B2	4066	I_{ZSM} = column 10 of table III.
B3	1027	I_Z = column 15 of table III, adjust T_A, mounting, or both, to achieve T_C = 142ºC minimum.
B3	1037	2,000 cycles. See 4.5.6 herein (separate samples may be used)
B5	4081	$R_{\Theta JC}$ = 12°C/W maximum; T_A = +25°C. For purposes of this test, "junction to case" shall be used in lieu of "junction to lead" and "$R_{\Theta JC}$" shall be used in lieu of "$R_{\Theta JL}$".The case shall be the reference point for calculation of junction to case thermal resistance ($R_{\Theta JC}$). The mounting arrangement shall be with heat sink to case.
B6	1032	T_A = +200°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

4.4.3 Group C inspection. Group C inspection shall be conducted in accordance with the conditions specified for subgroup testing in table E-VII of MIL-PRF-19500 and as follows. Electrical measurements (end-points) and delta requirements shall be in accordance with the applicable steps of table II herein.

* 4.4.3.1 Group C inspection, table E-VII of MIL-PRF-19500.

Subgroup	Method	Conditions
C2	2036	Tension: Test condition A; 20 pounds; t = 15 ±3 s.
C2	2036	Torque (terminal): Test condition D_1; 10 inch-ounces; t = 15 ±3 s.
C2	2036	Torque (stud): Test condition D_2; 15 inch-pounds; t = 30 ±3 s.
C2	2036	Bending stress: Test condition F; 3 pounds; t = 15 ±3 s, method B.
C6	1027	I_Z = column 15 of table III, adjust T_A, mounting, or both, to achieve T_C = 142ºC minimum.
C6	1037	6,000 cycles. See 4.5.6 herein (separate samples may be used).
C8	4071	22 devices, c = 0, JAN, JANTX, and JANTXV levels only. Temperature coefficient of breakdown voltage (see 4.5.3 and 4.5.4). I_Z = column 5 of table III, T_A = +25°C; $T_2 = T_1$ + 100°C; each sublot; αV_Z = %/°C column14 of table III. Voltage regulation (see 4.5.2) each sublot. $V_{Z(reg)}$ = V dc, column 9 of table III.

4.5 Methods of inspection. Methods of inspection shall be as specified in the appropriate tables and as follows:

4.5.1 Surge current I_{ZSM}. The currents specified in column 10 of table III shall be applied in the reverse direction and shall be superimposed on the current (I_Z = column 5 of table III) a total of five surges at 1-minute intervals. Each individual surge shall be a one-half square wave pulse of 1/120-second duration or an equivalent one-half sine wave with the same effective (rms) current.

4.5.2 Voltage regulation $V_{Z(reg)}$. A current at 10 percent of I_Z (column 8) shall be maintained until thermal equilibrium is obtained, and the V_Z shall then be increased to a level of 50 percent of I_Z (column 8) and maintained at this level for a period of time until thermal equilibrium is obtained at which time the voltage change shall not exceed column 9 of table III. During this test, the temperature shall be equal to T_A = +25°C.

4.5.3 Regulator voltage. The I_Z test current (column 5 of table III) shall be applied until thermal equilibrium is obtained prior to reading the regulator voltage. During this test, the temperature shall be equal to T_A = +25°C

4.5.4 Temperature coefficient of regulator voltage (αV_Z). The device shall be temperature stabilized with current applied prior to reading regulator voltage at the specified case temperatures.

4.5.5 Inspection condition. Unless otherwise specified in MIL-PRF-19500 or herein, all inspections shall be made at temperature shall be equal to T_A = +25°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

* 4.5.6 DC intermittent operation life. A cycle shall consist of an "on" period, when forward current is applied suddenly, not gradually, to the device for the time necessary to achieve an increase (delta) case temperature of +85°C +15°C, -0°C followed by an "off" period, when the current is suddenly removed for cooling the case through a similar delta temperature. Auxiliary (forced) cooling is permitted during the "off" period only. Forward current and "on" time, within specific limits, and "off" time may be adjusted to achieve the delta case temperature. Heat sinks shall only be used if, and to the degree necessary, to maintain test samples within the desired delta temperature tolerance. The heating time shall be such that 30 s $\leq t_{heating} \leq$ 180 s. The forward current may be steady-state dc, full-wave rectified dc, or the equivalent half-sine wave dc, of the specified value. Alternately, I_Z may be used to achieve heating. The test duration shall be the specified number of cycles. Within the time interval of 50 cycles before and 500 cycles after the termination of the test, the sample units shall be removed from the specified test conditions and allowed to reach room ambient conditions. Specified end-point measurements for qualification and quality conformance inspections shall be completed within 96 hours after removal of sample units from the specified test conditions. Additional readings may be taken at the discretion of the manufacturer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection.

Inspection 1/	MIL-STD-750		Symbol	Limits 2/		Unit
	Method	Conditions		Min	Max	
Subgroup 1						
Visual and mechanical examination	2071					
Subgroup 2						
Forward voltage	4011	I_F = 2 A dc	V_F		1.5	V dc
Reverse current	4016	V_R = column 11 of table III, DC method	I_{R1}		Column 12	µA dc
Regulator voltage (see 4.5.2)	4022	I_Z = column 5 of table III	V_{Z1}	Column 3	Column 4	V dc
Regulator voltage (see 4.5.2)	4022	I_{Z2} = 20 mA dc	V_{Z2}	Column 3	Column 4	V dc
Subgroup 3						
High temperature operation		T_A = 150°C				
Reverse current	4016	DC method, V_R = column 11 of table III	I_{R2}		500	µA dc
Subgroup 4						
Small-signal reverse breakdown impedance	4051	I_Z = column 5 of table III, I_{sig} = 10 of percent I_{ZT}	Z_Z		Column 6	ohms
Knee impedance		I_{ZK} = 1 mA dc, I_{sig} = 10 percent of I_{ZK}	Z_{ZK}		Column 7	ohms
Subgroups 5						
Not applicable						

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

TABLE I. Group A inspection - Continued.

Inspection 1/	MIL-STD-750		Symbol	Limit 2/		Unit
	Method	Conditions		Min	Max	
Subgroup 6						
Surge current (see 4.5.1)	4066	T_C = +25°C; I_{ZSM} = column 10 of table III				
End-point electrical measurements		See table II, steps 1, 3, and 4				
Subgroup 7		JANS level only				
Voltage regulation (see 4.5.2)			$V_{Z(reg)}$		Column 9	V dc
Temperature coefficient of breakdown voltage (see 4.5.4)		I_Z = column 5 of table III; T_A = +25°C; $T_2 = T_1$ +100°C	αV_Z		Column 14	%/°C

1/ For sampling plan, see MIL-PRF-19500.
2/ Column references are to table III herein.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

TABLE II. Groups B and C electrical and delta measurements. 1/ 2/ 3/

Step	Inspection	MIL-STD-750		Symbol	Limits 4/		Unit
		Method	Conditions		Min	Max	
1.	Reverse current	4016	DC method; V_R = column 11 of table III	I_{R1}		Column 12	μA dc
2.	Reverse current	4016	DC method; V_R = column 11 of table III	I_{R3}		Column 13	μA dc
3.	Breakdown voltage	4022	I_Z = column 5 of table III	V_Z	Column 3	Column 4	V dc
4	Small signal breakdown impedance	4051	I_Z = column 5 of table III, I_{sig} = 10 percent of I_Z	Z_Z		Column 6	ohms
5.	Knee impedance	4051	I_{ZK} = 1 mA dc I_{sig} = 10 percent of I_{ZK}	Z_{ZK}		Column 7	ohms
6.	Forward voltage	4011	I_F = 2.0 A dc	ΔV_F 5/		1.5	V dc

1/ The electrical measurements for table E-VIa (JANS) of MIL-PRF-19500 are as follows:
   a. Subgroup 3, see table II herein, steps 1, 3, 4, 5, and 6.
   b. Subgroup 4, see table II herein, steps 1, 3, 4, 5, and 6.
   c. Subgroup 5, see table II herein, steps 2, 3, 4, 5, and 6.

2/ The electrical measurements for table E-VIb (JANTX and JANTXV) of MIL-PRF-19500 are as follows:
   a. Subgroup 2, see table II herein, steps 1, 3, and 4.
   b. Subgroup 3, see table II herein, steps 2, 3, and 4.
   c. Subgroup 6, see table II herein, steps 2, 3, and 4.

3/ The electrical measurements for table E-VII of MIL-PRF-19500 are as follows:
   a. Subgroup 2, see table II herein, steps 1, 3, 4, 5, and 6 (JANS) and steps 1, 3, and 4 (JAN, JANTX, and JANTXV).
   b. Subgroup 3, see table II herein, steps 1, 3, 4, 5, and 6 (JANS), 1, 3, and 4 (JAN, JANTX, and JANTXV).
   c. Subgroup 6, see table II herein, steps 2, 3, 4, 5, and 6 (JANS) steps 2, 3, and 4 (JAN, JANTX, and JANTXV).

4/ Column references are to table III.

5/ Devices which exceed the group A limits for this test shall not be accepted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

TABLE III. Test ratings. 1/

Col.1	Col.2	Col.3	Col.4	Col.5	Col.6	Col.7	Col.8	Col.9	Col.10	Col.11	Col.12	Col.13	Col.14	Col.15
Type	V_Z	V_Z	V_Z	I_{ZT}	Z_Z	Z_{ZK}	I_{ZM} 2/	$V_{Z(reg)}$	I_{ZSM}	V_R	I_{R1}	I_{R3}	αV_Z	I_Z
				Test current	Imped-ance	Knee Imped-ance	T_A = +25°C	Voltage reg	T_A = +25°C	Reverse voltage	Reverse current	Reverse current / After life test	Temp coeff-icient	Max dc current T_C = 150° +5, -0°C
	Nom	Min	Max	Max			Max dc		Max		dc Max	dc Max	Max	
	volts	volts	volts	mA	ohms	ohms	mA	volts	mA	volts	µA	µA	%/°C	mA
1N3993A	3.9	3.70	4.10	640	2.0	400	2,440	0.80	12,000	.5	100	200	-.060	610
1N3994A	4.3	4.08	4.52	580	1.5	400	2,200	0.72	11,000	.5	100	200	-.050	550
1N3995A	4.7	4.45	4.94	530	1.2	550	2,000	0.68	1,0000	1.0	50	100	+.025	500
1N3996A	5.1	4.84	5.36	490	1.1	550	1,840	0.64	9,000	1.0	10	20	+.030	460
1N3997A	5.6	5.32	5.88	445	1.0	600	1,680	0.60	8,000	1.0	10	20	+.040	399
1N3998A	6.2	5.89	6.51	405	1.1	700	1,520	0.56	7,000	2.0	10	20	+.045	361
1N2970B	6.8	6.46	7.14	370	1.2	500	1,500	0.4	7,500	5.2	150	300	+.057	351.5
1N2971B	7.5	7.13	7.87	335	1.3	250	1,350	0.45	6,750	5.7	100	200	+.067	311.55
1N2972B	8.2	7.79	8.61	305	1.5	250	1,180	0.5	5,900	6.2	50	100	+.070	283.65
1N2973B	9.1	8.65	9.55	275	2.0	250	1,100	0.55	5,500	6.9	25	50	+.075	253
1N2974B	10	9.50	10.50	250	3.0	250	980	0.6	4,900	7.6	25	50	+.081	230
1N2975B	11	10.45	11.55	230	3.0	250	890	0.7	4,450	8.4	10	20	+.085	211.6
1N2976B	12	11.40	12.60	210	3.0	250	820	0.8	4,100	9.1	10	20	+.079	193.2
1N2977B	13	12.35	13.65	190	3.0	250	750	0.85	3,750	9.9	10	20	+.080	174.8
1N2979B	15	14.25	15.75	170	3.0	250	640	1.0	3,200	11.4	10	20	+.082	154.7
1N2980B	16	15.20	16.80	155	4.0	250	605	1.1	3,000	12.2	10	20	+.083	141.05
1N2982B	18	17.10	18.90	140	4.0	250	525	1.25	2,600	13.7	10	20	+.085	127.4
1N2984B	20	19.0	21.0	125	4.0	250	480	1.35	2,400	15.2	10	20	+.086	113.75
1N2985B	22	20.9	23.1	115	5.0	250	435	1.5	2,180	16.7	10	20	+.087	104.65
1N2986B	24	22.8	25.2	105	5.0	250	400	1.65	2,000	18.2	10	20	+.088	95.55
1N2988B	27	25.7	28.3	95	7.0	250	340	1.92	1,700	20.6	10	20	+.090	86.45
1N2989B	30	28.5	31.5	85	8.0	300	320	2.15	1,600	22.8	10	20	+.091	77.35
1N2990B	33	31.4	34.6	75	9.0	300	300	2.30	1,500	25.1	10	20	+.092	68.25

See footnotes at end of table.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

TABLE III. Test ratings - Continued. 1/

Col.1	Col.2	Col.3	Col.4	Col.5	Col.6	Col.7	Col.8	Col.9	Col.10	Col.11	Col.12	Col.13	Col.14	Col.15
Type	V_Z	V_Z	V_Z	I_{ZT}	Z_Z	Z_{ZK}	I_{ZM} 2/	$V_{Z(reg)}$	I_{ZSM}	V_R	I_{R1}	I_{R3}	αV_Z	I_Z
				Test current	Imped-ance	Knee Imped-ance	T_A = +25°C	Voltage reg	T_A = +25°C	Reverse voltage	Reverse current	Reverse current dc max (after life test)	Temp coeff	Max dc current T_C = 150 +5 -0°C
	Nom	Min	Max	Max	Max		dc Max		Max		dc Max		Max	
	volts	volts	volts	mA	ohms	ohms	mA	volts	mA	volts	µA	µA	%/°C	mA
1N2991B	36	34.2	37.8	70	10.0	300	260	2.45	1,300	27.4	10	20	+.093	63
1N2992B	39	37.1	40.9	65	11.0	300	240	2.55	1,200	29.7	10	20	+.094	58.5
1N2993B	43	40.9	45.1	60	12.0	400	220	2.75	1,100	32.7	10	20	+.095	54
1N2995B	47	44.7	49.3	55	14.0	400	200	3.0	1,000	35.8	10	20	+.095	49.5
1N2997B	51	48.5	53.5	50	15.0	500	185	3.1	925	38.8	10	20	+.096	45
1N2999B	56	53.2	58.8	45	16.0	500	170	3.3	850	42.6	10	20	+.096	40.5
1N3000B	62	58.9	65.1	40	17	600	150	3.5	750	47.1	10	20	+.097	36
1N3001B	68	64.6	71.4	37	18	600	137	3.8	685	51.7	10	20	+.097	33.3
1N3002B	75	71.3	78.7	33	22	600	125	4.4	625	56.0	10	20	+.098	29.7
1N3003B	82	77.9	86.1	30	25	700	115	4.7	575	62.2	10	20	+.098	27
1N3004B	91	86.5	95.5	28	35	800	97	5.1	485	69.2	10	20	+.099	25.2
1N3005B	100	95.0	105.0	25	40	900	91	6.1	450	76.0	10	20	+.110	22.25
1N3007B	110	104.5	115.5	23	55	1,100	82	6.9	410	83.6	10	20	+.110	20.47
1N3008B	120	114.0	126.0	20	75	1,200	77	7.9	380	91.2	10	20	+.110	2.2
1N3009B	130	123.5	136.5	19	100	1,300	71	8.8	350	98.8	10	20	+.110	16.91
1N3011B	150	142.5	157.5	17	175	1,500	62	11.0	310	114.0	10	20	+.110	15.13
1N3012B	160	152.0	168.0	16	200	1,600	58	11.8	290	121.6	10	20	+.110	1.76
1N3014B	180	171.0	189.0	14	260	1,850	52	13.8	260	136.8	10	20	+.110	12.46
1N3015B	200	190.0	210.0	12	300	2,000	46	14.8	230	152.0	10	20	+.110	10.68

1/ The test ratings are applicable to all devices.
2/ Derate I_Z linearly to 0.0 mA dc at +175°C, for T_C > +55°C.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When packaging of materiel is to be performed by DoD or in-house contractor personnel, these personnel need to contact the responsible packaging activity to ascertain packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activities within the Military Service or Defense Agency, or within the Military Service's system commands. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD-ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory. The notes specified in MIL-PRF-19500 are applicable to this specification.)

6.1 Intended use. Semiconductors conforming to this specification are intended for original equipment design applications and logistic support of existing equipment.

6.2 Acquisition requirements. The acquisition requirements are as specified in MIL-PRF-19500.

* 6.3 Qualification. With respect to products requiring qualification, awards will be made only for products which are, at the time of award of contract, qualified for inclusion in Qualified Manufacturers List (QML-19500) whether or not such products have actually been so listed by that date. The attention of the contractors is called to these requirements, and manufacturers are urged to arrange to have the products that they propose to offer to the Federal Government tested for qualification in order that they may be eligible to be awarded contracts or orders for the products covered by this specification. Information pertaining to qualification of products may be obtained from Defense Supply Center, Columbus, ATTN: DSCC/VQE, P.O. Box 3990, Columbus, OH 43218-3990 or e-mail vqe.chief@dla.mil . An online listing of products qualified to this specification may be found in the Qualified Products Database (QPD) at https://assist.daps.dla.mil.

6.4 Substitution information. Devices covered by this specification are substitutable for the manufacturer's and user's Part or Identifying Number (PIN). This information in no way implies that manufacturer's PINs are subitable for the military PIN.

Preferred types military PIN	Commercial PIN
1N3999A	1N2970B
1N3999RA	1N2970RB
1N4000A	1N2971B
1N4000RA	1N2971RB

6.4.1 Obsoleted part numbers. MIL-S-19500/272 for Part or Identifying Number (PIN) 1N3993A, RA through 1N4000A, RA is obsolete. PINs 1N3993A, RA through 1N3998A, RA have been incorporated into MIL-PRF-19500/124. PINs 1N3999A, RA and 1N4000A, RA have been deleted, as they are redundant to 1N2970RB, B and 1N2971RB, B respectively.

6.5 Changes from previous issue. The margins of this specification are marked with asterisks to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.

Custodians:
Army - CR
Navy - EC
Air Force - 85
NASA - NA
DLA - CC

Preparing activity:
DLA - CC

Review activities:
Army - AR, MI, SM
Navy - AS, MC
Air Force - 19, 99

(Project 5961-2010-002)

* NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.daps.dla.mil .

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:18Z
Check the source to verify that this is the current version before use.