MILITARY SPECIFICATION

SEMICONDUCTOR DEVICES, SILICON, HIGH VOLTAGE RECTIFIER

TYPES 1N1731A, 1N1733A, AND 1N1734A

This amendment forms a part of Military Specification MIL-S-19500/142A, dated 13 May 1964, and is mandatory for use by all Departments and Agencies of the Department of Defense.

Page 1, paragraph 1.2, i_f column: Delete "1.05" and substitute "1.1."

Page 1, paragraph 1.2, BAROMETRIC PRESSURE, REDUCED (ALTITUDE OPERATION): Change to read: "15 mm Hg for 1N1731A; 33 mm Hg for 1N1733A; and 69 mm Hg for 1N1734A."

* Page 3, add the following paragraph.

"3.3.1 Encapsulating materials. Encapsulating materials for all devices shall only be organic polymers."

Page 3: Delete paragraph 4.4.3, Pulse technique.

Page 4, Table I, Group A inspection, Subgroup 2: Change "Forward voltage" test to read as follows:

Examination or test	MIL-STD-750		LTPD	Min. Rej. No.	Symbol	Limits		
	Method	Details				Min	Max	Unit
" Forward voltage	4011	$t_p \leq 8.3$ msec; duty cycle $\leq 2\%$; (pulse)			v_f			
1N1731A		$i_f = 1.1$ a(pk)				0.8	3.6	v(pk)
1N1733A		$i_f = 1.1$ a(pk)				2.4	6.6	v(pk)
1N1734A		$i_f = 1.1$ a(pk)				4.0	9.9	v(pk) "

Page 4, Table II, Group B inspection, Subgroup 2, End points: Change "Forward voltage" test to read as follows:

" Forward voltage	4011	$t_p \leq 8.3$ msec; duty cycle $\leq 2\%$; (pulse)			v_f			
1N1731A		$i_f = 1.1$ a(pk)				0.8	3.6	v(pk)
1N1733A		$i_f = 1.1$ a(pk)				2.4	6.6	v(pk)
1N1734A		$i_f = 1.1$ a(pk)				4.0	9.9	v(pk) "

* 1/ The margins of this document are marked with an asterisk to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T13:22Z
Check the source to verify that this is the current version before use.