INCH-POUND

MIL-S-20708/326
13 March 1989

SUPERSEDING
MIL-S-20708/32F
30 July 1987

# MILITARY SPECIFICATION SHEET

## SYNCHRO TORQUE RECEIVER TRANSMITTER TYPE 18TRX4A

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the Synchros described herein shall consist of this specification and the latest issue of MIL-S-20708.

TABLE I Requirements

| Requirement | Value | Unit | Tolerance |
|---|---|---|---|
| Frequency | 400 | Hz | ±1% |
| Primary Voltage | 115 | volts | ±1% |
| Primary Current | 400.0 | milliamps | maximum |
| Primary Power | 4.0 | watts | maximum |
| Impedance | | | |
| Zss | 16.0-21.0 | ohms | min-max |
| Impedance Angle | | | |
| Zss | 38.0-45.0 | degrees | min-max |
| Transformation Ratio | 0.783 | ------ | ±2% |
| Phase Shift (Lead) | 4.0 | degrees | maximum |
| Electrical Error | 8.0 | minutes | maximum |
| Receiver Error | 45.0 | minutes | maximum |
| Null Voltage | | | |
| Total | 100.0 | millivolts | maximum |
| Fundamental | 50.0 | millivolts | maximum |
| Synchronizing Time | | | |
| 30° ±2° | 1.0 | seconds | maximum |
| Synchronizing Time | | | |
| 177° ±2° | 2.0 | seconds | maximum |
| Torque Gradient | 0.10 | ounce-inches per degree | minimum |
| Radial Play | 0.0006 | inches | maximum |
| End Play | 0.0020 | inches | ±0.0015 |
| Temperature Rise | 35.0 | degrees (C) | maximum |
| Variation of voltage (+10%) and Freq (-5%) | 5.6 | watts | maximum |

Ⓖ denotes changes



"DISTRIBUTION STATEMENT A Approved for public release distribution is unlimited."

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:17Z
Check the source to verify that this is the current version before use.

TABLE II Military part number variant characteristics

| Military Part No 1/ | A ± 010 | b ± 010 | c Maximum | Shaft Style | Terminal End | U + 0000 − 0002 |
|---|---|---|---|---|---|---|
| M20708/32-01A | 555 | 500 | 2 388 | Splined | Terminal Board | 1872 |

1/Military part number M20708/32-01A shall be the NATO standard

1/The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation

TABLE III Military part number cross-references

| SUPERSEDED MILITARY PART NUMBERS | | NEW MILITARY PART NUMBERS |
|---|---|---|
| MIL-S-20708/32E | MIL-S-20708/32D | |
| M20708/32E-001 | M20708/32-001 | M20708/32-01A |

NOTE All line items shown in Table III refer to equivalent and interchangeable synchros of the same type designation modification Part number changes do not affect form, fit, or function of the synchros listed therein

Custodians
Army-AR
Navy-AS
Air Force-85

Review Activities
Army-MI AV
Navy-OS
Air Force-11 / 99
DLA-ES

User Activities
Navy-MC CG

Preparing Activity
Navy-AS

(Project 5990-0349-23)



Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:17Z
Check the source to verify that this is the current version before use.