NOT MEASUREMENT SENSITIVE

MIL-S-20708 9E
13 March 1989

SUPERSEDING
MIL-S-20708/9D
30 June 1987

MILITARY SPECIFICATION SHEET

SYNCHRO, CONTROL DIFFERENTIAL TRANSMITTER, TYPE 26V-11CDX4C

This specification is approved for use by all Departments and Agencies of the Department of Defense. The requirements for acquiring the Synchros described herein shall consist of this specification and the latest issue of MIL-S-20708.

TABLE I. Requirements

| Requirement | Value | Unit | Tolerance |
|---|---|---|---|
| Frequency | 400 | Hz | ±1% |
| Primary Voltage | 10.2 Ⓔ | volts | ±1% |
| Primary Current | 150.0 | milliamps | maximum |
| Primary Power | 0.30 | watts | maximum |
| Impedance | | | |
| Zso | 68.0-85.0 | ohms | min-max |
| Zrs | 20.0-26.0 | ohms | min-max |
| Impedance Angle | | | |
| Zso | 77.0-82.0 | degrees | min-max |
| Zrs | 22.0-30.0 | degrees | min-max |
| Transformation Ratio | 1.154 | ------ | ±2% |
| Phase Shift (Lead) | 6.0 | degrees | ±2.0 |
| Electrical Error | 7.0 | minutes | maximum |
| Null Voltage | | | |
| Total | 26.0 | millivolts | maximum |
| Fundamental | 17.0 | millivolts | maximum |
| Friction Torque | 0.07 | ounce-inches | maximum |
| Radial Play | 0.0006 | inches | maximum |
| End Play | 0.0010 | inches | ±0.0005 |
| Temperature Rise | 10.0 | degrees (C) | maximum |

Ⓔ denotes changes

AMSC N/A 1 of 2 FSC 5990

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:15Z
Check the source to verify that this is the current version before use.

TABLE II Military part number variant characteristics

| Military Part No. 1/ | A ± .010 | B ± .010 | C Maximum | Shaft Style | Terminal End | U +.0000 −.0002 |
|---|---|---|---|---|---|---|
| M20708/9-01C | .555 | .500 | 1.789 | Splined | Terminal Board | 1.872 |
| M20708/9-02C | .368 | .312 | 1.687 | Plain & Slotted | Wire Leads | 1.200 |
| M20708/9-03C | .430 | .375 | | | | |
| M20708/9-04C | .493 | .437 | | | | |
| M20708/9-05C | .555 | .500 | | | | |
| M20708/9-06C | .618 | .562 | | | | |

1/ Military part number M20708/9-01C shall be the NA10 standard

2/ The suffix letter following the numerical dash number corresponds to the latest modification letter in the type designation

TABLE III Military part number cross-references

| SUPERSEDED MILITARY PART NUMBERS | | NEW MILITARY PART NUMBERS |
|---|---|---|
| MIL-S-20708/9C | MIL-S-20708/9B | |
| M20708/9C-001 | M20708/9-001 | M20708/9-01C |
| M20708/9C-002 | | M20708/9-02C |
| M20708/9C-003 | | M20708/9-03C |
| M20708/9C-004 | | M20708/9-04C |
| M20708/9C-005 | | M20708/9-05C |
| M20708/9C-006 | | M20708/9-06C |

NOTE All line items shown in Table III refer to equivalent and interchangeable synchros of the same type designation modification. Part number changes do not affect form, fit, or function of the synchros listed therein

Custodians
Army-AR
Navy-AS
Air Force-85

Preparing Activity
Navy-AS

(Project 5990-0949-9

Review Activities
Army-MI, AV
Navy-OS, MC
Air Force-11, 17, 99
DLA-ES

User Activities

Source: https://assist.dla.mil -- Downloaded: 2026-10-19T08:15Z
Check the source to verify that this is the current version before use.