MILITARY SPECIFICATION

ACTIVATOR, ANTITANK MINE: PRACTICE, M1; PARTS FOR AND LOADING, ASSEMBLING AND PACKING

This specification is approved for use by the U. S. Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers quality assurance provisions and preparation for delivery for the Practice Activator: M1.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified (see 6.2), the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-48078	Ammunition, Standard Quality Assurance Provisions, General Specification For.

STANDARDS

MILITARY

MIL-STD-105	Sampling Procedures and Tables for Inspection by Attributes.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents form a part of this specification to the extent specified herein.

DRAWINGS (See 6.4)

U. S. ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

7548390	Box, Packing, Ammo For Activator Practice Ml.
7548391	Container, Metal For Activator Practice Ml.
9340668	Activator, Antitank Mine: Practice, Ml,

(Copies of specifications, standards and drawings required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.1.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Materials and parts. Materials and parts shall be in accordance with the applicable drawings, specifications and standards.

3.2 Activator assembly. The activator assembly shall comply with all requirements specified on Drawing (Dwg.) 9340668, all associated drawings, and with all applicable specifications and standards.

3.3 Output. The activator shall emit a smoke column of ten (10) feet, minimum height, and be visible at a minimum distance of one hundred (100) meters at the end of one (1) second, maximum time, when tested as specified in 4.5.1.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. The activator shall be fabricated and finished in a thorough, workmanlike manner. It shall be free of burrs, chips, sharp edges, cracks, unblended radii, surface defects, dirt, grease, rust, corrosion products, and other foreign matter. The cleaning method used shall not be injurious to the device nor shall the parts be contaminated by the cleaning agents. All required markings and stampings shall be neat and sharply defined. The activator shall be manufactured and processed in such a manner as to be uniform in quality, and free from defects that will affect life, configuration and serviceability.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The inspections specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated below and Table 1.

Part Description	Drawings	Quantity
Body	9340669	10
Cup	9340671	10
Plug, Activator	9340670	10
Puse	9340719	10
Cup, Closing	9340720	10
Cup, Igniter	9340721	10
Igniter Cup Assembly	9340722	10
Activator, Practice: M1	9340668	30

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-63529(AR)

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
	Activator, Practice, M1				See Below
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Body				
	(Dwg. 9340669) Examination for defects	10		3.2	4.4.2.1
	Cup				
	(Dwg. 9340671) Examination for defects	10		3.2	4.4.2.2
	Plug, Activator				
	(Dwg. 9340670) Examination for defects	10		3.2	4.4.2.3
	Fuse				
	(Dwg. 9340719) Examination for defects	10		3.2	4.4.2.4

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-63529(AR)

PARAGRAPH	TITLE: Activator, Practice, Ml	SHEET 2 OF 2	DRAWING NUMBER: See Below
			NEXT HIGHER ASSEMBLY: --

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Cup, Closing				
	(Dwg. 9340720) Examination for defects	10		3.2	4.4.2.5
	Cup, Igniter				
	(Dwg. 9340721) Examination for defects	10		3.2	4.4.2.6
	Igniter Cup Assembly				
	(Dwg. 9340722) Examination for defects	10		3.2	4.4.2.7
	Activator, Practice: Ml (Dwg. 9340668)				
	Examination for defects	30		3.2	4.4.2.8
	Output	30(a)		3.3	4.5.1

NOTES: (a) 10 samples shall be fired at -25°F-5°F; 10 samples shall be fired at 70°F ± 10°F; 10 samples shall be fired at +125°F + 5°F.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Tests Tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-63529(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Body				9340669
					NEXT HIGHER ASSEMBLY 9340668
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Major diameter external thread		0.40%(a)	3.2	Gage
102	Pitch diameter external thread		0.40%(a)	3.2	Gage
103	Minor diameter internal thread		0.40%(a)	3.2	Gage
104	Pitch diameter internal thread		0.40%(a)	3.2	Gage
105	Length of internal thread, min		0.40%(a)	3.2	Gage
106	Depth of internal thread cavity		0.40%(a)	3.2	Gage
107	Length to seat surface from external thread face		0.40%(a)	3.2	Gage
108	Depth of cavity from external thread face		0.40%(a)	3.2	Gage
109	Diameter of cup thread		0.40%(a)	3.2	Gage
110	Diameter before external thread, max		0.40%(a)	3.2	Gage
111	Total length		0.40%(a)	3.2	Gage
112	Counter bore missing at internal thread		0.40%(a)	3.2	Visual
113	External thread damaged		0.40%(a)	3.2	Visual
Minor					
201	Color incorrect (See Dwg. note)		0.65%(a)	3.2	Visual
202	Markings misleading, unidentifiable or missing		0.65%(a)	3.2	Visual
203	Poor workmanship		1.0%(a)	3.5	Visual

NOTES: a. See 4.4.5 for alternative method of sampling.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-63529(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.2	Cup				9340671
					NEXT HIGHER ASSEMBLY
					9340668
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Outside diameter		0.40%(a)	3.2	Gage
102	Smaller diameter of thread		0.40%(a)	3.2	Gage
103	Inside diameter, open thread end		0.40%(a)	3.2	Gage
104	Total length		0.40%(a)	3.2	Gage
105	Depth to seat bottom of thread from face, min		0.40%(a)	3.2	Gage
106	Inside diameter behind threads, min		0.40%(a)	3.2	Gage
107	Thickness through bottom, min		0.40%(a)	3.2	Gage
Minor					
201	Color incorrect		0.65%	3.2	Visual
202	Marking misleading, unidentifiable or missing		0.65%	3.2	Visual
203	Plastic workmanship unsatisfactory		0.65%	3.2	Visual
204	Poor workmanship		1.0%	3.5	Visual

NOTES: a. See 4.4.5 for alternative method of sampling.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-63529(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.3	Plug, Activator				9340670
					NEXT HIGHER ASSEMBLY
					9340668
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined.				
Major					
101	Major diameter of thread		0.40%(a)	3.2	Gage
102	Pitch diameter of thread		0.40%(a)	3.2	Gage
103	Length to end of thread from face, min		0.40%(a)	3.2	Gage
104	Length to flange		0.40%(a)	3.2	Gage
105	Total length		0.40%(a)	3.2	Gage
106	Diameter of flange		0.40%(a)	3.2	Gage
107	Thread damaged		0.40%(a)	3.2	Visual
Minor					
201	Color incorrect		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.5	Visual

NOTES: a. See 4.4.5 for alternative method of sampling.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-63529(AR)

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.4	Fuse		9340719
			NEXT HIGHER ASSEMBLY 9340668

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length		0.40%	3.2	Gage
Minor					
201	Poor workmanship		1.0%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-63529(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Cup, Closing				9340720
					NEXT HIGHER ASSEMBLY 9340722
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Inside diameter		0.40%(a)	3.2	Gage
102	Width		0.40%(a)	3.2	Gage
103	Thickness through bottom, min		0.40%(a)	3.2	Gage
104	Outside diameter, max		0.40%(a)	3.2	Gage
Minor					
201	Poor workmanship (including tears and punctures)		1.0%(a)	3.5	Visual

NOTES: a. See 4.4.5 for alternative method of sampling.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Cup, Igniter	1 OF 1	9340721
			NEXT HIGHER ASSEMBLY: 9340722

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Outside diameter		0.40%(a)	3.2	Gage
102	Inside diameter		0.40%(a)	3.2	Gage
103	Length		0.40%(a)	3.2	Gage
Minor					
201	Poor workmanship (including tears and punctures)		1.0%(a)	3.5	Visual

NOTES: a. See 4.4.5 for alternative method of sampling.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

Quality conformance inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-63529(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.7	Igniter Cup Assembly				9340722
					NEXT HIGHER ASSEMBLY 9340668
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Assembly loose		0.40%	3.2	Manual
102	Charge missing		0.40%	3.2	Manual
103	Charge on any exterior surface		0.40%	3.2	Visual
Minor					
201	Poor workmanship (Including tears and punctures)		1.0%	3.5	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-A-63529(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Activator, Practice: M1	1 of 1	9340668
			NEXT HIGHER ASSEMBLY
			--

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Output	50(a)		3.3	4.5.1
102	Total length, max		0.40%	3.2	Gage
103	Length to body shoulder, max		0.40%	3.2	Gage
104	Cup loose on body		0.40%	3.2	Manual
105	Cement on igniter cup (See Dwg.note)		0.40%	3.2	Visual
106	Cup not seated against body		0.40%	3.2	Visual
107	Thread damaged		0.40%	3.2	Visual
108	Part missing (Smoke composition, fuse, plug, gasket, cushion, igniter cup assembly)		0.40%	3.2	Visual
Minor					
201	Marking on cup misleading, unidentifiable or missing		0.65%	3.2	Visual
202	Poor workmanship		1.0%	3.5	Visual

NOTES: (a) The lot shall be rejected if two (2) or more samples fail to comply with the specified requirements.

DRDAR-QA Form 160 Jul 77 Replaces SARPA-QA Form 2567 Feb 74 Which is Obsolete

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examination and test prescribed herein is described in the Paragraph Reference Inspection Method column in the tables of Paragraphs 4.4.2.1 through 4.4.2.8. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See MIL-A-48078 and 6.3 herein.

4.4.5 Dimensional control of molded parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, and after a curing time for the parts has been approved (See Note), a sample of three (3) parts (as molded) from each cavity may be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of each cavity during production.

The inspection of the parts shall be performed only when the curing time for the parts has been reached. The inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of each 5000 parts or at the end of each shift, providing the number of parts produced during that shift is less than 5000 parts. Of the three (3) samples, one (1) sample shall be the last part produced. Parts that fail to comply with dimensional requirements after dimensional stability has been attained shall be classed defective.

If any defective parts are found during qualification of the cavity, the cavity producing the defective parts shall not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault may, after reworking, be returned to production providing they pass the qualification test as above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

NOTE: For establishing a curing time, dimensionally check ten (10) parts from each cavity at periodic intervals (e.g., every 30 min, 60 min, etc.), until dimensional stability is attained. The curing time will be from the time the part comes out of the mold until dimensional stability is attained. The inspection data used in determining the curing time shall be sent to ARRADCOM, Dover, NJ 07801, ATTN: DRDAR-QAT-M. If there is a change in material, cycle time, or if a cavity is reworked, or a new cavity is used, a new curing time shall be established and approved.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

4.5 Methods of inspection.

4.5.1 Output. The sample shall be activated by an Ml Pull Type firing device. For this test, wind velocity should not exceed fifteen miles per hour. Any sample failing to comply with all requirements specified in 3.3 shall be classed defective.

5. PACKAGING

5.1 Preservation and Packaging. Each activator shall be preserved and packaged in accordance with Dwg. 7548391.

5.2 Packing. The activator, preserved and packaged as above, shall be packed for shipment in accordance with Dwg. 7548390.

5.3 Marking. Marking of the fiberboard box and wood box shall be in accordance with Dwgs. 7548390 and 7548391.

5.4 Shipping. When activator packages of more than one lot are shipped together, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

6.1 Intended use. The activator covered by this specification is intended for use as a training device for practice mines.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. (See MIL-A-48078). Equipment designs shall be submitted as required to: Commander, U.S. Army Armament Research and Development Command, ATTN: DRDAR-QAT-I, Dover, New Jersey 07801. Request letter of submittal should state contractor, contract number, specification number, item nomenclature, and classification of defects and test paragraph number.

6.4 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under the cognizance of ARRADCOM.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

6.5 Distribution of Certificate of Compliance. Distribution of the certificate of compliance for each activator lot shall include the following:

Commander
ARRADCOM
ATTN: DRDAR-QAT-M
Dover, NJ 07801

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A193)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE MIL-A-63529(AR): Activator, Antitank Mine: Practice, M1; Parts For and Loading, Assembling and Packing

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*

TELEPHONE NO.

DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:03Z
Check the source to verify that this is the current version before use.