INCH-POUND

MIL-C-52299D
4 November 1991
SUPERSEDING
MIL-C-52299C
31 August 1983

MILITARY SPECIFICATION

CLAMP ASSEMBLY, TRESTLE BRACING

This specification is approved for use by Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope. This specification covers a clamp assembly and its components to be used with a trestle assembly (MIL-T-52150).

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

SPECIFICATIONS

FEDERAL

PPP-B-601 - Boxes, Wood, Cleated-Plywood.
PPP-B-621 - Boxes, Wood, Nailed and Lock-Corner.
PPP-B-636 - Boxes, Shipping, Fiberboard.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 5420

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-P-116 - Preservation, Methods of.
MIL-T-704 - Treatment and Painting of Materiel.

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129 - Marking for Shipment and Storage.
MIL-STD-889 - Dissimilar Metals.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Building 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Government drawings. The following Government drawings form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS

ME

TA13207E9719 - Clamp Assembly, Trestle Bridge.

(Copies of drawings required by contractors in connection with specific acquisition functions should be obtained from the USA Belvoir Research, Development and Engineering Center, ATTN: STRBE-JBS, Fort Belvoir, VA 22060-5606.)

2.2 Non-Government publications. The following document(s) form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation (see 6.2).

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

D 3953 - Strapping, Flat Steel and Seals.
D 4675 - Selection and Use of Flat Strapping Materials.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, PA 19103-1187.)

MIL-C-52299D(MI) Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

NATIONAL MOTOR FREIGHT TRAFFIC ASSOCIATION INC. AGENT

National Motor Freight Classification Rules.

(Application for copies should be addressed to the American Trucking Association, Inc., ATTN: Order Section, 2200 Mill Rd, Alexandria, VA 22314.)

UNIFORM CLASSIFICATION COMMITTEE AGENT

Uniform Freight Classification Rules

(Application for copies should be addressed to Uniform Classification Committee, ATTN: Tariff Publishing Officer, Rm 1106, 222 S. Riverside Plaza, Chicago, IL 60606.)

(Non-Government standards and other publications are normally available from the organizations that prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The clamp assembly and components shall be as shown on Top Assembly TA13207E9719 and as specified herein.

3.1.1 Drawings. The drawings forming a part of this specification are end product drawings. No deviations from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to insure correct fit, assembly, and operation of the clamp assembly. Any data (e.g., shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available upon request, for inspection by the contracting officer or the designated representative.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 6.3) in accordance with 4.3.

3.3 Materials. The materials shall be as specified herein and on the drawings. Materials not specified shall be selected by the contractor, and shall be subject to all provisions of this specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

3.3.1 Material deterioration prevention and control. The clamp assembly shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the clamp assembly may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the clamp assembly may be newly fabricated from recovered materials to the maximum extent practicable, provided the clamp assembly produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the clamp assembly.

3.4 Identification marking. The clamp assembly shall be metal die stamped as shown on the applicable drawing. Die stamping shall be legible after printing. When the identification marking is cast, the marking may be located other than as shown, provided it is on the outside surface of the movable half of the column clamp.

3.5 Treatment and painting. The clamp assembly and components, except pins and threaded portions of components, shall be cleaned, treated, and painted in accordance with MIL-T-704, type B. The contact surfaces of all dissimilar metals shall be painted prior to assembly.

3.6 Workmanship. All holes shall be drilled to full size or drilled undersize and reamed to full size through steel templates. All burrs and projections shall be removed from holes and edges of components. Components shall be free from porosity, fins, twists, bends, and cracks. Castings shall be free of blowholes, porosity, hard spots, shrinkage defects, cracks, and shall be smooth and well cleaned.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:14Z
Check the source to verify that this is the current version before use.

Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items shall meet all requirements of sections 3 and 5. The inspections set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling inspection, as part of manufacturing operations, is an acceptable practice to ascertain conformance to requirements, however, this does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to accept defective material.

4.1.2 Component and material inspection. The contractor is responsible for ensuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications and standards, as applicable.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.3).
b. Quality conformance inspection (see 4.4).
c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article shall be examined for the defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for inspection shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when 0 defects are found and rejected when one or more defects are found.

4.4.2 Examination. Sample selected in accordance with 4.4.1 shall be examined for defects specified in 4.5.1. Presence of one or more defects shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

4.5 Inspection procedure.

4.5.1 Examination. The clamp assembly or components, as applicable, shall be examined as specified herein for the following defects:

101. Dimensions not as specified and components missing or not as specified (see 3.1).
102. Materials not as specified (see 3.3).
103. Materials not resistant to corrosion and deterioration, or treated to be resistant to corrosion and deterioration of the applicable operating and storage environments (see 3.3.1).
104. Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other (see 3.3.1.1).
105. Contractor does not have documentation available for identification of materials, material finishes, or treatment (see 3.3.1.2).
106. Used, rebuilt or remanufactured components, pieces, and parts incorporated in the connecting bar (see 3.3.2).
107. Identification marking incorrect, missing, or illegible (see 3.4).
108. Treatment and painting not as specified (see 3.5).
109. Workmanship not as specified (see 3.6).

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of pack.

4.6.1.1 Unit of product. For the purpose of inspection, a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105. Sample size shall be determined by using MIL-STD-105, table I and table IIa. A lot shall be accepted when zero defects are found and rejected when one or more defects are found.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. One or more defects shall be cause for rejection.

110. Methods and containers not as specified for level A or B.
111. Unpainted and threaded surfaces not coated for level A.
112. Blocking, bracing, or securing not provided to prevent movement for level A or B.
113. Strapping not zinc coated for level A.
114. Gross weight or size exceeds the limitations of the fiberboard box for level B.
115. Fiberboard box not sealed and reinforced as specified for level B.
116. Marking missing, illegible, incorrect, or incomplete.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:14Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation. Preservation shall be level A or C as specified (see 6.2).

5.1.1 Level A. Unpainted and threaded surfaces of clamp assemblies, or clamp assembly bolts when procured separately from the clamp assembly, shall be coated with type P-1 preservative. The preservative shall conform to the applicable specification listed in and shall be applied in accordance with MIL-P-116.

5.1.2 Level C. Unpainted and threaded surfaces of clamp assemblies, or clamp assembly bolts when procured separately from the clamp assembly, shall be preserved in a manner to afford protection against deterioration and damage from the contractor to the initial destination.

5.2 Packing. Packing shall be level A, B, or C, as specified (see 6.2).

5.2.1 Level A. Ten complete clamp assemblies shall be packed in a close-fitting box conforming to PPP-B-621, class 2, style 2. Blocking and bracing to prevent movement shall be provided. Strapping shall be in accordance with ASTM D 3953, type 1 or 2, zinc-coated, size as applicable, and ASTM D 4675.

5.2.1.1 Clamp assembly bolts. When procured separately from the clamp assembly, the bolts shall be packed together in close-fitting boxes conforming to PPP-B-621, class 2, style optional; or PPP-B-601, overseas type, style optional. The bolts shall be secured within the box in a manner to prevent free movement. The boxes shall be closed in accordance with the appendix to the applicable box specification. Strapping shall be as specified in 5.2.1.

5.2.2 Level B. Ten complete clamp assemblies shall be packed as specified for level A, except the box shall be class 1. Strapping is not required to be zinc coated.

5.2.2.1 Clamp assembly bolts. Clamp assembly bolts procured separately from the clamp assembly shall be packed together in close-fitting boxes conforming to PPP-B-621, class 1, style optional; PPP-B-601, domestic type, style optional; or PPP-B-636, V3c, style optional. The bolts shall be secured within the box in a manner to prevent free movement. The gross weight or size of fiberboard boxes shall not exceed the limitations of the box specification, and the boxes shall be waterproof sealed and reinforced with bands of reinforced tape in accordance with the appendix to the box specification.

5.2.3 Level C. Ten complete clamp assemblies shall be packed together in a wooden box. The clamp assembly bolts, when procured separately from the clamp assembly, shall be packed together in wooden or fiberboard boxes. The boxes shall be close-fitting and shall assure carrier acceptance and safe delivery

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

to destination at lowest rating in compliance with Uniform Freight Classification Rules or National Motor Freight Classification Rules.

5.3 Marking. In addition to any special marking specified in the contract or purchase order (see 6.2), shipping containers shall be marked in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The clamp assembly and its components are intended for use in floating and fixed bridges for connecting the struts to the columns of the trestle assembly.

6.2 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.
b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).
c. When a first article is required for inspection and approval, and the number of units required (see 3.2, 4.3 and 6.3).
d. Level of preservation and packing (see 5.1 and 5.2).
e. Any special marking (see 5.3).

6.3 First article. When a first article inspection is required, the clamp assembly should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, approval of the first article test results and disposition of the first articles. Invitation for bids should provide that the Government reserves the right to waive the requirement for samples for first article inspection to those bidders offering a product which has been previously acquired or tested by the Government, and that bidders offering such products, who wish to rely on such production or test, must furnish evidence with the bid that prior Government approval is presently appropriate for the pending contract. Bidders should not submit alternate bids unless specifically requested to do so in the solicitation.

6.4 Subject term (key word) listing.

Bridge clamp
Clamp
Clamp assembly
Connector
Trestle clamp

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

6.5 Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - ME

Review activity:
Navy - MC

Preparing activity:
Army - ME

Project 5420-0191

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

RECOMMEND A CHANGE:	1. DOCUMENT NUMBER MIL-C-52299D	2. DOCUMENT DATE (YYMMDD) 911104

3. DOCUMENT TITLE: Clamp Assembly, Trestle Bracing

4. NATURE OF CHANGE (Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (if applicable) (2) AUTOVON	7. DATE SUBMITTED

8. PREPARING ACTIVITY

a. NAME Gerry Marlow	b. TELEPHONE (Include Area Code) (1) Commercial (703) 664-1806	(2) AUTOVON 354-1806
c. ADDRESS (Include Zip Code) US Army Belvoir RDE Center ATTN: STRBE-TSE Fort Belvoir, VA 22060-5606	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:14Z
Check the source to verify that this is the current version before use.