MILITARY SPECIFICATION

CRANE, TRUCK MOUNTED, HYDRAULIC

This specification is approved for use by the Mobility Equipment Research and Development Command, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a truck-mounted crane having a lifting capacity of not less than two thousand five hundred pounds (2,500 lbs.) at its maximum reach, and all hardware with instructions necessary to mount the crane on a specified truck.

2. APPLICABLE DOCUMENTS

2.1 Issues of documents. The following documents of the issue in effect on date of invitation for bids or request for proposal form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-V-173	- Varnish, Moisture-And-Fungus-Resistant (For Treatment of Communications, Electronic, and Associated Equipment.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-C-3580	- Crane and Crane-Shovels, Truck, Crawler, and Wheel-Mounted, Full-Revolving, and Their Attachments, Packaging of.

FSC 3950

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: US Army Mobility Equipment Research and Development Command, ATTN: DRDME-DS, Fort Belvoir, VA 22060 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:47Z
Check the source to verify that this is the current version before use.

MIL-E-52798 - Enamel, Alkyd, Camouflage.

STANDARDS

MILITARY

MIL-STD-129 - Marking For Shipment and Storage.
MIL-STD-130 - Identification Marking of US Military Property.
MIL-STD-461 - Electromagnetic Interference Characteristics Requirements For Equipment.
MIL-STD-1474 - Noise Limits For Army Materiel.

(Copies of specifications and standards required by contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids or request for proposal shall apply.

AMERICAN NATIONAL STANDARDS INSTITUTE (ANSI)

B30.15 - Mobile Hydraulic Cranes, Safety Standards For.

(Application for copies should be addressed to the American National Standards Institute, 1430 Broadway, New York, NY 10018).

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE Handbook.

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15086.)

SOUTHERN CALIFORNIA AIR POLLUTION CONTROL DISTRICT

Rule 102 - Photochemically Reactive Solvents.

(Application for copies should be addressed to the Southern California Air Pollution Control District, 434 South San Pedro Street, Los Angeles, CA 90013.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

TECHNICAL INFORMATION PACKAGE

(Application for copies should be addressed to US Army Mobility Equipment Research and Development Command, ATTN: DRDME-HM, Fort Belvoir, VA 22060.)

(Technical society and technical association specifications and standards are generally available for reference from libraries. They are also distributed among technical groups and using Federal agencies.)

3. REQUIREMENTS

3.1 Description. The crane shall be the type mounted on the deck or frame of a cargo truck. It may be articulating or telescoping boom type, or combination thereof. The boom shall be hydraulically capable of slewing, raising, lowering, extending and retracting. The crane shall be provided with a power winch for raising and lowering the crane hook. It shall be provided with power from the host truck. The crane shall be the manufacturer's current commercial product and shall have been in production, marketed, and in use for a minimum of one year preceding the solicitation for procurement. The introduction of product improvement changes in this one year period is acceptable. The crane shall be equipped with instruments, components, and accessories required for safe and effective operation and for installation on the specified truck. The crane shall be complete with all components that are standard with the manufacturer's products whether stipulated herein or not, together with such accessories as may be specified herein. The crane shall be furnished as a kit, complete with all components and instructions necessary for mounting on the specified truck (see 6.3).

3.2 First article inspection and demonstration (first produced crane). The contractor shall furnish one or more cranes as specified, mounted on Government furnished trucks for inspection and demonstration within the time frame specified (see 6.2) to prove that his production methods, choice of design detail and mounting procedures will produce cranes that, when mounted on the specified truck, will comply with the requirements of this specification. Inspection shall be as specified in Section 4 and shall be subject to surveillance and approval by the Government.

3.3 Safety. The crane when mounted on the truck shall comply with safety standards as specified in ANSI B30.15.

3.4 Human factors engineering. The characteristics of the crane shall provide for operation by personnel ranging from the small man clothed through the large man arctic-clothed, in accordance with SAE J833 and J925.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:47Z
Check the source to verify that this is the current version before use.

3.5 Electromagnetic interference. The electromagnetic interference emission characteristics of the crane shall conform to MIL-STD-461, Class IIC.

3.6 Truck crane interface. The contractor shall provide all hardware and instructions required to mount his crane on the specified truck (see 6.2), in a manner which will satisfy all provisions of this specification. The interface shall be compatible with the resisting bending moment (RBM) of the specified truck, and the interface shall be considered integral to the crane throughout this specification. Instructions and hardware shall be provided by the contractor which when used will retain the form, fit and function of the area of the truck's cargo tray not preempted by the crane.

3.6.1 Weight. Weight of the crane, with associated accessories required to mount crane on the specified truck, shall not exceed one thousand five hundred pounds (1,500 lbs.).

3.6.2 Bed space. The crane in folded position for travel shall not extend beyond the plan outline of the specified truck and shall not preempt or obstruct the use of more than 1,900 square inches of bed cargo area.

3.6.3 Height. The height of the crane in folded position for travel on the empty specified truck shall not exceed 102 inches above ground level.

3.6.4 Angles of approach, departure and interaxle and ground clearance. The interface with crane in folded position for travel shall not change the host truck's original angles of approach, departure, and interaxle and ground clearance capability.

3.7 Hydraulic system. The hydraulic system shall consist of all hydraulic components necessary for operation of slew, raise, lower, extend, retract or articulate functions. The system shall include a main relief and individual circuit reliefs to prevent overloading the crane. Means shall be incorporated into the hydraulic system to prevent any occurrence of underpressure in the hydraulic system. Constant flow valves shall be incorporated into the hydraulic system to meter the lowering of the boom system. Check valves shall be incorporated into each lift cylinder and extension cylinder circuit to prevent load drop in the event of hydraulic hose failure.

3.7.1 Crane hydraulic system controls. Controls to operate the crane shall comply with the requirements of SAE J298 and as specified herein.

3.7.1.1 Manual controls. Manual controls shall be provided and shall be the cross mounted type to allow for crane operation from either side of the specified truck.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:47Z
Check the source to verify that this is the current version before use.

3.7.1.2 Remote control. The crane shall be provided with a remote control system designed to provide full proportional control of all crane functions except stabilizers. The remote control shall be designed such that in case of failure, the manual cross mounted controls can be used immediately. A minimum of 20 feet of controller cable shall be provided. Controller and cable shall be carried in a storage box mounted close to the manual control station. Storage box shall be waterproof and designed to take shock loads.

3.7.2 Winch. The crane shall be equipped with a hydraulically operated winch for raising and lowering the hook. The cable shall be non-twist type with a safety load factor of at least five times the rated load. The line on the drum shall be of a length to allow the hook to touch the ground when the boom is fully extended and elevated with not less than five full turns remaining on the drum. The drum diameter to cable diameter shall be not less than 18:1 and the winch shall be equipped with a safety brake.

3.7.3 Stabilizer(s). Stabilizer(s), if required, to assure stability of the specified truck when handling rated loads under all conditions of this specification, shall be provided. Stabilizer(s) in travel position shall not protrude beyond the plan outline of the specified truck. Check valves shall be mounted on each extension cylinder to prevent loss of stability in the event of hose failure.

3.8 Performance and characteristics. The crane when mounted on the specified truck shall meet the performance requirements and characteristics specified herein.

3.8.1 Rated load. The crane shall have the capacity to lift, lower, and slew a 2,500 pound plus or minus 1 percent homogenous cube whose dimensions shall not be more than 48 inches or less than 40 inches.

3.8.2 Load placement. The crane shall be capable of placing the rated load to any pallet position of rated load size on the cargo bed of the truck on which the crane is mounted and to any pallet position of rated load size on the cargo bed of an identical truck without a crane when the trucks are parked parallel at least 18 inches apart.

3.8.3 Vertical load placement. The crane shall be capable of vertically raising the rated load from 6 inches below ground level to a height of 12 feet measured from the ground level to the bottom of rated load pallet when the center of the pallet is at least 10 feet from the truck's side edge.

3.8.4 Power slewing. The crane shall be capable of power slewing a minimum of 270 degrees.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:47Z
Check the source to verify that this is the currentversion before use.

3.8.4 Stability. The crane shall be located and configured to preclude upset of the empty truck parked on 5 degree side slopes when handling a 125 percent rated load at maximum extension when tested in accordance with SAE J765. Stabilizers, if required, shall be supplied by the contractor, and if supplied, shall extend and retract hydraulically.

3.8.5.1 Stability warning device. A warning device shall be provided which warns the operator whenever crane operation is attempted on side slopes which exceed 5 degrees from the horizontal.

3.8.6 Winch lift speed. The winch shall have a line speed, when lifting rated load, of not less than 30 feet per minute and when lowering rated load of not more than 40 feet per minute. The winch shall comply with SAE J706.

3.9 Lights. The crane shall be equipped with a minimum of two manually adjusted lights, a control switch, and equipment compatible with the host truck's electrical system. The control switch shall be wired into the truck's electrical circuit in a manner which will prevent use during blackout operations. Lights shall be positioned to light up hook and rated load. Brush guards shall be provided. Lighting shall be in accordance with SAE J598.

3.10 Power take off (PTO). When not furnished by the Government (see 6.2), the contractor shall provide a PTO which conforms to SAE J705, and in-cab panel mounted PTO controls. An in-cab indicator shall be provided which indicates to the operator that the PTO is engaged.

3.11 Load rating chart. Load rating charts conforming to ANSI B30.15 shall be prominently placed at both manual control stations. The chart and display plate shall conform to MIL-P-514, Type III, Composition C, of Type I, Grade A, Class 1 material.

3.12 Crane instruction plate. Three crane operating instruction plates shall be furnished conforming to MIL-P-514, Type III, Composition C, of Type I, Grade A, Class 1 material. One plate shall be installed on the truck instrument panel and one on each side of the crane at the operator's stations. The instruction plate shall contain as a minimum the following instructions:

(a) Position truck as near level as possible.
(b) Apply and set parking brake.
(c) Start truck engine.
(d) Engage hydraulic system to operate crane.
(e) Set hand throttle for desired engine speed.
(f) Operate crane functions in accordance with crane manufacturer's instructions.
(g) Stow crane in accordance with crane manufacturer's instructions.
(h) Unlock hand throttle and return to neutral.
(i) Disengage hydraulic system to crane.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

3.13 Camouflage paint. Unless otherwise specified (see 6.2), the crane shall be treated and painted in accordance with MIL-T-704, Type A and be top coated with a camouflage forest green paint conforming to MIL-E-52798.

3.14 Identification marking. The crane shall be identified in accordance with MIL-STD-130. The marking shall be applied to the crane on plates conforming to MIL-P-514, Type I, Style 1, Composition C, of Type I, Grade A, Class 1 material. Plates shall be attached by screws, bolts, or rivets in a location where the plates will be both visible and legible.

3.15 Lubrication. Lubrication means shall be provided for all moving parts that require lubrication. The types of lubricants shall be selected from and in accordance with SAE J754. All initial fills of lubricants shall be limited to the types approved by the component manufacturers. Grease lube fittings shall conform to SAE J534.

3.16 Fungus and moisture resistance. The electrical circuitry, including all components and connections, except as specified below, shall be protected from the effects of fungus growth and moisture by an overall treatment with a varnish conforming to MIL-V-173, Composition I or II, as applicable (see 3.6.1), with 1 percent copper 8-quinolinolate (by weight) based on the nonvolatile content of the varnish.

(a) Components or circuit elements that are inherently fungus and moisture resistant or which are hermetically sealed need not be treated.
(b) Components or circuit elements whose functions will be adversely affected by the varnish coating shall not be treated.

When used, the varnish shall be applied by spray, brush, or a combination of both to give a dry-film thickness of not less than 1 mil to component or element surfaces previously cleaned and prepared so that the surfaces are free from all foreign matter which would interfere with the adherence or function of the varnish.

3.16.1 Composition. Composition II shall be used only in the case when local air pollution regulations governing the application of varnish precludes the use of Composition I. When Composition II is used, the contractor shall provide evidence to the Government that the use of Composition II is required, and shall certify that the Composition II material complies with Rule 102, Southern California Air Pollution Control District.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:47Z
Check the source to verify that this is the currentversion before use.

3.17 Technical information package (TIP). The contractor shall complete the TIP to depict the crane and its components exactly as they will be furnished. Notation shall be made of all components which have not been in commercial use for a minimum of 1 year, and shall include identification of the component or part previously used. The contractor shall certify, by signing the TIP, that the items to be furnished are identical to those being procured for commercial use, except for modifications permitted in 3.1 of this specification. The TIP shall be submitted with all bids and proposals.

3.18 Identical items. All cranes furnished under this specification shall be physically and mechanically identical to the first article crane approved by the Government, except that product improvements incorporated in the contractor's standard commercial product lines are permitted at no cost, subject to the following:

Physical and performance characteristics defined herein have not been infringed;
New components involving Government selected repair parts are directly interchangeable with the superseded component or part;
The Government is notified of all changes and alterations a minimum of 15 days in advance of production commitment dates; and production effectivity, by serial number and date, has been identified; and
Appropriate changes are issued to the Government validated operating, maintenance, and parts manuals.

3.19 Sound level.

3.19.1 Personnel noise requirement. The noise at the operator's stations shall be less than or equal to 85dB(A). If the noise level exceeds 85dB(A), warning labels conforming to MIL-STD-1474 shall be applied. Also, a discussion conforming to MIL-STD-1474 relative to the hazard of this sound level shall be included in the operator manual provided by the contractor.

3.19.2 Exterior noise requirement. The noise level shall be 88dB(A) or less. If the exterior noise level exceeds 88dB(A), warning labels conforming to MIL-STD-1474 shall be applied. Also, a discussion conforming to MIL-STD-1474 relative to the hazards of this sound level shall be included in the operator manual provided by the contractor.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. The contractor is responsible for the performance of all inspection and demonstrations. Inspection and demonstrations will be witnessed by Government personnel. Except as otherwise specified in the contract, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspection or demonstrations set forth in the specification where such inspection or demonstrations are deemed necessary to assure supplies and services conform to the prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-22T21:47Z
Check the source to verify that this is the currentversion before use.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection and demonstration (see 4.3 and 4.4).
(b) Quality conformance inspection (see 4.6).
(c) Inspection of packaging (see 4.7).

4.3 First article crane inspection and demonstration. Prior to delivery, the manufacturer shall make one or more cranes available, selected at random from cranes being produced from production tooling, for first article crane inspection and demonstration. The crane and its components shall be inspected by comparison to the manufacturer's completed Technical Information Package (see 3.17), and published literature, calculations and test data, to verify compliance with this specification. The results of this inspection shall be presented in a test report (see 4.5). The crane shall then be subjected to a demonstration as specified herein. Permanent deformation, malfunction, failure to meet performance requirements, failure to complete any demonstration, or leakage of hydraulic fluid or lubricants shall be basis for rejection of the first article crane. If such deficiencies do arise, they shall be corrected and the first article inspection and demonstration shall be repeated.

4.4 Demonstration tests. The contractor shall perform the following demonstrations on first produced crane mounted on the truck specified (see 6.2) and include the test results in a report for Government review and approval prior to commencing production.

4.4.1 Demonstration conditions. Unless otherwise specified herein, the demonstration shall be conducted at the ambient temperature and climatic conditions existing at the place of demonstration. Only that maintenance established by the contractor and submitted as a maintenance schedule prior to commencement of the demonstrations shall be performed during the demonstrations.

4.4.2 Operational demonstration. Operational demonstration of the crane shall be performed by:

(a) Using the manual controls to operate the crane through forty cycles of loading and unloading the truck parked on a 5 degree side slope. Twenty cycles shall be controlled from each side of the truck. A cycle consists of loading and unloading 4 pallets of the rated load.
(b) Using the remote control to operate the crane through twenty cycles of loading and unloading the truck parked on a 5 degree side slope. A cycle consists of loading and unloading 4 pallets of the rated load.

Source: https://assist.dla.mil -- Downloaded: 20260-22T21:47Z
Check the source to verify that this is the current version before use.

4.4.3 Performance demonstration. Demonstrate that the crane has the following performance capabilities:

(a) Human factors characteristics which conform to the requirements of 3.4.
(b) Electromagnetic interference characteristics which conform to the requirements of 3.5.
(c) Hydraulic safety features and devices which conform to the requirements of 3.7.
(d) An overload shut-down system which conforms to the requirements of 3.7.
(e) Crane controls which conform to the requirements of 3.7.1.
(f) A stability warning device which conforms to the requirements of 3.8.5.1.

4.4.4 Stability. Demonstrate stability when tested in accordance with SAE J765 when handling 125 percent rated load on 5 degree slopes at maximum extension. Nonconformance to SAE J765 shall be cause for rejection.

(a) If stabilizers are required, demonstrate proper check valve functioning on each stabilizer extension cylinder. Nonconformance to 3.7.3 shall be cause for rejection.

4.4.5 Load placement demonstration. On at least a 5 degree side slope, park truck with crane (Truck A) parallel and at least 18 inches downslope from an identical truck without crane (Truck B). Demonstrate the ability to transfer the rated load pallet from any possible pallet position on Truck A to any pallet position on Truck B. Demonstrate the crane's ability to transfer the rated load pallet from any pallet position on Truck B to any pallet position on Truck A. Nonconformance to 3.8.2 shall be cause for rejection.

4.4.6 Vertical load placement demonstration. Park truck on level surface, place rated load's bottom 6 inches below the level surface with its center at least 10 feet from the truck's side edge. Raise rated load vertically to maximum lift height using winch. Measure and record distance from ground level to bottom of rated load pallet. Inability to raise load vertically, interference between any part of rated load and crane, and nonconformance to 3.8.3 shall be cause for rejection.

4.4.7 Winch. Perform applicable rating tests as specified in SAE J706. Nonconformance to SAE J706 shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 202610-22T21:47Z
Check the source to verify that this is the currentversion before use.

4.4.8 Winch lifting and lowering speed demonstration. Determine and record winch line speed when rated load is raised and lowered. Nonconformance to 3.8.6 shall be cause for rejection.

4.4.9 Crane rating-ANSI B30.15. Demonstrate conformance to ANSI B30.15. Nonconformance to ANSI B30.15 shall be cause for rejection.

4.4.10 Angles of approach, departure, interaxle, and ground clearance. Determine and record empty truck (with crane mounted) angles of approach, departure, and interaxle in accordance with SAE J894, and ground clearance capability. Nonconformance to 3.6.4 shall be cause for rejection.

4.4.11 Weight and dimensions of crane. Measure and record maximum weight of crane, truck bed space preempted by crane, and maximum height of crane. Nonconformance to 3.6, 3.6.1, 3.6.2, and 3.6.3, respectively, shall be cause for rejection.

4.4.12 Sound level testing.

4.4.12.1 Personnel noise level. The crane shall be tested in accordance with MIL-STD-1474, for steady state noise to determine the personnel noise level at the operator's stations. If the personnel sound level exceeds the requirement in 3.19, the labels and discussion provided for in 3.19.1 shall be supplied.

4.4.12.2 Exterior noise level. The crane shall be tested in accordance with MIL-STD-1474, exterior noise to determine the exterior noise level using test procedure SAE J88. If the exterior noise level exceeds the requirement specified in 3.19.2, the labels and discussion provided for in 3.19.2 shall be supplied.

4.5 First article demonstration report. The contractor shall prepare and submit the first article demonstration report to the contracting officer for approval within the time frame specified (see 6.2). The report shall include a detailed description of the inspection and demonstrations performed, deficiencies encountered and actions taken to correct the deficiencies.

4.6 Quality conformance inspection. Each crane shall be examined for dimensions, marking, workmanship, and components. Nonconformance to 3.18 shall be cause for rejection. Each crane shall then, with rated load attached, be operated through the complete range of all its functions. This operation shall be accomplished using the remote control and both cross mounted controls. Malfunction or leakage of hydraulic fluid shall be cause for rejection.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

4.7 Inspection of packaging. The preservation, packing and marking shall be examined to determine compliance with the packaging requirements in Section 5 of this specification.

5. PACKAGING

5.1 Preservation. Preservation shall be Level A, Level B, or Level C, as specified (see 6.2).

5.1.1 Level A. Each complete crane shall be preserved in accordance with MIL-C-3580, Level A.

5.1.2 Level B. Each complete crane shall be preserved in accordance with MIL-C-3580, Level B.

5.1.3 Level C. Each complete crane and all items issued with the crane shall be suitably preserved and packaged for retail distribution directly to a using customer and in a manner to assure carrier acceptance and safe delivery to destination at lowest ratings in compliance with carrier rules and regulations applicable to the mode of transportation. In addition, the following specific requirements shall be accomplished. Items with critical surfaces required for fit or function shall be provided protection by the use of preservative coating, volatile corrosion inhibitors, or dessicated packs. Items requiring protection from physical damage to surfaces, or which are fragile by nature shall be protected by wrapping, pack compartmentization, or cartonizing of the individual item. A guide shall be furnished indicating the preservation and packing materials to be removed in detail, and any other servicing required prior to placing the crane in operation.

5.2 Packing. Packing shall be Level A, Level B, or Level C, as specified (see 6.2).

5.2.1 Level A. Each complete crane preserved as specified in 5.1, shall be packed in accordance with MIL-C-3580, Level A.

5.2.2 Level B. Each complete crane, preserved as specified in 5.1, shall be packed in accordance with MIL-C-3580, Level B.

5.2.3 Level C. Each complete crane, preserved as specified in 5.1, shall be prepared for mobile shipment in a manner to assure carrier acceptance and safe delivery to destination at the lowest ratings of the carrier.

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

6.1 Intended use. The crane will be utilized for self-loading, self unloading, and positioning of unitized and palletized loads onto specified trucks (see 3.2) used by combat and combat support units worldwide.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

6.2 Ordering data.

(a) Title, number, and date of this specification.
(b) Time frame required for submission of first produced crane and number of cranes required (see 3.2).
(c) Complete identification of cargo truck with which crane must interface. Two each of these trucks to be provided as Government furnished equipment to the contractor (see 3.2 and 3.6).
(d) When color shall be other than specified (see 3.13).
(e) When PTO will not be furnished by the Government (see 3.10).
(f) Time frame for submitting the first article demonstration report (see 4.5).
(g) Level of preservation and level of packing required (see 5.1 and 5.2).

6.3 Recycled material. It is encouraged that recycled material be used, when practical, as long as it meets the requirements of this specification.

Custodian:
Army - ME

Review activities:
Army - AT
DLA - CS

Preparing activity:
Army - ME

Project 3950-A211

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.
NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE
MIL-C-52989(ME) Crane, Truck Mounted, Hydraulic

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

BUSINESS REPLY CARD

FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
USA Mobility Equipment R&D Command
ATTN: DRDME-DS
Ft. Belvoir, VA 22060

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T21:47Z
Check the source to verify that this is the current version before use.