# MILITARY SPECIFICATION

## COORDINATE CONVERTER MARK 54 MOD 0

This specification has been approved by the
Bureau of Naval Weapons, Department of the Navy.

## 1. SCOPE

1.1 Scope. - This specification establishes the requirements for the procurement of a Coordinate Converter Mk 54 Mod 0, BUWEPS LD 162276.

## 2. APPLICABLE DOCUMENTS

2.1 The following specifications, standards, drawings and publications, of the issue in effect on the date of invitation for bids, or request for proposal, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

| | |
|---|---|
| PPP-B-566 | Boxes, Folding |
| PPP-B-636 | Boxes, Fiber |
| PPP-B-676 | Boxes, Setup |

MILITARY

| | |
|---|---|
| MIL-P-116 | Preservation, Methods of |
| MIL-S-901 | Shockproof Equipment, Class HI (High Impact) Shipboard Application, Tests for |
| MIL-E-2036 | Enclosures for Electric and Electronic Equipment (Naval Shipboard use) |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

| | |
|---|---|
| MIL-E-5272 | Environmental Testing; Aeronautical and Associated Equipment, General Specification for |
| MIL-E-16400 | Electronic Equipment, Naval Ship and Shore; General Specification |
| MIL-E-17555 | Preparation for Delivery of Electronic, Electrical, and Electro-Mechanical Equipment and Associated Repair Parts |
| MIL-F-18870 | Fire Control, Optical and Associated Equipment Intended for Shipboard Use; the General Specification for Design and Procurement of |
| MIL-W-21927 | Weapons, Handling and Preparation for Delivery of; General Requirements for |

STANDARDS

MILITARY

| | |
|---|---|
| MIL-STD-108 | Definitions of and Basic Requirements for Enclosures for Electric and Electronic Equipment |
| MIL-STD-129 | Marking for Shipment and Storage |
| MIL-STD-167 | Mechanical Vibrations for Shipboard Equipment |

DRAWINGS

NAVY DEPARTMENT

| | |
|---|---|
| BUWEPS LD 162276 | Coordinate Converter Mk 54 Mod 0 |

PUBLICATIONS

BUREAU OF NAVAL WEAPONS

| | |
|---|---|
| QAP - 81089 | Quality Assurance Provisions for Coordinate Converter Mk 54 Mod 0 |



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

(Copies of specifications, standards, and drawings requested by the contractors in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.2 Other Publications. - The following documents form a part of the specification. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

NATIONAL BUREAU OF STANDARDS PUBLICATION

Handbook H28 — Screw Thread Standards for the Federal Services

(Application for copies should be addressed to the Superintendent of Documents, Government Printing Office, Washington 25, D. C.)

CONSOLIDATED CLASSIFICATION COMMITTEE PUBLICATION

Consolidated Freight Classification Rules

(Application for copies should be addressed to the Consolidated Classification Committee, 202 Chicago Union Station, Chicago 6, Illinois.)

AMERICAN TRUCKING ASSOCIATION, INC., PUBLICATION

Motor Freight Classification Rules

(Application for copies should be addressed to the Issuing Officer, American Trucking Association, Inc., 1424 16th St., N. W., Washington 6, D. C.)

## 3. REQUIREMENTS

3.1 Description. - The Coordinate Converter Mk 54 Mod 0 is used in conjunction with the Torpedo Director Mk 37 Mod 1 and the NC-2 Plotter. This converter converts Cartesian scaled voltage quantities of torpedo position, transmitted from the tropedo director, to polar synchro quantities for display by the plotter.

3.2 General Requirements.

3.2.1 Pre-production Samples. - Unless otherwise specified in the contract or order, pre-production samples of the converter shall be manufactured using the methods and procedures proposed for the production lot. The sample shall be tested as specified in Section 4 herein and is for the purpose of determining that, prior to starting production, the contractor's methods are capable of yielding items that comply with the technical requirements of the contract.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

3.2.2 Materials. - Unless otherwise specified in the contract, requisition or order, all materials and purchased parts entering into the final assembly of the converter shall conform strictly to the detailed requirements indicated on the applicable drawings, specifications and publications listed in BUWEPS LD 162276.

3.2.3 Finishes, Coatings, Construction and Dimensions. - Finishes, coatings, construction and dimensions for the converter shall be strictly in accordance with the applicable drawings, specifications and publications listed in BUWEPS LD 162276.

3.2.4 Moisture, Fungus and Corrosion. - The converter shall be rendered moisture, fungus and corrosion resistant in accordance with detail requirements specified in the drawings and specifications listed in BUWEPS LD 162276.

3.2.5 Marking. - Marking of assemblies, sub-assemblies and parts shall be in accordance with the applicable drawings listed in BUWEPS LD 162276.

3.2.6 Interchangeability. - Individual parts of assemblies, fabricated in agreement with their applicable drawings and specifications shall be interchangeable with mating parts of the unit and other like units. If deviation greater or smaller than the tolerances shown on the drawings or specifications is required for interchangeability, or if hand fitting beyond that shown on applicable drawings is required, then changes in dimensions are necessary and revision and correction of the applicable drawings are required. (See 3.2.9.)

3.2.7 Threads. - Unless otherwise specified, all threads shall be in accordance with the National Bureau of Standards Handbook H28. The class or fit for threads shall be as specified on the applicable drawings, and the "NO-GO" gaging practice shall be as set forth in the aforementioned Handbook H28.

3.2.8 Requests for Deviation. - Each request that a deviation be authorized shall have been submitted to the Procuring Activity, and the deviation shall have been authorized by the Bureau of Naval Weapons or by a Naval Activity delegated such authority, prior to the production of the affected item, or prior to the performance of a particular operation on the item. The deviation shall apply only to this specific item or operation. The request shall define the suggested deviation in sufficient detail to permit the Procuring Activity to evaluate its effect on performance and reliability, and the reasons for the suggested deviation shall be stated. Each request that a deviation be authorized, and the authorization, shall state specifically the extent of the departure, the identifying number of the item, the contractor (or bidder) and the contract number. A deviation



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

is essentially temporary in character, and usually represents a departure limited to a specific period, to a specific number of items, or to the contract to which it applies. It may require an equitable reduction in contract price if a decrease in the cost of performance results therefrom.

3.2.9 Conflicting Requirements. - Conflicting requirements arising between this specification or any specifications, publications, or drawings listed herein shall be referred in writing to the procuring agency or appointed agent for interpretation and clarification.

3.3 Performance Requirements and Product Characteristics. - The converter shall meet the following performance requirements and product characteristics.

3.3.1 Dielectric and Insulation Resistance. - Circuits of the converter which have a potential between 28 and 125 volts shall be capable of withstanding a potential of not less than 1000 VAC, without damage. Circuits having a potential of 28 volts or less shall be capable of withstanding a potential of not less than 300 VAC, without damage. Each circuit shall show an insulation resistance of not less than three megohms when a potential of 500 VDC is applied immediately after the circuit successfully passes the applicable dielectric test.

3.3.2 Function. - From inputs of distance, North or South, and East or West, the converter shall be capable of computing range and true bearing with an allowable maximum error of 300 percent and an allowable average error of 100 percent.

3.3.3 Endurance. - The converter shall be capable of withstanding the endurance test specified in 4.5.8, and thereafter shall show no damage and shall meet all the performance requirements and product characteristics of this specification.

3.3.4 Power System Variations. - The converter shall function in accordance with the performance requirements of this specification during the power variation test specified in 4.5.6.

3.4 Environmental Requirements.

3.4.1 Spraytightness. - The converter shall show no entry of water and shall meet the performance and other requirements as specified in this specification after being subjected to the spray-tight test specified in 4.5.1.

3.4.2 Inclination. - The converter shall be capable of withstanding inclination tests as specified in 4.5.2, and thereafter shall show no damage and shall meet all the performance requirements and product characteristics of this specification.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

3.4.3 Vibration.

3.4.3.1 Transportation. - The converter shall be capable of withstanding the vibration tests specified in 4.5.3.1 and thereafter show no damage and shall meet all the requirements of section 3.

3.4.3.2 Operating. - The converter, less pack and packaging, shall be capable of withstanding the vibration tests specified in 4.5.3.2. During and after the tests, the converter shall show no damage and shall meet all the performance requirements and product characteristics of this specification.

3.4.4 Shock.

3.4.4.1 Transportation, Storage and Handling. - The converter shall be capable of withstanding the shock tests specified in 4.5.4.1 and thereafter shall show no damage and shall meet all the requirements of section 3.

3.4.4.2 Operating. - The converter, mounted as specified in 4.5.4.2, shall be capable of withstanding shock tests as specified in 4.5.4.2. During and after the test, the converter shall show no damage and shall meet all performance requirements and product characteristics of this specification.

3.4.5 Climatic Condition. - The converter shall be capable of withstanding the climatic conditions specified in 4.5.5 and thereafter shall show no corrosion or damage and shall meet all the performance requirements and product characteristics of this specification.

3.4.6 Humidity and Fungus. - The converter shall be capable of withstanding humidity and fungus tests specified in 4.5.7, and thereafter shall show no corrosion or damage and shall meet all the performance requirements and product characteristics of this specification.

3.5 Clean-up. - Prior to and after final assembly, all parts, components and the assembly shall be thoroughly cleaned of loose, spattered, or excess solder, metal chips, and other foreign matter. Burrs and sharp edges as well as rosin flash shall be removed.

3.6 Workmanship. - The converter, including all parts and accessories, shall be constructed and finished in a manner to assure compliance with all requirements of this specification. Particular attention shall be paid to neatness and thoroughness of soldering, wiring, impregnation of coils, marking of parts and assemblies, plating, painting, riveting, machine screw assemblage, welding, brazing, and freedom of parts from burrs and sharp edges.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

3.6.1 The standards of workmanship exhibited in any approved pre-production sample, subject to any qualification stated in the Governments notice of approval, shall be determinative of the requirements of the contract relative to workmanship insofar as not specifically covered by applicable specifications.

## 4. QUALITY ASSURANCE PROVISIONS

4.1 Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified, the supplier may utilize his own facilities or any commercial laboratory acceptable to the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Gages. - The contractor shall provide himself with whatever gages are necessary and adequate to insure that the material to which this specification applies will meet the dimensional requirements shown on the applicable drawings. If so stipulated in the contract, order, or requisition, the Government will furnish drawings of pertinent Navy final inspection gages for guidance in the design of the contractor's inspection gages. However, such procedure shall not serve to relieve the contractor of his responsibility, in the design and manufacture of such gages as may be required in the satisfactory fulfillment of the contract requirements, but is intended to facilitate acceptance of all components and assemblies by Navy final inspection gages.

4.1.2 Classification of Inspections. - Inspection of the converter shall be classified as follows:

a. Pre-production inspection (paragraph 4.5)
b. Acceptance inspection (paragraph 4.4)
c. Periodic production inspection (paragraph 4.5).

4.2 Sampling

4.2.1 Pre-production Sampling. - A pre-production sample of one (1) converter manufactured in accordance with 3.2 shall be subjected to the pre-production tests detailed in 4.5 at an activity designated by the procuring activity. Acceptance of the pre-production sample shall be based on no defects in the sample. Further production of the converter by the supplier, prior to approval of the pre-production sample shall be at the supplier's risk.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

4.2.2 Periodic Production Sampling. - Periodic production samples shall be selected from units that have satisfactorily passed the acceptance inspections of 4.4. These samples shall be subjected to the tests of 4.5 at an activity designated by the procuring activity. Periodic production sampling shall be as follows:

Step 1. Upon initiation of production, randomly select one (1) unit from each group of ten (10) units. Upon satisfactory compliance of samples selected from three (3) consecutive groups, shift to Step 2.

Step 2. Randomly select one (1) unit from each group of twenty-five (25) units. Upon satisfactory compliance of samples from three (3) consecutive groups, shift to Step 3.

Step 3. Randomly select one (1) unit from each group of fifty (50) units. Continue with Step 3 for the balance of the contract or until a defective unit is found.

When a defective unit is found in any group, acceptance of all units on hand shall be withheld and the contractor shall:

a. Determine the cause and effect.

b. Take the necessary actions to correct or eliminate the defect from all units on hand and, if so directed by the procuring activity, from those units previously shipped.

c. Submit to the procuring activity for approval, the proposed corrective action to prevent recurrence of the defect.

Return to Step 1 and proceed as indicated when inspection is resumed.

4.3 Test Equipment. - Items of test equipment required to perform acceptance tests set forth in this specification are listed in QAP-81089

4.4 Acceptance Inspection.

4.4.1 Each converter delivered under contract shall be subjected to all the tests detailed in QAP-81089. Failure to satisfactorily pass any test specified therein shall be considered cause for rejection.

4.4.2 Test Conditions. - Unless otherwise specified, the converter shall be subjected to acceptance tests under the following conditions.

4.4.2.1 Temperature. - Room ambient 65 degrees F to 95 degrees F (18.33 degrees C to 35.0 degrees C).

4.4.2.2 Altitude. - Normal ground.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

4.4.2.3 Vibration. - None.

4.4.2.4 Humidity. - Room ambient to 95 percent relative (maximum).

4.4.3 Test and Inspection Equipment and Facilities. - The manufacturer shall furnish and maintain all necessary test equipment, facilities, and personnel for performing all acceptance tests. The test equipment shall be adequate in quantity, and when definite requirements are not specified they shall be of sufficient accuracy and quality to permit performance of the required acceptance tests.

4.4.4 Inspection and Test Procedures. - The converter shall be inspected and tested in accordance with the following procedures.

4.4.4.1 Inspection. - The converter shall be inspected in accordance with QAP-81089,(Process Verification, and Panel and Chassis Assembly Inspection).

4.4.4.2 Dielectric and Insulation Resistance. - The converter shall be subjected to the tests specified in QAP-81089,(Dielectric and Insulation Resistance Tests).

4.4.4.3 Function. - The converter shall be tested in accordance with the test procedures specified in QAP81089, (Performance Tests).

4.4.4.4 Preservation, Packing and Packaging. - Preservation, packing and packaging of the converter shall be inspected for conformance to Section 5 of this specification.

4.5 Pre-production and Periodic Production Inspection.

4.5.1 Spray Tightness. - The converter shall be tested in accordance with Standard MIL-STD-108 or Specification MIL-E-2036.

4.5.2 Inclination. - The converter shall be tested for satisfactory operation while undergoing the inclination tests outlined in Specification MIL-E-16400. At the conclusion of the tests, the converter shall meet the performance and other requirements specified in this specification.

4.5.3 Vibration.

4.5.3.1 Vibration, Transportation. - The converter, packaged and packed as specified in Section 5, shall be vibration tested as specified in **Weapons Requirement WR-11.**

4.5.3.2 Operating.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

4.5.3.2.1 Mounting. - The converter shall be mounted on the vibration testing machine to simulate as realistically as possible the service installation including vibration isolator or mounting devices. The converter shall be secured to the vibration testing machine in such a manner that the direction of vibration will be along each of the principle axes separately. The converter may be reoriented on the horizontal vibrating machine between each test, if necessary, to obtain such motion. At no time shall the converter be mounted in any other way than its normal position.

4.5.3.2.2 Test Procedures. - The converter shall be energized to perform its normal function in the operating condition and subjected to the vibration tests, specified in Standard MIL-STD-167, Type 1.

4.5.4 Shock.

4.5.4.1 Transportation, Storage and Handling. - The converter, packed and packaged as defined in 5., shall be subjected to the appropriate **shock isolation tests specified in Weapons Requirement WR-11. Selection of tests shall be in accordance with Weapons Requirement WR-11.**

4.5.4.2 Operating. - The converter shall be mounted on the standard mounting bracket of a shock testing machine in a manner most closely simulating actual service installation, including shock mounts. The converter shall be energized to perform its normal function in the operation condition, and shall be subjected to shock tests specified in Specification MIL-S-901.

4.5.5 Climatic Conditions. - The converter shall be tested for satisfactory operation at the ambient temperatures and conditions, and cold weather operation conditions as specified herein. When separate high temperature and low temperature chambers are not available, it is permissible to perform the hot and cold tests in the same chamber by raising the ambient air temperature from the low to the high temperature as specified in 4.5.5.2.

4.5.5.1 The converter shall be chilled to zero degrees F with power off and covers in place. When the air temperature inside the converter has dropped to within five degrees of the specified minimum, the power supply shall be turned on and the converter allowed to stand in a "ready" condition, but not operated for two hours. The converter shall then be tested for satisfactory operation.

4.5.5.2 After the tests described in 4.5.5.1, the ambient air temperature shall be raised to plus 110 degrees F with relative humidity between ninety-five percent and ninety-eight percent, the cover of the converter on, and the converter allowed to stand in a "ready" condition. The ambient air temperature rise shall not exceed 10 degrees per hour with a maximum of 30 degrees in 8 hours. The converter shall operate satisfactorily at



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

any time during this changing of the ambient air temperature. After 10 hours at 110 degrees, the converter shall be operated continuously for a minimum period of 50 hours under the conditions described and then tested for a satisfactory operation under these same conditions.

4.5.6 Power System Variations. - The converter shall be tested for satisfactory operation under power system variations as specified for line surges in Specification MIL-F-18870. This test may be run during the performance of any or all of the tests given in 4.5.1 to 4.5.5 inclusive of this specification.

4.5.7 Humidity and Fungus.

4.5.7.1 The converter shall be tested for resistance to humidity and fungus damage in accordance with the test of Specification MIL-E-5272.

4.5.7.2 Upon completion of the humidity and fungus tests, the converter shall be removed from the exposure chamber and operated for 24 hours. The converter shall then pass the dielectric and insulation resistance tests specified in 4.4.4.2.

4.5.8 Endurance. - After completion of all other tests of 4.5, the converter shall be operated and periodically tested for satisfactory operation until a total of 750 hours operating time has elapsed (including operating time elapsed during the performance of the tests under 4.5.1 through 4.5.7) and then shall again pass the test problems and operate satisfactorily. Test conditions during the endurance test may be any condition, or combination of conditions of inclination, ambient temperature, humidity, and power system variations that are specified in the other tests. Operating time shall be considered as time during which the converter is actually performing its intended use, and does not include time during which the converter is in "ready" or "standby" condition.

4.6 Failure of the converter to meet any of the requirements and tests of this specification shall be considered cause for rejection.

4.7 Waiver of Tests. - Tests specified in 4.5.3.1 and 4.5.4.1 may be waived by the procuring agency for level C packs only, provided the contractor guarantees safe delivery to the using activity.

4.8 Functional Tests. - At the conclusion of the tests specified in 4.5.3.1 and 4.5.4.1, functional and other tests, as applicable, shall be conducted on the converter to determine freedom from operational malfunction and compliance with all the requirements of section 3.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

## 5. PREPARATION FOR DELIVERY

5.1 Preservation and Packaging.

5.1.1 Level A. - In addition to the following, Level A packaging shall be in accordance with Specification MIL-P-17555.

5.1.1.1 Cleaning, Drying and Preservative Application. - Not applicable.

5.1.1.2 Unit Packaging. - Unit packaging of the converter shall be in accordance with Method IIb of Specification MIL-P-116. The unit package shall contain one converter packaged in paperboard boxes in accordance with Specifications PPP-B-566 or PPP-B-676.

5.1.1.3 Intermediate Package. - Not applicable.

5.1.1.4 Cushioning. - The unit package, and pack, shall incorporate sufficient cushioning material, bracing, or other adequate shock absorbing devices to ensure that the converter will meet all the requirements of Section 3 after being tested in accordance with 4.5.3.1 and 4.5.4.1.

At the time of packaging or packing, the moisture content of the cushioning material shall be no more than 5 percent. The pH range of the material shall be between 6.0 and 8.0.

5.1.2 Level B. - Not applicable.

5.1.3 Level C.

5.1.3.1 Cleaning, Drying and Preservative Application. - Not applicable.

5.1.3.2 Unit Packaging. - Unit packaging of the converter shall be in accordance with Method III of Specification MIL-P-116. The unit package shall contain one converter.

5.1.3.3 Intermediate Package. - Not applicable.

5.2 Packing.

5.2.1 Level A. - In addition to the following, Level A packing shall be in accordance with Specification MIL-P-17555.

5.2.1.1 Exterior Containers. - One (1) converter packaged as described in 5.1.1.2 shall be packed in a fiberboard box in accordance with Specification PPP-B-636, class 2.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

5.2.2 Level B. - In addition to the following, Level B packing shall be in accordance with Specification MIL-P-17555.

5.2.2.1 Exterior Containers. - One (1) converter packaged as described in 5.1.1.2 shall be packed in a fiberboard box in accordance with Specification PPP-B-636, class 1.

5.2.3 Level C. - The converter packaged in accordance with 5.1.3.2 shall be packed to afford protection against damage during shipment from the supply source to the first receiving activity for immediate use. Containers shall comply with Consolidated Freight Classification Rules or other common carrier regulations applicable to the mode of transportation.

5.3 Marking.

5.3.1 Special Marking. - None, unless otherwise specified.

5.3.2 Normal Marking. - In addition to the markings required by the contract or order, unit packages and shipping containers shall be marked in accordance with the requirements of Standard MIL-STD-129, including serial numbers.

6. NOTES

6.1 Intended Use. - The Coordinate Converter Mk 54 Mod 0 is intended for use in Fire Control Systems Mk 105 having wire guided capabilities and the NC-2 Plotter.

6.2 Ordering Data. - Procurement documents should specify the specific title, number, and date of this specification and other documents. Section 5 should be adhered to for selection of applicable levels of preservation, packaging, and packing. Selection of Level C shall not be made unless immediate use is definitely known.

6.2.1 The attention of the contracting officer is invited to the Quality Assurance Provisions and options in Specification MIL-P-116, and to para 4.7 of this document.

6.3 Criteria for use of proper level of preservation, packaging and packing shall be as follows:

For Level A. - This level shall be used for those items which are to be shipped to indeterminate destinations or stored under indeterminate conditions for redistribution anywhere.

For Level B. - This level shall be used only when it is definitely known that the item will be held in covered storage, either in domestic or overseas locations, for a period of 6 months or less.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

For Level C. - This level shall be used only when it is definitely known that the packaged item is to be shipped to domestic installations for immediate use at the first receiving activity.

6.4 Guarantee. - The contract or order shall include a requirement for a guarantee stating that any converter which fails to meet the requirements of this specification within one year after delivery because of a defect in material or workmanship or because of the vendor's failure to comply with the requirements of the applicable drawings and specifications shall be replaced by the vendor at no cost to the Government.

6.5 The contract or order shall include a sufficient number of extra converters to cover pre-production and periodic production inspection samples. All additional samples required because of failure of any converter to pass the prescribed periodic production inspections shall be provided and inspected at the expense of the supplier.



Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

# SPECIFICATION ANALYSIS SHEET

Form Approved
Budget Bureau No. 119-R004

INSTRUCTIONS

This sheet is to be filled out by personnel either Government or contractor, involved in the use of the specification in procurement of products for ultimate use by the Department of Defense. This sheet is provided for obtaining information on the use of this specification which will insure that suitable products can be procured with a minimum amount of delay and at the least cost. Comments and the return of this form will be appreciated. Fold on lines on reverse side, staple in corner, and send to preparing activity *(as indicated on reverse hereof)*.

SPECIFICATION
MIL-C-81089(Wep) Coordinate Converter Mark 54 Mod 0

| ORGANIZATION *(Of submitter)* | CITY AND STATE |
|---|---|
| | |

| CONTRACT NO. | QUANTITY OF ITEMS PROCURED | DOLLAR AMOUNT |
|---|---|---|
| | | $ |

MATERIAL PROCURED UNDER A

☐ DIRECT GOVERNMENT CONTRACT ☐ SUBCONTRACT

1. HAS ANY PART OF THE SPECIFICATION CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE?

A. GIVE PARAGRAPH NUMBER AND WORDING.

B. RECOMMENDATIONS FOR CORRECTING THE DEFICIENCIES.

2. COMMENTS ON ANY SPECIFICATION REQUIREMENT CONSIDERED TOO RIGID

3. IS THE SPECIFICATION RESTRICTIVE?

☐ YES ☐ NO IF "YES", IN WHAT WAY?

4. REMARKS *(Attach any pertinent data which may be of use in improving this specification. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity)*

| SUBMITTED BY *(Printed or typed name and activity)* | DATE |
|---|---|
| | |

DD FORM 1 APR 63 1426

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.

FOLD

DEPARTMENT OF THE NAVY

POSTAGE AND FEES PAID
NAVY DEPARTMENT

OFFICIAL BUSINESS

FOLD

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:58Z
Check the source to verify that this is the current version before use.