MILITARY SPECIFICATION

DISPENSER, GROUND: HE, M131 MINE SYSTEM LOADING, ASSEMBLING AND PACKING INCLUDING HE MINE, ANTIPERSONNEL AND ANTITANK

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings, and provides quality assurance provisions for the loading, assembling and packing of Dispenser and Mine, Ground: Antipersonnel, Antitank HE, M131 System.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise, specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, listed in the solicitation.

SPECIFICATIONS

MILITARY

MIL-S-45743 - Soldering, Manual Type High Reliability Electrical and Electronic Equipment.
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions General Specification For.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S. Army Armament, Munitions and Chemical Command, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 1345
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:37Z
Check the source to verify that this is the current version before use.

STANDARDS

MILITARY

MIL-STD-105	-	Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-286	-	Propellant, Solid: Sampling, Examination and Testing.
MIL-STD-331	-	Fuze and Fuze Components, Environmental and Performance Test for.
MIL-STD-810	-	Environmental Test Methods and Engineering Guidelines.

(Copies of specifications, standards, drawings, publication and other Government documents required by the suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the Contracting Officer.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS

U.S. ARMY ARMAMENT RESEARCH DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWING

9292865	-	Housing Assembly Out-of-Line Safety.
9332371	-	Test Specification for BLU 91/B Aerially Delivered Mine.
9332860	-	Control and Sensor (Schematic).
9332870	-	Remote Control Unit, Land Mine System M71.
9332913-1	-	Battery, Lithium - BA-5598/U.
9332919	-	Coil, Magnetic Coupling Device.
9333036	-	Control Indicator.
9337379	-	Mine, Antitank: High Explosive.
9337380	-	Spring Finger.
9337422	-	Mine AP HE.
9337504	-	Coil and Spacer Assembly.
9337505	-	Loaded Tube Assembly M131 System.
9337506	-	Dispenser and Mine, Ground AP M131.
9337507	-	Loaded Module Assembly M131 System.
9337511	-	Plate Assembly, Retainer.
9337525	-	Cable and Connector Assembly.
9337533	-	Wiring Diagram, MOPMS Dispenser.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:37Z
Check the source to verify that this is the current version before use.

2.1.3 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issue of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of document not listed in the DODISS shall be the issue of the nongovernment documents which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D792 - Specific Gravity and Density of Plastics by Displacement, Method A-1
ASTM B117 - Standard Method of Salt Spray (Fog) Testing

(American Society for Testing and Materials, 1917 Race Street, Philadelphia, Pennsylvania 19103).

2.1.4 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Material shall be in accordance with the applicable drawings, specifications, and standards.

3.2 Requirements of Dispenser and Mine Ground: Antipersonnel/Antitank M131. This section contains specific requirements pertaining to assembly of the Dispenser and Mine, Ground: Anti-Personnel/Antitank System.

3.2.1 Safe condition and circuit continuity verification.

3.2.1.1 Documentation of plan for safety in handling and processing of munitions. Prior to loading, the contractor shall document a detailed plan of the procedures to be employed during handling of the munition. This documentation shall describe, as a minimum, the procedures to be employed to assure that the temperature of the electronics assemblies, mine assemblies, do not exceed 165°F at any time during processing or storage and in such instances the time at 165°F shall not exceed one (1) hour unless otherwise specified herein. In no case shall continuous storage of the items be at a temperature above 100°F for a period exceeding 30 days.

Preparation of the plan shall be in accordance with data item description DI-R-5372 (tailored). (See 6.9)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

3.2.1.2 Housing assembly, out-of-line safety. The Housing Assembly, Out-Of-Line Safety Device (Drawing 9292865) shall be in the full safe condition as evidenced by presence and proper position of the following safety features or components after final assembly into dispenser:

a. Interrupter- Present and in safe position
b. Spring- Present
c. Bellows Actuator- Present and unactuated with .050 minimum GAP between it and the interrupter.

3.2.1.3 Dispenser activation circuit continuity/resistance. The Tube Drive Lines (Mine Battery Activation/Data Transfer Lines), Bellows Activator Line, Detonator Line and Magnetic Coupling Device Lines shall have the following circuit resistance when measured at the connector of the dispenser cable and connector assembly (Drawing 9337525).

Line	Resistance
Tube Drive Line	.275 + .075 ohms
Bellows Actuator Line	.200 + .070 ohms
Detonator Line	.500 + .400 ohms
Magnet Coupling Device Line	3.0 + 2.0 ohms

3.2.1.4 Soldering. All soldered electrical connections shall comply with MIL-S-45743.

3.2.1.5 Polarity of coil, Magnetic Coupling Device (MCD)-9332919. With a D.C. current applied to the magnetic coupling device (MCD) with plus polarity to the MCD pin identified with a white dot, the coil will produce a north magnetic field at the center of the coil and a south magnetic field at the outer shell.

3.2.1.6 Isolation of cable shields. The shields of the cable and connector assembly shall not be connected to the shell of connector M24308/4-3 nor shall there be electrical continuity between the shields and the MCU bracket of the loaded module assembly 9337515.

3.2.1.7 Dispenser sealing. The dispenser shall be sealed against moisture entry.

3.2.1.8 Dispenser safe separation time. The dispenser shall have a 5 minute safe separation time.

3.2.1.9 Dispenser function. The dispenser shall function as defined in 4.4.3.3.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

3.2.1.10 Lamp "Push-To-Test" check. The lamps on the module control unit shall light when pressed.

3.2.1.11 Self test. When the Control Indicator selector switch is turned the "Test" position the shall check the battery voltage and the "Battery" lamp will light indicating that battery voltage is correct; and the Control Indicator shall check internal circuits and the "CKT OK" lamp will light indicating successful internal tests.

3.2.1.12 Data load. With the Control Indicator control switch in the "Data Load" position, and after the proper data transmitted to the dispenser by a M71 remote control unit, the "Data In" light will light indicating that data was entered into the Control Indicator.

3.2.2 Mine Functions.

3.2.2.1 Target sensor functioning. The armed (AP) mine, with trip line sensors deployed, shall function upon application of a tensile load on the line as per drawing 9292972. The armed (AT) mine, when subjected to a valid target signature shall produce a high order detonation and perforation of one (1) inch thick and two one-half (1/2) inch thick hot rolled steel plates spaced four (4) inches apart, and shall produce spall on subsequent witness plates. Spall is defined as any evidence of particle indentation on the third witness plate.

3.2.2.2 Self-destruct (SD) function. The armed mine shall function properly within the self destruct time specified on Drawing as evidence by high order detonation of the main charge.

3.2.2.3 Recycled self-destruct (RSD) function. The self-destruct time out function of an armed and unevented mine shall be capable of being reset or recycled if the mine received a group identification code per 3.2.1.12. With a group identification code in the mine, the self-destruct time out function shall be reset to "zero" when the mine receives a RSD command from the Remote Control Unit (RCU) used to code the deploying dispenser per 4.4.3.3.3 at a R.F. field strength of 9.0 + 1.0 MV/M. Once reset, the mine shall function per 3.2.2.1 with the self destruct time measured from the time of the RSD command. The mine shall be capable of being recycled in this manner until the mine batteries are exhausted.

3.2.2.4 Command destruct function. If a mine received a group identification code per 3.2.1.12 it shall be capable of being destroyed on command. With a group identification code in the mine, the mine shall event when it receives a "Command Destruct" signal from the RCU used to code the deploying dispenser per 4.4.3.3.3 at an R.F. field strength of 9.0 to 1.0 MV/M.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:37Z
Check the source to verify that this is the current version before use.

3.2.2.5 Functioning after maximum time. The armed mine which fails to self destruct (SD) after the maximum (max.) SD time as specified on Drawing has elapsed, shall not be capable of being functioned by trip line sensor, target sensor command destruct or any other stimuli.

3.2.3 Controls in use of adhesives. The contractor shall develop a documented operational procedure for utilization of adhesives. This procedure shall provide for quality control of raw materials and processes to be used; details associated with intended use, such as proper handling, dispensing, mixing, curing cycles, pot life, etc., cleaning agents, safety precautions, special ventilation, drying or othe processes, and any other information of a similar nature that is considered necessary for the particular adhesive in use. This procedure shall be updated whenever a change is made such that the original assurance of product quality is affected. Preparation of this procedure shall be in accordance with Data Item Description DI-T-5372 (Tailored). (See 6.9).

3.3 Environmental conditions.

3.3.1 Operating temperature. The dispenser and mines shall perform as required over a temperature range of -35° to 145°F.

3.3.2 Storage temperature. The dispenser and mines shall be able to survive storage temperatures over a temperature range of -65° to +165°F.

3.3.3 Transportation vibration. The dispenser shall be safe to handle during transport and shall show no evidence of internal or external damage that will affect its function following transportation vibration test MIL-STD-331 T104.

3.3.4 Seven foot drop. The dispenser shall be safe to handle and show no evidence of internal or external damage that will affect its function following a seven (7) foot drop test.

3.4 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. All parts and assemblies shall be fabricated, loaded and assembled in a thorough workmanlike manner; and all manufacturing, processing, and assembling operations shall be correctly performed. All parts and assemblies shall be clean, free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any part, nor shall the parts be contiminated by the cleaning agent(s). Exterior surface coating shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined. Required packing shall be dry.

Source: https://assist.dla.mil -- Downloaded: 202640-22T19:37Z
Check the source to verify that this is the current version before use.

3.6 Data requirement. When specified in the contract, the contractor shall generate data in accordance with the requirements of the data item description cited in 6.9.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein, or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specification.

4.2 Classification of inspections. The following types of inspections shall be conducted on this item.

a. First Article Inspection.
b. Quality Conformance Inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the items and quantities listed in Table I.

4.3.2 Inspection and tests to be performed.

4.3.2.1 Components. See MIL-A-48078 and Table I specified herein.

4.3.2.2 Dispenser. The dispenser listed in Table I shall be subjected to the following tests:

4.3.2.2.1 Transportation Vibration (TV). In accordance with the requirement of MIL-STD-331, Test No. 119, Procedure 2.

4.3.2.2.2 Seven foot drop. The dispenser shall be safe to handle and show no evidence of internal or external damage that will affect its function following a seven (7) foot drop test.

4.3.2.2.3 Temperature shock. Subject the dispenser to a temperature shock described in MIL-STD-810, Method 503.1.

4.3.2.2.4 Hot temperature conditioning. Following the seven foot drop test the loaded dispenser listed in Table I shall be conditioned at +145°F for at least 4 hours per MIL-STD-810.

4.3.2.2.5 Cold temperature conditioning. Following the seven foot drop test the loaded dispenser listed in Table I shall be conditioned at -35°F for at least 4 hours per MIL-STD-810.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.3.2.2.6 Ambient temperature conditioning. Following the seven foot drop test the loaded dispenser listed in Table I shall be conditioned at 70°F for at least 4 hours.

4.3.2.2.7 Function tests. The dispenser shall function when tested in the modes and temperatures noted above and paragraph 4.4.2.6.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-48688 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Dispenser and Mine, Ground: Anti-personnel/Antitank M131 System				See Below NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Dispenser and Mine,Ground: AP/AT M 131 System (Dwg. 9337506)				
	Examination of defects	6		3.2	4.4.2.5
	Transportation TV test	6		3.2	4.3.2.2.1
	Seven Foot Drop test	6		3.2	4.3.2.2.2
	Temperature shock	6		3.2	4.3.2.2.3
	Hot temperature conditioning	2		3.2	4.3.2.2.4
	Cold temperature conditioning	2		3.2	4.3.2.2.5
	Ambient temperature conditioning	2		3.2	4.3.2.2.6
	Functioning	6		3.2	4.3.2.2.7 - 4.4.2.6

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

4.3.3 Rejection. See MIL-A-48078.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078.

Maximum lot size shall be no more than one (1) month production (30 calendar day period).

4.4.2 Examination. See MIL-A-48078 and 4.4.2.1 through 4.4.2.6. Unless otherwise specified in the Classification of Defects and Test tables, sampling plans and procedures for major and minor defects shall be in accordance with MIL-STD-105.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-48688 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.1	Coil and Spacer Assembly				9337504
					NEXT HIGHER ASSEMBLY 9337505
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None Defined				
Major					
101	Polarity of coil		100%	3.2	Test fixture
102	Correct connection of wires to coil		0.65%	3.2	Visual
103	Presence of parts:		0.65%	3.2	Visual
	1. Insulation sleeving				
	2. Flat cable				
	3. Solder sleeve 2 places				
	4. Spacer				
	5. Data transfer coil				
	6. Disk tape				
Minor					
201	Poor workmanship		4.0%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85

Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-48688(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Loaded Tube Assembly M13 System	1 OF 1	9337505
			NEXT HIGHER ASSEMBLY 9337507

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Spring finger does not press directly on leadwire		0.65%	3.2	Visual during assembly
102	Presence of spider and orientation		0.65%	3.2	Visual during assembly
103	Presence of obturator and orientation		0.65%	3.2	Visual during assembly
104	Orientation of mine, at 3 places		0.65%	3.2	Visual during assembly
105	Orientation of coil & spacer assy 3 places		0.65%	3.2	Visual during assembly
106	Orientation of retainer plate assy 3 places		0.65%	3.2	Visual during assembly
Minor					
201	Shear pin oriented symetrically		4.0%	3.2	Visual
202	Presence of caps, shear pin 2 places		4.0%	3.2	Visual
203	Presence of tape, pressure sensitive		4.0%	3.2	Visual during assembly
204	Presence of conical spring 2 places and orientation		4.0%	3.2	Visual during assembly
205	Presence of shear ring		4.0%	3.2	Visual
206	Poor workmanship		4.0%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 — Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER
4.4.2.3	Loaded Module Assembly M131 System				9337507
					NEXT HIGHER ASSEMBLY 9337506
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
1	Safe condition of out of line safety housing assembly		100%	3.2	Visual
Major					
101	Proper connection of leads, Note 3 of print		100%	3.2	Visual
102	Breech plug engagement with breech		0.65%	3.2	Gage
103	Presence of parts:		0.65%	3.2	Visual
	1. Foamed module				
	2. Detonating cord assy				
	3. Cable and connector assy.				
	4. Housing assy				
	5. Tube assy				
	6. Breech spacer				
	7. Pressure seal disc				
	8. Cartridge assy.				
	9. Performed packing				
	10. Breech plug				
	11. Sealing compound				
	12. Initiation system disk				
104	Continuity and circuit resistance		100%	3.2	Test Fixture
105	Solder workmanship		100%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-48688 (AR)

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER
4.4.2.3 (cont.)	Loaded Module Assembly M131 System				9337507
					NEXT HIGHER ASSEMBLY 9337506
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Presence of actuator and sealing compound		4.0%	3.2	Visual
202	Orientation of Cable and Connector Assy		4.0%	3.2	Visual
203	Cable secured by clamps		4.0%	3.2	Visual
204	Presence of parts		4.0%	3.2	Visual
205	Poor workmanship		4.0%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9337511
4.4.2.4	Plate Assembly, Retainer				NEXT HIGHER ASSEMBLY 9337505
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Presence of stake		0.65%	3.2	Visual
102	Orientation of borerider pin		0.65%	3.2	Visual
103	Presence of borerider pin		0.65%	3.2	Visual
104	Diameter of borerider pin		0.65%	3.2	Gage
Minor					
201	Poor workmanship		4.0%	3.5	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-D-48688 (AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.5	Dispenser and Mine, Ground: M131				9337506
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Proper connection of MCD coil and cable and connector assy.		100%	3.2	Visual
102	Continuity test of connection in M101		100%	3.2	4.4.3.2.2, 4.4.3.2.3, 4.4.3.2.4
103	Leak test		100%	3.2	4.4.3.2.5
104	MCU self test		100%	3.2	4.4.3.2.3
105	MCU data load test		100%	3.2	4.4.3.3.3
106	Presence of parts		100%	3.2	Visual
107	Presence of name plate data		0.40%	3.2	Visual
Minor					
201	Poor workmanship		4.0%	3.5	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T19:37Z
Check the source to verify that this is the current version before use.

DISPENSER AND MINE, GROUND: ANTIPERSONNEL ANTITANK M131 (DWG. 9337506)

					Dispenser Command						
					Hard Wire			R.F.			
Inspection Lot Size	Sample Size	Leak Test	Built In Test	Safe Separation	Hot	AMB	Cold	Rejection Inval Comm	Hot	AMB	Cold
26-50	4	4	4	4	1	-	1	2	1	-	1
51-150	6	6	6	6	1	1	1	3	1	1	1
151-500	8	8	8	8	1	1	2	4	1	1	2
501-1200	10	10	10	10	2	1	2	5	2	1	2
Accept/Reject Criteria											
Sample Size	4	1-2	0-1	0-1	0-1	-	0-1	0-1	0-1	-	0-1
	6	1-2	0-1	0-1	0-1	0-1	0-1	0-1	0-1	0-1	0-1
	8	2-3	0-1	0-1	0-1	0-1	0-1	0-1	0-1	0-1	0-1
	10	2-3	0-1	0-1	0-1	0-1	0-1	0-1	0-1	0-1	0-1

Sample Size (Mines Ejected)* (Dispensers)	Deployment	Deployed Mines Function	Hazardous Duds
84	0-1	5-6	0-1
126	3-4	8-9	0-1
168	3-4	11-12	0-1
210	6-7	15-16	0-1

* The number of ejected mines per dispenser is 21.

NOTE: 1. Environmental and safety constraints require that all testing be done at a proving ground.

Source: https://assist.dla.mil - Downloaded: 2026-02-22T20:07Z
Check the source to verify that this is the current version before use.

4.4.3 Testing.

4.4.3.1 Testing of Dispenser and Mine, Ground: Antipersonnel/Antitank M131. This section includes testing requirements that pertain to the Dispenser and Mine, Ground: Antipersonnel/Antitank M131.

4.4.3.2 Safety determination and circuit integrity.

4.4.3.2.1 Out-of-line safety. After assembly of the Housing Assembly, Out-Of-Line Safety Device (9292865) into the dispenser, the following conditions shall exists:

a. Interrupter- Present and in safe position
b. Spring- Present
c. Bellows Activator- Present and unactuated with .050 minimum gap between it and the interrupter.

4.4.3.2.2 Continuity/resistance of dispenser circuits. Prior to installation of the Module Control Unit (Drawing 9333036), circuit continuity of the following circuits as measured from the connector cable and connector assembly (Drawing 9337525) shall meet the requirements listed (Reference wire diagram, MOPMS Dispenser Drawing 9337533).

Circuit	Connector Pin Number	Requirement
Tube 1	3 and 16	.275 to .350 ohms
Tube 2	4 and 17	.275 to .350 ohms
Tube 3	5 and 18	.275 to .350 ohms
Tube 4	6 and 19	.275 to .350 ohms
Tube 5	7 and 20	.275 to .350 ohms
Tube 6	8 and 21	.275 to .350 ohms
Tube 7	9 and 22	.275 to .350 ohms
Bellows Actuator	12 and 24	.200 to .270 ohms
Detonators	13 and 25	.500 to .900 ohms
MCD Coil	14 and D1	3.0 to 5.0 ohms

4.4.3.2.3 Magnetic coupling and device polarity. With a D.C. current of 75 ± 25 milliampers applied to the connector of the dispenser cable and connector assembly (9337525) positive (+) lead on pin 14 and negative (-) on pin 1, a magnetic compass will point toward the MCD coil when it is brought near the coil on the coil center line.

4.4.3.2.4 Dielectric resistance crack. The dielectric resistance between the shields, acessed through pins 10 and 23 of Connector M24308/4-3 of cable and Connector Assembly 9337525, and the Control Indicator bracket of Loaded Modular Assembly 9337515 shall be 50 megohms or greater when measured with a 500 ± 50 volt megohometer.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:37Z
Check the source to verify that this is the current version before use.

4.4.3.2.5 Leak test. With an air pressure of .5 + .1 psi applied to the inside of the dispenser and allowed to stabalize, the pressure of the captive air shall not drop more than .05 psi in one (1) minute after the supply pressure has been shut off.

4.4.3.3 Dispenser function. Prior to any functional testing and with the Control Indicator knob in the "Position Safe", a BA-5598/U Lithium Battery (9332913-1) measuring no less than 14.4 volts (open circuit) will be installed into the control indicator of the dispenser. After assembly of this battery, the dispenser will function as follows:

NOTE: Hazardous condition. It is mandatory that the control knob of the control indicator be in the "Safe" position before assembly of the battery BU-5598/U.

4.4.3.3.1 Lamp check. The "Battery", "CKT OK" and "Data In" lamps must light when tested by pushing in on the lamp housing, Ref. 3.4.6.

4.4.3.3.2 Self test. When the control indicator select switch is turned to the "TEST" position, the "BATTERY" lamp on the control indicator face must light immediately. and the "CKT OK" lamp must light in less than 2 seconds. This test indicates that the battery voltage is adequate and that selected circuits within the control indicator and dispenser are functioning properly.

4.4.3.3.3 Data load. With the control indicator selector switch in the "Data Load" position, a M-71 remote controller unit (RCU) properly located between the guide rails of the dispenser cover and the RCU properly activated to load data into the dispenser; the "DATA IN" light on the face of the control indicator shall light immediately indicating that a group identification codes has been loaded into the dispenser, Ref. 3.2.1.12.

4.4.3.3.4 Arming of dispenser. The dispenser arming cycle begins when the selector switch on the control indicator is pushed in and turned to the "ARMED" position. and at 5 minutes and 35 seconds or later, the dispenser must accept a proper dispense command to eject the stored mines.

4.4.3.3.5 Safe separation time test. The dispenser must not accept a dispense command per paragraph 4.4.3.3.6 or 4.4.3.3.7 until at least 4 minutes and 35 seconds after the Control Indicator selector switch has been turned to the armed position paragraph 4.4.3.3.4 above, and must not eject stored mines.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:37Z
Check the source to verify that this is the currentversion before use.

4.4.3.3.6 Dispense command - R.F. After arming per paragraph 4.4.3.3.4, the dispenser shall accept a properly coded "DISPENSE" command of 9.0 ± 1.0 MV/M field strength sent by a M-71 RCU. "PROPERLY CODED" means the same code that was loaded into the dispenser in 4.4.3.3.3 was transmitted. If the dispenser was not "properly" coded paragraph 4.4.3.3.3, it must not accept a R.F. dispense command.

4.4.3.3.7 Dispense command - hardwire. After arming per paragraph 4.4.3.3.4 the dispenser shall accept a "DISPENSE COMMAND" from a M32 or M34 blasting machine, or an M57 firing device when properly connected to the "HARDWIRE" terminals on the MCU.

4.4.3.3.8 Rejection of invalid R.F. command. After arming, paragraph 4.4.3.3.4, the dispenser shall reject any incorrectly coded, 9.0 MV/M or greater field strength signal from M-71 RCU.

4.4.3.3.9 Deployment cycle. The deployment cycle shall begin upon receipt of a valid dispenser command, per paragraph 4.4.3.3.6. The cycle shall include activation of the batteries within the stored mines, coding of the mines and ejection of the mines 55 ± 20 seconds later.

4.4.3.3.10 Coding of mines. If a group identification code was loaded into the dispenser per paragraph 4.4.3.3.3 this identification code will be loaded into the mines after battery activation in the deployment cycle. Mines coded with a group identification code can have their self destruct time recycled or be "COMMAND DESTRUCTED" by the M-71 RCU that coded the dispenser per 4.4.3.3.3.

If the dispenser did not receive a group identification code per paragraph 4.4.3.3.3 and received a dispense command, paragraph 4.4.3.3.6, a "BLANK" code will be loaded into mines after battery activation in the deployment cycle. Mines coded with a "BLANK" code cannot have their self destruct timer reset, they cannot be "COMMAND DESTRUCTED" and they shall have only a single self destruct option 3.2.2.2. After deployment, the mines will be functioning per 3.2.2.1 or 3.2.2.2.

4.4.3.3.11 Mine field pattern. The ejected mines shall fall in an area defined as a half section of an annulus with a minor radius of 10 meters and a major radius of 40 meters.

4.4.3.3.12 Mine function. After deployment, the mines shall be capable of functioning in the prime target sensor mode. a self-destruct mode recycled self-destruct mode and command destruct mode.

4.4.3.3.13 Lot acceptance testing. The dispenser lot acceptance test shall be subjected to:

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:37Z
Check the source to verify that this is the current version before use.

a. Transportation vibration (TV) in accordance with the requirement of MIL-STD-331, Test No. 119, Procedure 2.

b. Seven foot drop. The dispenser shall be safe to handle and show no evidence of damage that will affect its function following a seven (7) foot drop test.

c. Temperature group: Hot ($145^{o}F + 5^{o}F$), Ambient ($70^{o}F + 10^{o}F$) and Cold ($-40^{o}F -5^{o}F$).

d. The preconditioned unit shall meet the functional requirements when tested per 4.4.2.6.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in the tables starting with 4.4.2.1. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

5. PACKAGING

5.1. Preservation and packaging.

5.1.1. Level A. Preservation and packaging shall be in accordance with Dwg. 9349988.

5.2. Packing.

5.2.1. Level A. Packing shall be in accordance with Dwg. 9349988.

5.3. Marking.

5.3.1. Level A. Marking shall be in accordance with Dwg. 9349988.

6. NOTES

6.1 Intended use. The Mine, Antitank/Antipersonnel: High Explosives covered by this specification is intended for use as an antitank and antipersonnel mine dispensed from the MOPMS Dispenser.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, U.S. Army Arament Research Development and Engineering Center, AMSMC-QAT-I(D), Dover, New Jersey 07801-5001.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:37Z
Check the source to verify that this is the current version before use.

6.4 Distribution of ammunition data cards and test data. Distribution of data cards shall include the following: Commander, U.S. Army Armament Research Development and Engineering Center, AMSMC-QAT-M(D), Dover, New Jersey 07801-5001.

6.5 Drawings. Drawings in Section 2 of this specification under the heading US Army Armament Research Development and Engineering Center (ARDEC), may also include drawings prepared by, and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, (ARRADCOM) or Picatinny Arsenal drawings. Technical data originally prepared by these activities are now under cognizance of ARDEC.

6.6 Definitions. For purposes of the tests in this specification, the following terms are defined:

a. Premature arming. Is defined as arming of the S&A assy (evidenced by actuation of piston actuator) before the minimum arming actuator output time specified on Drawing 9333026.

b. Premature detonation. Is defined as detonation of a mine (S&A armed) occurring before the minimum sensor enable time specified on Drawing 9333026.

c. Early self destruct. Is defined as detonation of the mine (S&A armed) occurring at or after the minimum sensor enable time specified on Drawing 9333026.

d. Enable time. If defined as the maximum sensor enable time specified on Drawing 9333026, plus 5 minutes, after application of the electromagnetic activation pulse.

e. Hazardous dud. Is defined as an armed mine capable of being functioned, after the Self Destruct time has elapsed, by target sensor, self-destruction or any other stimuli.(See 3.3.4.2)

f. Non-hazardous dud (Dud). Is defined as a mine incapable of being functioned, after the set SD time has elapsed, by any of the modes listed in 6.7e above. (See 3.3.4.2)

g. High order functioning. HE Mine: High order functioning will be evidenced by high order detonation of the Main charge train.

6.7 Submission of results from contractor conducted examinations and tests. Unless otherwise specified by the Contracting Officer, the contractor shall forward requested records of eximinations and tests to Commander, ARDEC, ATTN: AMSMC-QAT-M(D), Dover, New Jersey 07801-5001.

6.8 Submission of procedures. Submission of procedures specified in 3.6 shall be addressed to Commander, ARDEC, ATTN: AMSMC-QAT-M(D), Dover, New Jersey 07801-5001.

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:37Z
Check the source to verify that this is the current version before use.

6.9 Data requirements. Deliverable data required by this specification is cited in the following paragraphs:

Paragraph	Data Requirements	Applicable DID
3.2.3	Plan for control in use of adhesives	DI-T-5372 (Tailored)
3.2.1.1, 6.8	Safety Plans	DI-T-5372 (Tailored)
4.4.3	Quality Inspection	DI-R-1724
6.7	Test, Demonstration and Evaluation Report	
6.4	Ammunition Data Card	DI-L-1410

6.10 Subject term (key word) listing.

Dispenser, Mine

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A357)

Source: https://assist.dla.mil -- Downloaded: 202610-22T19:37Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-D-48688 (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil/ - Downloaded: 2026-02-22T19:37Z
Check the source to verify that this is the current version before use.