MILITARY SPECIFICATION

MINE, ANTI-PERSONNEL: HE, M74 LOADING, ASSEMBLING AND PACKING

This specification is approved for use within the U.S. Army Armament, Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification contains requirements not normally covered by the drawings, and provides quality assurance provisions for the loading, assembling and packing for one type of mine designated as Mine, Anti-personnel: HE, M74.

2. APPLICABLE DOCUMENTS

2.1 Government documents;

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation.

SPECIFICATIONS

MILITARY

MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, U.S Army Armament, Munitions and Chemical Command, Attn: AMSMC-QA, Dover, New Jersey 07801-5001 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

DISTRIBUTION STATEMENT A. Approved for public release; distribution is, unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

STANDARDS-

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein. Unless otherwise specified, the issues shall be those in effect on the date of the solicitation.

DRAWINGS (See 6.7)

US ARMY ARMAMENT RESEARCH DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

PRODUCT AND PACKAGING DRAWINGS

9243805	-	Pkg & Mkg for Shipping & Storage Container, Mine for Mine, AT: HE, M75; Mine, AP: HE, M74; or Mine, AT, Prac: M79 in Container, Ammo, Plastic: PA-83.
9292600		Mine, Anti-personnel: HE, M74.
9333791		Pkg for Plastic Ammunition Container: PA-83, for Mine,AP: HE, M74 or Mine, AT, Prac: M79.
12624467	-	M74 and M75 Mine Performance Requirements.
12624514	-	Pkg & Mkg for Shipping & Storage Container, Mine for Mine, AT: HE, M75; Mine, AP: HE, M74 or Mine, AT, Prac: M79.
12624515	-	Pkg & Mkg for Container, Fiberboard for Mine, AP: HE, M74; Mine, AT: HE, M75; or Mine, AT, Prac: M79.

INSPECTION EQUIPMENT DRAWINGS

9293021	-	Power Supply, Transmitter.
9293046	-	Transmitter Assembly.
9334065	-	Test Mine, AP Assembly.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

US ARMY MATERIEL DEVELOPMENT AND READINESS COMMAND

19-48-4116/95M-20PA1002- Unitization Procedures for Boxed Ammunition and Components on 4-Way Entry Pallets.

(Copies of specifications, standards, drawings, and publications listed above or in the item detail specification required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.)

2.1.3 Other publications. The following document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specfied, the issues of documents-not listed in the DODISS shall be the issue of the nongovernment documents' which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM-D-792 - Specific Gravity and Density of Plastic by Displacement, Method A-1.

(ASTM materials are available from ASTM, 1916 Race Street, Philadelphia, PA 19103.)

2.2 Order of Precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets or MS standards), the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings, specifications and standards.

3.2 Assembly. The assembly shall comply with all requirements specified on Drawing (Dwg.) 9292600 and all associated drawings and with all requirements specified in applicable specifications and standards.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

3.3 Pretest of main charge explosive. Each lot of Composition 34 Explosive used to load the case assembly to make the kill mechanism Dwg. 9292638 shall be statically tested for qualification prior to its use in production. The HE explosive fill, when initiated by normal production booster pellets, shall produce high order of detonation as evidenced by high degree of fragmentation of the Case Assembly Dwg. 929.2639 (See 4.5.2).

3.4 HE explosive exudation. The completely assembled Kill Mechanism with loading holes facing down shall not exude externally when conditioned at a temperature of 160° + 5°F for a period of twenty-four (24) hours (See 4.5.3).

3.5 Verification of safe condition of body assembly. Prior to assembly of explosive leads and closure plug, positive verification of safe condition of each body assembly shall be performed to assure the following:

a. Both battery cells are not activated (See Table II).

b. Firing Capacitor is shorted by shorting bar (See Table II).

c. S&A slider assembly is in safe position (distance from end of S&A to slider assembly, max) (See Dwg. 9292683).

Verification shall be performed as specified in 4.5.4.

3.6 Verification of body assembly circuit resistance. Prior to assembly of explosive leads, circuit resistance checks of each Body assembly shall be performed to verify that all tripline, receiver oil, pressure cartridge, S&A piston actuator and S&A detonator circuits meet the resistance values listed in Table II.

3.7 Anti-disturbance (AD) mode functioning. The mine shall function high order, as evidenced by a high degree of fragmentation of its case assembly, when subjected to the following conditions:

a. Initiated by a device simulating the spin and electromagnetic pulse feature of the M128 dispenser (See 4.4.5).

b. After the enable time has occurred, the mine shall be disturbed by tilting, rotating, jarring or any other tampering possible (See 4.5.6).

The mine shall not arm or detonate prematurely (See 4.5.6.2).

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:36Z
Check the source to verify that this is the current version before use.

3.8 Documentation of plan for safety in handling and processing of munitions. Prior to loading, the contractor shall document a detailed plan of the procedures to be employed during handling of the munition. This documentation shall describe, as a minimum, the procedures to be employed to assure that the temperature of the mine assemblies does not exceed 165°F at any time during processing or storage and in such instances the time at 165°F shall not exceed one (1) hour unless otherwise specified in this specification. In no case shall continuous storage of the items be at a temperature above 100°F for a period exceeding 30 days.

Submission of the plan shall be in accordance with data item description DI-T-5372 (tailored).

3.9 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.10 Workmanship. All Parts and assemblies shall be fabricated, loaded and assembled in a thorough workmanlike manner. All parts and assemblies shall be clean, free of burrs, sharp edges, cracks, dirt, grease, rust, and other foreign matter that may impair proper functioning. The cleaning method used shall not be injurious to any part, nor shall the parts be contaminated by the cleaning agent(s). Exterior surface coating shall be continuous except for a few light scratches not exposing base material. All required markings shall be neat and sharply defined.

3.11 Data requirement. The contractor shall generate data in accordance with the requirements of the data item description cited in 6.6.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:36Z
Check the source to verify that this is the current version before use.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set for the in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements' in the specification shall not releive the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual/ nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The following types of inspections shall be conducted,on this item.

a. First Article Inspection

b. Quality Conformance, Inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with the provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Part Description	Drawings	Quantity
Pellet, Booster	9292604	5
Kill Mechanism	9292638	10
Mine, Antipersonnel: HE, M74	9292600	10

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63304A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Mine, Antipersonnel: HE, M74				See Below
					NEXT HIGHER ASSEMBLY
					--
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Pellet, Booster (Dwg. 9292604)				
	Examination for Defects	5		3.2	4.4.2.1
	Kill Mechanism (Dwg. 9292638)				
	Examination for Defects	10		3.2	4.4.2.2
	Pretest of Main Charge Explosive, 1/	5		3.3	4.5.2
	HE Exudation Test, 1/	5		3.4	4.5.3
	Mine, Antipersonnel: HE, M74				
	Examination for Defects	10		3.2	4.4.2.4
	Anti-Disturbance Functioning Test, 1/	10		3.7	4.5.6

NOTES:

1/ Data item description DI-R-1724 applies for these tests.

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:36Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, inspection lots of mines shall contain:

a. Metal parts assemblies of one lot interfix number from one manufacturer.

b. Body Assemblies (DWG 9292680) from one lot interfix number from one manufacturer.

c. Explosive Composition B4 Type I from one lot interfix number from one manufacturer.

d. Booster Pellets (DWG 9292604) from one lot interfix number from one manufacturer.

e. PA509 Explosive Leads (DWG 9292601) from one lot interfix number. from one manufacturer.

Maximum lot size shall be no more than one (1) month production . 30 calendar day period).

4.4.2 Examination. See MIL-A-48078 and 4.4.2.1 to 4.4.2.9 herein.

a. Sampling plans. Unless otherwise specified in the classification of Defects and Test Forms, sampling plans and procedures far major and minor defects shall be in accordance with

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63304A(AR)

PARAGRAPH	TITLE			SHEET 1 OF 1	DRAWING NUMBER 9292604
4.4.2.1	Pellet, Booster				NEXT HIGHER ASSEMBLY 9292600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Length	(a)		3.2	Gage, 4.4.3.1
102	Diameter	(a)		3.2	Gage, 4.4.3.1
103	Cracks or laminations	(a)		3.2	Visual
104	Weight	(a)		3.2	Balance, 4.4.3.1
105	Density (when required, see Note 6 of dwg.)	(a)		3.2	4.5.1
Minor					
201	Poor workmanship	(a)	0.65%	3.10	Visual

NOTES:

(a) See 4.4.3.1 for sampling plan.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63304A(AR)

PARAGRAPH 4.4.2.2	TITLE Kill Mechanism		SHEET 1 OF 1		DRAWING NUMBER 9292638
					NEXT HIGHER ASSEMBLY 9292600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
	After assembly of Sleeves and Plugs				
1	Explosive on exposed surfaces		100%	3.2	Visual
Major					
	Prior to assembly of Sleeves and Plugs				
101	Cavity depth, min., 2 places		0.40%	3.2	Gage
102	Explosive weight, min.		0.40%	3.2	Scale
	After assembly of Sleeves and Plugs				
103	Cement between sleeves and plugs missing		0.40%	3.2	Visual
104	Plug improperly assembled, 2 places		0.40%	3.2	Visual
105	Sleeve improperly oriented or not seated, 2 places		0.40%	3.2	Gage
106	Pretest of Composition B4 Explosive 1/, 3/	5	0-1	3.3	4.5.2
107	Exudation Test. 2/, 3/	5	0-1	3.4	4.5.3
Minor					
	After assembly of Sleeves and Plugs				
201	Poor workmanship		0.65%	3.10	Visual

NOTES:
1/ Sample of five (5) Kill Mechanisms per lot of Comp. B4: For Qualification of lot.
2/ Sample of five (5) Kill Mechanisms per lot of Kill Mechanisms.
3/ Data item description DI-R-1724 applies for the tests. Submit each time test is performed.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 2		DRAWING NUMBER 9292683
4.4.2.3	Loaded Body Assembly				NEXT HIGHER ASSEMBLY 9292600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical					
	Prior to assy of Explosive Leads & Closure Plug				
1	Distance from end of S&A to slider assy, max.	100%	3.5	4.5.4	
2	Resistance across shorted Firing Capacitor	100%	3.5	4.5.4	
Major					
	Prior to assy of Explosive Leads				
101	Resistance of Tripline Sensors, max, 4 places		100%	3.6	4.5.5
102	Resistance of Receiver Coil Circuit		100%	3.6	4.5.5
103	Resistance of Pressure Cartridge		100%	3.6	4.5.5
104	Resistance of Piston Actuator		100%	3.6	4.5.5
105	Resistance of Detonator		100%	3.6	4.5.5
106	Unactivated cell voltage, max, 2 places		100%	3.5	4.5.4

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

PARAGRAPH	TITLE		SHEET 2 OF 2		DRAWING NUMBER 9292683
4.4.2.3	Loaded Body Assembly				NEXT HIGHER ASSEMBLY 9292600
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	After assy of Explosive Leads & Closure Plug				
107	Any Explosive Lead(s) missing or improperly assembled (loose or green end not visible)		0.40%	3.2	Visual/Manual
108	Any Lead Retainer(s) missing or improperly assembled		0.40%	3.2	Visual
109	Closure Plug missing or not flush to below flush		0.40%	3.2	Visual
Minor					
	After assy of Explosive Leads & Closure Plug				
201	Poor workmanship		0.65%	3.10	Visual

NOTES:
1. Data item description DI-R-1721 applies to the Critical Defects - supply report whenever defects are found.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63304A(AR)

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Mine, Antipersonnel: HE, M74				9292600
					NEXT HIGHER ASSEMBLY ---
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
	Prior to assy of Body Assembly				
101	Any Booster Pellet missing		0.40%	3.2	Visual
102	Any Booster Pellet retaining tape missing or improperly installed		0.40%	3.2	Visual
103	Preform packing (O-Ring) missing or not greased (Upper Housing Assy end)		0.40%	3.2	Visual
	After completed Mine Assembly				
104	Any cover loose		0.40%	3.2	Visual/Manual
105	Crimp improper, both sides of mine		0.40%	3.2	Visual
106	Overall diameter, max		0.40%	3.2	Gage
107	Overall height, max		100	3.2	Gage
Minor					
201	Marking missing, incorrect or illegible		0.65%	3.2	Visual
202	Paint damaged or incomplete		0.65%	3.2	Visual
203	Poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Pkg for Plastic Ammunition Container: PA-83, for Mine, AP: HE, M74 or Mine, AT, Prac: M79	1 OF 1	9333791
			NEXT HIGHER ASSEMBLY 9243805

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any mines missing from container		0.40%	3.2	Visual/Manual
102	Retainers (2) not secured properly		0.40%	3.2	Visual/Manual
103	Marking missing, incorrect or illegible		0.40%	3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.10	Visual

NOTES:

AMSMC Form 1570, 1 Feb 85 Replaces DRSMC-QA (D) Form 160, 1 Aug 83, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63304A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Pkg & Mkg for Shipping & Storage Container, Mine for Mine, AT: HE, M75; Mine,AP: HE, M74; or Mine, AT, Prac: M79, In cntr, Ammo,Plastics: PA83	1 OF 1	9243805
			NEXT HIGHER ASSEMBLY ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
	Prior to Securing Cover				
101	Marking missing, incorrect or illegible		100%	3.2	Visual
102	Bag(s) of Desiccant missing		0.40%	3.2	Visual
103	Filler on bottom missing		0.40%	3.2	Visual
104	Any plastic Ammo Container missing		0.40%	3.2	Visual
105	Number of Slotted Fillers not adequate for tight packing		0.40%	3.2	Visual/Manual
106	Slotted Fillers positioned incorrectly		0.40%	3.2	Visual
107	Number of top fillers not adequate for tight packing		0.40%	3.2	Visual/Manual
108	Dirt or foreign material on Gasket or Gasket Track (Cover and Base)		0.40%	3.2	Visual
109	Any lifting strap missing (8 required)		0.40%	3.2	Visual
	After Securing Cover				
110	Vent Assembly Cap not hand tight		0.40%	3.2	Manual
111	Humidity Indicator torqued improperly		0.40%	3.2	Gage
112	Fastener Nut(s) torqued improperly		0.40%	3.2	Gage
113	Vent Assembly Nut torqued improperly		0.40%	3.2	Gage
114	Humidity indicator dots not proper color		100%	3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63304A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Pkg. & Mkg for Container, Fiberboard for Mine,AP: HE, M74: Mine,AT: HE,M75; or Mine, AT, Prac: M79	1 OF 1	12624515
			NEXT HIGHER ASSEMBLY 12624514

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Any mines missing from container		0.40%	3.2	Visual/Manual
102	Closure; not properly sealed		0.40%	3.2	Visual/Manual
103	Markings missing, incorrect or illegible		0.40%	3.2	Visual
Minor					
201	Poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

MIL-M-63304A(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.8	Pkg & Mkg for Shipping & Storage Container, Mine for Mine, AT: HE, M75; Mine,AP: HE, M74 or Mine, AT, Prac: M79	1 OF 1	12624514
			NEXT HIGHER ASSEMBLY ---

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
	Prior to Securing Cover				
101	Marking missing, incorrect or illegible		100%	3.2	Visual
102	Bag(s) of Desiccant missing		0.40%	3.2	Visual
103	Filler on bottom missing		0.40%	3.2	Visual
104	Any Fiberboard Ammo Container missing		0.40%	3.2	Visual
105	Number of Slotted Fillers not adequate for tight packing		0.40%	3.2	Visual/Manual
106	Slotted Fillers positioned incorrectly		0.40%	3.2	Visual
107	Number of top fillers not adequate for tight packing		0.40%	3.2	Visual/Manual
108	Dirt or foreign material on Gasket or Gasket Track (Cover and Base)		0.40%	3.2	Visual
	After Securing Cover				
110	Vent Assembly Cap not hand tight		0.40%	3.2	Manual
111	Humidity Indicator torqued improperly		0.40%	3.2	Gage
112	Fastener Nut(s) torqued improperly		0.40%	3.2	Gage
113	Vent Assembly Nut torqued improperly		0.40%	3.2	Gage
114	Humidity indicator dots not proper color		100%	3.2	Visual
Minor					
201	Fiberboard Ammo Containers not positioned properly		0.65%	3.2	Visual
202	Poor workmanship		0.65%	3.10	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202640-23T02:36Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

4.4.2.9 Mine, Antipersonnel: HE, M74

LOT ACCEPTANCE TEST (AMBIENT), 3/

Mine Assy Insp. Lot	Sample Size	AD Mode	Premature Arming 1/	Premature Detonation 1/	Early SD 2/	Low Order Function And/Failure To Function	Requirement	Test Method
501-1200	20	20	0-1	0-1	2-3	1-2	3.7	4.5.6
1201-3200	32	32	0-1	0-1	3-4	1-2	3.7	4.5.6
3201-10,000	50	50	0-1	0-1	5-6	2-3	3.7	4.5.6

1/ Premature arming and detonation is defined in 4.5.6.2. CRITICAL.
2/ Early self destruct (SD) is defined in 4.5.6.2.
3/ Data item description DI-R-1724 applies for LAT.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

4.4.3 Testing

4.4.3.1 Dimensional and weight control of booster pellet (See Dwg. 9292604). The dimensions and weight specified in 4.4.2.1 for the booster pellets shall be checked by randomly selecting three (3) samples from the quantity produced by each press during a period not to exceed four (4) hours. The quantity represented by the samples shall be identified and not used in production until the dimensional and weight inspections are completed. If any sample fails to comply with the dimensional requirements, the quantity of parts represented by the sample shall be subjected to 100% inspection. If any sample meets the dimensional requirements but fails to comply with the applicable weight requirement, its density shall be determined as specified in 4.5.1. The above inspection shall also be performed each time a new lot of explosive material is used.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed in this specification is identified, “either directly or by reference, in the “Paragraph Reference\Inspection Method” column of the First Article or Quality Conformance Inspection Forms herein. The contractor shall submit inspection equipment designs to the Government for approval in accordance with the terms of the contract. See Section 6 of MIL-A-48078, and 6.3 herein.

4.4.5 M128 mine dispenser simulator. The Simulator Device(s) shall simulate the M128 Dispenser launch features of spin and electromagnetic pulse environments to initiate the arming and the batteries of the mine followed by emplacement of the mine in a test container or pit for subsequent functioning. SPIN: 3075 to 3600 RPM. Transmitter Assembly: can be set for normal or long (extended) Self Destruct as required (See Dwg’s 9293021 and 9293046).

4.5 Methods of inspection

4.5.1 Density of booster pellet. Density of the booster pellet, when required - See 4.4.3.1 and Dwg. 9292604, shall be performed in accordance with the procedure specified in ASTM D792 - "Specific Gravity and Density of Plastics of Displacement", Method A-1. The contractor may use alternate procedures than that specified herein, subject to the approval of the Government. If the sample of pellets from 4.4.3.1 fails to comply with the density requirements, the quantity of parts represented by the sample shall be subjected to 100% weight inspection. (Non-destructive inspection)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

TABLE II

Body Assembly Electrical Checks

Prior to Loading

ELECTRICAL CHECK	TEST POINTS	REQUIREMENT
SHORT ACROSS FIRING CAPACITOR	13 to 8	1.25 OHMS MAX.
UNACTIVATED BATTERY CELL VOLTAGE	18 to 8	0.005 VDC MAX./CELL
UNACTIVATED BATTERY CELL VOLTAGE	18 to 10	
TRIPLINE RESISTANCE (#1 & 7)	3 to 8	6.0 OHMS MAX.
TRIPLINE RESISTANCE (#2 & 6)	4 to 8	6.0 OHMS MAX.
TRIPLINE RESISTANCE (#3 & 8)	1 to 8	6.0 OHMS MAX.
TRIPLINE RESISTANCE (#4 & 5)	2 to 8	6.0 OHMS MAX.
RECEIVER COIL RESISTANCE 1/	5 to 8	0.8 - 1.7 OHMS
PRESSURE CARTRIDGE RESISTANCE	19 to 8	2.0 - 6.1 OHMS
PISTON ACTUATOR RESISTANCE	20 to 8	4.0 -11.0 OHMS
DETONATOR RESISTANCE	17 to 8	3.0 -12.5 OHMS

1/ The Receiver Coil is in parallel to a series connected shorting bar and Electric Battery Primer.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

4.5.2 Pretest of composition B4 type 1 explosive. Each lot of explosive used to manufacture the main charges shall be tested prior to use in production in accordance with the following:

a. Test Mine, AP Assembly, M74 - Part No. 9334065-1 shall be the test vehicle.

b. Five (5) Test Mine Samples, with case assemblies filled with Composition B4 Type 1 shall be used in qualification of the explosive lot.

c. Each sample mine shall be marked with the weight of the kill mechanism and lot number of the explosive.

d. Normal production S&A explosive leads (PA 517), explosive leads (PA 509) and booster pellets shall be used in sample mines.

e. The sample mines shall be functioned in a test pit or inclosure for containing debris for later evaluation and determination of order of detonation of H.E. charge.

f. Observation shall be made for compliance with requirements of 3.3. Failure of any sample shall reject the lot. Any Kill Mechanism which fails to function due to initiator, explosive leads (PA 517), explosive leads (PA 509) or booster pellets shall be considered a no test and a replacement test mine shall be tested in its place.

Results of test shall be supplied in accordance with 6.6.

4.5.3 HE explosive exudation test. A sample of five (5) Kill Mechanism, Dwg. 9292638, with loading holes facing down shall be placed in conditioning chamber and subjected to a temperature of 1600 + 5°F for a period of twenty-four (24) hours. Observation shall be made for compliance with requirement of 3.4. Any failure shall reject the lot of kill mechanisms. (Destructive test) Results of test shall be supplied in accordance with 6.6.

4.5.4 Verification of safe condition of body assembly. Prior to assembly of explosive leads and closure plug, positive verification of each Body Assembly shall be performed. A ten (10) megohm input impedance voltmeter shall be used to test battery cells and a milliohmmeter having a test current of one milliamp or less shall be used to test short across capacitor.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

A flush pin gage shall be used to measure safe position of slider assembly. Observation shall be made for compliance with requirements of 3.5. Any Body Assembly failing any requirement shall be classed defective and removed from the lot. (Non-destructive tests)

4.5.5 Verification of body assembly circuit resistance. Prior to assembly of explosive leads, resistance checks of each Body Assembly shall be made for all triplines, receiver coil, pressure cartridge, S&A piston actuator and S&A detonator circuits. A milliohmmeter having a test current of one milliamp or less shall be used. Observation shall be made for conformance with requirement of 3.6. Any Body Assembly failing a requirement shall be classed defective and removed from the lot. (Non-destructive tests)

4.5.6 Anti-disturbance (AD) functioning test. Final acceptance of each lot of loaded mines shall consist of initiating/arming a sample of- tactical mines utilizing a device which simulates the M128 Dispenser as specified in 4.4.5. The mines shall be set for Normal Self Destruct (See 4.4.5). Recording equipment shall be used to determine the time of test events of each mine. The starting time for test events shall begin at the application of the electromagnetic pulse. All mines shall be serialized before the launch and their location noted to insure that the correct times are recorded for each mine. Fifty percent of the mines shall be emplaced and functioned with the receiver coil end facing up. After enable time has occurred, the mines shall be disturbed by tilting, rotating, jarring or any other tampering possible to cause mines to function in the intended AD Mode. If a mine fails to function, it shall be destroyed in place.

NOTE: Enable time is defined as the maximum GROUP C electronic arm time specified on Drawing 12624467 plus 5 minutes minimum after application of electromagnetic pulse.

4.5.6.1 Recording of data. A record, by serial number, shall be made for each mine tested and shall include the following:

a. Time to premature detonation (See 4.5.6.2).
b. Time to micropiston actuator function.
c. Number of triplines deployed (If feasible).
d. Time to early self destruct (See 4.5.6.2).
e. Time to AD functioning.
f. Degree of fragmentation\Order of detonation.
g. The end of the mine facing up (See 4.5.6).

Lot acceptance test results for each inspection lot shall be forwarded to the address specified in 6.4.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

4.5.6.2 Premature arming; premature detonation; early self destruct. For purposes of this test, the following terms are defined:

a. Premature arming is defined as arming of the S&A assy (evidenced by actuation of piston actuator) before the minimum S&A arming time specified on Dwg. 12624467.

b. Premature detonation is defined as detonation of the mine (S&A armed) occuring before the minimum electronic arm time specified on Dwg. 12624467.

c. Early self destruct is defined as detonation of the mine (S&A armed) occuring at or after the minimum electronic arm time specified on Dwg. 12624467, but before being functioned by A.D.

5. PACKAGING

5.1 Preservation and Packaging

5.1.1 Level A. (Fiberboard sleeve) The mines shall be preserved and packaged in accordance with Dwg. 12624515.

5.1.2 Level A. (Plastic sleeve) The mines shall be preserved and packaged in accordance with Dwg. 9333791.

5.2 Packing

5.2.1 Level A. (Fiberboard sleeve) Packing shall be in accordance with Dwg 12624514.

5.2.2 Level A. (Plastic sleeve) Packing shall be in accordance with Dwg 9243805.

5.3 Marking

5.3.1 Level A. Marking shall be in accordance with Dwgs. (9333791 and 9243805) or (12624515 and 12624514) as applicable.

5.4 Unitization

5.4.1 Level A. Unitization of mines as packed in 5.2.1 or 5.2.2 shall be in accordance with Dwg. 19-48-4116/95M-20PA1002 (DARCOM Ammo Center).

5.5 Packing.

5.5.1 Packing Packing of the mines in Fiberboard Ammunition Containers

Source: https://assist.dla.mil -- Downloaded: 202610-23T02:36Z
Check the source to verify that this is the current version before use.

and the corresponding Steel Shipping and Storage Container (in accordance with Dwgs. 12624515 and 12624514) is the preferred packaging. Packing in Plastic Ammunition Container: PA-83 and corresponding Steel Container (in accordance with Dwgs. 9333791 and 9243805) is the alternative method.

5.6 Shipping. When mines from more than one lot interfix are shipped at one time, each lot shall be' kept separate and the division between lots clearly indicated to prevent mixing of the lots in transist.

6. NOTES

6.1 Intended use. The Mine, Antipersonnel: HE, M74 covered by this specification is intended for use as an antipersonnel mine dispensed from Dispenser, Mine, Ground Vehicle, M128.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs as required to Commander, US Army Armament Research, Development and Engineering Center, AMSMC-QAT-I (D), Dover, New Jersey 07801-5001.

6.4 Distribution of ammunition data cards and test data. Distribution of data cards and test data shall include the following: Commander, US Army Armament Research, Development and Engineering Center, ATTN: AMSMC-QAT-M (D), Dover, New Jersey 07801-5001.

6.5 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research. Development and Engineering Center (ARDEC) may also include drawings prepared by, and identified as, Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal, ARRADCOM, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under cognizance of ARDEC.

6.6 Changes from previous issue. Due to the extensiveness of the changes, asterisks to identify changes with respect to the previous issue are not used in this revision.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

6.6 Data requirements. Deliverable data required by the specification is cited in the following paragraphs:

Paragraph	Data Requirements	Applicable DID
3.8	Safety Plans	DI-T-5372 (Tailored)
4.4.2.3	Quality Inspection Defects Reports	DI-R-1721
TABLE I. 4.4.2.2, 4.4.2.9	Quality Inspection Test, Demonstration & Evaluation Report	DI-R-1724
6.4	Ammunition Data Card	DI-L-1410

6.7 Subject term (key word) listing.

Mine
Anti-personnel
HE, M74
Main charge
HE charge
Explosive
Anti-disturbance
Body assembly
M128 mine dispenser

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1345-A404)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE: This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document*(s)* or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

NO POSTAGE NECESSARY IF MAILED IN THE UNITED STATES

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO 12062 WASHINGTON D C

POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

Commander
US Army Armament Munitions &
Chemical Command
ATTN: AMSMC-QA
Dover, NJ 07801-5001

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-M-63304A (AR)	

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T02:36Z
Check the source to verify that this is the current version before use.