MIL-P-50875B (AR)
23 DECEMBER 1982
SUPERSEDING
MIL-P-50875A (PA)
29 September 1975

MILITARY SPECIFICATION

PLUG, LIFTING, ASSEMBLY, FUSIBLE FOR 155MM AND 8 INCH PROJECTILES

This specification is approved for use by the U.S. Army Armament Research and Development Command, and is available for use by all departments and agencies of the Department of Defense.

1. SCOPE

1.1 This specification covers requirements, provides quality assurance provisions, and packaging for the metal parts and assembly for one type of lifting plug designated as Fusible Lifting Plug Assembly for 155MM and 8 Inch Projectiles.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. Unless otherwise specified, the following specifications and standards of the issue listed in that issue of the Department of Defense Index of Specifications and Standards (DoDISS) specified in the solicitation, form a part of this specification to the extent specified herein.

SPECIFICATIONS

FEDERAL

PPP-B-587 - Box, Wood, Wirebound Pallet Type
QQ-S-781 - Steel, Strapping Flat
TT-C-490 - Cleaning Methods and Pretreatment of Ferrous Surfaces for Organic Coatings

FSC 1320

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Commander, US Army Armament Research and Development Command, Attn. DRDAR-QA, Dover, New Jersey 07801 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

MILITARY

MIL-B-121 - Barrier Material, Water Vaporproof, Flexible
MIL-B-13239 - Barrier Material, Waterproofed, Flexible All Temperature
MIL-A-48078 - Ammunition, Standard Quality Assurance Provisions, General Specification For

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes
MIL-STD-1169 - Packaging, Packing and Marking for Shipment of Inert Ammunition Components

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this specification to the extent specified herein.

DRAWINGS (see 6.6)

US ARMY ARMAMENT RESEARCH AND DEVELOPMENT COMMAND (ARRADCOM)

9215390 - Plug, Lifting, Assembly, Fusible

(Copies of specifications, standards, handbooks, drawings, and publications required by manufacturers in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting officer.)

2.2 Other publications. The following document(s) form a part of this specification to the extent specified herein. The issues of the documents which are indicated as DoD adopted shall be the issue listed in the current DoDISS and the supplement thereto, if applicable.

AMERICAN SOCIETY FOR TESTING AND MATERIALS

ASTM D 950-54 - Standard Method of Test for Impact Strength of Adhesive Bonds

(Applications for copies should be addressed to: American Society for Testing and Materials, 1916 Race St., Philadelphia. Pa. 19103).

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein, the text of this specification shall take precedence.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with the applicable drawings and specifications.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:41Z
Check the source to verify that this is the current version before use.

3.2 Fusible plug. The fusible plug shall comply with all requirements specified on Dwg. 9215390, all associated drawings, and with all requirements specified in applicable specificaions.

3.3 Heat treatment. All heat treatment (including stress relief) procedures shall be controlled so as to produce in each lot of lifting plugs the mechanical properties specified on the applicable component drawing and in applicable specifications.

3.4 Load test. The plug shall sustain a load of 8,000 ± 50 pounds without any sign of crack or break when tested as specified in 4.5.3.

3.5 Ductility. The plug shall show no cracking of the eye following deformation when tested as specified in 4.5.4.

3.6 Metal imperfections (applicable to malleable iron only). The plug shall be free from porosity and shrinks or discontinuous structure when tested as specified in 4.5.5.

3.7 First article inspection. This specification contains technical provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specfied in the contract.

3.8 Workmanship. All parts shall be fabricated and finished in a thorough, workmanlike manner. They shall be clean and free of burrs, sharp edges, unblended radii, cracks, surface defects, chips, dirt, grease, rust and other foreign matter. The cleaning method used shall not be injurious to any part nor shall the parts be contaminated by the cleaning agent. All marking and stamping shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection and standard quality assurance provisions. Unless otherwise specified herein or in the contract, the provisions of MIL-A-48078 shall apply and are hereby made a part of this detail specfication.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection

b. Quality conformance inspection

4.3 First article inspection

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall consist of the following items in sample quantities as indicated.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

Part description	Drawings	Quantity
Fusible lifting plug assembly	9215390	50
Plug	9215392	25 min (at least 3 per cavity)
Fusible alloy	9215391	1 lb.

4.3.2 Inspections to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

TABLE I - FIRST ARTICLE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
	Plug, Lifting, Assembly, Fusible				See Below
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
	Fusible Lifing Plug Assembly (Dwg. 9215390)				
	Examination for defects	50	-	3.2	4.4.2.3
	Air pressure test	50	-	3.2	4.5.2
	Plug (Dwg. 9215392)				
	Examination for defects	Note a	-	3.2	4.4.2.1
	Fusible Alloy (Dwg. 9215391)				
	Melting test	1 lb	-	3.2	4.5.1

NOTES:

a. Twenty-five (25) minimum; at least 3 per cavity.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.4 Quality conformance inpection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provisions of MIL-A-48078. In addition, each inspection lot shall contain:

a. Ternary Eutectic Alloy from one lot number.

b. Plugs of one lot interfix number from one manufacturer.

4.4.2 Examination. See MIL-A-48078.

a. Sampling plans. Unless otherwise specified in the Classification of Defects and Test Tables, sampling plans for major and minor defects shall be in accordance with MIL-STD-105, Inspection Level II.

b. Dimensional control of cast parts. In place of the normal sampling associated with the Classification of Defects, and with the approval of the Contracting Officer, a sample of at least five (5) parts (as cast) from each cavity may be dimensionally inspected to qualify a new or reworked cavity for use in production or as a control of the cavity during production. Inspection for control of each cavity during production shall be performed on the above quantities from each cavity after production of every 5000 parts. Individual cavity identification must be provided.

If any defective parts are found during qualification of the cavity, the cavity producing the defective part shall not be used in production. If any defective parts are found when inspection is performed for control of the cavity, the cavity producing the defective part shall be removed from production. Further, that portion of production since the last control check shall be returned to the contractor for corrective action.

All cavities formerly removed from production because of some fault, may, after reworking, be returned to production providing they pass the qualification test specified above. The contractor may request a change of inspection frequency providing he presents objective evidence to substantiate the request to the Contracting Officer.

Use of these plans are limited to those dimensions and features controlled by the mold cavity. For all specified tests, visual examinations and examinations of dimensions or features not developed exclusively by the mold cavity, these optional plans are not applicable.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:41Z
Check the source to verify that this is the currentversion before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50875B (AR)

PARAGRAPH	TITLE	SHEET 1 OF 3	DRAWING NUMBER
4.4.2.1	Plug		9215392
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Load test	Note a	-	3.4	4.5.3
102	Ductility	Note b	-	3.5	4.5.4
103	Metal imperfections	Note c	-	3.6	4.5.5
104	Outside diameter		0.40%	3.2	Gage
105	Pitch diameter of threads		0.40%	3.2	Gage
106	Major diameter of threads		0.40%	3.2	Gage
107	Diameter of hole in plug		0.40%	3.2	Gage
108	Outside diameter between threads and flange		0.40%	3.2	Gage
109	Diameter of cored recess		0.40%	3.2	Gage
110	Depth of cored recess		0.40%	3.2	Gage

NOTES:

a. Twenty (20) samples minimum at least 1 per cavity.
b. Same samples as Major 101.
c. Twenty (20) samples minimum at least 1 per cavity.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

MIL-P-50875B (AR)

PARAGRAPH	TITLE	SHEET 2 OF 3	DRAWING NUMBER 9215392
4.4.2.1	CONTINUATION SHEET		NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Minor					
201	Distance from end of plug to bottom of flange		0.65%	3.2	Gage
202	Distance from end of threads to bottom of flange		0.65%	3.2	Gage
203	Thickness of eye		0.65%	3.2	Gage
204	Height of eye		0.65%	3.2	Gage
205	Width of eye		0.65%	3.2	Gage
206	Surface finish improper on any surface		0.65%	3.2	Visual
207	Mold identification missing		0.65%	3.2	Visual
208	Evidence of poor workmanship		0.65%	3.8	Visual

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 20260430-22T20:41Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 3 OF 3		DRAWING NUMBER
4.4.2.2	Fusible Plug Assembly (Prior to Pouring Alloy)				9215390
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Primer or sealing compound not present on noted surface		0.40%	3.2	Visual
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.3	Fusible Plug Assembly (After Pouring Alloy)		9215390
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Salt spray	Note a	Note a	3.2	4.5.7
102	Air pressure test		100%	3.2	4.5.2
103	Alloy excessively below or excessively above noted surface		0.40%	3.2	Gage
Minor					
201	Evidence of poor workmanship		0.65%	3.8	Visual
202	Protective compound missing from threaded area		0.65%	3.2	Visual

NOTES:

a. Sampling plan as specified in TT-C-490.

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 20260-22T20:41Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER
4.4.2.4	Container (Sealed)				See Section 5
					NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Container damaged		0.40%	3.2	Visual
102	Contents of container loose		0.40%	3.2	Visual-Manual
103	Container incorrect according to size and weight		0.40%	3.2	Visual-Gage
104	Closing of container incorrect or incomplete		0.40%	3.2	Visual
105	Marking data missing, illegible or incomplete		0.40%	3.2	Visual
Minor					
201	Size of marking letters incorrect		0.65%	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE		SHEET 1 OF 1		DRAWING NUMBER 9215391
4.4.2.5	Ternary Eutectic Alloy				NEXT HIGHER ASSEMBLY
CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Melting test	5	-	3.2	4.5.1
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-02-22T20:41Z
Check the source to verify that this is the current version before use.

QUALITY CONFORMANCE INSPECTION

CLASSIFICATION OF DEFECTS & TESTS

PARAGRAPH	TITLE	SHEET 1 OF 1	DRAWING NUMBER
4.4.2.6	Adhesive		9215393
			NEXT HIGHER ASSEMBLY

CATEGORY	EXAMINATION OR TEST	NO. OF SAMPLE UNITS	AQL OR 100%	REQUIREMENT PARAGRAPH	PARAGRAPH REFERENCE /INSPECTION METHOD
Critical	None defined				
Major					
101	Impact resistance test	10	-	3.2	4.5.6
Minor	None defined				

NOTES:

DRDAR-QA Form 160 Jul 77

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described on the 'Paragraph Reference/Inspection Method' column in the tables starting with paragraph 4.4.2.1. The contractor shall submit for approval inspection equipment designs in accordance with the terms of the contract. See Section 6 of MIL-A-48078 and 6.3 herein.

4.5 Test methods and procedures.

4.5.1 Melting test of ternary eutectic alloy. Five (5) samples of approximately one quarter (1/4) pound each shall be randomly taken from each lot of ternary eutectic alloy to be used in each lot of fusible plug assemblies. The samples selected shall be indivisually tested by placing each in a beaker of distilled water at ambient temperature. The tempeature of the water shall then be raised at a rate not to exceed 10°F per minute. The water shall be stirred to assure uniform heating. A tempeature-indicating device such as a thermometer or thermocouple, suitable for the required temperature range, shall be inserted in the water. When the alloy is observed to melt, the indicated temperature shall be recorded. The measured temperature shall then be compared with the value specified on the applicable drawing to determine compliance or non-compliance of the sample with the melting point requirement. If any sample fails to comply with the specified melting point, the alloy lot shall be rejected. In addition, all fusible plug assemblies containing the rejected lot of ternary eutectic alloy shall be rejected.

4.5.2 Air pressure test of fusible plug assembly. Every plug shall be subjected to this test. The test shall be performed by sealing the open end of the plug and completely immersing the plug in water. The air pressure specified on the applicable drawing shall then be applied through the sealed end of the plug for the specified time intended. Observation shall be made for air bubbles originating from the area of the fusible alloy indicating a leaking plug. All such leaking plugs shall be classed defective and removed from the lot. The plug assemblies shall be thoroughly dried after completion of this test.

All equipment used in this test shall be capable of performing the test accurately and consistently. Equipment shall be calibrated prior to the start of each shift and, thereafter, at four (4) hour intervals of continuous operation. At the start of each shift and every three (3) hours thereafter, the equipment shall be checked with a known leaker.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

4.5.3 Load test. Five (5) lifting plugs shall be selected from each lot after final heat treatment and prior to pouring of the alloy for this test. The lifting plug shall be screwed into a threaded plate or other suitable fixture and a load of 8,000 ± 50 pounds applied through the medium of a 3/4 inch diameter bolt or pin passing through the eye of the plug. The full load shall be transmitted through the screw threads of the plug. Visual observation shall be made to determine compliance with 3.4. If any plug fails to comply with the requirement, the lot represented by the plugs shall be rejected.

4.5.4 Ductility. The five (5) samples from the load test shall be used for this test. The plugs shall be cooled to minus 40 degrees Fahrenheit (F.) for a minimum of thirty (30) minutes. The eye of each plug shall be flattened by either pressure or blows in any direction until the inner diameter of the eye is reduced by 0.050 inch while at minus 40 degrees F. Visual observation shall be made for any evidence of cracking. If any plug fails to meet the applicable requirement, the lot represented by these samples shall be rejected.

4.5.5 Metal imperfections. Five (5) lifting plugs shall be selected from each heat treatment lot after final heat treatment for this test. The body of each sample malleable iron casting shall be cut through the thickest section for inspection. The plug shall be observed for discontinuous structure, porosity or shrink. If any sample fails to comply with the requirement, the batch represented by the samples shall be rejected.

4.5.6 Impact resistance of adhesive. The bottle of adhesive representing the lot which will be used for a week's production will be tested prior to use for impact resistance. A total of ten specimens shall be prepared and tested in accordance with the procedures and methods specified in ASTM D-950-54. If any sample tested fails to meet an impact resistance of 10 minus one (10-1) ft. lbs. (Foot pounds), the lot or batch of adhesive shall be rejected.

4.5.7 Salt spray test. The sampling plan for this test shall be as specified in TT-C-490. The test shall be performed on the plug assemblies as specfied in TT-C-490. The number of hours and the percentage of sodium chloride solution shall be as indicated on the applicable drawing. Examination shall be made for any evidence of corrosion on the painted areas. If any plug assembly fails to comply with the specified requirements, it shall be classified defective and corrective actions taken as specfied in TT-C-490.

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:41Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation.

5.1.1 Level A. See 5.2.1.

5.1.2 Level B. See 5.2.2.

5.2 Packing.

5.2.1 Level A. Fusible lifting plugs shall be packed in wirebound wood pallet type boxes of the same size as required for Level B and shall comply completely with Type I, Class 2 of Specification PPP-B-587, including assembly, closing and strapping requirements. Interior packaging shall be the same as required for Level B except that the top and all sides of the load shall be shrouded using the same material as specified for the top cover in Level B.

5.2.2 Level B. The fusible plug assemblies shall be preserved, packaged and packed in accordance with MIL-STD-1169, bulk packaging must be avoided and all threaded parts must be protected from damage. Alternately, lifting plugs shall be packed in wirebound wood pallet type boxes as specified herein.

5.2.2.1 Trays. Thirty-six (36) lifting plugs shall be placed in a tray, Panta-Pak Number L.A. 36 cavity, made from 10-mil thick polyvinyl chloride (PVC) 13 1/2 inches by 16 1/8 inches (see 6.5); trays of equivalent design and material may also be used. The PVC tray shall be placed in a 125 -pound test, B flute, corrugated fiberboard tray. The tray shall be made from a corner cut sheet 17 5/8 by 20 1/4 inches, outside dimensions, cut and scored to form 2-inch flaps. The inside tray dimensions when the flaps are folded 90° shall be 16 1/4 by 13 5/8 inches.

5.2.2.2 Shipping container. Forty-two (42) trays (1512 lifting plugs), shall be arranged 2 by 3 trays in a layer, 7 layers high, in a wirebound pallet box conforming to the general requirements of Type 1, Class 2 of Federal Specification PPP-B-587 and the following requirements. The inside dimensions shall be approximately 32 3/4 by 41 1/4 by 23 1/8 inches. All dimensions for the base, sides and top stated below are minimum dimensions. A sheet of CW 2 or T2 barrier paper complying with requirements of Military Specification MIL-B-13239 shall be located across the top of the load and completely cover the top layer of trays. Alternately, Type 2, Grade A, Class 1 barrier material complying with Military Specification MIL-B-121 may be used. Box assembly shall include driving a minimum of three, 2 1/2 inch long, 11 gage (.120 diameter) drive screw nails

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

through the sheating and bottom cleat of each side section into the adjacent riser batten of the base. Two 3/4 x .028 steel straps complying with Type 1 or IV, Class A or C, of Federal Specification QQ-S-781 shall be applied parallel with the stringers, around the box over the 1 1/8 x 7/8 inch battens of the top.

5.2.2.2.1 The pallet base shall be constructed with three stringers 3 5/8 x 1 5/8. Three riser battens 2 3/4 wide by 15/16 thick shall be located at 90° to the stringers and 17/32 deck material located at 90° to the riser battens. Bottom deck boards are not required.

5.2.2.2.2 The four section box sidewalls shall consist of two edge and two intermediate 13/16 by 7/8 inch cleats at each section. The cleat dimensions from the bottom cleat to the intermediate cleats shall be approximately 6 and 16 inches. Sheathing shall consist of eight 3 5/8 wide by 3/8 inch thick boards at the corners of the made-up box. Additionally, two boards of like dimensions shall be located about 8 inches in from each outside corner of the longest sections of the box (front and back). The remaining portions of each box panel shall be sheathed with 7/32 veneer. One 12 gage galvanized binding wire ending in wide and narrow loops shall be stapled over row of cleats, and one at the approximate center of the panel. Staple spacing shall not exceed 1 1/2 inches.

5.2.2.2.3 The top shall be made of sheathing material which is 5/16 inch resawn boards stapled to three 2 1/4 wide x 3/8 inch thick liners equally spaced and two 1 1/8 inch x 7/8 inch thick battens, with ends mitered at 45 degrees, located midway between the outside and intermediate 3/8 thick liners. The liners and battens shall be on the outside of the top with the sheathing fitted inside the side cleats. Liners shall extend over the top cleats of the front, back and sides.

5.3 Marking. Marking of the carton shall comply with MIL-STD-1169.

6. NOTES

6.1 Intended use. The components covered by this specification are intended for use on Projectiles, 155MM and 8 Inch.

6.2 Ordering data. See MIL-A-48078.

6.3 Submission of inspection equipment designs for approval. See MIL-A-48078. Submit equipment designs, as required, to Commander, US Army Armament Research and Development Command, ATTN: DRDAR-QAR-I, Dover, NJ 07801.

☆U.S. GOVERNMENT PRINTING OFFICE: 1988—605-037/10001

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

6.4 Submission of results of contractor-conducted examinations and tests. Data shall be submitted in accordance with data item DI-R-1721 on the DD Form 1423 for the contract.

6.5 Panta-pak trays. Panta-pak trays are a product of the Pantacote Company, Panta-Pak Division, 26 Jefferson Street, Passaic, New Jersey 07056 (See 5.2.2.1).

6.6 Drawings. Drawings listed in Section 2 of this specification under the headings U.S. Army Armament Research and Development Command (ARRADCOM) may also include drawings prepared by and identified as Edgewood Arsenal, Frankford Arsenal, Rock Island Arsenal or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARRADCOM.

6.7 Changes from previous issue. The margins of this specification are marked with vertical lines to indicate where changes (additions, modifications, corrections, deletions) from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 1320-A643)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:41Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS: This form is provided to solicit beneficial comments which may improve this document and enhance its use. DoD contractors, government activities, manufacturers, vendors, or other prospective users of the document are invited to submit comments to the government. Fold on lines on reverse side, staple in corner, and send to preparing activity. Attach any pertinent data which may be of use in improving this document. If there are additional papers, attach to form and place both in an envelope addressed to preparing activity. A response will be provided to the submitter, when name and address is provided, within 30 days indicating that the 1426 was received and when any appropriate action on it will be completed.

NOTE: This form shall not be used to submit requests for waivers, deviations or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

DOCUMENT IDENTIFIER *(Number)* AND TITLE

MIL-P-50875B PLUG, LIFTING, ASSEMBLY, FUSIBLE FOR 155MM AND 8 INCH PROJECTILE

NAME OF ORGANIZATION AND ADDRESS OF SUBMITTER

☐ VENDOR ☐ USER ☐ MANUFACTURER

1. ☐ HAS ANY PART OF THE DOCUMENT CREATED PROBLEMS OR REQUIRED INTERPRETATION IN PROCUREMENT USE? ☐ IS ANY PART OF IT TOO RIGID, RESTRICTIVE, LOOSE OR AMBIGUOUS? PLEASE EXPLAIN BELOW.

A. GIVE PARAGRAPH NUMBER AND WORDING

B. RECOMMENDED WORDING CHANGE

C. REASON FOR RECOMMENDED CHANGE(S)

2. REMARKS

SUBMITTED BY *(Printed or typed name and address — Optional)*	TELEPHONE NO.
	DATE

DD FORM 1 OCT 76 1426 EDITION OF 1 JAN 72 WILL BE USED UNTIL EXHAUSTED.

Source: https://assist.dla.mil -- Downloaded: 202610-22T20:41Z
Check the source to verify that this is the current version before use.