INCH-POUND
MIL-T-70638 (AR)
18 NOVEMBER 1992
SUPERSEDING
MIL-P-63066 (AR)
1 June 1976

MILITARY SPECIFICATION

TEST PROJECTILE, 155MM, NON-HE, FOR M692/M731 TEST MINES LOADING, ASSEMBLING AND PACKING OF

This specification is approved for use by the U.S. Army Armament Munitions and Chemical Command, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers the loading, assembling and packing of a test Projectile, 155MM, containing non-high explosive loaded M692 and M731 mines and the assembly of the test hardware contained herein. (See 6.1)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issue of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation. (See 6.2)

SPECIFICATIONS

MILITARY

MIL-A-48078	-Ammunition, Standard Quality Assurance Provisions, General Specifications For. Assemblies.
MIL-P-48189	-Projectile, 155MM HE, M692 and M731 Housing, Timing, and Fuzing For
MIL-M-48245	-Molding Compound, Housing and Plug

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document, should be addressed to: Commander U.S. Army ARDEC, ATTN: SMCAR-BAC-S, Picatinny Arsenal, New Jersey 07806-5000 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A
FSC 1320
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:50Z
Check the source to verify that this is the current version before use.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Standardization Documents Order Desk, Bldg. 4D, 700 Robbins Avenue, Philadelphia, PA 19111-5094.)

2.1.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

DRAWINGS (See 6.7)

U.S. ARMY ARMAMENT RESEARCH, DEVELOPMENT AND ENGINEERING CENTER (ARDEC)

8837839	-Pallet for Projectile, 155MM, HE, GB Hollow Base TYl
9298319	-Special Test Projectile for 155MM M692/M731(U)
9298399	-Special Test Mine. Type I & Type II
9298714	-Self Destruct Time Requirements (C)

PUBLICATIONS

CODE OF FEDERAL REGULATIONS

Title 49	-Transportation, Parts 100-199.

(Copies of drawings, publications and other Government documents required by the contractor in connection with specific acquisition functions should be obtained from the contractiig activity or as directed by the contracting activity.)

Source: https://assist.dla.mil -- Downloaded: 2026l0-23T03:50Z
Check the source to verify that this is the currentversion before use.

2.1.3 Non-Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DoD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues of the documents cited in the solicitation. (See 6.2)

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D-695 - -Compressive Properties of Rigid Plastics

(Application for copies of ASTM publications should be addressed to the American Society for Testing and Materials, 1916 Race Street, Philadelphia, Pennsylvania, 19103-1187).

2.2 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document shall takes precedence. Nothing in this document, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Material. Materials shall be in accordance with applicable drawings and specification.

3.2 Components and assemblies.

3.2.1 Projectile. The Projectile Assembly and Components shall comply with all requirements specified on Drawing (Dwg.) 9298319, all associated drawings and with all requirements specified in applicable specification.

3.2.2 Munition. The munition and components shall comply with all requirements specified on Dwg. 9298399, all associated drawings and with all requirements specified in applicable specifications.

3.2.3 Documentation of plan for safety in handling of munitions. Prior to loading, the contractor shall document a detailed plan of the procedures to be employed during handling of the munition.

3.2.4 Compressive strength of molding compound. The molding compound for assembling the inert kit mechanism in the housing shall comply with MIL-M-48245. The resin/hardener weight ratio shall be 2.0/1.0 $\pm$ 5% (1.8/1 to 2.2/1) and the ultimate compressive strength shall be 29,000 to 38,000 psi.

Source: https://assist.dla.mil -- Downloaded: 202640-23T03:50Z
Check the source to verify that this is the currentversion before use.

3.3 Temperature control during molding and cure of munition. The munition shall not be subjected to temperatures exceeding 165°F. at any time.

3.4 First article inspection. This specification makes provisions for first article inspection. Requirements for the submission of first article samples by the contractor shall be as specified in the contract.

3.5 Workmanship. All parts and assemblies shall be fabricated and assembled in a thorough, workmanlike manner. They shall be free of burrs, cracks, chips, sharp edges, unblended radii, surface defects, dirt, grease, hot rolling defects, rust, corrosion products and other foreign matter. The cleaning method used shall not be injurious to any part not shall the parts by contaminated by the cleaning agent. Surface coatings shall be continuous except for a few light scratches. All required markings shall be neat and sharply defined.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements (examinations and tests) as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in this specification where such inspections are deemed necessary to ensure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this document shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of ensuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

4.2 Classification of inspections. The following types of inspection shall be conducted on this item:

a. First article inspection.

b. Quality conformance inspection.

4.3 First article inspection.

4.3.1 Submission. The contractor shall submit a first article sample as designated by the Contracting Officer for evaluation in accordance with provisions of 4.3.2. The first article sample shall be in accordance with Table I.

4.3.2 Inspection to be performed. See MIL-A-48078 and Table I specified herein.

4.3.3 Rejection. See MIL-A-48078 and MIL-P-48189.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

MIL-T-70638(AR)

PARAGRAPH	TITLE: Test Projectile, 155MM, Non-HE, For M692/M731 Loading, Assembling and Packing of	SHEET 1 OF 3	DRAWING NUMBER / NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Special Test Mine (prior to Final Assembly of the mine) (Dwg. 9298399) Examination for defects	216	3.2	4.4.2.1
	Special Test Mine (After Sealing) (Dwg. 9298399) Examination for defects	216	3.2	4.4.2.2
	Compressive strength of molding compound	216	3.4	4.4.2.2
	Battery Activation Assembly (Dwg. 9298890) Examination for defects	100%	3.2	4.4.2.3
	Special Test Mine (Immediately prior to Assembly into Stack-Up) (Dwg. 9298399) Examination for defects	216	3.2	4.4.2.4
	Munition Stack-Up (Layers 1 to 8 prior to Assembly into projectiles) Examination for defects	100%	3.2	4.4.2.5

NOTES: (1) Contractor may manufacture and submit to Government inspector more than 216 HTF wedges due to assembly fallout.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

MIL-T-70638(AR)

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Test Projectile, 155MM, Non-HE, For M692/M731 Loading, Assembling and Packing of	SHEET 2 OF 3	DRAWING NUMBER NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Projectile (During and after assembly of Munitions and prior to assembly of Base Plug (Dwg. 9298319) Examination for defects	100%	3.2	4.4.2.6
	Base Plug (Prior to Asembly of Body) (Dwg. 9298335) Examination for defects	100%	3.2	4.4.2.7
	Projectile (After Assembly of Base and Prior to Assembly of Ogive) (Dwg. 9298319) Examination for defects	100%	3.2	4.4.2.8
	Shim, Ogive (Prior to Assembly to Projectile (Dwg. 9298339) Examination for defects	100%	3.2	4.4.2.9
	Ogive (Prior to Assembly to projectile (Dwg. 9298324) Examination for defects	100%	3.2	4.4.2.10

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

TABLE I. First article inspection

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE Test Projectile, 155MM, Non-HE, For M692/M731 Loading, Assembling and Packing of	SHEET 3 OF 3	DRAWING NUMBER NEXT HIGHER ASSEMBLY
CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
	Projectile (Immediately After Assembly of Ogive and Prior to Assembly change and Sleeve assembly (Dwg. 9298319) Examination for defects	100%	3.2	4.4.2.11
	Projectile (After assembling of charge and sleeve assembly and prior to assembly of lifting plug (Dwg. 9298319) Examination for defects	100%	3.2	4.4.2.12
	Projectile (Prior to assembly of grommet) (Dwg. 9298319) Examination for defects	100%	3.2	4.4.2.13
	Pallet (Dwg. 8837839) Examination of defects	100%	3.2	4.4.2.14

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

4.4. Quality conformance inspection.

4.4.1 Inspection lot formation. Inspection lots shall comply with the lot formation provision of MIL-A-48078 and MIL-P-48189.

4.4.2 Examination and tests.

a. Classification of characteristics. Quality conformance examinations and tests are specified in the following Classification of Characteristics paragraphs. The contractor's quality program or detailed inspection system shall provide assurance of compliance of all characteristics with the applicable drawing and specification requirements utilizing as a minimum the conformance criteria specified herein. Where cited herein, attributes sampling inspection shall be conducted in accordance with Table II below, using the inspection levels stated in the Classification of Characteristics paragraphs.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

TABLE II Atttributes sampling inspection

Lot Size	Inspection Level I	II	III	IV	V	VI
2 to 8	*	*	*	*	5	3
9 to 15	*	*	*	13	5	3
16 to 25	*	*	*	13	5	3
26 to 50	*	*	32	13	5	3
51 to 90	*	*	32	13	13	5
91 to 150	*	125	32	13	13	5
151 to 280	*	125	32	32	20	8
281 to 500	*	125	32	32	20	8
501 to 1200	*	125	80	50	20	13
1201 to 3200	1250	125	80	50	32	13
3201 to 10000	1250	125	125	50	32	13
10001 to 35000	1250	315	125	80	50	13
35001 to 150000	1250	315	125	80	50	13

Numbers under inspection levels indicate sample size; asterisks indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection. Accept on zero and reject on one or more for all inspection levels.

b. Alternative quality conformance provisions. Alternative quality conformance procedures, methods, or equipment, such as statistical process control, tool control, other types of sampling procedures, etc., may be used by contractor when they provide as a minimum, the level of quality assurance required by the provisions specified herein. Prior to applying such alternative procedures, methods, or equipment, the contractor shall describe them in a written proposal submitted to the Government for evaluation (see 6.3). When required, the contractor shall demonstrate that the effectiveness of each proposed alternative is equivalent to or better than the specified quality assurance provisions herein. In cases of dispute as to whether the contractor's proposed alternative provides equivalent assurance, the provisions of this specification shall apply. All approved alternative provisions shall be specifically incorporated into the contractor's quality program or detailed inspection system, as applicable.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.1	Special Test Mine (Prior to Final Assembly of the Mine	1 OF 1	9298399
			NEXT HIGHER ASSEMBLY 9298399

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical 1	Presence of HE kill mechanism and overlay assembly	100%	3.2(1)	Visual
Major 101	Housing not marked to indicate inert filler	Level III	3.2	Visual
Minor 201	Poor workmanship	1.0%	3.7	Visual

NOTES: (1) Applicable only at facilities where HE kill Mechanisms are present.

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-T-70638(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.2	Special Test Mine (After Final Potting)	1 OF 1	9298399
			NEXT HIGHER ASSEMBLY ---

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Any evidence of battery activation during molding.	Level III	3.2	Voltmeter/Visual
102	Height	Level III	3.2	Gage
103	Distance from arc face to apex gaging radius	Level III	3.2	Gage
104	Resin/hardener weight ratio of molding compound.	(1)	3.4	4.5.2
105	Temperature control during cure	(2)	3.5	4.5.1
106	Compressive strength of loading material	(1)	3.4	4.5.2
107	Molding compound shelf life expired	(1)	3.1	Visual
108	Any sensor restricted (caps not removed)	Level III	3.2	Visual
Minor				
201	Surface finish on arc face	Level V	3.2	Finish blocks
202	Voids in molding compound bonding area	Level V	3.2	Visual
203	Perpendicularity of arc face to triangular face	Level V	3.2	Gage
204	Poor workmanship	Level V	3.7	Visual

NOTES: (1) Per lot as required LAP units will use certification and tests from HTF wedge lot material in use. (2) Cure temperature and cure time shall be monitored for each batch of housings.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.3	TITLE Battery Activation Assembly	SHEET 1 OF 1	DRAWING NUMBER 9298890
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Distance from top of piston to forward face of pusher plate, max.	100%	3.2	Gage
102	Distance from top of piston to second shoulder on battery rod, max.	100%	3.2	Gage
103	O-ring missing, damaged, or not lubricated	Level III	3.2	Visual
104	Battery rod bent or without cutouts	Level III	3.2	VIsual
Minor				
201	Adhesive missing from threads (prior to assembly)	Level V	3.2	Visual
202	Excessive adhesive around threaded joints	Level V	3.2	Visual
203	Poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.4	TITLE Special Test Mine (Immediately Prior Assembly Into Stack-Up)	SHEET 1 OF 1	DRAWING NUMBER 9298399
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Shorting bar missing, broken, or damaged	100%	3.2	Visual
102	Any sensor deployed	100%	3.2	Visual
103	Type I munition being assembled into stack-up for M692 projectile	100%	3.2/3.6	Visual
104	Munition damaged	Level III	3.2	Visual
105	Marking missing or incorrect	Level III	3.2	Visual
106	Type II munition being assembled into stack-up for M731 projectile	100%	3.2/3.6	Visual
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.5	Munition Stack-Up (Layers 1 to 8 Prior to Assembly into Projectile)	1 OF 1	9298319
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Segment column height to munition column height incorrect	100%	3.2	Gage
102	Sizing ring for radial compressive load incorrect for projectile diameter	100%	3.2	Visual
103	Disc pad missing from pusher plate	100%	3.2	Visual
104	Any plate pad missing	100%	3.2	Visual
105	Any munition missing or damaged	100%	3.2	Visual
106	Any layer not properly aligned with keyway	100%	3.2	Visual
107	Any layer not radially sized or failing	100%	3.2	Visual
108	Column siegment alignment	100%	3.2	Visual
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.6	Projectile (During and After Assembly of Munitions and Prior to Assembly of Base Plug	1 OF 1	9298319
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Base pad missing	100%	3.2	Visual
102	Base clearance inadequate	100%	3.2	Gage
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.7	Base Plug (Prior to Assembly to Body)	1 OF 1	9298335
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	none defined			
Major				
101	Seal ring missing	Level III	3.2	Visual
Minor				
201	Sealant not applied to threads	Level V	3.2	Visual
202	Threads damaged	Level V	3.2	Visual
203	Nicks on shoulder adjacent to threads	Level V	3.2	Visual
204	Seal ring not lubricated	Level V	3.2	Visual
205	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH 4.4.2.8	TITLE Projectile (After Assembly of Base and Prior to Assembly of Ogive)	SHEET 1 OF 1	DRAWING NUMBER 9298319
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Base turns when specified disassembly torque is applied	100%	3.2	Gage
102	Excessive gap between body and base	100%	3.2	Gage
Minor				
201	Sealant on exterior surface	Level V	3.2	Visual
202	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.9	Shim, Ogive (Prior to Assembly to Projectile)	OF 1	9298339
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major 101	Thickness incorrect for required preload	100%	3.2	Gage
Minor 201	None defined			

NOTES:

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.10	Ogive (Prior to Assembly to Projectile	1 OF	9298324
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Seal ring missing	Level III	3.2	Visual
Minor				
201	Compound not applied to external threads	Level V	3.2	Visual
202	External threads damaged	Level V	3.2	Visual
203	Nicks on shoulder adjacent to external threads	Level V	3.2	Visual
204	Seal ring not lubricated	Level V	3.2	Visual
205	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-T-70638(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.11	Projectile (Immediately After Assembly of Ogive)	1 OF 1	9298319
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Special				
A	Marking or paint color incorrect	100%	3.2	Visual
Major				
101	Gap between body and ogive beyond specified limits	100%	3.2	Gage
102	Concentricity of ogive to bourrelets (2 places)	100%	3.2	Gage
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.12	Projectile (Prior to Assembly of Lifting Plug)	1 of 1	9298319
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Weight and weight marking	100%	3.2	4.5.6
102	Lifting plug threads not greased	Level III	3.2	Visual
103	Threads damaged	Level III	3.2	Visual
104	Lifting plug or gasket missing or damaged	100%	3.2	Visual
Minor				
201	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89

Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-T-70638(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.13	Projectile (Prior to Assembly of Gromet)	1 OF 1	9298319
			NEXT HIGHER ASSEMBLY 9298319

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Diameter of bourrelet, max. (applicable after retouching paint	Level III	3.2	Gage
102	Rotating band damaged	Level III	3.2	Visual
103	Obturator missing or damaged	Level III	3.2	Visual
104	Base metal of base plug exposed	100%	3.2	Visual
Minor				
201	Protective coating with a total of bare areas in excess of 1/4 square inch	Level V	3.2	Visual
202	Marking missing or unidentifiable	Level V	3.2	Visual
203	Poor workmanship	Level V	3.7	Visual

NOTES:

AMSMC Form 1570b, 1 Jul 89 Replaces 1570, 1 Feb 85, which may not be used.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:50Z
Check the source to verify that this is the current version before use.

CLASSIFICATION OF CHARACTERISTICS

MIL-T-70638(AR)

PARAGRAPH	TITLE	SHEET	DRAWING NUMBER
4.4.2.14	Pallet (Loaded)	1 OF 1	8837839
			NEXT HIGHER ASSEMBLY

CLASSIFICATION	EXAMINATION OR TEST	CONFORMANCE CRITERIA	REQUIREMENT PARAGRAPH	INSPECTION METHOD REFERENCE
Critical	None defined			
Major				
101	Projectile lifting plug missing or damaged, or wrong type (not fusible)	Level III	3.2	Visual
102	Projectile grommet assembly missing, damaged, or improperly assembled	Level III	3.2	Visual
103	Board broken or split	Level III	3.2	Visual
104	Cover support missing (8 places)	100%	3.2	Visual
Minor				
201	Strap width incorrect	Level V	3.2	Visual
202	Strapping improperly assembled	Level V	3.2	Visual
203	Marking missing, incorrect or unidentified	Level V	3.2	Visual

NOTES:

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:50Z
Check the source to verify that this is the current version before use.

4.4.3 Testing. Testing is described in the First Article and Quality Conformance Inspection Tables.

4.4.4 Inspection equipment. The inspection equipment required to perform the examinations and tests prescribed herein is described in the "Paragraph Reference/Inspection Method" column in tables starting with paragraph 4.4.2.1. The contractor shall submit inspection equipment designs for approval in accordance with the terms of the contract. See Section 6 of MIL-A-48078.

4.5 Methods of inspection.

4.5.1 Temperature control during molding/cure operations. Whenever the housing or mine is subjected to heating in ovens, temperature records shall be maintained and reviewed to assure that the minimum temperature has been reached and that the maximum temperature has not been exceeded. If any units have been subjected to temperatures beyond the maximum limit at any time, regardless of duration, they shall be rejected. Temperature measuring instruments shall be approved and calibrated in accordance with 4.4.4.

In addition, if units are stored where temperature may exceed the limit specified in 3.3, temperature monitoring equipment shall be provided and constant records maintained of the temperature to assure that the temperature limit is not exceeded.

4.5.2 Mixing and cure control. One(1) test bar from each batch of molding compound (see 4.5.2) shall be molded at the same time the batch is used to mold bond plugs to housings for lot acceptance testing. Vibration and evacuation as necessary may be used to mold the bar. The mix ratio limits shall be 2.0/1.0 ± 5% (1.8/1 to 2.2/1). The test bar shall be processed with the items molded from the batch of molding compound which the bar represents i.e., the bar shall be cured in the same ovens and subjected to the same temperatures for the same time periods as the items it represents. After completion of the cure, the bar shall be tested for ultimate compressive strength, as specified in ASTM D-695 (69) except that the specimen dimensions shall be 0.5 inch by 0.5 inch by 1.0 inch or 0.5 inch diameter by 1.0 inch long. Tolerance on specimen dimensions shall be ± 0.01 inches. The ends shall be flat and parallel to within .003 inch, and shall be perpendicular to the long axis of the specimen. Speed of testing shall be as specified in the ASTM. if the results of this test are outside the limits specified in 3.2.4, the items represented by the bar shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Level A. The projectiles shall be packed in accordance with Dwg. F-8837839.

5.2 Marking. Marking shall be in accordance with Dwg. 8837839 and Code of Federal Regulations, Title 49, Parts 100-199.

5.3 Shipping. When projectiles from more than one lot are shipped at one time, each lot shall be kept separate and the division between lots clearly indicated to prevent mixing of the lots in transit.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. This specification is intended for use in loading, assembling and packing the test projectile M692/M731, 155MM and the munition contained therein for lot acceptance testing of housing assemblies.

6.2 Acquisition requirements. Acquisition documents must specify the following:

a. Title, number, and date of the specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced in section 2.1.

6.3 Submission of alternative quality conformance provisions. Unless otherwise specified in the contract, proposed alternative quality conformance provisions will be submitted by the contractor to the procuring officer.

6.4 Submission of designs for approval. (See MIL-A-48078). Submit equipment designs as required to: Commander, US Army Armamment Research, Development and Engineering Center (ARDEC), ATTN: SMCAR-QAT-I (D), Picatinny Arsenal, NJ 07806-5000. This address will be specified on the Contract Data Requirements List, DD form 1423 in the contract.

Source: https://assist.dla.mil -- Downloaded: 202610-23T03:50Z
Check the source to verify that this is the current version before use.

6.5 First article sample sizes.

6.5.1 Munition. First Article sample sizes noted are for loading six complete projectiles. The contractor may prepare spare munitions to be used in the event a sample(s) are damaged during handling or loading.

6.5.2 Projectile. The 100% requirement noted refers to complete round loading for six projectile.

6.6 Subject term (keyword) listing.

Bath Soldering
Molding Compound
Integrated Circuit
Propellant

6.7 Drawings. Drawings listed in Section 2 of this specification under the heading US Army Armament Research and Development and Engineering Center (ARDEC) may also include drawings prepared by and identified as, US Army Armament Research and Development Command, Edgewood Arsenal, Frankford arsenal Rock Island Arsenal, or Picatinny Arsenal drawings. Technical data originally prepared by these activities is now under the cognizance of ARDEC.

Custodian:
Army-AR

Preparing activity:
Army-AR

Project 1320-AC70)

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.
2. The submitter of this form must complete blocks 4, 5, 6, and 7.
3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE (YYMMDD)
	MIL-T-70638	18 NOVEMBER 1992

3. DOCUMENT TITLE: TEST PROJECTILE, 155MM, NON-HE, FOR M692/M731 TEST MINES LOADING, ASSEMBLING AND PACKING

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets if needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME (Last, First, Middle Initial)	b. ORGANIZATION	
c. ADDRESS (Include Zip Code)	d. TELEPHONE (Include Area Code) (1) Commercial (2) AUTOVON (If applicable)	7. DATE SUBMITTED (YYMMDD)

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE (Include Area Code)	
U.S ARMY ARDEC STANDARDIZATION OFFICE	(1) Commercial 201-724-6675	(2) AUTOVON DSN-880-6675
c. ADDRESS (Include Zip Code) ATTN: SMACA-BAC-S PICATINNY ARSENAL, NJ 07806-5000	IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT: Defense Quality and Standardization Office 5203 Leesburg Pike, Suite 1403, Falls Church, VA 22041-3466 Telephone (703) 756-2340 AUTOVON 289-2340	

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T03:50Z
Check the source to verify that this is the current version before use.