MILITARY SPECIFICATION

WELDING MACHINES (MICROWELDER), RESISTANCE, SINGLE PHASE, BENCH MOUNTED

This specification is approved for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers bench mounted, direct energy, single phase, resistance welding machines with equipment and accessories specified herein.

1.2 Classification. The welding machines shall be of the following sizes. The size to be furnished shall be as specified (see 6.2.1).

Size 1 - 0.5 KVA rating.
Size 2 - 1.0 KVA rating.
Size 3 - 2.0 KVA rating.
Size 4 - 3.0 KVA rating.
Size 5 - 5.0 KVA rating.

1.2.1 Machine size. The machine size is expressed in terms of kilovolt amperes (KVA) at 50 percent duty cycle of the welding transformer.

1.2.2 Part number. Part numbers shall be compiled from the following code:

M	80124	X	X
Prefix	Spec No.	Size (See 1.2)	Type head (See 3.4.4)

2. APPLICABLE DOCUMENTS

2.1 Government documents.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Defense Industrial Plant Equipment Center, ATTN: DIPEC-SSG, Memphis, TN 38114-5051, by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 3432
DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

2.1.1 Specification and standards. The following specification and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents shall be those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation.

SPECIFICATION

MILITARY

MIL-W-45562 - Welding and Soldering Equipment, Supplies and Accessories, Packaging of.

STANDARDS

FEDERAL

FED-STD-H28 - Screw Thread Standards for Federal Service.

FED-STD-376 - Preferred Metric Units for General Use by the Federal Government.

MILITARY

MIL-STD-1276 - Leads, Weldable, for Electronic Component Parts.

2.1.2 Other Government document. The following other Government document forms a part of this specification to the extent specified herein. Unless otherwise specified, the issue shall be that in effect on the date of the solicitation.

U. S. DEPARTMENT OF LABOR

29 CFR, CHAPTER XVII, PART 1910 - Occupational Safety and Health Standards.

(Copies of specifications, standards, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the contracting activity or as directed by the contracting activity.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted shall be those listed in the issue of the DODISS specified in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS shall be the issue of the nongovernment document which is current on the date of the solicitation.

AMERICAN SOCIETY FOR TESTING AND MATERIALS (ASTM)

ASTM D 3951 - Standard Practice for Commercial Packaging.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

(Application for copies should be addressed to the American Society for Testing and Materials, 1916 Race St., Philadelphia, PA 19103-1187.)

NATIONAL ELECTRICAL MANUFACTURERS ASSOCIATION (NEMA)

NEMA ICS 5 - Resistance Welding Control.

(Application for copies should be addressed to the National Electrical Manufacturers Association, 2101 L Street, N.W., Washington, DC 20037-1580.)

NATIONAL FIRE PROTECTION ASSOCIATION (NFPA)

NFPA 70 - National Electrical Code.

(Application for copies should be addressed to the National Fire Protection Association, Batterymarch Park, Quincy, MA 02269-9101.)

RESISTANCE WELDER MANUFACTURERS ASSOCIATION (RWMA)

RWMA Bulletin Number 16 - Resistance Welding Equipment Standards.

(Application for copies should be addressed to the Resistance Welder Manufacturers Association, 1900 Arch Street, Philadelphia, PA 19103-1403.)

(Nongovernment standards and other publications are normally available from the organizations which prepare or distribute the documents. These documents also may be available in or through libraries or other informational services.)

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein the text of this specification shall take precedence. Nothing in this specification, however, shall supersede applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 First article. When specified in the contract or purchase order (see 6.2.1), a sample shall be subjected to first article inspection (see 4.4 and 6.3).

3.2 Design. The welding machine shall be new and one of the manufacturer's current models capable of precision microwelding of ferrous and non-ferrous wire and sheet material in accordance with the requirements herein. The welding machine shall include all components, parts, and features necessary to meet the performance requirements specified herein. All parts subject to wear, breakage, or distortion shall be accessible for adjustment, replacement, and repair.

3.2.1 Dimensional system. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used in the design and construction of the welding machine. When only one di-

Source: https://assist.dla.mil - Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

mensional system is acceptable, the particular system required shall be as specified (see 6.2.1). In this specification, all dimensions, measurements, sizes, and capacities are given in US units. These dimensions may be converted to SI units through the use of the conversion factors and methods specified in FED-STD-376.

3.2.1.1 Measuring and indicating device calibrations. Unless otherwise specified, either the U.S. Customary System of Units (US) or the International System of Units (SI) shall be used to graduate measuring and indicating devices such as pressure gauges, temperature indicators, and other similar devices. When only one system of graduation is acceptable, the particular graduation required shall be as specified (see 6.2.1). Regardless of the measurement system used, all measuring and indicating devices on the welding machine shall be graduated in the same system.

3.2.2 Reclaimed materials. The welding machine may contain reclaimed materials provided such materials will not jeopardize the intended use and performance of the machine. The reclaimed materials shall have been reprocessed, remanufactured, or recycled in a manner which will restore them to the same chemical composition and physical properties as the materials originally selected for use on the welding machine.

3.2.3 Energy efficiency. The welding machine and its components that directly consume energy in normal operation shall be designed and constructed for the highest degree of energy efficiency as governed by the latest developments available within the industry.

3.2.4 Controls. All operating controls shall be located conveniently to the operator at his normal work station.

3.2.5 Safety and health requirements. Covers, guards, or other safety devices shall be provided for all parts of the welding machine that present safety hazards. The safety devices shall not interfere with the operation of the welding machine. The safety devices shall prevent unintentional contact with the guarded part, and shall be removable to facilitate inspection, maintenance, and repair of the parts. All parts, components, mechanisms, and assemblies furnished on the welding machine, whether or not specifically required herein, shall comply with all of the requirements of 29 CFR, Chapter XVII, Part 1910 that are applicable to the machine itself. The welding machine shall be equipped with all point-of-operation guarding normally furnished as standard on the manufacturer's commercial welding machine supplied to the commercial market. If specific point-of-operation guarding is required, the procuring activity should specify the exact configuration of the guard required because the guard configuration is dependent on the size and configuration of the workpieces. The above, and any other additional safety and health requirements should be specified in detail (see 6.2.1).

3.2.6 Mercury restriction. The welding machine shall not contain mercury or mercury compounds nor be exposed to free mercury during manufacture.

3.2.7 Asbestos restriction. Asbestos and materials containing asbestos shall not be used on or in the welding machine.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

3.2.8 Environmental protection. The machine shall be so designed and constructed that, under the operating, service, transportation, and storage conditions described herein, the welding machine shall not emit materials hazardous to the ecological system as prohibited by Federal, state, or local statutes in effect at the point of installation.

3.2.9 Interchangeability. All parts shall be manufactured to definite dimensions and tolerances that will permit installation of replacement parts without modification of the part or machine.

3.3 Construction. The welding machine shall be constructed of parts which are new, without defects, and free of repairs. The structure shall be capable of withstanding all forces encountered during operation of the machine at its maximum rating and capacity without permanent distortion.

3.3.1 Castings and forgings. All castings and forgings shall be free from defects, scale, and mismatching. Processes such as welding, peening, plugging, or filling with solders or pastes shall not be used on castings or forgings to reclaim any defective components for use on the machine. Such processes may be used only for enhancing surface finish and appearance.

3.3.2 Welding, brazing, or soldering. Welding, brazing, or soldering shall be employed only where specified in the original design. None of these processes shall be employed as a repair measure for any defective part.

3.3.3 Fastening devices. All screws, pins, bolts, and other fasteners shall be installed in a manner to prevent change of tightness. Fastening devices subject to removal or adjustment shall not be swaged, peened, staked, or otherwise permanently installed.

3.3.4 Surfaces. All surfaces shall be clean and free of sand, dirt, fins, sprues, flash, scale, flux, and other harmful or extraneous materials. All edges shall be either rounded or beveled unless sharpness is required to perform a necessary function. Except as otherwise specified herein, the condition and finish of all surfaces shall be in accordance with the manufacturer's commercial practice.

3.3.5 Painting. Unless otherwise specified (see 6.2.1), the welding machine shall be painted in accordance with the manufacturer's standard commercial practice and color.

3.3.6 Threads. All threaded parts used on the welding machine and its related attachments and accessories shall conform to FED-STD-H28.

3.4 Components. The welding machine shall consist of not less than an enclosure, a power supply unit, an electrical system, a welding head, and a microscope assembly.

3.4.1 Enclosure. The enclosure shall be constructed of corrosion resistant metal or metal treated to resist corrosion. Ventilation and cooling shall be adequate to prevent temperatures in excess of design requirements under normal operating conditions. When furnished, the cooling system shall be of the forced air type.

Source: https://assist.dla.mil Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

3.4.2 Power supply unit. The power supply unit shall include the welding transformer, timers, controls, meters, and connections for cables from the welding head. The power supply shall be furnished with input power cables not less than six feet in length.

3.4.2.1 Welding transformer. The welding transformer shall conform to the requirements of RWMA Bulletin Number 16 and shall have class B, or better, insulation. When specified (see 6.2.1), a temperature responsive device shall be furnished to prevent energization of the transformer if the temperature exceeds design limits.

3.4.2.2 Control equipment. Unless otherwise specified (see 6.2.1), the welding machine shall be provided with a synchronous precision control conforming to NEMA ICS 5 type 1BS. Control equipment shall be capable of operation on input voltage that may vary ± 10 percent from the voltage for which the equipment is adjusted. All calibrations and similar characteristics shall be clearly marked in standard terms.

3.4.2.3 Operator control panel. The operator control panel shall have an on-off switch, or a weld - no weld switch, which prevents firing the power supply inadvertently, a power on light, a current control adjustment, a weld timer selector, a weld power cable or head connectors, and external unit connectors. When furnished, all meters shall have an accuracy of ± 2 percent of full scale reading.

3.4.2.4 Current adjustment control. The welding machine shall be provided with a continuously variable current adjustment control from the upper to the lower limits of the machine capacity. The control shall be graduated in increments of 1 from 0 to not less than 99 or from 20 percent to not less than 99 percent for convienence in identifying settings.

3.4.2.5 Welding contactor. The welding contactor shall be the solid state silicon controlled rectifier (SCR) type. The SCR shall be protected from excessive current demands and overheating.

3.4.2.6 Weld timer. The weld timer shall be calibrated in cycles conforming to input line frequency. The cycles range shall be from a low of not more than 1/2 cycles to a high of not less than 29 cycles. Unless otherwise specified (see 6.2.1), the repeat accuracy shall be ± zero cycles.

3.4.2.7 Pre-heat and post-heat timer. When specified (see 6.2.1), the machine shall be provided with pre-heat or post-heat or a combination pre-heat and post-heat timing control with adjustment variable to not less than 20 cycles.

3.4.2.8 Up-slope and down-slope timer. When specified (see 6.2.1), the machine shall be provided with up-slope or a combination up-slope and down-slope timing control having at least 6 selections.

3.4.3 Electrical system. Unless otherwise specified (see 6.2.1), the electrical system and components shall conform to the requirements of NFPA 70. Each sub-panel shall be arranged so that it may be removed independently of

Source: https://assist.dla.mil - Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

any other sub-panel. All terminals and units shall be clearly identifiable from the machines electrical wiring diagram. Solid state shall be used throughout for electronic components.

3.4.3.1 Electrical service requirements. Unless otherwise specified (see 6.2.1), the welding machine shall operate on a single phase, 60 Hertz (Hz), 230 volts primary electrical service.

3.4.3.2 Main disconnect switch. The welding machine shall be provided with a main fusible type disconnect switch or a circuit breaker to serve as an overload protector and an on-off switch.

3.4.4 Welding head. The welding head shall support the welding electrodes and shall perform the functions of spot type joining of the materials specified. The welding head shall be compatible with the power supply for performing the various welding and bonding processes. The welding head shall be attached to the power supply by plug-in or bolt type connections. Unless otherwise specified (see 6.2.1), the throat depth shall be not less than 2 inches for sizes 1 and 2 machines and shall be not less than 6 inches, which may include the use of extension arms, for sizes 3, 4, and 5 machines. The welding head shall be one of the following types as specified (see 6.2.1).

a. Opposed
b. Parallel gap
c. Dual heads
d. Thermocompression bonder
e. Solder reflow
f. Special

3.4.4.1 Welding head actuation. The welding head shall be actuated by the hand, knee, or foot of the operator. The welding head movement shall have fast acceleration, low inertia, and low friction. The electrode force shall be calibrated and adjustable. Weld current shall flow only after the preselected force has been obtained with repeat accuracy of $\pm$ 3 percent of the setting. The electrode closing rate shall be adjustable.

3.4.4.1.1 Pneumatic system. When specified (see 6.2.1), the welding head shall be equipped with a pneumatic force system sized to operate on shop air pressure of not less than 80 pounds per square inch gauge. The pneumatic system shall be provided with a filter separator unit with a suitable drain cock or valve for draining accumulations. A lubricator, air pressure regulator, pressure gauge with protective snubber, air muffler, air speed control valves, and air cylinder cushions shall be furnished.

3.4.4.2 Extension arms and electrodes. When specified (see 6.2.1), the welding head shall be equipped with extension arms. The arms shall have provisions for replaceable electrodes and adapters. Electrodes conforming to RWMA Bulletin Number 16 shall be furnished with the welding machine. The type, alloy, style, and quantity shall be as specified (see 6.2.1).

3.4.4.3 Interconnecting cables. The interconnecting control and weld power cables shall be flexible, with an oil-resistant covering, and shall have polarized or keyed connections to ensure proper installation.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

3.4.5 Microscope assembly. When specified (see 6.2.1), the welding machine shall be provided with a stereo zoom optic assembly with 7x to 30x magnification at a 4 inch work distance. The optic assembly shall rotate in an arc of not less than 180 degrees. A spot illuminator shall be provided with a mounting bracket to the optic assembly.

3.5 Size and capacity. Unless otherwise specified (see 6.2.1), the size and capacity of the welding machine shall be not less than those specified in table I for the machine size specified.

TABLE I. Machine capacity and performance requirements.

Machine size	KVA rating	Material weld capacity			
		Crosswire diameter range, nickel 1/ (inches)		Sheet thickness range, nickel 1/ (inches)	
		min	max	min	max
1	0.5	0.001	0.015	0.0004	0.0100
2	1	0.002	0.020	0.0005	0.0150
3	2	0.002	0.025	0.0005	0.0150
4	3	0.002	0.030	0.0015	0.0200
5	5	0.004	0.035	0.0020	0.0250

1/ MIL-STD-1276, type N for alloy composition only. Where a range is shown, the requirements are from the minimum or less to the maximum or more.

3.6 Performance. The welding machine shall be capable of producing quality welds using two thicknesses of the materials specified in table I.

3.6.1 Additional performance requirements. Performance features required in addition to, or in lieu of, the requirements herein shall be as specified and fully described (see 6.2.1).

3.7 Standard equipment. Unless otherwise specified, all equipment normally furnished with the manufacturer's standard commercial welding machine shall be furnished. When specified (see 6.2.1), required additional equipment shall be furnished and fully described.

3.8 Optional equipment. Optional equipment shall be furnished as specified and shall be fully described (see 6.2.1).

3.9 Repair parts. Repair parts shall be furnished as specified (see 6.2.1).

3.10 Marking on plates and charts. All words on plates and charts shall be in the English language. Characters shall be engraved, etched, embossed, or stamped in boldface on a contrasting background.

3.10.1 Nameplate. A nameplate shall be securely attached to each welding machine. The nameplate shall contain the information listed below. If the machine is a special model, the model designation shall include the model of

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

the basic standard machine and a suffix identified in the manufacturer's permanent records. The captions listed may be shortened or abbreviated, provided the entry for each caption is clear as to its identity.

Nomenclature
Manufacturer's name
Manufacturer's model designation
Manufacturer's serial number
Power input (volts, total amps, phase, frequency)
KVA rating at 50 percent duty cycle
Contract Number or Order Number
National Stock Number or Plant Equipment Code
Date of manufacture

3.11 Technical data. When technical data is required it shall be furnished in accordance with the requirements of the contract. All technical data furnished shall be written in the English language.

3.12 Workmanship. Workmanship of the welding machine and accessories shall be of a quality equal to that of the manufacturer's commercial equipment of the type specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspections. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

4.2 Classification of inspections. The inspection requirements specified herein are classified as follows:

a. First article inspection (see 4.4).

b. Quality conformance inspection (see 4.5).

4.3 Inspection conditions. Unless otherwise specified herein, all inspections, tests, and examinations shall be performed in the manufacturer's

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

designated indoor test area under the ambient temperature, the relative humidity, and the air pressure existing inside the building at the time the inspections, tests, and examinations are performed.

4.4 First article inspection. When first article inspection is required, it shall be applied to the first article submitted in accordance with 3.1. Unless otherwise specified (see 6.2.1), first article inspection shall consist of the examination in 4.6 and all tests in 4.7. Failure of the item to pass the first article examination and all tests shall be cause for rejection.

4.5 Quality conformance inspection. A quality conformance inspection shall be applied to each item prior to being offered for acceptance under the contract. Unless otherwise specified (see 6.2.1), the quality conformance inspection shall consist of the examination in 4.6, the test in 4.7.1, and the inspection in 4.8. Failure of the item to pass the examination, the test, and the inspection shall be cause for rejection.

4.6 Examination. The welding machine shall be visually examined to determine compliance with all requirements of this specification.

4.7 Tests.

4.7.1 Operational test. The welding machine shall be operated at no load for not less than 10 minutes. Proper operation of all controls, motors, adjusting mechanisms, and accessories shall be verified during the trial period.

4.7.2 Welding test. Welds shall be made using the minimum and maximum thickness material in crosswire and sheet as specified in table I for the size machine specified. Thirty consecutive welds shall be made in both size materials.

4.7.2.1 Weld inspection. Five weld specimens each of the minimum and maximum size material required in 4.7.2 shall be examined by 30 power magnification. There shall be no evidence of cracks or lack of fusion in the welds.

4.7.2.2 Weld strength test. The specimen welds shall be subjected to a strength test by pulling or peeling the two pieces apart. There shall be no separation of the weld nuggets.

4.7.3 Performance tests. The machine shall be adjusted for its maximum output capacity and repetition rate of 100 welds per hour. The electrodes shall be short-circuted and simulated welds shall be made for 10 minutes. There shall be no evidence of malfunction or overheating.

4.7.4 Optional tests. When special welding, brazing, soldering, bonding, or wirebonding and sheet not covered by table I is specified, the type material and testing procedure shall be as specified (see 6.2.1). The supplier shall submit weld schedule and test procedures to the procuring activity for approval.

4.8 Packaging inspection. Packaging of each item shall be inspected to determine compliance with the requirements of section 5.

Source: https://assist.dla.mil Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

5. PACKAGING

5.1 Preservation, packing, and marking. Unless otherwise specified, preservation, packing, and marking shall be in accordance with ASTM D 3951. When specified (see 6.2.1), level A or level B preservation, level A or level B packing, and marking shall be accomplished in accordance with MIL-W-45562.

6. NOTES

6.1 Intended use. The equipment covered by this specification is intended for precision microwelding applications such as welding integrated packages to circuit boards, and wire or ribbon to plating. Weld application for this equipment is found in thin-film lead welding, wire welding, controlled brazing, soldering, and fusion welding requiring an annealing process.

6.2 Ordering data.

6.2.1 Acquisition requirements. Acquisition documents should specify the following:

a. Title, number, and date of this specification.

b. Machine size required (see 1.2).

c. First article, if required (see 3.1).

d. If welding machine design and construction is required in a specific dimensional system (US or SI), state required system (see 3.2.1).

e. If measuring and indicating devices are required to be graduated in a specific measurement system (US or SI), state required system (see 3.2.1.1).

f. Additional safety and health requirements, if required (see 3.2.5).

g. Painting, if different (see 3.3.5).

h. Transformer temperature responsive device, if required (see 3.4.2.1).

i. Controller, if different (see 3.4.2.2).

j. Weld timer, if different (see 3.4.2.6).

k. Pre-heat and post heat timer, if required (see 3.4.2.7).

l. Slope control timer characteristics, if required (see 3.4.2.8).

m. Electrical system, if different (see 3.4.3).

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

n. Input power, if different (see 3.4.3.1).

o. Throat depth, if different (see 3.4.4).

p. Welding head type, if different (see 3.4.4).

q. Pneumatic force system, if required (see 3.4.4.1.1).

r. Extension arms, if required (see 3.4.4.2).

s. Electrode type, alloy, style, and quantity required (see 3.4.4.2).

t. Microscope assembly, if required (3.4.5).

u. Size and capacity, if different (see 3.5.).

v. Additional performance features, if required (see 3.6.1).

w. Standard equipment, if different (see 3.7).

x. Specify and fully describe optional equipment, if required (see 3.8).

y. Specify applicable repair parts, if required (see 3.9).

z. First article inspection, if different (see 4.4).

aa. Quality conformance inspection, if different (see 4.5).

bb. Welding test for optional process, if required (see 4.7.4).

cc. If preservation, packing, and marking in accordance with MIL-W-45562 is required, specify level of preservation and packing required (see 5.1).

6.2.2 Contract data requirements. Required technical data such as operator's manuals, parts lists, wiring diagrams, and acceptance test reports should be specified on a DD Form 1423, Contract Data Requirements List, incorporated into the contract.

6.3 First article. When first article inspection is required, the item to be tested should be the first item offered for acceptance under the contract. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examination, test, and approval of the first article.

6.4 Subject term (key word) listing.

Bonding
Brazing
Microscope assembly
Microwelder

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

Resistance welder
Thermocompression bonding
Timer, down-slope
Timer, post-heat
Timer, pre-heat
Timer, up-slope
Welding machine

6.5 Changes from previous issue. Asterisks are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodians:
Army - AL
Navy - SH
Air Force - 99

Review activities:
Air Force - 84
DLA-GS

User activities:
Army - AR, AV, MI
Navy - MC

Preparing activity:
DLA - IP

(Project 3432-0135)

☆U.S. GOVERNMENT PRINTING OFFICE: 1987—505-033/75757

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-W-80124C	Welding Machines, (Microwelding) Resistance, Single-Phase, Bench Mounted

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR
b. ADDRESS *(Street, City, State, ZIP Code)*	☐ USER
	☐ MANUFACTURER
	☐ OTHER *(Specify)*: _____

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE.

Source: https://assist.dla.mil -- Downloaded: 2026-10-23T04:40Z
Check the source to verify that this is the current version before use.