NN-H-101

AMENDMENT—4
MAY 27, 1944

SUPERSEDING
AMENDMENT—3
September 25, 1937, and
EMERGENCY ALTERNATE
E–NN–H–101
July 12, 1943

FEDERAL STANDARD STOCK CATALOG

Section IV

(Part 5)

FEDERAL SPECIFICATION

FOR

HANDLES; MOP*

This amendment was approved on the above date by the Director of Procurement, for the use of all departments and establishments of the Government, and shall become effective not later than August 1, 1944. It may be put into effect, however, at any earlier date after promulgation.

The following changes shall be made in Federal Specification NN–H–101, dated February 6, 1934:

Page 1:

Paragraph B–1. Delete and substitute:

B–1. Mop handles in accordance with this specification shall be furnished in one grade and in the following types, as specified in the invitation for bids:

Type I.—Screw type: Malleable iron or pressed steel head.

Type II.—Spring-lever type: Malleable iron or pressed steel head, either with or without collar, unless collar is specified.

Type III.—Alternate types (see par. E–3).

Paragraph C–1a:

Line 3. After "fir" insert "poplar or tupelo."

Page NN–H–101–2:

Paragraph E–1:

Lines 3 and 4. Delete last sentence and substitute: "The overall length of mop handles shall be not less than 48 inches."

---

*Certain provisions of this amendment are intended to conserve critical or strategic materials. When the present emergency is over, this amendment will be considered for revision.

Source: https://assist.dla.mil -
Check the source to verify that t

Paragraphs **E–1b (1)** and **E–1b (2)**. Delete and substitute:

E–1b (1). *Bail.*—The bail shall be made of steel wire 0.244 inch, plus or minus 0.01 inch, in diameter (steel wire gage No. 3), and shall be securely fastened to the stick in an approved manner and strengthened with a steel, a cast-iron, or a malleable-iron ferrule. The inside dimension of the end of the bail shall be 6½ inches with an allowable minus tolerance of ⅛ inch. When the head is raised to a maximum, there shall be an opening of at least 1½ inches between the end of the bail and the head to provide for the insertion of the mop.

E–1b (2). *Head.*—The head shall be of malleable iron or pressed steel. If pressed steel is used, it shall be not lighter than No. 24 gage (0.0245 inch) when used double thickness and No. 22 gage (0.0306 inch) when used single thickness. The head may be made of a suitable plastic material having strength equal to the metal head.

Paragraph **E–1c**. Delete and substitute:

E–1c. *Finish.*—The bail, head, screw pin, and wing nut shall be made corrosion resisting by zinc or other suitable coating.

Paragraph **E–2**:

Lines 3 and 4. Delete last sentence and substitute: "The overall length of mop handles shall be not less than 48 inches."

Paragraph **E–2b (1)**. Delete and substitute:

E–2b (1). *Bail.*—The bail shall be made of steel wire 0.177 inch, plus or minus 0.015 inch, in diameter (steel wire gage No. 7), securely fastened to the lever in an approved manner. The inside dimension of the bail shall be 6½ inches with an allowable minus tolerance of ⅛ inch. When the lever is fully raised there shall be an opening of at least 1¼ inches between the end of the bail and the head for the insertion of the mop.

Paragraph **E–2b (2)**. Delete and substitute:

E–2b (2). *Head.*—The head shall be made of malleable iron or pressed steel. If pressed steel is used, it shall be not lighter than No. 24 gage (0.0245 inch) when used double thickness, and No. 22 gage (0.0306 inch) when used single thickness. The head shall be securely fastened to the stick by a nail, screw, staple, or other equally secure means. The head may be made of a suitable plastic material having strength equal to the metal head.

Paragraph **E–2b (3) a.** Delete and substitute:

E–2b (3) a. *Spring.*—The spring shall be made of spring steel wire 0.1350 inch, plus or minus 0.08 inch, in diameter (steel wire gage No. 10). It shall be so constructed that sufficient pressure shall be produced to maintain the mop in a secure position.

Source: https://assist.dla.mil -- Check the source to verify that th

Paragraph **E–2b (3) b.**

Lines 1 and 2. Delete first sentence and substitute: "The collar shall be made of malleable iron or heavy pressed steel."

Page NN–H–101–3:

Paragraph **E–2b (3) c.** Delete and substitute:

E–2b (3)c. *Lever.*—The lever shall be made of pressed steel. Steel 0.049 inch thick, plus or minus 0.004 inch (U. S. standard gage No. 18), shall be used if lever is embossed for added strength, and 0.061 inch thick, plus or minus 0.004 inch (U. S. standard gage No. 16), shall be used if lever is plain. Where no collar is provided the lever shall be securely attached to the lower turn of the spring so as not to become detached.

Paragraph **E–2c.** Delete paragraph and substitute:

E–2c. *Finish.*—The head, lever, collar, and bail shall be made corrosion resisting by zinc or other suitable coating.

Section **E.** Insert paragraph **E–3** as follows:

E–3. *Alternate types* may be either type I, type II with or without collar, or any other equally substantial construction approved by the purchasing officer.

Page NN–H–101–4:

Paragraph **I–1.**

Line 2. Delete "class, etc."

Page NN–H–101–5:

Paragraphs **I–4** and **I–6.** Delete paragraphs entirely.

Paragraphs **I–5, I–7,** and **I–8.** Renumber as **I–4, I–5,** and **I–6,** respectively.

Source: https://assist.dla.mil -
Check the source to verify that