NN–H–101a
AMENDMENT—2
JUNE 8, 1953
SUPERSEDING
AMENDMENT—1
24 April 1952

FEDERAL SPECIFICATION

HANDLES, MOP

This amendment which forms a part of Federal Specification NN–H–101a, dated 13 March 1951, was approved by the Commissioner, Federal Supply Service, General Services Administration, for the use of all Federal agencies.

Page 1, paragraph **2.1:** Delete and substitute:

2.1 The following Federal Specifications, of the issues in effect on date of invitation for bids, form a part of this specification:

NN–B–601—Boxes; Wood - Cleated - Plywood, for Domestic Shipment.
NN–B–621—Boxes; Wood, Nailed and Lock-Corner.
NN–B–631—Boxes; Wood, Wirebound (for Domestic Shipment).
LLL–B–631—Boxes; Fiber, Corrugated (for Domestic Shipment).
LLL–B–636—Boxes; Fiber, Solid (for Domestic Shipment).

Page 1, paragraph **2.1:** Delete parenthetical paragraph and substitute the following:

(Copies of Federal specifications and the Federal Specifications Index may be obtained upon application, accompanied by check, money order, cash, or Government Printing Office coupons, to the General Services Administration, Business Service Center, Region 3, 7th and D Streets, SW., Washington 25, D. C. This office will also honor deposit account numbers issued by the Government Printing Office. Single copies of product specifications required for bidding purposes are available without charge at the GSA Regional Offices in Boston, New York, Atlanta, Chicago, Kansas City, Mo., Dallas, Denver, San Francisco, Los Angeles, Seattle, and Washington, D. C. Prices of additional copies may be obtained from the GSA Regional Offices.)

Page 1, section 2: Following paragraph **2.1** and parenthetical paragraph, add new paragraph **2.2** as follows:

2.2 Specifications and other publications applicable only to individual departments are listed in section 7.

Page 1, paragraph **3.1:** Delete second sentence and substitute the following: "The overall length of the stick and the head shall be not less than 54, 60 or 72 inches, as specified in the invitation for bids."

Page 1, paragraphs **3.2** and **3.2.1:** Delete and substitute the following:

3.2 *Sticks.*—The wood of the sticks shall be thoroughly seasoned close- and straight-grained ash, beech, birch, elm, Douglas fir, hickory, maple, pecan, red gum, red or white oak, or southern yellow pine. Sticks shall be straight and uniform in diameter, smoothly finished, rounded at the hand end, and be coated with transparent varnish or lacquer. The diameter of the sticks shall be 1⅛ inches. Each stick shall have a hole approximately $^{3}/_{16}$ inch in diameter, 2 to 3 inches from the hand end, completely through the stick.

Page 1, paragraph **3.3.2.1,** line **6:** Delete "6" and substitute "6½".

Page 1, paragraph **3.3.2.4:** Delete and substitute the following:

3.3.2.4 *Finish.*—The bail, head, screw-pin, wing-nut, and ferrule shall be made corrosion resistant with either an electroplated zinc coating or cadmium plating.

Page 3, paragraph **5.2:** Delete and substitute:

5.2 Packing.—Thirty-six handles shall be packed, by placing one-half of the heads at each end of box, in one of the following shipping containers:

5.2.1 *Fiberboard boxes.*—Corrugated or solid-fiberboard containers constructed in accordance with the requirements for style **OLC** of Federal Specifications **LLL–B–631** and **LLL–B–636,** respectively. Bursting strength of fiberboard shall be not less than 275 pounds per square inch. Manufacturer's joint shall be stitched. Each inside end of the box shall be provided with a scored and slotted tray having 3-inch-wide flanges all around, constructed of the same material as used in the box. All flaps of the fiberboard box shall be securely sealed with a good quality adhesive

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:58Z
Check the source to verify that this is the current version before use.

applied throughout the entire area of contact between the flaps. The top and bottom flanges of the tray shall be glued to the box.

Three flat steel straps not less than ⅜ inch by 0.015 inch shall be applied around the top, sides, and bottom of each box. One strap shall be positioned approximately 6 inches from each end; the third strap centered equidistant from the end straps.

5.2.2 *Nailed wood boxes.*—Nailed wood boxes shall be constructed, sealed, and strapped in accordance with the requirements for style 4 of Federal Specification NN–B–621.

5.2.3 *Wood-cleated plywood boxes.*—Wood-cleated plywood boxes shall be constructed in accordance with the requirements for style B of Federal Specification NN–B–601.

5.2.4 *Wirebound wood boxes.*—Wirebound wood boxes constructed in accordance with the requirements for style 2 or 2A of Federal Specification NN–B–631, style F battens.

Pages 3, 4, and 6, paragraphs **7.2, 7.3,** and **7.4:** Delete and substitute:

7.2 Army, Navy, and Air Force.

7.2.1 *Applicable specifications and standard.*

Military Specifications:

JAN–P–105—Packaging and Packing for Overseas Shipment—Boxes, Wood, Cleated, Plywood.

JAN–P–106—Packaging and Packing for Overseas Shipment—Boxes, Wood, Nailed.

JAN–P–132—Packaging and Packing for Overseas Shipment—Crates; Unsheathed, Wood; Nailed.

Military Standard:

MIL–STD–129—Marking of Shipments.

Navy Department Specification:

General Specifications for Inspection of Material.

(Copies of specifications and standards required by the contractor in connection with specific procurement functions should be obtained from the procuring agency or as directed by the contracting officer.)

7.2.2 *Packing for overseas shipment.*—Thirty-six handles shall be packed, by placing one-half of the heads at each end of the box, in one of the following type shipping containers:

7.2.2.1 *Nailed wood boxes.*—Nailed wood boxes shall be constructed, sealed, and strapped in accordance with the requirements for style 4, type 3 load, of Military Specification JAN–P–106.

7.2.2.2 *Nailed wood crates.*—Nailed wood crates shall be constructed, sealed, and strapped in accordance with the requirements for style C of Military Specification JAN–P–132.

7.2.2.3 *Wood-cleated plywood boxes.*—Wood-cleated plywood boxes shall be constructed, sealed, and strapped in accordance with the requirements for style B of Military Specification JAN–P–105.

7.2.3 *Marking.*—Each shipping container shall be marked to comply with the requirements of Military Standard MIL–STD–129.

7.2.4 *Inspection procedures (Navy only).*—For naval purchases, the general inspection procedures shall be in accordance with Navy Department General Specification for Inspection of Material.

Page 6: Delete last sentence at the bottom of the page and substitute:

Copies of this specification can be purchased for 5 cents each from the General Services Administration, Business Service Center, Region 3, 7th and D Streets, SW., Washington 25, D. C. Single copies required for bidding purposes are available without charge at the nearest GSA Regional Office.

This amendment is a part of Section IV, Part 5, of the Federal Standard Stock Catalog.

Source: https://assist.dla.mil -- Downloaded: 2024-10-26T14:58Z
Check the source to verify that this is the current version before use.