AMENDMENT

TO

INTERIM FEDERAL SPECIFICATION

FLASHLIGHT, TRAFFIC

This amendment was developed by the General Services Administration, Federal Supply Service, Washington, D.C. 20406, based upon currently available technical information. The General Services Administration has authorized the use of this amendment as a valid exception to Interim Federal Specification W-F-001247(GSA-FSS), dated November 17, 1967.

PAGE 3

Paragraph 3.3.2, first and second sentences. In the first sentence delete the wording "25 inch pounds" and substitute "30 pound inches". In the second sentence delete the wording "30 inch pounds" and substitute "50 pound inches".

Paragraph 3.3.5, fourth sentence, delete wording "15 cycles" and substitute "15 to 20 cycles".

PAGE 4

Paragraphs 4.1.1, 4.2, 4.2.1, 4.2.2 and 4.3, delete in entirety and replace with the following:

"4.1.1 Classification of inspection. Inspection shall be classified as follows:

(a) Preproduction or beginning of contractual year inspection (see 4.2).

(b) Quality conformance inspection (see 4.3).

(c) Inspection of preparation for delivery (see 4.5).

4.2 Preproduction of beginning of contractual year inspection. This inspection shall be accomplished before production of flashlights is commenced or at the beginning of each contractual year and shall consist of an examination as specified in 4.2.1 and tests as specified in 4.2.2.

4.2.1 Examination. Five sample flashlights of each type, class, and style to be supplied under this specification shall be examined to determine compliance with all requirements of section 3 above that do not require a specific section 4 test. Presence of one or more defects shall be cause for rejection.

4.2.2 Tests. Following successful completion of the examination specified in 4.2.1 above, the five samples shall be subjected to all tests specified in 4.4. Failure of any test shall be cause for rejection. Unless otherwise specified, all tests shall be conducted at room temperature, pressure and humidity."

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.

"4.3 Quality conformance inspection.

4.3.1 Sampling. Sampling for quality conformance inspection shall be in accordance with MIL-STD-105. For purposes of inspection, the test lot shall consist of all flashlights of a particular type, style, and class presented for inspection at one time. The sample unit shall be one flashlight.

4.3.2 Examination. Samples selected in accordance with 4.3.1 shall be examined as cited in 4.2.1 above. The inspection level shall be level S-4 and the Acceptable Quality Level (AQL) shall be 2.5, expressed in terms of percent defective.

4.3.3 Tests. Samples selected in accordance with 4.3.1 shall be subjected to the tests specified in 4.4.1, 4.4.2, 4.4.3, 4.4.4, 4.4.5, 4.4.9, and 4.4.10. The inspection level shall be level S-3 and the AQL shall be 2.5, expressed in terms of percent defective. Unless otherwise specified, tests shall be conducted at room temperature, pressure, and humidity."

PAGE 5

Paragraph 4.4.3, first sentence delete the wording "8 feet" and substitute "12 feet".

Paragraph 4.4.4, delete in its entirety and replace with the following:

"4.4.4 Thread test. Flashlights of each type, class, and style shall be completely assembled using batteries. All component parts that are threaded shall be backed off a minimum of two (2) complete threads and retightened using the manufacturer's recommended torque for tightening parts, a torque not to exceed 30 pound inches. This shall be considered as one test cycle. There shall be a minimum of 100 test cycles all of which shall use the same torque used in the first test cycle, a torque not exceeding 30 pound inches. The parts shall remain tightened for at least two minutes during each cycle. Upon completion of the last test cycle, the flashlight shall be assembled using a torque of 50 pound inches $\pm$ 2 pound inches, whereupon compliance with 3.3.2 shall be determined."

Paragraph 4.4.6, first and third sentences. Delete the first sentence in its entirety and replace with the following: "Sample flashlights, completely assembled including batteries, shall be subjected to a temperature of 150°F $\pm$ 5°F dry heat for 16 hours, followed by a temperature of 110°F $\pm$ 2°F at 85 percent $\pm$ 5 percent relative humidity for 6 hours." In the third sentence, delete the word "test" and replace with "tested".

Paragraph 4.4.7, first sentence, delete the wording "25,000 cycles at a rate of 15 cycles per minute" and replace with "25,000 continuous cycles at a rate of 15 to 20 cycles per minute".

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T11:34Z
Check the source to verify that this is the current version before use.