INCH-POUND

MIL-DTL-3922/57C
27 May 2008
SUPERSEDING
MIL-F-3922/57B
4 May 1976

DETAIL SPECIFICATION SHEET

FLANGES, WAVEGUIDE (COVER) (ROUND, 8 HOLE) (2 HOLES CENTERED HORIZONTALLY, 2 HOLES CENTERS VERTICALLY)

This specification is approved for use by all Departments and Agencies of the Department of Defense.

Inactive for new design after 18 September 1998.

Requirements for acquiring the flanges described herein shall consist of this document and MIL-DTL-3922.



NOTES:

1. Dimensions are in inches. Dimensions are in accordance with ASME Y14.5M.
2. Millimeter equivalents (to the nearest 0.01 mm) are given for general information only and are based upon 1.00 inch = 25.4 mm.
3. Millimeter equivalents are tabulated.
4. Roughness of mating surfaces shall not exceed 63 micro-inches in accordance with ASME B46-1, except that flaws shall be included in the roughness height measurement.

FIGURE 1. Flange configuration.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:06Z
Check the source to verify that this is the current version before use.

Inches	mm
.0015	0.04
.002	0.05
.005	0.13
.015	0.38
.094	2.39
.250	6.35

TABLE I. Dash numbers and dimensions.

PIN M3922/57-			1/ Dimensions								
Dash no.	Used with		A +.003 (0.08) -.000	B +.003 (0.08) -.000	C ±.015 (0.38)	D BSC	E Max Rad	F +.004 (0.10) -.000	G ±.015 (0.38)	H ±.015 (0.38)	J ±.015 (0.38)
	Waveguide M85/1-	Mating flange M3922/62-									
001 3/	053	001	2.002 (50.85)	1.002 (25.45)	3.625 (92.08)	3.250 (82.55)	.031 (0.79)	.199 (5.05)	2.625 (66.68)	.250 (6.35)	.375 (9.53)
002 2/	055	002									

1/ Dimensions are in inches (millimeters are in parentheses). Dimensions are in accordance with ASME Y14.5M.
2/ Copper alloy.
3/ Aluminum alloy.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:06Z
Check the source to verify that this is the current version before use.

REQUIREMENTS:

Dimensions and configuration: See figure 1 and table I.

Material: Metallic alloy as specified in table I.

Marking: See figure 1.

Part or Identifying Number (PIN): M3922/57- (and dash number from table I).

TABLE II. Cross-reference and engineering information.

PIN M3922/57-	AN nomenclature	Frequency range (GHz)
001	UG-407/U	3.95 - 5.85
002	UG-149A/U	3.95 - 5.85

Changes from previous issue. Marginal notations are not used in this revision to identify changes with respect to the previous issue due to the extent of the changes.

Referenced documents. In addition to MIL-DTL-3922, this document references ASME B46.1 and ASME Y14.5M.

Custodians:
Army - CR
Navy - EC
Air Force - 11
DLA - CC

Review activities:
Army - AV, MI
Navy - AS, MC, OS, SH
Air Force - 99

Preparing activity:
DLA - CC

(Project 5985-2008-038)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at http://assist.daps.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-16T22:06Z
Check the source to verify that this is the current version before use.