MILITARY SPECIFICATION

CARTRIDGE, 40MM, HE, XM684
LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-C-50466 (MU), dated 21 November 1969, and is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 1

Add the following preamble underneath the title:

"This specification is approved for use by the US Army Armament Research and Development Command and is available for use by all Departments and Agencies of the Department of Defense."

Delete "8865431 and 8865432" and substitute "9251995 and 9251996" wherever referenced in this specification.

PAGE 8

4.3.2.8: Add Major defect 104 as follows:

"104. Support missing Visual 08004."

PAGE 11

4.3.3.11: Delete last sentence in its entirety and substitute the following:

"The sample cartridges shall be selected at random prior to linking and then linked with the same lot of links to which its respective end item lot has been assembled."

4.3.3.11.1: Delete "f and g" in their entirety and substitute the following:

"f. Major - Twelve (12) or more fail high order proper detonation at target area (see 6.12).

g. Major - Less than 65 are not between 2 and 25 feet."

FSC 1310

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:25Z
Check the source to verify that this is the current version before use.

PAGE 13

Add new paragraphs 4.3.3.14 and 4.3.3.15 as follows:

"4.3.3.14 Pot life of adhesive (see 6.13) (See Dwg. 9217500), Major Defect, Code No. 25001. - Each batch of adhesive mixed for use in assembly of fuzes to bodies shall be subjected to this determination. If any batch fails to comply with applicable requirement, it shall not be used for assembly of fuzes to bodies. Projectile assemblies which have been assembled with adhesive which exceed the pot life requirement shall be disassembled, cleaned and new adhesive applied. The test shall be performed as specified in 4.4.13.

4.3.3.15 Disassembly torque of fuze (See Dwg. 9247851). Major defect Code No. 26001. - One (1) cartridge shall be selected from each batch of adhesive and held for 24 hours, after which each of the selected cartridges shall be subjected to this test. If any cartridge fails to comply with the applicable requirement the lot shall be rejected. This test shall be performed as specified in 4.4.13 using equipment in accordance with 4.3.4."

PAGE 16

Add new paragraphs 4.4.13 and 4.4.14 as follows:

"4.4.13 Pot life of adhesive - The time from preparation of the adhesive for use in assembly of fuzes to bodies, to its application shall be determined. Any method considered satisfactory to the Contracting Officer may be used in performing this determination. This is a non-destructive test. Adhesive so tested shall be returned to the lot.

4.4.14 Disassembly torque of fuze. The projectile assembly shall be placed in a fixture as specified on the Equipment List and the torque specified on Dwg. 9247851 shall be applied. This is a destructive test, no cartridge so tested may be returned to the lot."

PAGE 20

6.12: Delete in its entirety and substitute the following:

"6.12 Proper ambient functions are defined as from the surface to 35 feet."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:25Z
Check the source to verify that this is the current version before use.

Add new paragraph 6.13 as follows:

"6.13 The period of time during which an adhesive after mixing with catalyst, solvent, or other compounding ingredients, remains suitable for use."

Custodian:
Army-AR

Preparing Activity:
Army-AR

(Project 1310-A278)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:25Z
Check the source to verify that this is the current version before use.