MIL-C-50513B (AR)
AMENDMENT 2
10 August 1981
SUPERSEDING
AMENDMENT 1
23 March 1981

MILITARY SPECIFICATION

CARTRIDGE, IGNITION, M2A2
PARTS FOR, LOADING, ASSEMBLING AND PACKING

This amendment forms a part of Military Specification MIL-P-50513B (AR) dated 27 February 1981.

PAGE 15

* 4.4.2.8, NOTES: Delete "Samples shall be selected at random from each lot at inspection level S-4 under MIL-STD-105 or at inspection level I for use under multi-level sampling plan CSP-M of MIL-STD-1235" and substitute "Sampling, acceptance criterea and test procedure for this test shall be as specified in MIL-P-116".

PAGE 18

4.5.3, line 6: Delete "5 sec." and substitute "3 sec."
line 9: Delete "0.25 psi" and substitute "0.15 psi"

PAGE 19

* 4.5.4: Delete "paragraph in its entirety" and substitute "4.5.4 Proving ground. This test shall be performed at a government proving ground. The ignition cartridge with inert loaded M329A2 projectile shall be assembled into a M329A2 cartridge to a weight of 22.12 plus or minus .01 pounds. The sample shall be fired at the 5 increment charge. Each round in the sample shall contain a bag loading assembly (minimum charge) and a five increment bundle. The bag loading assembly shall be centered over the flash holes on the cartridge container and the five increment bundle shall be placed forward of and against the bag. The bag loading assembly and propellant increment bundle shall be from an acceptable stock lot. The rounds shall be fired from a 4.2 Inch M30 mortar at an elevation of 900 mils.

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.

Conditioning rounds will be assembled from stock components and fired to condition the weapon, to check-out instrumentation and spot the field. The number of conditioning rounds required for the temperature conditions specified are as follows:

Ambient Temp.	Number of Rounds
Above 72°F	2
32°F to 72°F	3
Below 32°F	4

Individual muzzle velocites and standard deviation of the sample be recorded and reported for information purposes."

PAGE 20

* 5.3.1 under 25-CARTRIDGE, IGNITION, M2A2: Delete
"LOT (MFR SYMBOL NO.)
LOADED (MO/YR)"
and substitute "LOT NUMBER (See 4.4.1 of MIL-A-48078)"

NOTE: The margins of this amemdment are marked with an asterisk to indicate where changes from the previous amendments were made. This was done as a convenience only and the Government assues no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous amendment.

Custodian:
ARMY-AR

Preparing Activity:
ARMY-AR

Project Number: 1315-A399

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:27Z
Check the source to verify that this is the current version before use.