MIL-S-50347(AR)
AMENDMENT 2
30 April 1982
SUPERSEDING
AMENDMENT 1
1 April 1975

MILITARY SPECIFICATION

SIMULATOR, TARGET: 10558244

This amendment forms a part of Military Specification MIL-S- 50347 (MU) dated 10 November 1969, and is approved for use by the US Army Armament Research and Development Command, and is available for use by all Departments and Agencies of the Department of Defense.

PAGE 3

Delete "MIL-S-60347(MU)" and substitute "MIL-S-50347 (AR)"

PAGES 7 , 8, 9 & 10

TABLE I: Delete in its entirety and substitute new Table 1.

TABLE I. INPUT AND OUTPUT CHARACTERISTICS

REQUIREMENT	CHARACTERISTICS	TERMINALS
Input power	6.0 ± 0.3 Vdc regulated, ac ripple not greater than 50 mV peak-to-peak 300 mA capacity.	P1-30 31, 32(+) and P1-24 25, 26 (Ret)
	33 ± 1 Vdc ac ripple not greater than 0.1V peak-to-peak, 10 mA capacity.	P1-5(-) P1-25 (Ret)
INPUT SIGNALS		
Signal #1	positive pulse from zero volts to not less than 15 Vdc, 0.2 to 0.6 usec pulse width at the 50% points , rise time of 40 nsec max into 50 Ω as measured between 10% and 90% points, 20 kHz + 10% PRF.	P1-19 and P1-18 (Ret)
Signal #2	positive pulse from 0 V to 3.0 Vdc, 0.35 ± 0.05 usec pulse width, delayed 15.0 ± [illegible] usec after signal #1.	P1-20 and P1-22 (Ret)

FSC 4931

Source: https://assist.dla.mil -- Downloaded: 202640-22T20:22Z
Check the source to verify that this is the current version before use.

OUTPUT SIGNALS

Simulated Target	0.2 ± 0.1 usec positive pulse from 0 V to not less than +3 Vdc, delayed 2 to not more than 34 usec from Signal #1. Delay controlled by resistance between J1-42 and J1-47 and proper switching between J1-33 through J1-38.	P1-16 and P1-14 (Ret)
Sum Doppler	2.5 kHz 10% square wave FORM 0 V to not less than +3 Vdc.	P1-9 and P1-10 (Ret)
Difference Doppler	2.5 kHz 10% square wave, from 0 V to not less than +3 Vdc out of phase with the sum doppler when simulated target appears before Signal #2.	P1-12 and P1-8 (Ret)

PAGE 17

4.5.2.2: Item 2, Description: Delete "5Vdc + 0.3" and substitute "6 Vdc + 0.3."

PAGE 18

Item 4, Description: Delete in its entirety and substitute: "positive pulse, O V to no less than 15 Vdc, 0.2 to 0.6 usec pulse width at the 50% points, rise time of 40 nsec max. into 524-L as measured between 10% and 90% points, 20 kHz ± 10% PRF."

Item 5, Description Add: "and have an adjustable delay from SYNC SIGNAL to OUTPUT SIGNAL 0 tO 20 usec MIN."

PAGE 19

4.6.1.1: After 4.9.1.3 does not apply, add: "The frequency and amplitude limits of paragraph 3.3.1 of this specification shall be used."

PAGE 20

4.6.1 .4.2: Delete "-40°F" and "4.6.2" and substitute: "+ 32°F" and "4.6.2."

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:22Z
Check the source to verify that this is the current version before use.

PAGE 23

4.6.3.1(b): Delete: "2 to 10 usec with adjustment of R1" and substitute: "not more than 2 to not more than 1[illegible] usec with the adjustment of R1. Performance can degrade at temperature extremes not more than 2 to not more than 20u sec, with adjustment of R1".

4.6.3.1(e): Delete: "10 + 1.0 usec to 20 + 1.0 usec" and substitute: "not more than 11 to not more than 26 Usec . Performance can degrade ac temperature extremes not more than 11 to not more than 30 usec."

PAGE 24

4.6.3.l(h): Delete: “20 + 1.0 Usec to 30 + 1.0 usec" end substitute: "not more than 19 to not–more than 34 usec. Performance can degrade at temperature extremes net more than 19 to not more than 40u sec.”

4.6.3.2(b): Delete: “not less than 3 volts P-P in phase when R1 is CCW and out of phase when R1 is CW" and substitute: “not less than 3 volts P-P in phase when R1 is CW and nut of phase when Rl is CCW."

NOTE : The margins of this amendment are marked with an asterisk or vertical lines to indicate where changes from the previous amendment were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relati onship to the last previous amendment.

Custodian:
Army - AR

Preparing activity:
Army - AR

(Project 4931-A190)

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:22Z
Check the source to verify that this is the current version before use.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T20:22Z
Check the source to verify that this is the current version before use.