METRIC

MIL−PRF−14512L(EA)
13 March 2000
SUPERSEDING
MIL−DTL−14512KEA)
22 October 1997

PERFORMANCE SPECIFICATION

FILTER, GAS, 340 L/M, M12A2

This specification is approved for use by the U.S. Army Edgewood Chemical Biological Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This performance specification covers a 340 liters per minute (l/m) gas filter which filters out airborne toxic chemical agents as part of a Nuclear, Biological and Chemical (NBC) filtration system in the armored weapons systems.

2. APPLICABLE DOCUMENTS

2.1 General. The documents listed in this section are specified in sections 3 and 4 of this specification. This section does not include documents cited in other sections of this specification or recommended for additional information or as examples. While every effort has been made to insure the completeness of this list, document users are cautioned that they must meet all specified requirements documents cited in sections 3 and 4 of this specification, whether or not they are listed.

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: Technical Director, U.S. Army Edgewood Chemical Biological Center, ATTN: AMSSB−REN−SS, Aberdeen Proving Ground, MD 21010−5424 by using the self−addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A FSC 4240

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

2.2 Government documents.

2.2.1 Specifications, standards, and handbooks. The following specifications, standards, and handbooks form a part of this document to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DoDISS) and supplement thereto, cited in the solicitation (see 6.2).

STANDARDS

FEDERAL

FED−STD−191 − Textile Test Methods

DEPARTMENT OF DEFENSE

MIL–STD–810 – Environmental Test Methods and Engineering Guidelines

MIL–STD–1168 – Ammunition Lot Numbering

(Unless otherwise indicated, copies of the above specifications, standards and handbooks are available from the Standardization Document Ordering Desk, 700 Robbins Avenue, Building 4D, Philadelphia, PA 19111–5094.)

2.2.2 Other Government documents, drawings, and publications. The following other Government documents, drawings, and publications form a part of this document to the extent specified herein. Unless otherwise specified, the issues are those cited in the solicitation.

U.S. ARMY EDGEWOOD CHEMICAL BIOLOGICAL CENTER

PURCHASE DESCRIPTIONS

EA−DTL−1704 − Carbon, Activated, Impregnated, Copper−Silver−Zinc−Molybdenum − Triethylenediamine (ASZM − TEDA)

DRAWINGS

136−41−1755 − Tester, Filter Life, 12 CFM, Q223, Assembly
5−19−2295 − Filter, Gas, 12 CFM, M12A2 (ASZM−TEDA)

(Copies are available from Technical Director, U.S. Army Edgewood Chemical Biological Center, ATTN: AMSSB–REN–SE, Aberdeen Proving Ground, MD 21010–5424.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

CODE OF FEDERAL REGULATIONS

40 CFR Part 261 − Hazardous Waste Management

(The Code of Federal Regulations is for sale on a subscription basis from the Superintendent of Documents, U.S. Government Printing Office, Washington, DC 20402. When indicated, reprints of certain regulations may be obtained from the federal agency responsible for issuance thereof.)

2.3 Non−Government publications. The following documents form a part of this document to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issue of the documents cited in the solicitation (see 6.2).

AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS

ACGIH publication − Threshold Limit Values and Biological Exposure Indices (see 6.2)

(Application for copies should be addressed to American Conference of Governmental Industrial Hygienists, 1330 Kemper Meadows Drive, Cincinnati, OH 45240) (http://www.acgih.org)

ASTM STANDARDS

D 2867 − Moisture in Activated Carbon

(Application for copies should be addressed to ASTM, 100 Barr Harbor Drive, West Conshohocken, PA 19428−2959.)

AIR−CONDITIONING AND REFRIGERATION INSTITUTE (ARI)

ARI STANDARD 700 − Standard for Specifications for Fluorocarbons and other Refrigerants

(Application for copies should be addressed to ARI, 4301 North Fairfax Drive, Arlington, VA 22203.)

2.4 Order of precedence. In the event of a conflict between the text of this document and the references cited herein, the text of this document takes precedence. Nothing in this document, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

3. REQUIREMENTS

3.1 Materials and components.

3.1.1 Materials. The filter shall be constructed so that it conforms to the requirements of this specification. The contractor shall select materials, which pose no potential inhalation hazard to the user in excess of the limits as recommended by the American Conference of Governmental Industrial Hygienists (ACGIH publication). Unused or uncontaminated filters and packaging materials at the time of disposal shall not be a Resource Conservation Recovery Act (RCRA) hazardous waste as defined in 40 CFR 261.21–261.24 or 40 CFR 261.33 (e) and (f).

3.1.2 Adsorbent media. The adsorbent media shall fully meet the requirements of EA–DTL–1704 when ASZM–TEDA carbon is used, or the adsorbent media shall meet the hardness requirement of EA–DTL–1704 and performance requirements in 3.5.7 of this specification if ASZM–TEDA carbon is not used. In any case, the adsorbent shall be chromium free and pose no health hazards or potential environmental problems. For adsorbent other than ASZM–TEDA carbon, the lotting shall be equivalent to those requirements found in EA–DTL–1704.

3.2 First article. When specified (see 6.2), a sample shall be subjected to the first article inspection in accordance with 4.2.

3.3 Physical characteristics.

3.3.1 Filter body. The filter body shall be of a design strong enough to withstand all tests delineated in this specification without any visible damage and/or degradation.

3.3.2 Filter weight. The weight of the complete unpackaged filter shall not exceed 1.6 kilograms.

3.4 Interface.

3.4.1 Filter size. The external dimensions of the filter shall be form and fit equivalent to those in Drawing 5−19−2295.

3.4.2 Interfacing surfaces. The interfacing inlet and outlet surfaces of the filter shall be equivalent to those in Drawing 5–19–2295. The filter inlet shall contain a flat edge and the filter outlet shall contain a protruding edge per Drawing 5–19–2295.

3.5 Performance characteristics.

3.5.1 Air flow resistance. The air flow resistance of the filter shall not exceed 122 millimeters (mm) of water at a 340 standard liters per minute with an air stream temperature of 21˚C and a barometric pressure of 760 mm Hg.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

3.5.2 Leakage. The filter shall not leak when a concentration of 1000 parts per million (ppm) of R−134a (1,1,1,2 tetrafluoroethane) refrigerant is introduced at the filter inlet. A filter leak is defined as the presence of 1 ppm or more of R134a in the effluent air within two minutes after the introduction of the refrigerant at the inlet.

3.5.3 Moisture content of adsorbent. The moisture content of the adsorbent taken immediately before packaging shall not exceed 3.0 percent.

3.5.4 Structural integrity. The filter shall withstand rough handling consisting of 200 drops per minute for 15 minutes, where each drop represents a 19–millimeter fall. Sample filters shall show no evidence of cracks, dents or structural damage, upon visual inspection after completion of testing.

3.5.5 Dimethylmethylphosphonate (DMMP) gas life (destructive). After meeting the requirements of 3.5.4, the filter shall have a DMMP gas life of not less than 100 minutes at rated flow (340 liters per minute) when subjected to a DMMP challenge of 2.0±0.2 milligrams per liter with an air stream temperature of 28±3˚C. Break concentration shall be 0.04 micrograms per liter.

3.5.6 Cyanogen Chloride (CK) gas life (destructive). The filter shall have a CK gas life of no less than 30 minutes at rated flow (340 liters per minute) when subjected to a CK challenge concentration of 4.0±0.2 milligrams per liter, with an air stream relative humidity (R.H.) of 80±3 percent and air stream temperature of 24±3˚C. Break concentration shall be 5 micrograms per liter. Filters shall be equilibrated to 80 percent R.H. prior to test.

3.5.7 Adsorbent media gas life capacity. If a material other than ASZM–TEDA adsorbent is proposed as the adsorbent media, the material must be pre–qualified in a gas life test program in advance of First Article inspection. The qualification test program shall demonstrate to the Government that gas life before and after environmental open–air exposure is equal or greater than that of ASZM–TEDA carbon for agents hydrogen cyanide (AC), CK, phosgene (CG) and DMMP as listed in EA–DTL–1704 and any additional chemical agents or simulants that are specified by the Government (see 6.5). For those agents or simulants not listed in this paragraph, the Government reserves the right to establish gas life requirements for those agents or simulants.

3.5.8 Fines retention. Internal fines media shall retain the adsorbent in the adsorbent bed, so that the adsorbent emission from any individual filter shall not exceed 50 milligrams.

3.5.9 Fines media. The fines media material, if made from natural cloth or any other organic material, shall resist dampness and mildew. The material shall have a minimum spray rating of 50.0 and no visible growth of mildew on the material shall be evident after testing.

3.6 Markings. The exterior filter body shall be marked with the filter nomenclature: “FILTER, GAS, 340 L/M, M12A2” and the lot number in a nominal 6 mm high lettering. Additional informa-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

tion may be required by solicitation. The distance between the lines of lettering shall be a nominal 9.5–mm. The marking shall be black paint or ink.

3.7 Workmanship.

3.7.1 Safety. Filters shall be free from sharp edges and burrs that might injure personnel or damage Mission Oriented Protective Posture (MOPP) IV gloves during handling.

3.7.2 Appearance. Filters shall be free from foreign matter and cracked, dented or bent sections.

4. VERIFICATION

4.1 Classification of inspections. The inspection requirements specified herein are classified as follows:

(a) First article inspection (see 4.2)
(b) Conformance inspection (see 4.3)

4.2 First article inspection.

4.2.1 Sample. The first article sample shall consist of 20 consecutively produced filters which pass airflow and leakage requirements (3.5.1 and 3.5.2). The first article sample shall be manufactured using the same methods, materials, equipment, and processes as will be used during regular production. The first article sample shall be submitted for inspection and approval in accordance with the terms of the contract.

4.2.2 Inspection procedure. Unless otherwise specified by the terms of the contract, the sample first article items shall be subjected to any or all of the examinations and tests specified in this specification and be inspected for compliance with all of the requirements of the applicable packaging requirements.

4.2.2.1 For examination. The sample filters shall be examined for all visual and measurable requirements of this specification.

4.2.2.2 For test. Samples of at least 100 grams each of adsorbent shall be taken during the filling of the first, tenth and twentieth filters and placed in separate open containers whose diameters are such that the depth of the carbon will be 38±13 mm deep. Those samples of adsorbent shall be exposed to the same conditions of temperature and humidity as their associated filters. Each filter shall be tested for airflow resistance (4.3.6.1) and leakage (4.3.6.2). Six of the 20 filters shall then be tested in accordance with the fines retention test (4.3.6.8), and dampness and mildew resistance tests (4.3.6.9) after being examined for workmanship. Following leakage testing, the 14 remaining acceptable filters shall be packaged using the same methods, materials, equipment, and processes as will be used during regular production. Concurrent with or immediately following the packaging of the fil-

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

ters corresponding to each adsorbent sample, a 10–gram portion of each mixed adsorbent sample shall be tested for moisture content in accordance with 4.3.6.3. The packaged sample filters shall then be forwarded to the Government, and seven of them subjected to rough handling in accordance with 4.3.6.4. These seven filters shall be tested by the Government in accordance with the DMMP gas life test (4.3.6.5) and the other seven filters shall be tested in accordance with the CK value test (4.3.6.6). Any filter failing leakage or airflow resistance requirements shall be rejected and removed from the lot. If any sample filter from the lot fails to meet the other requirements in section 3, the first article lot shall be rejected.

4.2.3 Acceptance criteria. If any first article sample item fails to comply with any of the applicable requirements, the first article quantity shall be rejected. The Government reserves the right to terminate inspection upon any failure to comply with any of the requirements. The contractor shall obtain written approval from the contracting activity prior to proceeding with regular production.

4.3 Conformance inspection.

4.3.1 Lotting. A lot shall consist of the filters produced by one manufacturer on one production line, from the same materials, with the same process, and without a break in production of more than 10 calendar days. However, any one lot of filters shall contain no more than one lot of adsorbent, and a new lot of filters shall be started whenever any adsorbent filling or final assembly process equipment change is made. Each lot shall be identified and controlled in accordance with MIL−STD−1168.

4.3.2 Sampling.

4.3.2.1 For examination. Sampling of packaged filters shall be conducted in accordance with the classification of characteristics in 4.3.5 and, when specified, table I. Samples shall be selected at random.

4.3.2.2 For tests. Sample sizes for DMMP and CK gas life testing shall be as follows:

TABLE I. Sampling plan for filter gas life

Lot size	DMMP and Structural Integrity sample size	CK sample size
30 to 150	5	5
151 to 500	8	8
501 to 5000	13	13

4.3.3 Inspection procedure.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

4.3.3.1 For examination. Every item in the lot shall be inspected for critical characteristics. Sample filters shall be examined and tested in accordance with the classification of characteristics in 4.3.5. If a filter is found that does not conform to leakage or air flow resistance requirements, the non–conforming filter shall be rejected and removed from the lot. For major characteristics other than air flow resistance, failure of samples to conform to any characteristic based on sampling and acceptance criteria specified therein shall be cause for rejection of the lot. Failure of any sample filter to conform to any minor characteristic based on the sampling and acceptance criteria specified therein may be cause for rejection of the lot represented.

4.3.3.2 For test. A 100–gram sample of adsorbent shall be taken during the filling of the first and last filter manufactured each day and placed in separate open containers. Those samples of adsorbent shall be exposed to the same conditions of temperature and humidity as their associated filters. Each filter shall be tested for airflow resistance (4.3.6.1) and leakage (4.3.6.2). Following leakage testing, filters shall be packaged. Concurrent with or immediately following the packaging of the filters corresponding to each adsorbent sample, a 10–gram portion of each mixed adsorbent sample shall be tested for moisture content in accordance with 4.3.6.3. Packaged sample filters shall then be forwarded to the Government and half of them subjected to rough handling in accordance with 4.3.6.4. Following rough handling, the Government shall conduct gas life tests on sample filters (see Table I) in accordance with 4.3.6.5 and 4.3.6.6. Any filter failing leakage or air flow resistance requirements shall be rejected and removed from the lot. If any sample filter from the lot fails to meet the other requirements in section 3, the lot represented shall be rejected.

4.3.4 Inspection characteristics. Critical characteristics are characteristics whose nonconformance to specified requirements is likely to result in hazardous or unsafe conditions for individuals who use or maintain the product. Characteristics whose nonconformance to specified requirements is likely to prevent performance of the tactical function of a major end item are also critical characteristics. Major characteristics are characteristics whose nonconformance to specified requirements is likely to result in failure or to reduce materially the usability of the item for its intended purpose. Minor characteristics are characteristics whose nonconformance to specified requirements is not likely to reduce materially the operation or usability of the item for its intended purpose.

4.3.5 Classification of characteristics. Conformance examinations and tests shall be as specified in table III. When specified herein, accept on 0 and reject on 1 attributes sampling inspection shall be performed on the designated characteristics using the stated levels in table II for selection of sample sizes.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

TABLE II. Sampling

Lot size	Inspection levels and sample sizes										
	I	II	III	IV	V	VI	VII	VIII	IX	X	XI
2 to 8	*	*	*	*	*	*	*	*	5	3	2
9 to 15	*	*	*	*	*	*	13	8	5	3	2
16 to 25	*	*	*	*	*	20	13	8	5	3	3
26 to 50	*	*	*	*	32	20	13	8	5	5	5
51 to 90	*	*	*	50	32	20	13	8	7	6	5
91 to 150	*	*	125	50	32	20	13	12	11	7	6
151 to 280	*	*	125	50	32	20	20	19	13	10	7
281 to 500	*	315	125	50	48	47	29	21	16	11	9
501 to 1200	*	315	125	75	73	47	34	27	19	15	11
1201 to 3200	1250	315	125	116	73	53	42	35	23	18	13
3201 and above	1250	315	192	116	86	68	50	38	29	22	15

*Indicates one hundred percent inspection. If sample size exceeds lot size, perform one hundred percent inspection.
Accept the lot represented on zero nonconforming characteristics and reject the lot represented on one or more nonconforming characteristics for all inspection levels.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

TABLE III. Classification of characteristics

CATEGORY	CHARACTERISTIC	SAMPLING	REQUIRE–MENT PARAGRAPH	INSPECTION METHOD
Critical 1	Leakage	100%	3.5.2	4.3.6.2
Major				
101	Airflow resistance	100%	3.5.1	4.3.6.1
102	Moisture content	4.3.3.2	3.5.3	4.3.6.3
103	Gas life, DMMP* after rough handling	Table I	3.5.5	4.3.6.6
104	Gas life, CK*	Table I	3.5.6	4.3.6.7
105	Workmanship	Table II, level IX	3.7	VI
Minor				
201	Identification markings	Table II, level IX	3.6	VI

NOTES:

CE – Commercial inspection equipment
COC – Certificate of Compliance
VI – Visual inspection
D – Demonstration

*Failure may be considered a critical defect

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

4.3.6 Tests.

4.3.6.1 Air flow resistance. The pressure drop across the filter shall be in accordance with 3.5.1 and shall be determined at the rated airflow. The up−stream and down−stream static pressure measuring tubes shall be as close as possible to the filter and shall not be on a section of duct that has a changing cross sectional area. Test for air flow resistance as follows:

(a) Connect the filter to a source of forced air.
(b) Set the flow of air through the filter to 340 standard liters per minute.
. (c) Record the barometric pressure.
(d) Measure and record the air stream temperature.
(e) Determine and record the difference in static pressure head up−stream of the filter to that down−stream of the filter. If using test parameters different than those stated in 3.5.1, calculate and record the air flow resistance, ΔP(cal), using the equation below to correct test measurements to standard conditions.

$$\Delta P(cal) = \frac{P(test) \times \Delta P(measured) \times 86.2}{(492 + 1.8T)^{1.768}}$$

ΔP(cal) – Air flow resistance corrected to standard conditions in millimeters of water
P(test) – Barometric pressure at time of test in mm Hg
ΔP(measured) – Value recorded from test measurement in millimeters of water
T – Temperature of air stream flowing through filter in degrees C

If ΔP(cal) is more than the air flow resistance stated in 3.5.1, the filter shall be rejected.

4.3.6.2 Leakage. Rigidly position the sample gas filter in the test fixture with the inlet and outlet faces in a vertical plane. Use R–134a refrigerant that conforms to the characteristics of ARI STANDARD 700. Connect the filter to a source of forced air and place a mixing chamber at the influent side. Regulate the flow of air from the blower to 68 l/m (1/5 of the 340 l/m rated airflow). Introduce R–134a into the intake of the blower; monitor and maintain a concentration of 1000 ppm by volume of R–134a in airflow of 68 l/m on the influent side of the filter at 24±5˚C (75±9˚F) and relative humidity of no higher than 50 percent. Leakage shall be determined using a suitable leak detector (see 6.4) for sampling and detecting R–134a at the effluent side of the filter. Monitor the effluent airstream for at least 2 minutes. Determine whether the effluent concentration exceeds 1 ppm within 2 minutes after the introduction of the refrigerant at the inlet of the filter. Purge the filter by passing clean air in the reverse direction through the filter at rated flow for 3 minutes. Keep the exposure of the filter to air to a minimum.

4.3.6.3 Moisture content of filter. The filters shall meet the moisture content specified in 3.5.3 when the moisture content of the adsorbent is determined in accordance with ASTM D 2867, Oven–Drying Test Method, except that the oven temperature shall be 103–107˚C and the drying time shall

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

be 3 hours. If the moisture content of the adsorbent exceeds the requirement, the filters represented by the samples shall be considered unacceptable.

4.3.6.4 Structural integrity. Each sample filter shall be positioned with the inlet and outlet faces in a vertical position and clamped on a steel movable plate. The plate shall measure 76.2 centimeters by 76.2 centimeters and have a total weight of 109±9 kilograms including the holding clamps. When the filter is securely clamped in place, there shall be no distortion of the frame or body of the filter. The steel movable plate and filter shall be raised and let fall (free) 19±3 mm onto a steel plate at the rate of 200 drops per minute for 15±0.1 minutes. The steel base plate shall be part of the apparatus and shall be firmly anchored to a concrete floor capable of absorbing the impact of the vertical vibrations. The test shall be performed at a room temperature of 21±11˚C. Throughout the test the filter shall remain in a firm position. Filters may be padded or blocked where clamps press against the side or top of the frame, but not the bottom, to prevent distortion of the filter. The movable steel plate must be parallel to the base plate at all times to eliminate any horizontal movement and/or force. The filter shall meet the requirements of 3.5.4 after rough handling.

4.3.6.5 DMMP gas life (destructive). DMMP life shall be determined by the Government laboratory in accordance with 3.5.5 using the Q223 tester (Drawing 136−41−1755) or an equivalent tester.

4.3.6.6 CK gas life (destructive). The CK life shall be determined by the Government laboratory in accordance with 3.5.6 using the Q223 tester or an equivalent tester.

4.3.6.7 Adsorbent media. For adsorbent other than ASZM–TEDA adsorbent, all supporting test data shall be based on test paragraphs, conditions and methods described in EA–DTL–1704. Supporting test data will also be needed for any required test falling outside the scope of EA–DTL–1704 (see 6.5).

4.3.6.8 Fines retention test. The filter shall be rigidly mounted with the top face in the vertical position and subjected to the test of MIL−STD−810, Method 516.4, Procedure I. A total of three half sine wave shock pulses shall be applied in both directions along each of three mutually perpendicular axes. Peak amplitude shall be 40±4 g, 11±0.2 milliseconds (ms). At the conclusion of the test, examine the filter for adsorbent fines emission and record the total amount of emission through the fines filters. The filter shall meet the adsorbent emission limits of 3.5.8.

4.3.6.9 Dampness and mildew resistance tests. The dampness resistance test shall be in accordance with 5526 of FED−STD−191 and the mildew resistance test shall be in accordance with 5750 of FED–STD–191. A minimum of two samples of fines media from filters shall be subjected to each test.

5. PACKAGING

5.1 Packaging. For acquisition purposes, the packaging requirements shall be as specified in the contract or order (see 6.2). When actual packaging of materiel is to be performed by DoD

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

personnel, these personnel need to contact the responsible packaging activity to ascertain requisite packaging requirements. Packaging requirements are maintained by the Inventory Control Point's packaging activity within the Military Department or Defense Agency, or within the Military Department's System Command. Packaging data retrieval is available from the managing Military Department's or Defense Agency's automated packaging files, CD−ROM products, or by contacting the responsible packaging activity.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful, but is not mandatory.)

6.1 Intended use. The gas filter covered by this performance specification is intended to be used as a component of NBC filtration systems in military armored vehicles such as the Bradley Fighting Vehicle. This filtration device (M2A2 Air Purifier) normally provides purified air to four crewmembers inside a closed vehicle in a chemical agent contaminated environment. The M12A2 gas filter fits inside the purifier along with the M13 particulate filter. The M12A2 gas filter is military unique with no known commercial application.

6.2 Acquisition requirements. Acquisition documents must specify the following:

(a) Title, number, and date of this specification
(b) Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.2.1)
(c) The American Conference of Governmental Industrial Hygienists (ACGIH) ordering number or designation for their publication listing threshold limit values to be applicable for the solicitation.
(d) First article (when required):
  (1) Time allowed for contractor submission of samples for Government test and evaluation after award of contract when testing is performed by the Government.
  (2) Name and address of test facility and shipping instructions when testing is performed by the Government.
  (3) Time required for the Government to notify the contractor whether or not to proceed with production.
(e) Packaging requirements.
(f) Additional identification or marking requirements, if required, must be in the contract and cite the identification method and responsibility for the items affected,

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

such as test units, components, serial numbers, Julian date, lot numbers, contract number, etc.

6.3 DMMP and CK life tests. Samples for these tests should be forwarded by the contractor, together with DD Form 1222, to Director, U.S. Army Edgewood, Chemical Biological Center, ATTN: AMSSB−RRT−CC, Building E5165, Aberdeen Proving Ground, MD 21010−5424.

6.4 Leakage detector. The halide leak detector, model F1000, manufactured by Nucon, Inc. has been found suitable for this purpose. When using this detector, the presence of high vapor pressure halogenated contaminants in the refrigerant could interfere with the filter leak test, resulting in false indications of filter leakage. Should false leakage indications be suspected, the refrigerant should be checked for the presence of such contaminants.

6.5 Adsorbent media. Although manufacturers may consider using alternate adsorbent media, development tests comparable to those done on ASZM−TEDA adsorbent specified by EA−DTL−1704 must first be performed by the contractor, and then approved for use by the Government. Contractors are forewarned that such testing, which includes gas life capacity testing using a variety of chemical agents before and after open−air environmental exposure, may be lengthy and costly. All such costs will probably be borne by the contractor, including costs for Government testing

6.6 Drying of filters. Filters not meeting the moisture requirement may be dried by passing contaminant free air at a temperature not to exceed 100˚C through the filters.

6.7 Gasket. A wool felt gasket has been successfully used in the past as a seal on the inside flange of the filter body on the outlet side of the filter.

6.8 Subject term (key word) listing.

CK (cyanogen chloride)
DMMP
Filtered air
Gas filter
R−134a (1,1,1,2 tetrafluoroethane)

6.9 Manufacture. The following method of manufacture has been found to produce a satisfactory filter. This procedure is furnished with the distinct understanding that the supplier is not required to follow the method, that the provisions of this specification must be met regardless of the method of manufacture, and that the Government does not guarantee that material made in accordance with the method will pass the specification requirement.

Filling sorbent container.

(a) A container with the felt gasket and perforated sorbent retainer assembly installed

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

should be placed in position on a suitable gravity type filling machine.

(b) A measured amount of properly screened carbon conforming to EA−DTL−1704 should be fed gradually and uniformly from a height of 2 feet into the container.

(c) The second perforated sorbent retainer assembly should be put over the carbon and a retainer should be placed on top.

(d) A 1000 pound load should be uniformly applied to the retainer and, while under load, the retainer should be spot welded to the container.

The weight of carbon required to properly fill the container will vary according to the bulk density and moisture content. The required weight has been found to be approximately 1−7/8 pounds, however, a volumetric measure will vary much less than a gravimetric measure. It is advisable to predetermine experimentally the required amount of carbon to fill a container so that the dimensions specified on Drawing 5−19−2295 are met after the weight load has been applied to the retainer.

Custodian:

Army − EA

Preparing activity:

Army − EA

Project No. 4240−A230

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

INSTRUCTIONS

1. The preparing activity must complete blocks 1, 2, 3, and 8. In block 1, both the document number and revision letter should be given.

2. The submitter of this form must complete blocks 4, 5, 6, and 7, and send to preparing activity.

3. The preparing activity must provide a reply within 30 days from receipt of the form.

NOTE: This form may not be used to request copies of documents, nor to request waivers, or clarification of requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

I RECOMMEND A CHANGE:	1. DOCUMENT NUMBER	2. DOCUMENT DATE *(YYYYMMDD)*
	MIL-PRF-14512L(EA)	20000313

3. DOCUMENT TITLE

FILTER, GAS, 340 L/M, M12A2

4. NATURE OF CHANGE *(Identify paragraph number and include proposed rewrite, if possible. Attach extra sheets as needed.)*

5. REASON FOR RECOMMENDATION

6. SUBMITTER

a. NAME *(Last, First, Middle Initial)*	b. ORGANIZATION	
c. ADDRESS *(Include ZIP Code)*	d. TELEPHONE *(Include Area Code)* (1) Commercial (2) DSN *(If applicable)*	**7. DATE SUBMITTED** *(YYYYMMDD)*

8. PREPARING ACTIVITY

a. NAME	b. TELEPHONE *(Include Area Code)*	
U.S. Army Edgewood Chemical Biological Center	(1) Commercial (410) 436-3230	(2) DSN 584-3230
c. ADDRESS *(Include ZIP Code)* ATTN: AMSSB-REN-SS, E3331 5183 Blackhawk Road Aberdeen Proving Ground, MD 21010-5424	**IF YOU DO NOT RECEIVE A REPLY WITHIN 45 DAYS, CONTACT:** Defense Standardization Program Office (DLSC-LM) 8725 John J. Kingman Road, Suite 2533 Fort Belvoir, Virginia 22060-6221 Telephone (703) 767-6888 DSN 427-6888	

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:22Z
Check the source to verify that this is the current version before use.