INCH-POUND

MIL-T-14419C(ME)
20 December 1988
SUPERSEDING
MIL-T-14419B(ME)
6 July 1978

MILITARY SPECIFICATION

TESTER, LEAK DETECTOR, VACUUM TYPE:

FOR SEAMS IN BOLTED AND WELDED LIQUID STORAGE TANKS

This specification is approved for use within the USA Belvoir Research, Development, and Engineering Center, Department of the Army, and is available for use by all Departments and Agencies of the Department of Defense.

1. SCOPE

1.1 Scope. This specification covers a vacuum seam tester for locating leaks in the bottoms of bolted and welded liquid storage tanks, together with carrying chest.

2. APPLICABLE DOCUMENTS

2.1 Government documents.

2.1.1 Specifications and standards. The following specifications and standards form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of these documents are those listed in the issue of the Department of Defense Index of Specifications and Standards (DODISS) and supplement thereto, cited in the solicitation (see 6.2).

Beneficial comments (recommendations, additions, deletions) and any pertinent data which may be of use in improving this document should be addressed to: USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-TSE, Fort Belvoir, VA 22060-5606 by using the self-addressed Standardization Document Improvement Proposal (DD Form 1426) appearing at the end of this document or by letter.

AMSC N/A

FSC 5430

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:17Z
Check the source to verify that this is the current version before use.

SPECIFICATIONS

FEDERAL

QQ-S-781	- Strapping, Steel, and Seals.
PPP-B-601	- Boxes, Wood, Cleated-Plywood.
PPP-B-636	- Boxes, Shipping, Fiberboard.
PPP-C-843	- Cushioning Material, Cellulosic.
PPP-T-60	- Tape: Packaging, Waterproof.

MILITARY

MIL-P-116	- Preservation, Methods of.
MIL-P-514	- Plates, Identification, Instruction and Marking, Blank.
MIL-T-704	- Treatment and Painting of Materiel.
MIL-C-12044	- Chests, Plywood.
MIL-L-21260	- Lubricating Oil, Internal Combustion Engine, Preservative and Break-In.
MIL-C-46168	- Coating, Aliphatic Polyurethane, Chemical Agent Resistant.

STANDARDS

MILITARY

MIL-STD-105	- Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-129	- Marking for Shipment and Storage.
MIL-STD-130	- Identification Marking of US Military Property.
MIL-STD-461	- Electromagnetic Emission and Susceptibility Requirements for the Control of Electromagnetic Interference.
MIL-STD-462	- Electromagnetic Interference Characteristics, Measurement of.
MIL-STD-889	- Dissimilar Metals.
MIL-STD-1472	- Human Engineering Design Criteria for Military System, Equipment and Facilities.

(Unless otherwise indicated, copies of federal and military specifications, standards, and handbooks are available from the Naval Publications and Forms Center, (ATTN: NPODS), 5801 Tabor Avenue, Philadelphia, PA 19120-5099.)

2.1.2 Other Government drawings. The following other Government drawings form a part of this specification to the extent specified herein. Unless otherwise specified, the issues are those in effect on the date of the solicitation.

Source: https://assist.dla.mil -- Downloaded: 202640-18T03:17Z
Check the source to verify that this is the current version before use.

DRAWINGS

ME

TA13218E6736 - Tester, Leak Detector, for Seams in Liquid Storage Tanks.
D13218E6764 - Chest, Vacuum Seam Tester.

(Copies of drawings, publications, and other Government documents required by contractors in connection with specific acquisition functions should be obtained from the USA Belvoir Research, Development, and Engineering Center, ATTN: STRBE-FSH, Fort Belvoir, VA 22060-5606.)

2.2 Other publications. The following documents form a part of this specification to the extent specified herein. Unless otherwise specified, the issues of the documents which are DOD adopted are those listed in the issue of the DODISS cited in the solicitation. Unless otherwise specified, the issues of documents not listed in the DODISS are the issues cited in the solicitation (see 6.2).

AMERICAN SOCIETY OF MECHANICAL ENGINEERS (ASME)

Boiler and Pressure Vessel Code, Section IX, Welding Qualifications.

(Application for copies should be addressed to the American Society of Mechanical Engineers, 345 East 47th Street, New York, NY 10017.)

AMERICAN WELDING SOCIETY, INC. (AWS)

AWS B2.1 - Standard for Welding Procedure and Performance Qualification.

(Application for copies should be addressed to the American Welding Society, Inc. 550 NW Lejeune Road, Miami, FL 33126.)

SOCIETY OF AUTOMOTIVE ENGINEERS (SAE)

SAE J429 - Mechanical and Material Requirements for Externally Threaded Fasteners.

(Application for copies should be addressed to the Society of Automotive Engineers, 400 Commonwealth Drive, Warrendale, PA 15096.)

(Non-Government standards and other publications are normally available from the organizations which prepare or which distribute the documents. These documents also may be available in or through libraries or other informational services.)

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:17Z
Check the source to verify that this is the current version before use.

2.3 Order of precedence. In the event of a conflict between the text of this specification and the references cited herein (except for associated detail specifications, specification sheets, or MS standards), the text of this specification takes precedence. Nothing in this specification, however, supersedes applicable laws and regulations unless a specific exemption has been obtained.

3. REQUIREMENTS

3.1 Description. The vacuum seam tester (hereafter called the tester) shall be in accordance with Top Assembly TA13218E6736 and as specified herein.

3.1.1 Chest. The chest shall be constructed in accordance with Drawing No. D13218E6764 and MIL-C-12044.

3.1.2 Drawings. The drawings forming a part of this specification are end product drawings. No deviation from the prescribed dimensions or tolerances is permissible without prior approval of the contracting officer. Where tolerances could cumulatively result in incorrect fits, the contractor shall provide tolerances within those prescribed on the drawings to ensure correct fit, assembly, and operation of the tester. Any data (e.g. shop drawings, layouts, flow sheets, processing procedures, etc.) prepared by the contractor or obtained from a vendor to support fabrication and manufacture of the production item shall be made available, upon request, for inspection by the contracting officer or the designated representative.

3.2 First article. Unless otherwise specified (see 6.2), a sample shall be subjected to first article inspection (see 4.3 and 6.3). Any changes or deviations of tester and chest from the approved first article during production will be subject to the approval of the contracting officer. Approval of the first article will not relieve the contractor of his obligation to furnish the tester and chest in accordance with this specification.

3.3 Materials. Materials shall be as specified herein and on the applicable drawings. Materials not specified shall be selected by the contractor and shall be subject to all provisions of this specification.

3.3.1 Material deterioration prevention and control. The tester and chest shall be fabricated from compatible materials, inherently corrosion resistant or treated to provide protection against the various forms of corrosion and deterioration that may be encountered in any of the applicable operating and storage environments to which the tester and chest may be exposed.

3.3.1.1 Dissimilar metals. Dissimilar metals shall not be used in intimate contact with each other unless protected against galvanic corrosion. Dissimilar metals and methods of protection are defined and detailed in MIL-STD-889.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:17Z
Check the source to verify that this is the current version before use.

3.3.1.2 Identification of materials and finishes. The contractor shall identify the specific material, material finish or treatment for use with component and subcomponent, and shall make information available upon request to the contracting officer or designated representative.

3.3.2 Recovered materials. For the purpose of this requirement, recovered materials are those materials which have been collected from solid waste and reprocessed to become a source of raw materials, as distinguished from virgin raw materials. The components, pieces and parts incorporated in the tester and chest may be newly fabricated from recovered materials to the maximum extent practicable, provided the tester and chest produced meets all other requirements of this specification. Used, rebuilt or remanufactured components, pieces and parts shall not be incorporated in the tester and chest.

3.4 Operational performance. The tester shall be capable of developing 23.87 inches of mercury absolute in not less than 10 seconds and maintaining that vacuum for an additional five minutes. The vacuum box shall be capable of holding a 9.57 inches of mercury absolute without loss for a period of not less than 5 minutes with the valve closed.

3.5 Human factors engineering. The tester shall be in accordance with accepted Human Factors Engineering Design Criteria as described in MIL-STD-1472. Special design emphasis shall be given, but not limited to, 4. (General Requirements), 5.1 (Control/Display Integration), 5.2 (Visual Displays), 5.4 (Controls), 5.5 (Labeling), 5.9 (Design for Maintainability), and 5.13 (Hazards and Safety), of MIL-STD-1472, as applicable.

3.6 Safety. All exposed parts that are subject to high operating temperatures or that are energized electrically shall be insulated, fully enclosed, or guarded. All moving parts that are of such nature or so located as to be a hazard to operating or maintenance personnel shall be fully enclosed or guarded. Protective devices shall not impair the operating functions.

3.7 Electromagnetic interference. The electromagnetic interference emission and susceptibility characteristics of the tester shall be in accordance with MIL-STD-461, class B.

3.8 Treatment and painting. The portions of the tester and chest normally painted, internally and externally, shall be cleaned, treated, and painted in accordance with MIL-T-704, type A. Unless otherwise specified (see 6.2), top coat color shall be camouflage green 383 in accordance with MIL-C-46168.

3.9 Identification marking. The tester and chest shall be identified in accordance with MIL-STD-130. The marking shall be applied to the tester on plates in accordance with MIL-P-514, type III, composition C. Plates shall be attached with screws, bolts, or rivets in a conspicuous, protected location.

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:17Z
Check the source to verify that this is the current version before use.

3.10 Instruction plates. The tester shall be equipped with instruction plates or diagrams, including warnings and cautions, describing any special or important procedures to be followed in assembling, operating, or servicing the tester. Instruction plates shall be in accordance with MIL-P-514, type III, composition C. Plates shall be attached with screws, bolts, or rivets in a conspicuous, protected location.

3.11 Valve controls. Valve controls shall be provided with double-ended arrows showing the direction of operations and labeled at each end to indicate functional result (eg. open & close, etc).

3.12 Workmanship.

3.12.1 Metal fabrication. Metal used in fabrication shall be free from kinks and sharp bends. The straightening of material shall be done by methods that will not cause injury to the material. Corners shall be square and true. Flame cutting, using tips suitable for the thickness of the steel, may be employed instead of shearing and sawing. All bends shall be made with controlled means to ensure uniformity of size and shape. Precaution shall be taken to avoid overheating. Heated steel shall be allowed to cool slowly. External surfaces shall be free of burrs, sharp edges, and corners, except when sharp edges or corners are required or where they are not detrimental to safety.

3.12.2 Castings. All parts, components, and assemblies of the tester which include castings shall be cleaned of harmful extraneous material such as sand, dirt, sprues, scale, and flux. Rework shall be limited to procedures which do not reduce mechanical properties or affect function. A casting may be reworked once. Additional rework must be approved prior to rework by the procuring activity.

3.12.3 Welding. The surfaces of parts to be welded shall be free from rust, scale, paint, grease, mill scale that can be removed by chipping and wire brushing, and other foreign matter. Parent materials, weld filler metals, and fabrication techniques shall be as required to enable the tester to be in accordance with the examination and test requirements specified in section 4. Parts to be joined by fillet welds shall be brought into as close contact as possible, and in no event shall be separated by more than 0.1875 inch (4.763 mm) unless appropriate bridging techniques are used. Unless otherwise specified (see 6.2), the welding process used in fabrication of the tester shall be at the option of the contractor. Welds may be ground, filed, buffed, or chipped but shall not be hammered, and shall be free from discontinuities such as base metal cracks adjacent to or behind welds, cracks in weld metal, undercutting of base metal, lack of fusion with parent metal or between parts, lack of penetration, lack of prescribed fit, or spatter.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:17Z
Check the source to verify that this is the current version before use.

3.12.4 Aiuminum welding. The aluminum surfaces of parts to be welded shall be free from scale, paint, grease, oxide film, and other foreign matter. The welding shall be done by the inert gas, shielded-arc method.

3.12.5 Welders. Before assigning any welder to manual welding work covered by this specification, the contractor shall obtain certification that the welder has passed qualification tests as prescribed by either of the following listed codes for the materials joined and the type of welding operation to be performed and that such qualification is effective as defined by the particular code:

AWS B2.1 Standard for Procedure and Performance Qualification.

ASME Boiler and Pressure Vessel Code, Section IX.

Contractors who only make horizontal welds need not qualify welders for "all position welding". The contractor is responsible for determining that automatic welding equipment operators are capable of producing quality welds in accordance with AWS or ASME codes. In the event of evidence of poor welds, the Government reserves the right to require retesting of any welder or welding operator. The test results shall be made available for review by the contracting officer or the contracting officer's representative.

3.12.6 Welding practice.

a. Preheat of materials being welded and maximum interpass temperature during welding shall be in accordance with the contractor's recommendations.

b. Tack welds shall be subject to the same quality requirements as final welds.

c. Work shall be positioned for flat welding whenever practicable.

d. Procedures and sequences shall be such that distortion and shrinkage will be held to a minimum. When straightening is required, caution shall be exercised to ensure that the straightening process does not weaken the part and the tester.

e. A weld joint may be repaired by rewelding once. Any additional rewelding shall require prior approval by the procuring agency. A joint shall be prepared by grinding, chipping or machining techniques. Extra care must be used when removing cracks. All metal containing a crack, and sound metal at each end of the crack equal to a minimum of twice the base metal thickness, shall be removed before repair welding. The repaired welds shall be subject to the same weld quality requirements as the original weld.

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:17Z
Check the source to verify that this is the current version before use.

3.12.7 Weld quality.

a. All welds shall be 100 percent visually inspected. The contractor shall be responsible for additional inspections needed to ensure that, when the welded parts are assembled together to make the tester, the tester shall be in accordance with the inspection requirements specified in section 4.

b. All weldments shall be free of slag, flux, weld spatter, and other impurities.

c. Undercut in weldments shall be held to a minimum and shall not be more than 0.0312 inch (0.792 mm) deep. The accumulated length from both sides of undercut may be 2 inches for a 12-inch length of weld. For length less than 12 inches, the permitted length should be proportional to the actual length.

3.12.8 Bolted connections. Bolt holes shall be accurately formed and shall have the burrs removed. Washers or lockwashers shall be provided where necessary. Matching thread areas securing bolts shall be in accordance with SAE J429, or capscrews shall be of sufficient strength to withstand the tensile strength of the bolt. All fasteners shall be correctly torqued and shall have full thread engagement. Bolts shall protrude not more than two full threads.

3.12.9 Machine work. Tolerances and gages for metal fits shall be in accordance with the limits specified herein.

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection. Unless otherwise specified in the contract or purchase order, the contractor is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or purchase order, the contractor may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services are in accordance with the prescribed requirements.

4.1.1 Responsibility for compliance. All items must meet all requirements of sections 3 and 5. The inspection set forth in this specification shall become a part of the contractor's overall inspection system or quality program. The absence of any inspection requirements in the specification shall not relieve the contractor of the responsibility of assuring that all products or supplies submitted to the Government for acceptance comply with all requirements of the contract. Sampling in quality conformance does not authorize submission of known defective material, either indicated or actual, nor does it commit the Government to acceptance of defective material.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:17Z
Check the source to verify that this is the current version before use.

4.1.2 Component and material inspection. The contractor is responsible for ensuring that components and materials used are manufactured, examined, and tested in accordance with referenced specifications, standards, and drawings, as applicable.

4.1.3 Disassembly inspection. Failure of any examination or test by the first article tester and chest shall be cause for disassembly, in the presence of a Government representative, of the first article tester and chest to the extent necessary to determine the cause of the failure. Each disassembled part shall be examined in detail in accordance with this specification and referenced drawings in regard to materials, dimensions, tolerances, and workmanship. Parts not in accordance with such requirements shall be rejected and shall be cause for rejection of the first article tester and chest. Reassembly with replacement parts and retesting shall be the responsibility of the contractor.

4.2 Classification of inspections. The inspections specified herein are classified as follows:

a. First article inspection (see 4.3).

b. Quality conformance inspection (see 4.4).

c. Inspection of packaging (see 4.6).

4.3 First article inspection.

4.3.1 Examination. The first article shall be examined as specified in 4.5.1 in the order shown. The presence of one or more defects shall be cause for rejection or for performing the disassembly inspection specified in 4.1.3.

4.3.2 Tests. The first article of the tester shall be tested as specified in 4.5.2. Failure of any test shall be cause for performing the inspection specified in 4.1.3.

4.4 Quality conformance inspection.

4.4.1 Sampling. Sampling for examination and tests shall be in accordance with MIL-STD-105.

4.4.2 Examination. Samples selected in accordance with 4.4.1 shall be examined for major and minor defects specified in 4.5.1. Acceptable quality level (AQL) shall be 1.0 percent defective for major defects and 2.5 percent defective for minor defects.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:17Z
Check the source to verify that this is the current version before use.

4.4.3 Tests.

4.4.3.1 Samples. Samples selected in accordance with 4.4.1 shall be tested as specified in 4.5.2. AQL shall be 1.0 percent defective.

4.5 Inspection procedure.

4.5.1 Examination. The tester and chest shall be examined as specified herein for the following defects:

Number	Defects	Requirement paragraph
	Major	
101.	Tester not in accordance with drawings.	3.1
102.	Chest not in accordance with drawings.	3.1.1
103.	Drawings not furnished.	3.1.2
104.	Material not as specified.	3.3
105.	Materials not resistant to corrosion and deterioration, or treated to be resistant to corrosion and deterioration for the applicable storage and operating environments.	3.3.1
106.	Dissimilar metals as defined in MIL-STD-889 are not effectively insulated from each other.	3.3.1.1
107.	Contractor does not have documentation available for identification of material, material finishes, or treatment.	3.3.1.2
108.	Used, rebuilt or remanufactured components, pieces, or parts incorported in the tester and chest.	3.3.2
109.	Performance not as specified.	3.4
110.	Human factors not as specified.	3.5
111.	Safety requirements not as specified.	3.6
112.	Electromagnetic interference not as specified.	3.7
113.	Treatment and painting not as specified.	3.8
114.	Color not as specified.	3.8
115.	Identification marking missing, incomplete or illegible.	3.9
116.	Plates not attached and located as specified.	3.9, 3.10
117.	Instruction plates not as specified.	3.10
118.	Valve controls not as specified.	3.11
119.	Workmanship not as specified.	3.12
120.	Metal fabrication not as specified.	3.12.1
121.	Castings not cleaned as specified.	3.12.2
122.	Welding not as specified; welds are not free from discontinuities.	3.12.3

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:17Z
Check the source to verify that this is the current version before use.

Number	Defects	Requirement paragraph
	Major	
123.	Aluminum welding not as specified; welds not free from foreign matter, incorrect welding process.	3.12.4
124.	Welders certification not made available for review.	3.12.5
125.	Welding practices and procedures not as specified.	3.12.6
126.	Weld quality not as specified.	3.12.7
127.	Bolted connections not as specified.	3.12.8
128.	Machine work, tolerances and gages not within the limits specified.	3.12.9

4.5.2 Tests.

4.5.2.1 Performance. The tester shall be tested by operating the unit with the vacuum box on a smooth surface. Inability to operate as specified in 3.4 shall constitute failure of this test.

4.5.2.2 Safety. The tester shall be evaluated for safety requirements throughout testing as specified in 4.5.2. Nonconformance to 3.6 shall constitute failure of this test.

4.5.2.3 Electromagnetic interference control. The tester shall be tested in accordance with MIL-STD-462 to determine compliance with the requirements of MIL-STD-461. Nonconformance to 3.7 shall constitute failure of this test.

4.6 Inspection of packaging.

4.6.1 Quality conformance inspection of packaging.

4.6.1.1 Unit of product. For the purpose of inspection,a completed pack prepared for shipment shall be considered a unit of product.

4.6.1.2 Sampling. Sampling for examination shall be in accordance with MIL-STD-105.

4.6.1.3 Examination. Samples selected in accordance with 4.6.1.2 shall be examined for the following defects. AQL shall be 1.0 percent defective.

129.	Unprotected surfaces not coated with preservative as specified (see 5.1.1).
130.	Vacuum pump not preserved and opening sealed as specified (see 5.1.2).
131.	Consolidation not as specified (see 5.1.6).
132.	Packing not as specified for level A, B, or C (see 5.2).

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:17Z
Check the source to verify that this is the current version before use.

133. Strapping not as specified for level A (see 5.2.1).
134. Marking missing, illegible, incorrect, or incomplete (see 5.3).

5. PACKAGING

5.1 Preservation. Each tester shall be preserved for level A in the following manner:

5.1.1 Unprotected surfaces. Unprotected exterior metal surfaces of components requiring application of a contact preservative in accordance with MIL-P-116, shall be coated with type P-1 preservative. The preservative shall be in accordance with the applicable specification listed in and shall be applied in accordance with MIL-P-116.

5.1.2 Vacuum pump. Interior surfaces of the pump shall be coated with preservative lubricating oil in accordance with MIL-L-21260, type I, grade 30, and the excess oil drained. Openings into the pump shall be sealed with tape in accordance with PPP-T-60, type IV.

5.1.3 Wedge gaskets. Wedge gaskets shall be preserved together in accordance with MIL-P-116, method IC-1 or IC-3.

5.1.4 Technical publications. Technical publications shall be preserved in accordance with MIL-P-116, method IC-1 or IC-3.

5.1.5 Repair parts. The preservative application criteria and applicable method(s) of preservation of MIL-P-116 shall be used to preserve the repair parts.

5.1.6 Consolidation. The components comprising a complete tester shall be consolidated in the chest as shown on the drawings. Cushioning shall be in accordance with PPP-C-843, type II, class A, and shall be provided, as required, to prevent movement of contents. The cover shall be closed and secured.

5.2 Packing. Packing shall be level A, B, or C as specified (see 6.2).

5.2.1 Level A. Each chest containing a complete tester, preserved as specified in 5.1, shall be packed in a close-fitting box in accordance with PPP-B-601, overseas type, style optional. Strapping shall be in accordance with QQ-S-781, class 1, type I or IV, finish B, size as applicable.

5.2.2 Level B. Each chest containing a complete tester, preserved as specified in 5.1, shall be packed in a close-fitting box in accordance with PPP-B-636, V3c, style optional. Box closure and reinforcement requirements shall be in accordance with the appendix to the box specification.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:17Z
Check the source to verify that this is the current version before use.

5.2.3 Level C. Each chest containing a complete tester, preserved as specified in 5.1, shall be packed as specified for level B, except the box shall be domestic class.

5.3 Marking. Marking shall be in accordance with MIL-STD-129.

6. NOTES

(This section contains information of a general or explanatory nature that may be helpful but is not mandatory.)

6.1 Intended use. The tester is intended for use in testing the seams in the floor of welded or bolted tanks for leaks prior to being put into service.

6.2 Acquisition requirements. Acquisition documents shall specify the following:

a. Title, number, and date of this specification.

b. Issue of DODISS to be cited in the solicitation, and if required, the specific issue of individual documents referenced (see 2.1.1 and 2.2).

c. Timeframe required for submission of the first article and number of testers and chests required (see 3.2).

d. When top coat color is other than as specified (see 3.8).

e. Welding process to be used (see 3.12.3).

f. Level of packing required (see 5.2).

6.3 First article. When a first article inspection is required, the items should be a preproduction model. The first article should consist of one or more units. The contracting officer should include specific instructions in acquisition documents regarding arrangements for examinations, tests, and approval of the first article test results and disposition of the first article.

6.4 Data requirements. The contracting officer should include requirements for such data as technical publications, instruc- tional materials, illustrated parts lists, and contractor's maintenance and operation manual to be furnished with each tester and chest.

6.5 Provisioning. The contracting officer should include provisioning requirements for repair parts and maintenance tools as necessary (including any special tools), and instructions regarding shipment of testers and chests.

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:17Z
Check the source to verify that this is the current version before use.

6.6 Subject term (key word) listing.

Leak detector, seams
Leak detector tester
Leak detector, vacuum
Seam tester
Tester, leak detector
Vacuum seam tester
Vacuum tester

6.7 Changes from previous issue. Asterisks (or vertical lines) are not used in this revision to identify changes with respect to the previous issue due to the extensiveness of the changes.

Custodian:
Army - ME

Preparing activity:
Army - ME

Project 5430-A142

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:17Z
Check the source to verify that this is the current version before use.

STANDARDIZATION DOCUMENT IMPROVEMENT PROPOSAL

(See Instructions – Reverse Side)

1. DOCUMENT NUMBER	2. DOCUMENT TITLE
MIL-T-14419C(ME)	Tester, Leak Detector, Vacuum Type: For Seams in Bolted + Welded Liquid Storage Tanks

3a. NAME OF SUBMITTING ORGANIZATION	4. TYPE OF ORGANIZATION *(Mark one)*
	☐ VENDOR ☐ USER ☐ MANUFACTURER ☐ OTHER *(Specify)*: _____
b. ADDRESS *(Street, City, State, ZIP Code)*	

5. PROBLEM AREAS

a. Paragraph Number and Wording:

b. Recommended Wording:

c. Reason/Rationale for Recommendation:

6. REMARKS

7a. NAME OF SUBMITTER *(Last, First, MI)* – Optional	b. WORK TELEPHONE NUMBER *(Include Area Code)* – Optional
c. MAILING ADDRESS *(Street, City, State, ZIP Code)* – Optional	8. DATE OF SUBMISSION *(YYMMDD)*

DD FORM 82 MAR 1426 PREVIOUS EDITION IS OBSOLETE

(TO DETACH THIS FORM, CUT ALONG THIS LINE.)

Source: https://assist.dla.mil -- Downloaded: 202610-18T03:17Z
Check the source to verify that this is the current version before use.

INSTRUCTIONS: In a continuing effort to make our standardization documents better, the DoD provides this form for use in submitting comments and suggestions for improvements. All users of military standardization documents are invited to provide suggestions. This form may be detached, folded along the lines indicated, taped along the loose edge *(DO NOT STAPLE)*, and mailed. In block 5, be as specific as possible about particular problem areas such as wording which required interpretation, was too rigid, restrictive, loose, ambiguous, or was incompatible, and give proposed wording changes which would alleviate the problems. Enter in block 6 any remarks not related to a specific paragraph of the document. If block 7 is filled out, an acknowledgement will be mailed to you within 30 days to let you know that your comments were received and are being considered.

NOTE. This form may not be used to request copies of documents, nor to request waivers, deviations, or clarification of specification requirements on current contracts. Comments submitted on this form do not constitute or imply authorization to waive any portion of the referenced document(s) or to amend contractual requirements.

(Fold along this line)

(Fold along this line)

DEPARTMENT OF THE ARMY

OFFICIAL BUSINESS
PENALTY FOR PRIVATE USE $300

BUSINESS REPLY MAIL
FIRST CLASS PERMIT NO. 12062 WASHINGTON D. C.
POSTAGE WILL BE PAID BY THE DEPARTMENT OF THE ARMY

USA Belvoir R D+E Center
Attn: STRBE-TSE
Fort Belvoir, VA 22060-5606

NO POSTAGE
NECESSARY
IF MAILED
IN THE
UNITED STATES

Source: https://assist.dla.mil -- Downloaded: 2026-10-18T03:17Z
Check the source to verify that this is the current version before use.