

FIRST DASH NO.	1	2	3	4	5	6	7	8	9	10	10A
THREAD T	10-32	10-32	1/4-28	5/16-24	3/8-24	7/16-20	1/2-20	9/16-18	3/4-16	7/8-14	7/8-14
A	7/16	7/16	29/64	33/64	35/64	35/64	19/32	21/32	47/64	51/64	51/64
C ±.005	.141	.141	.196	.250	.313	.360	.422	.482	.660	.773	.773
D ±.002	.205	.255	.317	.355	.455	.505	.605	.755	.905	1.050	1.153
E +.010 -.000 (3)	NO. 50 (.070)	NO.50 (.070)	NO.48 (.076)	NO.48 (.076)	NO 36 (.106)	NO 36 (.106)	NO. 36 (.106)	NO. 28 (.141)	NO. 28 (.141)	NO. 28 (.141)	NO. 28 (.141)
F	1/2	1/2	1/2	1/2	1/2	3/4	3/4	1	1	1-1/4	1-1/4
G	5/16	5/16	21/64	21/64	23/64	23/64	13/32	15/32	35/64	39/64	39/64
P (3)	3/64	3/64	3/64	1/16	1/16	1/16	1/16	5/64	3/32	3/32	3/32

ENGINEERING INFORMATION

NUT	AN320-3	AN320-3	AN320-4	AN320-5	AN320-6	AN320-7	AN320-8	AN320-9	AN320-12	AN320-14	AN320-14
(a) WASHER	AN975-3	AN975-3	AN975-4	AN975-5	AN975-6	AN975-7	AN975-8	AN975-9	AN975-12	AN975-14	AN975-14
COTTER	AN380-2-2	AN380-2-2	AN380-2-2	AN380-2-2	AN380-3-3	AN380-3-3	AN380-3-3	AN380-4-4	AN380-4-5	AN380-4-5	AN380-4-5
SELF LOCK NUT	AN364 -1032	AN364 -1032	AN364 -428	AN364 -524	AN364 -624	AN364 -720	AN364 -820	AN364 -918	AN364 -1216	AN364 1414	AN364 -1414

1 ST DASH NUMBER		GRIP	1	2	3	4	5	6	7	8	9	10	10A
2 ND DASH NUMBER			L = GRIP +1/8				L = GRIP +3/16				L = GRIP +1/4		
C.P. HOLE	NO HOLE												
6	6A	3/4											
7	7A	7/8											
8	8A	1											
9	9A	1-1/8											
10	10A	1-1/4											
11	11A	1-3/8											
12	12A	1-1/2											
13	13A	1-5/8											
14	14A	1-3/4											
15	15A	1-7/8											
16	16A	2											
17	17A	2-1/8											
18	18A	2-1/4											
19	19A	2-3/8											
20	20A	2-1/2											
21	21A	2-5/8											
22	22A	2-3/4											
23	23A	2-7/8											
24	24A	3											
25	25A	3-1/8											
26	26A	3-1/4											
27	27A	3-3/8											
28	28A	3-1/2											
29	29A	3-5/8											
30	30A	3-3/4											
31	31A	3-7/8											
32	32A	4											
34	34A	4-1/4											
36	36A	4-1/2											
38	38A	4-3/4											
40	40A	5											
42	42A	5-1/4											
44	44A	5-1/2											
46	46A	5-3/4											
48	48A	6											

DO NOT SPECIFY PINS LONGER THAN THOSE LISTED BETWEEN HEAVY LINES. LISTINGS COVER FULL RANGE OBTAINABLE FROM STANDARD B & S TAPER REAMERS THE NUMBERS OF WHICH ARE INDICATED BY THE FIRST DASH NUMBER. NO 10A REQUIRES NO 10 REAMER.

(3) (a) WASHER USED WITH BOTH TYPES OF NUTS.
MATERIAL STEEL, SPEC AN-S-9, AN-QQ-S-689, MIL-S-6049, MIL-S-6050, MIL-S-6098, OR MIL-S-6758, TENSILE STRENGTH 125,000 TO 145,000 PSI.
FINISH CADMIUM PLATE, SPEC QQ-P-416, TYPE I, CLASS C.
EXAMPLE OF PART NUMBER AN386-1-8 = PIN NO. 1 TAPER 8/8 OR 1 IN. GRIP WITH COTTER PIN HOLE.
AN386-1-8A = PIN NO. 1 TAPER 8/8 OR 1 IN. GRIP WITHOUT COTTER PIN HOLE.
THE FOLLOWING INSTRUCTION SHALL BE PLACED ON DRAWINGS IMMEDIATELY FOLLOWING THE PIN NUMBER: "SMALL END OF TAPERED SHANK SHALL NOT EXTEND MORE THAN 1/16 IN. ABOVE SURFACE OF WORK."
TAPERED SURFACE SHALL BE SMOOTH AND FREE FROM TOOL MARKS.
DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: FRACTIONS ±1/64.

NOTICE When Government drawings specifications or other ment procurement operation, the United States Government thereby ment may have formulated furnished or in any way supplied the said drawings specifications or other data is not to be regarded by implication or otherwise as in any manner licensing the holder or any other person or corporation, or conveying any rights or permission to manufacture use or sell any patented invention that may in any way be related thereto

NOTE: This drawing was approved by joint action of the Air Force and Navy Departments as the Air Force-Navy standard for this product. This drawing supersedes all antecedent standard drawings for the same product and shall become effective for the procurement of aeronautical supplies or for use in new design not later than 6 months after the latest date of approval shown

APPROVED 1 Dec 43 REVISED (1) 29 Mar 44 (2) 11 Jul 45 (3) 23 Feb 54

PROCUREMENT SPECIFICATION	AIR FORCE-NAVY AERONAUTICAL STANDARD	AN386
NONE	PIN — THREADED TAPER	

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:15Z
Check the source to verify that this is the current version before use.

NOTICE
OF VALIDATION

INCH-POUND

AN386 Rev 3
NOTICE 1
10 June 1994

MILITARY SPECIFICATION

PIN & THREADED TAPER

AN386 Rev 3 dated 23-FEB-54 has been reviewed and determined to be valid for use in acquisition.

Custodians:
Air Force - 99
Army - AV
Navy - AS

Preparing activity:
DLA-IS

AMSC N/A

FSC 5315

DISTRIBUTION STATEMENT A. Approved for public release; distribution is unlimited.

Source: https://assist.dla.mil -- Downloaded: 2026-10-26T14:15Z
Check the source to verify that this is the current version before use.