
THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(s) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL - F - 3541

Form Approved
OMB No. 0704-0188



MATERIAL: STEEL - BARS, SHAPES, OR FORGINGS.
TITANIUM ALLOY - BARS, SHAPES OR FORGINGS.
ALUMINUM ALLOY - BARS, SHAPES OR FORGINGS.
CORROSION RESISTANT STEEL - BARS, SHAPES OR FORGINGS.
SEE PROCUREMENT SPECIFICATION.

FINISH: SEE PROCUREMENT SPECIFICATION.

NO CODE LETTER IN PART NUMBER FOR STEEL.
ADD D IN PLACE OF DASH FOR ALUMINUM ALLOY (EXCEPT 7075-T73).
ADD J IN PLACE OF DASH FOR CORROSION RESISTANT STEEL, TYPE 304.
ADD K IN PLACE OF DASH FOR CORROSION RESISTANT STEEL, TYPE 316.
ADD R IN PLACE OF DASH FOR CORROSION RESISTANT STEEL, TYPE 321.
ADD T IN PLACE OF DASH FOR TITANIUM.
ADD W IN PLACE OF DASH FOR 7075-T73 ALUMINUM.

EXAMPLE OF PART NUMBERS:
AN804-8 - TEE, .500 TUBING, STEEL
AN804D8 - TEE, .500 TUBING, ALUMINUM ALLOY (EXCEPT 7075-T73).
AN804J8 - TEE, .500 TUBING, CORROSION RESISTANT STEEL, TYPE 304.
AN804K8 - TEE, .500 TUBING, CORROSION RESISTANT STEEL, TYPE 316.
AN804R8 - TEE, .500 TUBING, CORROSION RESISTANT STEEL, TYPE 321.
AN804T8 - TEE, .500 TUBING, TITANIUM.
AN804W8 - TEE, .500 TUBING, 7075-T73 ALUMINUM

BREAK ALL SHARP EDGES AND REMOVE ALL HANGING BURRS AND SLIVERS WHICH MIGHT BECOME DISLODGED UNDER USAGE.

DIMENSIONS IN INCHES. UNLESS OTHERWISE SPECIFIED, TOLERANCES: DECIMALS ± 0.15.

TITANIUM NOT TO BE USED IN OXYGEN SYSTEMS.

INCH-POUND

(G) ENTIRE STANDARD REVISED.

PREPARING ACTIVITY: 82 CUSTODIANS: ARMY - AV NAVY - AS AIR FORCE - 99 DLA - REVIEW: DLA-CS USER: PROJECT NUMBER: 4730-0038	MILITARY SPECIFICATION SHEET TITLE TEE, FLARED TUBE WITH BULKHEAD ON RUN	SPECIFICATION SHEET NUMBER AN804, REV G 11 April 1994 SUPERSEDING AN804F 5 AUG 83 AMSC. N/A FSC. 4730
DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE: DISTRIBUTION IS UNLIMITED.		Page 1 of 2

Source: https://assist.dla.mil -- Downloaded: 2026-01-26 14:04 GMT
Check the source to verify that this is the current version before use.

THIS SPECIFICATION IS APPROVED FOR USE BY ALL DEPARTMENTS AND AGENCIES OF THE DEPARTMENT OF DEFENSE.

THE REQUIREMENTS FOR ACQUIRING THE PRODUCT(S) DESCRIBED HEREIN SHALL CONSIST OF THIS SPECIFICATION SHEET AND THE ISSUE OF THE FOLLOWING SPECIFICATION LISTED IN THAT ISSUE OF THE DODISS SPECIFIED IN THE SOLICITATION: MIL - F - 5509

Form Approved
OMB No. 0704-0188

DASH NO.	TUBING O D	THREAD T (REF)	R RAD	M +.047 -0	Q +.047 -0	S +.047 -0	U RAD	V	W MIN	X MIN
2	.125	.312 -24UNJF-3A	.031	1.406	.766	.828	.062	.312	.312	.188
3	.188	.375 -24UNJF-3A		1.437	.828	.891		.375	.375	.250
4	.250	.437 -20UNJF-3A	.062	1.578	.891	.953		.437		
5	.312	.500 -20UNJF-3A		1.609	.953	1.016		.500	.469	.312
6	.375	.562 -18UNJF-3A	.094	1.797	1.062	1.078	.094	.562	.500	
8	.500	.750 -16UNJF-3A		2.094	1.250	1.344		.750	.688	.437
10	.625	.875 -14UNJF-3A		2.375	1.453	1.547		.875	.781	
12	.750	1.062 -12UNJ -3A		2.656	1.656	1.766	.125	1.062	.906	.500
16	1.000	1.312 -12UNJ -3A	.094	2.781	1.812	1.922		1.312	1.094	.625
20	1.250	1.625 -12UNJ -3A		3.109	2.062	2.156		1.625	1.312	.750
24	1.500	1.875 -12UNJ -3A		3.406	2.328	2.328	.188	1.875	1.500	.875
28	1.750	2.250 -12UNJ -3A		3.781	2.812	2.594		2.250	1.781	1.062
32	2.000	2.500 -12UNJ -3A		4.094	3.062	2.875		2.562	2.031	1.188

INCH-POUND

© ENTIRE STANDARD REVISED.

PREPARING ACTIVITY: 82
CUSTODIANS: ARMY - AV NAVY - AS
AIR FORCE - 99 DLA -
REVIEW: DLA-CS
USER:
PROJECT NUMBER: 4730-0038

MILITARY SPECIFICATION SHEET
TITLE
TEE, FLARED TUBE WITH BULKHEAD ON RUN

SPECIFICATION SHEET NUMBER
AN804, REV G 11 April 1994
SUPERSEDING
AN804F 5 AUG 83
AMSC. N/A FSC. 4730

DISTRIBUTION STATEMENT A. APPROVED FOR PUBLIC RELEASE; DISTRIBUTION IS UNLIMITED.

Page 2 of 2

Source: https://assist.dla.mil -- Downloaded: 20261026114162
Check the source to verify that this is the current version before use.