NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/406C(IH)
5 July 2023
SUPERSEDING
MIL-DTL-11484/406B(IH)
28 August 2018

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, DEFENSE CONTRACT MANAGEMENT AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No.C-230)

FINISH:
BASE: Epoxy resin 24K Gold Plated Mirror-like Polished and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 6.
DEVICE: Epoxy resin24K Gold Plated, Mirror- like Polish and shall match TIOH Metal Finish Chip Number 6.

DIMENSIONS:
BASE DIAMETER: 3/4 inch (REF)
DEVICE:
HEIGHT: 7/16 inch (REF)
WIDTH: 1/2 inch (REF)
THICKNESS BASE (End of the ray): 0.065 ± 0.010 inch
THICKNESS DEVICE (End of the wing): 0.040 ± 0.010 inch
THICKNESS OVERALL (End of the wing/ray): 0.098 ± 0.010 inch

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:09Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:

1: Attaching device will be a prong with pick and wing type clutch fused or soldered on the vertical center line 1/4 inch from the top of the lapel button.

2: The device will be secured to the base by two solid brass rivets and shall be dapped to insure a snug fit.

EPOXY:

1. Epoxy resin shall be applied to the Lapel Button as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below.

TIOH HARD ENAMEL COLOR CHIPS	
COLOR	**CHIP NUMBER**
White	#28
Blue	#33
Red	#1
Blue	#20

2. BASE: The background of the base shall be filled with Blue Epoxy #33. The stars shall be filled with White Epoxy #28. All epoxy will be floating epoxy.

3. DEVICE: The stripes on the shield shall be alternating White Epoxy #28 and Red Epoxy #1; beginning with white and ending with white. The lapel button shield has 7 stripes. The top of the shield shall be Blue Epoxy #20. All epoxy will be floating epoxy.

NOTES:

1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. The lapel button will be spherically dapped to radius of 10 inches + 1/4 inch - 0 when measured on the reverse.

3. Hard cloisonné enamel may be used in lieu of epoxy. If hard cloisonné enamel is used, the required base material shall be Gilding Metal 95/5 (UNS Alloy C-210).

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:09Z
Check the source to verify that this is the current version before use.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2023-181)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:09Z
Check the source to verify that this is the current version before use.