INCH - POUND

MIL-DTL-11484/410
30 August 2017

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, CIVILIAN VALOR, NATIONAL SECURITY AGENCY

This specification is approved for use by all
Departments and Agencies of the Department of Defense.

The requirements for acquiring the product described herein shall consist of this specification sheet and the latest issue of MIL-DTL-11484.



MATERIAL: Red Brass 85/15 (UNS Alloy No. C-230)

DIMENSIONS:
HEIGHT: 5/8 inch (REF)
WIDTH: 9/16 inch (REF)
THICKNESS: 0.085 inch ± 0.010 inch

FINISH: 24K Gold Plated, Matte Finish, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 8.

ATTACHING DEVICE:
1 The attaching device shall be prong with pick and wing type clutch.

2. The prong shall be centered on the vertical center line on the reverse side, 1/4 inch from the top and fused or soldered to the lapel button.

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:10Z
Check the source to verify that this is the current version before use.

EPOXY: Epoxy enamel shall be applied as indicated below, and shall match TIOH Hard Enamel Color Chip Numbers listed:

TIOH ENAMEL COLOR CHIP NUMBER	LOCATION
Blue #30	Top of the shield
White #28	First stripe and every alternating stripes
Red #1	Second stripes and every alternating stripes
Red #3	Background of the diamond behind the eagle

NOTES:
1: The term (REF) refers to the measurements taken from the obverse Government furnished hub or die.

2: All epoxy will be stoned epoxy

Custodian:
Army - IH

Preparing activity:
Army - IH

Review Activity:
DLA - CT

(Project No. 8455-2017-314)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:10Z
Check the source to verify that this is the current version before use.