NOT MEASUREMENT SENSITIVE

MIL-DTL-11484/415A(IH)
12 June 2023
SUPERSEDING
MIL-DTL-11484/415(IH)
6 August 2018

DETAIL SPECIFICATION SHEET

LAPEL BUTTON, CIVILIAN SERVICE, U.S. ARMY

This specification is approved for use by all
Departments and Agencies of the Department of Defense

The requirements for acquiring the product described herein shall consist of this specification sheet and MIL-DTL-11484.



DASH NUMBER
-1: Brass
-2: Silver
-3: Brass with Magnet
-4: Silver with Magnet

MATERIAL: (-1 Thru -4) Red Brass 85/15 (UNS Alloy No.C-230)

FINISH:
-1 and -3: Brass, Oxidized, Buffed Relieved, Polished Highlights and shall match The Institute of Heraldry (TIOH) Metal Finish Chip Number 5.
-2 and -4: Silver Plated, Oxidized, Buffed Relieved, matte Finish, Polished Highlights and shall match TIOH Metal Finish Chip Number 15.

DIMENSIONS:
DIAMETER: -1 thru -4: 11/16 inch (REF)
THICKNESS:
-1 and -2: 0.076 ± 0.010 inch
-3 and -4: 0.096 ± 0.010 inch

AMSC N/A FSC 8455

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:11Z
Check the source to verify that this is the current version before use.

ATTACHING DEVICE:
For -1 and -2, the attaching device shall be prong with pick and wing type clutch. The prong shall be fused or soldered on the reverse vertical center line 1/4 inch from the top of the lapel button.
For -3 and -4, the attaching device shall consist of two parts. The first part is a circular disc soldered to the back of the lapel The disc shall be 9/16 inch in diameter, .020 inch thick (± .005) and be made out of cold rolled steel. The second part is a neodymium magnet measuring 1/2 inch wide by 1/16 inch thick used to connect the lapel.

EPOXY: Epoxy resin shall be applied to the Lapel Button as indicated above, and shall match TIOH Hard Enamel Color Chip Numbers listed below.

TIOH HARD ENAMEL COLOR CHIPS	
COLOR AND NUMBER	**LOCATIONS**
Black # 26	Outer Scrolls

NOTES:
1. The term (REF) refers to the measurements taken from the Government furnished hub or die.

2. As an exception to MIL-DTL-11484 and for commercial sale only, manufacture may use a magnet device instead of prong.

CHANGES FROM PREVIOUS ISSUE: The margins of this specification are marked with vertical lines to indicate where changes from the previous issue were made. This was done as a convenience only and the Government assumes no liability whatsoever for any inaccuracies in these notations. Bidders and contractors are cautioned to evaluate the requirements of this document based on the entire content irrespective of the marginal notations and relationship to the last previous issue.

Custodian:
Army - IH

Preparing activity:
Army - IH

Review activity:
DLA - CT

(Project No. 8455-2023-156)

NOTE: The activities listed above were interested in this document as of the date of this document. Since organizations and responsibilities can change, you should verify the currency of the information above using the ASSIST Online database at https://assist.dla.mil.

Source: https://assist.dla.mil -- Downloaded: 2026-10-17T18:11Z
Check the source to verify that this is the current version before use.