MIL-C-46665A(MU)
27 October 1972
Superseding

MIL-C-46665(MU)
15 June 1962

MILITARY SPECIFICATION

CARTRIDGE, 105MM, TP-T, M467 LOADING, ASSEMBLING AND PACKING

1. SCOPE

1.1 This specification covers the loading, assembling and packing for one type of target practice cartridge designated as Cartridge, 105MM, TP-T, M467.

2. APPLICABLE DOCUMENTS

2.1 The following documents of the issue in effect on date of invitation for bids form a part of this specification to the extent specified herein.

SPECIFICATIONS

MILITARY

MIL-A-2550 - Ammunition and Special Weapons; General Specification for
MIL-I-45607 Inspection Equipment, Supply and Maintenance of

STANDARDS

MILITARY

MIL-STD-105 - Sampling Procedures and Tables for Inspection by Attributes.
MIL-STD-109 - Quality Assurance Terms and Definitions
MIL-STD-414 - Sampling Procedures and Tables for Inspection by Variables for Percent Defective
MIL-STD-1167 -Ammunition Data Card
MIL-STD-1168 -Lot Numbering of Ammunition
MIL-STD-1235 -Single and Multilevel Continuous Sampling

FSC: 1315

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

DRAWINGS

ARMY

8863618 - Cartridge, 105MM, TP-T, M467, Assembly and Marking Diagram.
8836004 - Box, Packing Ammunition for Cartridge, 105MM, TP-T, M467 for Gun M68 in Fiber Container M451
8836005 - Container, Ammunition, Fiber, M451 for Cartridge, 105MM, TP-T, M467 for Gun M68.

PUBLICATIONS

ARMY

ET 8863618 - Equipment Tabulation

(Copies of specifications, standards, drawings and publications required by suppliers in connection with specific procurement functions should be obtained from the procuring activity or as directed by the contracting officer.

2.2 Other Publications.-The following document forms a part of this specification to the extent specified herein. Unless otherwise indicated, the issue in effect on date of invitation for bids shall apply.

CODE OF FEDERAL REGULATIONS

49 CFR/1-199 - Department of Transportation Rules and Regulations for the Transportation of Explosives and Other Dangerous Articles.

(The Department of Transportation Regulations are now a part of the Code of Federal Regulations (1970 Edition) available from the Superintendent of Documents, Government Printing Office, Washington, D.C., 20402. Orders for the above publications should cite "Code of Federal Regulations, 49 CFR/1-199 (latest revision)".)

3. REQUIREMENTS

3.1 Materials.-All materials and parts shall be in accordance with applicable drawings and specifications.

3.2 Cartridges.-The cartridges shall comply with all requirements specified on Drawing (dwg.) 9963618, and with all requirements specified in applicable specifications.

3.3 Bullet pull.-The cartridge case shall separate from the projectile at a load of 3500 pounds, minimum, (min.) when tested as specified in 4.3.2.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

3.4 Proving Ground.

3.4.1 Muzzle Velocity.-The corrected muzzle velocity of the cartridge when fired at 70°F. shall be not more than 2430 feet per second (f.p.s.) nor less than 2370 f.p.s. and the standard deviation of the lot shall be not greater than 9.0 f.p.s. Testing shall be as specified in 4.3.3.

3.4.2 Tracer functioning.-The tracer shall ignite and there shall be visible evidence of the burning of the tracer composition to the 2000 meter target.

3.4.3 Safety.-There shall be no hangfires, premature bursts or indications of metal parts failure in the gun bore or in flight, prior to impact.

3.5 Workmanship

3.5.1 General.-The cartridges and all components shall be free of cracks or burrs; and chips, dirt, grease, rust or other foreign material. The cleaning method shall not be injurious to any of the parts nor shall the parts be contaminated by the cleaning agents. The cartridge shall not be damaged in any manner during the loading operation.

3.5.2 The painting and marking shall be restored by the assembling contractor on any components furnished to him painted and marked, when such paintings and markings have been marred or obliterated. (Bare spots in painting,other than marking, are allowable provided that they total not more than 1/4 square inch in aggregate, and that the maximum dimension of any individual bare spot does not exceed 3/16 inch).

4. QUALITY ASSURANCE PROVISIONS

4.1 Responsibility for inspection.-Unless otherwise specified in the contract or purchase order, the supplier is responsible for the performance of all inspection requirements as specified herein. Except as otherwise specified in the contract or order, the supplier may use his own or any other facilities suitable for the performance of the inspection requirements specified herein, unless disapproved by the Government. The Government reserves the right to perform any of the inspections set forth in the specification where such inspections are deemed necessary to assure supplies and services conform to prescribed requirements. Reference shall be made to Standard MIL-STD-109 in order to define terms used herein. The provisions of Specification MIL-A-2550 shall apply.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

4.1.1 Submission of product.-At the time each completed lot of items deliverable under the contract is submitted to the Government for acceptance, the contractor shall supply the following information accompanied by a certificate which attests that the information provided is correct and applicable to the product being submitted:

a. A statement that the lot complies with all of the quality assurance provisions specified in this specification.

b. Drawing and specification number anddate, together with an identification and date of changes thereto.

c. A statement that all material purchased by the contractor meets requirements, when such material is controlled by Government or commercial specifications referenced in any of the contractual documents, and that certificates of conformance are on file and available for review.

d. Number of items in the lot.

e. Date submitted.

The certificate shall be signed by a responsible agent of the certifying organization. The initial certificate submitted shall be substantiated by evidence of the agent's authority to bind his principal. Substantiation of the agent's authority will not be required with subsequent certificates unless, during the course of the contract, this authority is vested in another agent of the certifying organization.

4.2 Inspection provisions

4.2.1 Lot formation.-The term "inspection lot" as used in this specification is defined as an essentially homogeneous collection of units of product from which a representative sample is drawn and inspected to determine conformance applicable requirements. The sample selected shall represent only that quantity of units from which the sample was drawn and shall not be construed to represent any prior or subsequent quantities presented for inspection. Homogeneity shall be considered to exist provided the inspection lot has been produced by one manufacturer, in one unchanged process, using the same materials and methods in accordance with the same drawings, same drawing revisions, same specifications and same specification revisions and complies with the provisions for submission of product as specified in MIL-STD-105. Changes to the process, specifications, or drawings not affecting

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

safety, performance, interchangeability, or storage, as determined by the Government, shall not be deemed to alter the homogeneity of an inspection lot. All material submitted for inspection in accordance with this specification shall comply with the homogeneity criteria specified herein, regardless of the type of sampling procedure which is being applied to determine conformance with requirements. Lot numbering, as required, shall be in accordance with MIL-STD-1168. Each inspection lot of loaded complete round cartridges shall contain:

a. Cartridge cases from one manufacturer in accordance with the same drawing and drawing revision, same specification and specification revision, or if resized cases are used, from not more than one lot.

b. Projectiles of one lot interfix number from one manufacturer in accordance with the same drawing and drawing revision, same specification and specification revision.

c. Propellant of one lot from one manufacturer.

d. Loaded primers of one lot interfix number from one manufacturer.

e. Loaded tracers of one lot interfix number from one manufacturer.

f. Liners of one lot interfix number from one manufacturer.

4.2.2 Examination.-The examinations listed in the following subparagraphs shall be performed on inspection lots (see 4.2.1) of the components or assemblies designated in the applicable paragraph headings. Inspection for critical defects (and major defects, when so specified) shall be 100 percent. Sampling plans for major and minor defects shall be in accordance with MIL-STD-105 except that continuous sampling plans in accordance with MIL-STD-1235 may be used if approved by the Government. Instead of applying the AQL's designated herein to the groups of major and minor defects listed the contractor may elect to apply AQL's to individual defects using an AQL of 0.40 percent for each major defect and an AQL of 0.65 percent for each minor defect. When this method is elected, it shall be applied to all of the major and minor defects listed in the applicable subparagraph of this section, except where 100 percent inspection is specified, and be documented as part of the contractor's inspection system. Equipment necessary for the performance of the inspections listed shall be in accordance with 4.2.4.

4.2.2.1 Ring (see dwg. 8860609 covering a detail of dwg. 8863618).

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

Categories	Defects	Method of Inspection	Code No. (see 6.2)
Critical: None Defined.			
Major: None defined.			
Minor:	AQL 1.50 Percent		
201.	Thickness, max.	Gage	01001
202.	Material torn or otherwise damaged	Visual	01002
203.	Evidence of poor workmanship (see 3.5)	Visual	01003

4.2.2.2 Projectile loading assembly (see dwg. 8863616 covering a detail of dwg. 8863618)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 Percent		
101.	Tracer fails to withstand reapplication of minimum assembly torque	Test	02001
102.	Tracer disc damaged (other than wrinkles)	Visual	02002
103.	Ring missing or improperly located	Visual	02003
Minor:	AQL 1.50 Percent		
201.	Total length, maximum (max)	Gage	02004
202.	Marking misleading or unidentifiable, including incorrect color code	Visual	02005
203.	Adhesive missing from tracer threads	Visual	02006
204.	Evidence of poor workmanship (see 3.5)	Visual	02007

4.2.2.3 Assembly, prior to crimping cartridge case (see dwg. 8863618)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

Major: None defined.

Minor:			
	AQL 1.0 percent		
201.	Propelling charge assembled with foil at wrong end.....	Visual	03001
202.	Evidence of poor workmanship (see 3.5).....	Visual	03002

4.2.2.4 Assembly (see dwg. 8863618)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	100 percent inspection		
101.	Primer above flush.....	Straight Edge	04001
Major:	AQL 0.65 percent		
102.	Primer fails to withstand application of disassembly torque.....	Test	04002
103.	Distance from rear face of cartridge case to top of electrode, max.....	Gage	04003
104.	Gap between cartridge case and rotating band lip, max.....	Gage	04004
Minor:	AQL 1.00 percent		
201.	Marking misleading or unidentifiable including incorrect color code.....	Visual	04005
202.	Evidence of poor workmanship (see 3.5).....	Visual	04006

4.2.2.5 Unsealed fiber container (see dwg. 8836005)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.40 percent		
101.	Packing support missing.....	Visual	05001
Minor:	AQL 1.50 percent		
201.	Cartridge cannot be removed by hand.....	Manual	05002
202.	Container cap cannot be removed by hand.....	Manual	05003

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

203.	Glue or asphalt on cartridge	Visual	05004
204.	Packing components improperly assembled	Visual	05005

4.2.2.6 Sealed fiber container (see dwg. 8836005)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Tape incomplete or badly wrinkled	Visual	06001
102.	Container cut or damaged through all asphalt impregnated layers	Visual-Manual	06002
103.	Metal end loose or distorted	Visual-Manual	06003
Minor:	AQL 2.50 percent		
201.	Tear tab length, min	Gage	06004
202.	Gap between cover and body container exceeding 1/8 inch	Visual	06005
203.	Marking misleading or unidentifiable	Visual	06006
204.	Cuts, scuff or gouges in outer layers	Visual	06007
205.	Contents loose	Manual	06008

4.2.2.7 Sealed wood packing box (see dwg. 8836004)

Categories	Defects	Method of Inspection	Code No.
Critical: None defined.			
Major:	AQL 0.65 percent		
101.	Box damaged exposing contents	Visual	07001
102.	Hardware or strapping missing, broken or loose	Visual-Manual	07002
103.	DOD symbol missing or incorrect	Visual	07003
104.	Board broken	Visual	07004
Minor:	AQL 1.50 percent		
201.	Strapping or hardware improperly assembled	Visual-Manual	07005

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

202.	Handle missing or insecure...	Visual-Manual	07006
203.	Car seal missing, unsealed or improperly positioned.....	Visual	07007
204.	Marking misleading or unidentifiable.....	Visual	07008

4.2.3 Testing

4.2.3.1 Check test for possible deterioration (see applicable primer specification) Major defect, Code No. 03003.-If the total elapsed time between the original acceptance of any primer lot and the assembly of that lot into complete round cartridges exceeds two years, or if the primers have been subjected to adverse conditions, however brief, at any time since previous tests, the applicable lot shall be subjected to, and must satisfactorily pass, the check test for deterioration specified in applicable primer loading specification immediately before the primer lot is assembled into complete cartridges. The test shall be performed by the contractor on assemblies selected by the Government inspector at the facility assembling the complete cartridges (see 6.4).

4.2.3.2 Profile and alignment (see dwg. 8863618) Major defect, Code No. 04007.-The cartridges shall be gaged 100 percent for profile and alignment. Any cartridge which fails to meet the applicable requirement shall be classed defective and removed from the lot. Equipment shall be in accordance with 4.2.4.

4.2.3.3 Primer circuit electrical resistance (see dwg. 8863618) Major defect, Code No. 03004.-The cartridge cases, with primers assembled, shall be tested 100 percent for resistance. Any case-primer assembly which fails to comply with the resistance requirement shall be classed defective and removed from the lot. Testing shall be as specified in 4.3.1, with equipment in accordance with 4.2.4.

4.2.3.4 Bullet pull (see 3.3) Major defect, Code No. 04008. The sampling plan for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-1, code letter F and AQL 1.50 percent. The test shall be performed as specified in 4.3.2, with equipment in accordance with 4.2.4.

4.2.3.5 Proving ground tests.-The following tests shall be performed as specified in 4.3.3.

4.2.3.5.1 Muzzle velocity (see 3.4.1) Major defect, Code No. 07009.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

4.2.3.5.1.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, code letter I and AQL 1.0 percent. In addition, if the standard deviation of the sample cartridge multiplied by the factor 0.75 exceeds the lot requirement, the lot shall be rejected.

4.2.3.5.1.2 After three consecutive lots have met the criteria of 4.2.3.6.1.1, the sampling plan and procedure for this test shall be in accordance with Standard MIL-STD-414, Section B, Table B-3, code letter F, and AQL 1.0 percent. In addition, if the standard deviation of the sample multiplied by the factor 0.65 exceeds the applicable lot requirement, the lot shall be rejected.

4.2.3.5.2 Tracer functioning (see 3.4.2) Major defect, Code No. 07010.

4.2.3.5.2.1 Beginning with the first lot produced and continuing until three consecutive lots have complied with the applicable requirements specified, the sample cartridges fired in the test for muzzle velocity (see 4.2.3.5.1.1) shall be observed for tracer functioning. If two or more cartridges fail to comply with the applicable requirements, the lot shall be rejected.

4.2.3.5.2.2 After the three consecutive lots have met the criteria of 4.2.3.5.2.1, the sample cartridges fired in the test for muzzle velocity (see 4.2.3.5.1.2) shall be observed for tracer functioning. If two or more samples cartridges fail to comply with the applicable requirements, the lot shall be rejected.

4.2.3.5.3 Target impact dispersion (for information only). The sample cartridges fired in the test for muzzle velocity shall also be used for target impact dispersion information. The test procedure shall be in accordance with 4.3.3.1.1.)

4.2.3.5.4 Extreme temperature firing (for information only). Code No. 07011.-Twenty cartridges shall be selected from each of the first three production lots and fired for muzzle velocity, target-impact dispersion, and max. chamber pressure information at -40 degrees F. (10 rds) and 125 degrees F. (10 rds.). The test procedure shall be in accordance with 4.3.3.3.

4.2.3.5.5 Safety (see 3.4.3) Critical defect, Code No. 07012.-If any of the sample cartridges fired fail to comply with the applicable requirement, the lot shall be rejected.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

4.2.4 Inspection Equipment.-Equipment Tabulation Number ET-8863618 identifies the inspection equipment required to perform the examinations and tests prescribed in this section. The contractor shall design inspection equipment in accordance with the instructions in paragraph 6.3.

4.2.4.1 Government rights to documentation.-Inspection equipment drawings and lists provided and revised in accordance with the requirements of the ET may be used by DOD activities for design, procurement, manufacture, testing, evaluation, production and receiving inspection, overhaul, shipping, storage, identification of stock, ordering and storage of replacement parts, inspection of items at overhaul, general maintenance of equipment, construction, survey and whenever inspection equipment drawings are needed.

4.2.4.2 Supply and maintenance.-Supply and maintenance of the equipment listed on the ET shall be in accordance with Specification MIL-I-45607.

4.2.4.3 Government use of contractor's inspection equipment.-The contractor shall, as required, make available to the Government all inspection equipment necessary for determining conformance with contract requirements. Personnel for operation of the equipment and verification of its accuracy shall be supplied by the contractor when required by the Government in performance of its examination or test.

4.3 Test methods and procedures.

4.3.1 Electrical resistance.-The resistance shall be measured using an electrical circuit which limits the current through the primer to 20 milliamperes, maximum, with the primer electrode as one contact point and the cartridge case as the other.

4.3.2 Bullet pull.-The cartridge shall be tested in an appropriate tensile testing machine to determine the security of the crimp of the cartridge case to the projectile. The load shall be applied in the axial direction with the rate of travel of the testing machine head from 0.100 to 0.125 inch per minute.

4.3.3 Proving ground.-These tests shall be conducted at a Government proving ground in accordance with the latest revision of the Proving Ground Acceptance Test Procedure. The cartridges shall be fired alternately with an equal number of calibrated reference rounds in a gun for which it is standard and observation shall be made for conformance to all applicable requirements.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

4.3.3.1 Velocity - target impact dispersion. - The ammunition fired in this test shall be conditioned at a temperature of 70°F ± 2°F in a test chamber until all propellant is stabilized at a uniform temperature prior to firing. This normally requires a period of 24 hours. The cartridge shall be fired at a cloth target placed at a distance of 2000 meters from the muzzle of the gun. Vertical and horizontal hit pattern results shall be expressed as probable errors in mils and shall be recorded on the firing record for informational purposes only (see 6.5). Muzzle velocity shall be determined and recorded for each round.

4.3.3.2 Tracer functioning. - Cartridges fired during the velocity test shall be observed for tracer functioning to the 2000 meter target. The distance over which the tracer burns shall be recorded to the nearest estimated 500 meters (i.e., failure, 500 meters, 1000 meters, 1500 meters, 2000 meters).

4.3.3.3 Extreme temperature firing. (Information only). - For this test ten rounds shall be temperature conditioned at -40°F ± 2°F and ten rounds shall be temperature conditioned at +125°F ± 2°F until all propellant is stabilized at a uniform temperature prior to firing. This normally requires a period of 24 hours. The cartridge shall be fired at cloth target placed at a distance of 2000 meters from the muzzle of the gun. Muzzle velocity, max. chamber pressure, and target impact dispersion data shall be recorded.

4.3.3.4 Safety. - All rounds fired in the proving ground tests shall be observed for hangfires, premature bursts and other apparent safety hazards.

5. PREPARATION FOR DELIVERY

5.1 Preservation and packaging

5.1.1 Level A. - The cartridge shall be packaged in accordance with dwg. 8836005.

5.2 Packing

5.2.1 Level A. - The cartridges in containers shall be packed in accordance with dwg. 8836004.

5.3 Marking. - The marking shall be in accordance with dwg. 8836004 and 8836005.

6. NOTES

6.1 Ordering data. - Procurement documents shall specify the following:

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

a. Title, number and date of this specification.

b. Data cards.-Data cards shall be prepared for each lot in accordance with the information specified in Standard MIL-STD-1167.

6.2 Inspection code numbers.-The five digit code numbers assigned to the inspections herein are to facilitate future data collection and analysis by the Government. These code numbers are used to correlate the characteristics cited on the Equipment Lists with the inspections listed in this specification. They should also be cited as references on drawings of equipment designs submitted by the contractor (see 6.3.5).

6.3 Inspection equipment.-The contractor shall design inspection equipment as required by the inspection Equipment Lists (EL) referenced on the applicable ET in accordance with the instructions of paragraph 6.3.1 through 6.3.5.

6.3.1 Inspection equipment lists (EL).-Inspection equipment lists indicate the availability of inspection equipment designs by showing in the "number" column of the list of inspection equipment (Form SMUPA 1010) the numbers of drawings or Federal Stock numbers of existing equipment designs, or codes as indicated in paragraph 6.3.2. Design action required of the contractor is described in paragraphs 6.3.3 and 6.3.4. The contractor will be required to prepare detailed drawings in accordance with 6.3.4 for all the equipment coded as "Contractor Design" in the number column. These contractor designs must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.2 Inspection equipment list codes.-The inspection equipment as defined in 6.3.3 and 6.3.4 will be designated in the EL by the following codes:

CD - Contractor design or controlled contractor format and/or commercial equipment.
MU - Army design, mandatory for use.

6.3.3 Army designs.-Army designs are reflected on detailed drawings which completely depict all the information necessary for the fabrication of the item of inspection equipment. The contractor need provide no design when an Army design is listed for an item of inspection equipment. Army designs fall into two basic classifications; mandatory (designated "MU") and non-mandatory (indicated by drawing or Federal Stock Number). When an inspection equipment list references mandatory Army designs, the contractor shall comply with, and use these designs

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

accordingly. The contractor may, however, in connection with non-mandatory designs, design alternate inspection equipment or use comparable commercial equipment to facilitate his operations. Such contractor prepared designs or commercial equipment selections must be approved by the Government prior to fabrication or procuring of the equipment. Designs shall be submitted for approval as specified in 6.3.5.

6.3.4 Contractor designs.-Contractor designs are designs of inspection equipment for which the Government has assigned design responsibility to the contractor. Contractor designs shall be supported by detailed drawings which depict all information necessary to completely fabricate, calibrate and operate an item of inspection equipment. This requires that the necessary views, dimensions, materials, finish, notes, operating and calibration instructions be properly depicted in accordance with approved practices to the extent that further calculation or clarification will not be required. Unless otherwise specified, contractor designs may be developed on the format the contractor normally employs in his equipment design procedure provided such format reflects the detail and information specified above, subject to the following controls: All submitted contractor designs shall conform to MIL-D-1000, Category A, Form 2. Legibility and reproducibility shall permit conventional making of clearly understandable, high contrast reproductions. Contractors shall submit one copy of final designs as a flat set. Designs shall be submitted for approval as specified in 6.3.5.

6.3.5 Submission of contractor designs.-All submitted designs shall contain a reference to the applicable five digit Code Number contained in Section 4 of this specification and the appropriate component or assembly drawing number and revision letter to which the specific design applies. Unless otherwise specified on the EL, all designs of equipment for inspection of defects classified as critical and major shall be submitted for approval to the Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-A. All other designs of inspection equipment shall be approved by the inspection element of the agency administering the contract; submission shall be as directed by the contracting officer. Partial submission of inspection equipment designs is permissible and encouraged. However, the Arsenal completion date for design review will be based on the date of the final submission of designs. Picatinny Arsenal design review will be accomplished normally within one month after receipt.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

6.4 Cost of check test.-The contracting officer shall arrange for the contractor to be reimbursed for the expense incurred in the performance of the check tests. The test shall be conducted at Government expense without cost to the contractor who loaded the assemblies or to the contractor assembling the cartridge, and shall not constitute a basis for rejection against either contractor, except where deterioration has occurred as a direct result of carelessness in handling, storage, etc., permitted while the primer lot was under the jurisdiction of either contractor.

6.5 Submission of test data and ammunition data cards.-In addition to the normal distribution of records, when the cartridge is procured by the Army Munitions Command, one copy of all ballistic test data and ammunition data cards shall be forwarded to each of the following: Commanding Officer, Picatinny Arsenal, ATTN: SMUPA-QA-A-A and SMUPA-AD-E-A2, Dover, New Jersey, 07801.

6.6 Proving ground test

6.6.1 Test validity.-If for any reason the proving ground considers that the test conditions have detrimentally affected the test results, the test shall be declared invalid and a new test shall be performed with additional samples.

6.6.2 Test summary: See next page.

Custodian:
Army-MU

Preparing Activity:
Army-MU

Project Number: 1315-A006

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

6.6.2 Proving Ground Test Summary

TEST	SAMPLE SIZE INITIAL (NOTE 1)	SAMPLE SIZE SUBSEQUENT	REQUIREMENTS	SAMPLING PARAGRAPH	TEST PROCEDURES PARAGRAPH
Muzzle Velocity	25	10	a. Muzzle Velocity Velocity (3.4.1)	4.2.3.5.1	4.3.3.1
			b. Tracer Functioning (3.4.2)	4.2.3.5.2	4.3.3.2
			c. Target Impact Dispersion (info)	4.2.3.5.3	4.3.3.1
Extreme Temperature	20	-	a. Pressure (info)	4.2.3.5.4	4.3.3.3
			b. Muzzle Velocity (Info)	4.2.3.5.4	4.3.3.3
			c. Target Impact Dispersion (info)	4.2.3.5.4	4.3.3.3
			d. Safety (3.4.3)	4.2.3.5.5	4.3.3.4

NOTES

1. Until three (3) consecutive lots are accepted.

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.