MILITARY SPECIFICATION

CARTRIDGE, GRENADE, 7.62MM, NATO, RIFLE, M64

This Amendment forms a part of Military Specification MIL-C-46666B(AR), dated 10 August 1973, and is approved for use by the US Army Armament, Munitions and Chemical Command and is available for use by all Departments and Agencies of the Department of Defense.

Delete "AMCR 715-505 Volume 3" wherever it appears in the specification and substitute "SCATP-7.62mm".

PAGE 3

3.3: Delete "ambient temperature" and substitute "room temperature (65°F to 75°F)".

PAGE 7

4.3.3.2, Table III:

Change defect numbers from "2, 3 and 4" to "3, 4 and 5" respectively.

Add new defect number 2 as follows:

"2. Hangfire 3/ 0 -"

PAGE 8

Add footnote numbers 3 to Table III as follows:

"3/ For definition of hangfire, see SCATP-7.62, paragraph 10.6.2."

4.4.1: Delete "ambient temperature" and substitute "room temperature (65°F to 75°F)".

4.4.1.1: Delete "ambient temperature" and substitute "room temperature (65°F to 75°F)".

4.4.1.2: Delete the phrase "temperature at which the ammunition is conditioned shall be plus 125 to plus 130 degrees F" and substitute "test sample shall be stored for 4 to 5 hours at 125°F to 130° and fired at that temperature".

FSC 1305

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.

4.4.1.3, Add new paragraph as follows:

"4.4.1.3 Room temperature tests. The test sample shall be conditioned for not less than 2 hours at 65°F to 75°F (room temperature) and fired at that temperature.

Custodian:
Army-AR

Preparing activity:
Army-AR

(Project 1305-A979

Source: https://assist.dla.mil -- Downloaded: 2026-10-22T06:37Z
Check the source to verify that this is the current version before use.